

PetpoojaOnlineOrdering APIs

Version 2.1.0

Petpooja Integration Platform API enables restaurant partners to manage store, menus and orders received/placed from online order aggregators. Integrating with a restaurant partner's PoS system improves efficiency for menu management and order management of online orders.

All API methods use POST.

Access to developer account of staging/production: <https://developerapi.petpooja.com/>

Credentials for both staging and production environment will be provided by the Petpooja team.

SERVERS

- `https://internal_or_external_URL_Address.com` — Production server
- `https://developerapi.petpooja.com` — Developer/Staging server

AUTHENTICATION

- **app-key** (header) — Unique application key [32 characters]
- **app-secret** (header) — Unique application secret [40 characters]
- **access-token** (header) — Unique access token [40 characters]

Menu

APIs for menu synchronization between Petpooja and integration partners

POST /pushmenu_endpoint

Push Menu

This API helps an online order aggregator get a brand's menu items, choices and availability. Petpooja calls this integrator-provided endpoint whenever the merchant makes changes to the menu.

KEYS

KEY	TYPE	REQ	DESCRIPTION
success	string	optional	1=success, 0=failure
restaurants	array<Restaurant>	optional	
^L restaurantid	string	optional	
^L active	string	optional	
^L details	RestaurantDetails	optional	
^L menusharingcode	string	optional	Unique mapped Id for third-party restaurant
^L currency_html	string	optional	Currency HTML symbol
^L country	string	optional	
^L images	array<string>	optional	
^L restaurantname	string	optional	
^L address	string	optional	
^L contact	string	optional	
^L latitude	string	optional	
^L longitude	string	optional	
^L landmark	string	optional	
^L city	string	optional	
^L state	string	optional	
^L minimumorderamount	string	optional	
^L minimumdeliverytime	string	optional	
^L minimum_prep_time	string	optional	Minimum preparation time in minutes
^L deliverycharge	string	optional	
^L deliveryhoursfrom1	string	optional	
^L deliveryhoursto1	string	optional	
^L deliveryhoursfrom2	string	optional	
^L deliveryhoursto2	string	optional	
^L sc_applicable_on	string	optional	Service charge applicable on DineIn, Parcel & Home Delivery orders. Values: D, P, H
^L sc_type	string	optional	

KEY	TYPE	REQ	DESCRIPTION
			Service charge type. 1=Fixed, 2=Percentage
^L sc_calculate_on	string	optional	Service charge calculated on. 1=CORE, 2=TOTAL
^L sc_value	string	optional	Service charge value
^L tax_on_sc	string	optional	Tax applicable on service charge. 1=Applicable, 0=Not Applicable
^L calculatetaxonpacking	integer	optional	Calculate tax on packing. 0 or 1
^L pc_taxes_id	string	optional	Tax ids applicable on packing charges
^L calculatetaxondelivery	integer	optional	Calculate tax on delivery. 0 or 1
^L dc_taxes_id	string	optional	Tax ids applicable on delivery charges
^L packaging_applicable_on	string	optional	Packing charge applicable on. Values: NONE, ITEM, ORDER
^L packaging_charge	string	optional	
^L packaging_charge_type	string	optional	Packing charge type. Values: PERCENTAGE, FIXED
ordertypes	array<OrderType>	optional	
^L ordertypeid	integer	optional	Order type id
^L ordertype	string	optional	Order type name (Delivery, Pickup, DineIn)
categories	array<Category>	optional	
^L categoryid	string	optional	Category id
^L active	string	optional	Category status (boolean string)
^L categoryrank	string	optional	Category rank for ordering
^L parent_category_id	string	optional	Parent category id
^L categoryname	string	optional	Category name
^L categorytimings	string	optional	Active schedule days and time slot
^L category_image_url	string	optional	Category image URL
^L group_category_id	string	optional	ID of the group category this category belongs to
parentcategories	array<ParentCategory>	optional	
^L id	string	optional	
^L name	string	optional	
^L rank	string	optional	

KEY	TYPE	REQ	DESCRIPTION
^L image_url	string	optional	
^L status	string	optional	
group_categories	array<GroupCategory>	optional	Groups of categories (optional)
^L id	string	optional	Unique id of a group category
^L name	string	optional	Name of the group category
^L status	string	optional	Group category status (boolean string)
^L rank	string	optional	Rank for ordering/stacking
items	array<MenuItem>	optional	
^L itemid	string	optional	Item id
^L itemallowvariation	string	optional	Whether item allows variations. 1=yes, 0=no
^L itemrank	string	optional	Item rank for ordering/stacking
^L item_categoryid	string	optional	Category id from category object
^L item_ordertype	string	optional	Order types for this item (1=Home Delivery, 2=Parcel, 3=Dine In), comma-separated
^L item_tags	array<string>	optional	Optional tags. Possible values: vegan, chef-special, new
^L item_info	object	optional	
^L spice_level	enum	optional	Spice level. Default is not-applicable
^L item_packingcharges	string	optional	Item-level packing charge
^L itemallowaddon	string	optional	Whether item allows addons. 1=yes, 0=no
^L itemaddonbasedon	string	optional	Addon based on item or variations. 0=item, 1=variation
^L item_favorite	string	optional	Whether item is a favourite (boolean string)
^L ignore_taxes	string	optional	0=include in tax calculation, 1=ignore
^L ignore_discounts	string	optional	0=include in discount calculation, 1=ignore
^L in_stock	string	optional	Stock status
^L cuisine	array<string>	optional	Cuisine tags (can be multiple)
^L variation_groupname	string	optional	
^L variation	array<ItemVariation>	optional	
^L id	string	optional	Variation item id

KEY	TYPE	REQ	DESCRIPTION
^L variationid	string	optional	Variation master id
^L name	string	optional	Variation name
^L groupname	string	optional	Variation group (Size, Quantity, Volume, etc.)
^L price	string	optional	Variation price
^L markup_price	string	optional	Strike-through display price
^L active	string	optional	Active status (boolean string)
^L item_packingcharges	string	optional	Item-level packing charges for this variation
^L variationrank	string	optional	Rank for ordering
^L addon	array<AddonGroupRef>	optional	
^L addon_group_id	string	optional	Addon group id
^L addon_item_selection_min	string	optional	Minimum addon items to select
^L addon_item_selection_max	string	optional	Maximum addon items to select
^L variationallowaddon	integer	optional	Whether variation allows addons
^L addon	array<AddonGroupRef>	optional	
^L addon_group_id	string	optional	Addon group id
^L addon_item_selection_min	string	optional	Minimum addon items to select
^L addon_item_selection_max	string	optional	Maximum addon items to select
^L is_combo	string	optional	1 if item is a combo item
^L combo_items	array<ComboItem>	optional	Details of items in a combo. Present only if is_combo=1
^L item_id	string	optional	Item id included in this combo
^L is_variation	string	optional	1 if item is a variation
^L variation_item_id	string	optional	Exact variation id from the item
^L name	string	optional	Item or variation name
^L quantity	string	optional	Quantity included in this combo
^L is_recommend	string	optional	1=Restaurant recommended item
^L itemname	string	optional	Item name
^L item_attributeid	string	optional	Item attribute. 1=Veg, 2=Non-Veg, 5=Other, 24=Egg
^L itemdescription	string	optional	Item description

KEY	TYPE	REQ	DESCRIPTION
^L minimumpreparationtime	string	optional	Minimum preparation time (optional)
^L price	string	optional	Item price
^L markup_price	string	optional	Strike-through display price (optional)
^L active	string	optional	Item status (boolean string)
^L item_image_url	string	optional	Item image URL. Expires 24 hours after menu push.
^L item_tax	string	optional	Comma-separated tax master ids applicable to this item
^L tax_inclusive	boolean	optional	true if item price is inclusive of taxes. Default false
^L gst_type	enum	optional	GST liability. services=aggregator collects and pays GST to Gov; goods=aggregator collects and settles to restaurant
^L nutrition	Nutrition	optional	
^L foodAmount	NutritionAmount	optional	Amount of food. Provide in g, kg, ml or l
^L amount	number	optional	
^L unit	string	optional	
^L calories	NutritionAmount	optional	Amount of calories. Unit is kcal
^L amount	number	optional	
^L unit	string	optional	
^L protien	NutritionAmount	optional	Amount of protein. Unit is g
^L amount	number	optional	
^L unit	string	optional	
^L minerals	array<NutritionNamedAmount>	optional	Amount of minerals. Units can be g or mg
^L name	string	optional	
^L amount	number	optional	
^L unit	string	optional	
^L sodium	NutritionAmount	optional	Amount of sodium in mg
^L amount	number	optional	
^L unit	string	optional	
^L carbohydrate	NutritionAmount	optional	Amount of carbohydrate. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	

KEY	TYPE	REQ	DESCRIPTION
^L totalSugar	NutritionAmount	optional	Total sugar. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L addedSugar	NutritionAmount	optional	Added sugar. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L totalFat	NutritionAmount	optional	Total fat. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L saturatedFat	NutritionAmount	optional	Saturated fat. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L transFat	NutritionAmount	optional	Trans fat. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L cholesterol	NutritionAmount	optional	Cholesterol. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L vitamins	array<NutritionNamedAmount>	optional	Vitamins. Units can be g or mg
^L name	string	optional	
^L amount	number	optional	
^L unit	string	optional	
^L fiber	NutritionAmount	optional	Fiber. Units can be g or mg
^L amount	number	optional	
^L unit	string	optional	
^L additionalInfo	object	optional	Additional declaration from the restaurant
^L info	string	optional	
^L remark	string	optional	
^L servingInfo	enum	optional	Serving size information
^L additiveMap	object	optional	Additives. Supported keys: Polyols, Polydextrose,

KEY	TYPE	REQ	DESCRIPTION
			Caffeine, ArtificialSweetener, MSG. Units: g or mg
^L allergens	array<object>	optional	Allergens present in the food
^L allergen	string	optional	
^L allergenDesc	string	optional	
variations	array<object>	optional	Deprecated. Variation data is now embedded in each item object.
^L variationid	string	optional	
^L name	string	optional	
^L groupname	string	optional	
^L status	string	optional	
addongroups	array<AddonGroup>	optional	
^L addongroupid	string	optional	
^L addongroup_name	string	optional	
^L addongroup_rank	string	optional	
^L active	string	optional	
^L addongroupitems	array<AddonItem>	optional	
^L addonitemid	string	optional	
^L addonitem_name	string	optional	
^L addonitem_price	string	optional	
^L active	string	optional	
^L attributes	string	optional	Addon item attribute (veg, non-veg, egg)
^L addonitem_rank	string	optional	
attributes	array<Attribute>	optional	
^L attributeid	string	optional	
^L attribute	string	optional	Attribute name (veg, non-veg, egg)
^L active	string	optional	
discounts	array<Discount>	optional	
^L discountid	string	optional	
^L discountname	string	optional	
^L discounttype	string	optional	Discount type. 1=Percentage, 2=Fixed, 3=BOGO/BXGY, 7=Freebie
^L discount	string	optional	Discount value. For BOGO/ BXGY default is 100 (percentage)

KEY	TYPE	REQ	DESCRIPTION
L bogobuyqty	string	optional	BOGO/BXGY BUY quantity
L bogogetqty	string	optional	BOGO/BXGY GET quantity
L bogotype	integer	optional	BOGO type. Default 1=Percentage
L bogoapplicableonpurchase	string	optional	BOGO BUY applicable on: All, Items
L bogoapplicableonpurchaseitemid	string	optional	
L bogoapplicableon	string	optional	BOGO GET applicable on: All, Items
L bogoapplicableonitemid	string	optional	
L bogoitemamountlimit	integer	optional	
L discountordertype	string	optional	
L discountapplicableon	string	optional	Applicable on: All, Categories, Items
L discountdays	string	optional	Days: Sun,Mon,Tue,Wed,Thu,Fri,Sat or All
L discountontotal	string	optional	Apply on. 1=Total, 0=Core
L discountstarts	string	optional	
L discountends	string	optional	
L discounttimefrom	string	optional	
L discounttimeto	string	optional	
L discountminamount	string	optional	
L discountmaxamount	string	optional	
L discounthascoupon	string	optional	
L discountcategoryitemid	string	optional	
L active	string	optional	
L discountmaxlimit	string	optional	
L rank	string	optional	
L freebie_item_count	string	optional	Number of items for discounttype=7 (Freebie)
L freebie_item_ids	string	optional	Comma-separated item ids for freebie discount
taxes	array<Tax>	optional	
L taxid	string	optional	Tax id
L taxname	string	optional	Tax name
L tax	string	optional	Tax amount
L taxtype	string	optional	

KEY	TYPE	REQ	DESCRIPTION
			Tax type. 1=Percentage, 2=Fixed
^L tax_ordertype	string	optional	Order types for this tax. 1=Delivery, 2=Pick Up, 3=Dine In
^L active	string	optional	
^L tax_coreortotal	string	optional	Tax applied on. 1=Total, 2=Core
^L tax_taxtype	string	optional	Tax type. 1=forward tax, 2=backward tax
^L rank	string	optional	
^L consider_in_core_amount	string	optional	
^L description	string	optional	
serverdatetime	string	optional	
db_version	string	optional	
application_version	string	optional	
http_code	integer	optional	

REQUEST

See keys table for request structure.

RESPONSE & SCENARIOS

200 Menu items successfully received

```
{
  "success": "1",
  "message": "Menu items are successfully listed."
}
```

400 Menu sync failed (e.g. invalid restaurant ID)

```
{
  "success": "0",
  "message": "Menu sync failed"
}
```

POST /fetchmenu

Fetch Menu

In this method the integrator fetches the menu from the Petpooja endpoint on demand. Every time the integrator calls this endpoint, the current menu state is returned.

Dev URL: https://qle1yy2ydc.execute-api.ap-southeast-1.amazonaws.com/V1/mapped_restaurant_menus

KEYS

KEY	TYPE	REQ	DESCRIPTION
app-key	string	required	Application key for authentication
app-secret	string	required	Application secret for authentication
access-token	string	required	Access token for authentication
restID	string	required	Unique restaurant mapping id

REQUEST

```
{
  "restID": "xxxxxx"
}
```

RESPONSE & SCENARIOS

200 Menu data fetched successfully

No example payload.

400 Menu not available for this outlet

```
{
  "success": "0",
  "message": "Menu is not available for this outlet."
}
```

POST /item_stock

Update Item/Addon In Stock

This API endpoint must be provided by the integrator. Petpooja calls this endpoint for toggling the item stock status (in-stock) in the menu on the integrator platform for items already synced via menu sync APIs.

KEYS

KEY	TYPE	REQ	DESCRIPTION
restID	string	required	Mapped restaurant id for which item stock is toggled
type	enum	required	Type of stock update request
inStock	boolean	required	true=in-stock, false=out-of-stock
itemID	array<string>	required	List of Item or AddonItem IDs to toggle

REQUEST

```
{
  "restID": "xxxx",
  "type": "item",
  "inStock": true,
  "itemID": [
    "7778660",
    "7778659"
  ]
}
```

RESPONSE & SCENARIOS

200 Stock status updated successfully

```
{
  "code": 200,
  "status": "success",
  "message": "Stock status updated successfully"
}
```

400 Stock status update failed

```
{
  "code": 400,
  "status": "failed",
  "message": "Stock status not updated successfully"
}
```

POST /item_stock_off

Update Item/Addon Out of Stock

Endpoint to mark items or addons as out-of-stock. Note: It is recommended to use the same endpoint as item_stock and differentiate using the inStock field.

KEYS

KEY	TYPE	REQ	DESCRIPTION
restID	string	required	Mapped restaurant id
type	enum	required	
inStock	boolean	required	Should be false for out-of-stock
itemID	array<string>	required	List of Item or AddonItem IDs
autoTurnOnTime	string	required	When to auto turn on. Value: custom
customTurnOnTime	string	optional	Datetime to turn item back on (local restaurant timezone). Required if autoTurnOnTime=custom. Format: yyyy-MM-dd HH:mm

REQUEST

```
{
  "restID": "xxxx",
  "type": "item",
  "inStock": false,
  "itemID": [
    "7532306",
    "7865402"
  ],
  "autoTurnOnTime": "custom",
  "customTurnOnTime": "2020-02-24 18:00"
}
```

RESPONSE & SCENARIOS

200 Stock status updated successfully

```
{
  "code": 200,
  "status": "success",
  "message": "Stock status updated successfully"
}
```

400 Stock status update failed

```
{
  "code": 400,
  "status": "failed",
  "message": "Stock status not updated successfully"
}
```

Orders

APIs for order management

POST /saveorder

Save Order

Once a new order is placed by the end user, push the order to the Petpooja PoS application. On arrival, the order will be in Pending State until the restaurant partner responds (Accept/Reject).

Dev URL: https://47pfzh5sf2.execute-api.ap-southeast-1.amazonaws.com/V1/save_order

KEYS

KEY	TYPE	REQ	DESCRIPTION
app_key	string	required	Unique application key [32 characters]
app_secret	string	required	Unique application secret [40 characters]
access_token	string	required	Unique access token [40 characters]
orderinfo	object	required	
^L OrderInfo	object	optional	
^L Restaurant	object	optional	
^L details	object	optional	
^L res_name	string	optional	Name of third party restaurant
^L address	string	optional	Address of third party restaurant
^L contact_information	string	optional	
^L restID	string	optional	Unique Petpooja RestaurantID/ MappingID
^L Customer	object	optional	
^L details	object	optional	
^L email	string	optional	
^L name	string	optional	
^L address	string	optional	
^L phone	string	optional	10 digit mobile number
^L latitude	string	optional	
^L longitude	string	optional	
^L Order	object	optional	
^L details	OrderDetails	optional	
^L orderID	string	required	Unique third-party order id
^L preorder_date	string	required	Order creation date. Format: yyyy-mm-dd
^L preorder_time	string	required	Order creation time. Format: HH:mm:ss
^L service_charge	string	required	Service charge at order level

KEY	TYPE	REQ	DESCRIPTION
^L sc_tax_amount	string	required	Tax calculated on service charge
^L delivery_charges	string	optional	
^L dc_tax_percentage	string	required	Tax percentage on delivery charges
^L dc_tax_amount	string	required	Tax amount on delivery charges
^L dc_gst_details	array<GstDetail>	optional	Delivery charge GST breakdown. Required for Ecomm.
^L packing_charges	string	optional	
^L pc_tax_amount	string	required	Tax amount on packing charges
^L pc_tax_percentage	string	required	Tax percentage on packing charges
^L pc_gst_details	array<GstDetail>	optional	Packing charge GST breakdown. Required for Ecomm.
^L order_type	string	required	H=Home Delivery, P=Parcel, D=Dine In
^L ondc_bap	string	optional	Buyer app name if order is from ONDC (optional)
^L advanced_order	string	optional	Y or N
^L urgent_order	boolean	optional	Whether order is urgent
^L urgent_time	integer	optional	Urgent order time in minutes (if urgent_order=true)
^L payment_type	string	required	COD, CARD, CREDIT, ONLINE, OTHER
^L table_no	string	optional	Table number for Dine In orders
^L no_of_persons	string	optional	Number of persons for Dine In
^L discount_total	string	optional	
^L tax_total	string	optional	
^L discount_type	string	optional	P=Percentage, F=Fixed
^L total	string	optional	Order total including GST
^L description	string	optional	Special instructions
^L created_on	string	required	Order creation datetime. Format: yyyy-mm-dd H:i:s
^L enable_delivery	integer	optional	0=Third-party rider, 1=Self delivery
^L min_prep_time	integer	optional	Kitchen preparation time in minutes (optional)
^L callback_url	string	optional	URL for Petpooja to send order status updates
^L collect_cash	string	optional	Cash to collect (only for COD + self-delivery). Optional.
^L otp	string	optional	Pickup OTP for order verification (optional)

KEY	TYPE	REQ	DESCRIPTION
L OrderItem	object	optional	
L details	array<OrderItem>	optional	
L id	string	required	Unique PetPooja item id or variation item id
L name	string	required	Name of item
L tax_inclusive	boolean	optional	true if item amount is inclusive of tax
L gst_liability	string	optional	GST liability. vendor or restaurant. Required for Ecomm.
L item_tax	array<OrderItemTax>	required	Tax calculated at item level after discount
L item_discount	string	required	Discount amount at item level
L price	string	required	Unit price including addons/ variation price
L final_price	string	required	Item price after discount
L quantity	string	required	
L description	string	optional	Special instruction for item
L variation_name	string	optional	Variation name (required if item has variations)
L variation_id	string	optional	Variation ID (required if item has variations)
L AddonItem	object	optional	
L Tax	object	optional	
L details	array<OrderTax>	optional	
L id	string	required	Unique PetPooja tax id
L title	string	required	Tax title
L type	string	optional	P=Percentage, F=Fixed. Default P
L price	string	required	Tax percentage rate
L tax	string	optional	Total tax amount
L restaurant_liable_amt	string	optional	Tax amount restaurant is liable to pay. Required for Ecomm.
L Discount	object	optional	
L details	array<OrderDiscount>	optional	
L id	string	optional	Unique PetPooja discount id
L title	string	required	Discount title
L type	string	optional	P=Percentage, F=Fixed
L price	string	required	Discount amount
udid	string	optional	Unique device number for mobile orders

KEY	TYPE	REQ	DESCRIPTION
device_type	string	required	Type of device. Default: Web (case sensitive)

REQUEST

See keys table for request structure.

RESPONSE & SCENARIOS

200 Order saved successfully

```
{
  "success": "1",
  "message": "Your order is saved.",
  "restID": "xxxxxx",
  "clientOrderID": "A-1",
  "orderId": "26"
}
```

400 Validation error in order details

Order ID not provided

```
{
  "success": "0",
  "message": "There were some error in order details.",
  "errorCode": "S0_105",
  "validation_errors": {
    "orderId": [
      "Please provide order id."
    ]
  }
}
```

Item name not provided

```
{
  "success": "0",
  "message": "There were some error in order item details.",
  "errorCode": "S0_106",
  "validation_errors": {
    "name": [
      "Please enter item name."
    ]
  }
}
```

Preorder date invalid

```
{
  "success": "0",
  "message": "There were some error in order details.",
  "errorCode": "S0_105",
  "validation_errors": {
    "preorder_date": [
      "Preorder date is greater than current date.[Format:Y-m-d]"
    ]
  }
}
```

POST /callback

Order Callback

Online order integration partner must implement this endpoint to allow the PoS partner to notify about order status updates after a successful order relay. The integration partner passes this endpoint URL in every save order request via the `callback_url` field.

KEYS

KEY	TYPE	REQ	DESCRIPTION
restID	string	optional	Unique Petpooja Restaurant ID
orderID	string	optional	Unique client order id
status	string	optional	Order status. -1=Cancelled, 1/2/3=Accepted, 4=Dispatch, 5=Food Ready, 10=Delivered
cancel_reason	string	optional	Reason for cancellation
minimum_prep_time	integer	optional	Kitchen preparation time in minutes
minimum_delivery_time	string	optional	Delivery time. Can be ignored for platforms with logistics.
rider_name	string	optional	Rider name (for self-delivery, status 4)
rider_phone_number	string	optional	Rider phone (for self-delivery, status 4)
is_modified	string	optional	Whether order was modified at restaurant

REQUEST

```
{
  "restID": "xxxxxx",
  "orderID": "A-1",
  "status": "1",
  "cancel_reason": "",
  "minimum_prep_time": 20,
  "minimum_delivery_time": "",
  "rider_name": "",
  "rider_phone_number": "",
  "is_modified": "No"
}
```

RESPONSE & SCENARIOS

200 Callback received successfully

No example payload.

POST /orderstatus

Update Order Status

Integration partner can send updated order status to the PoS partner by calling this endpoint. Currently supports sending cancel order (-1) status only.

Dev URL: https://qle1yy2ydc.execute-api.ap-southeast-1.amazonaws.com/V1/update_order_status

KEYS

KEY	TYPE	REQ	DESCRIPTION
app_key	string	required	Unique application key [32 characters]
app_secret	string	required	Unique application secret [40 characters]
access_token	string	required	Unique access token [40 characters]
restID	string	required	Unique Petpooja Restaurant ID
orderID	string	optional	Unique PetPooja order id (deprecated, pass blank)
clientorderID	string	required	Unique integrator partner order id
cancelReason	string	required	Reason for cancelling order
status	string	required	-1=Cancelled

REQUEST

```
{
  "app_key": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx",
  "app_secret": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx",
  "access_token": "xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx",
  "restID": "xxxxxx",
  "orderID": "26",
  "clientorderID": "A-1",
  "cancelReason": "Please cancel my order.",
  "status": "-1"
}
```

RESPONSE & SCENARIOS

200 Order status updated successfully

```
{
  "success": "1",
  "message": "Order status updated successfully.",
  "restID": "xxxxxx",
  "orderID": "26",
  "status": "-1"
}
```

400

Error updating order status (e.g. order already modified by restaurant)

```
{
  "success": "0",
  "message": "There were some error in update order status.",
  "errorCode": "UOS_105",
  "validation_errors": ""
}
```

Delivery

APIs for delivery and rider management

POST /rider_info_webhook

Rider Info Webhook

Webhook to update the rider information for Petpooja POS in order to update order delivery status without continuously polling. This endpoint must be provided by the third party.

Dev URL: https://qle1yy2ydc.execute-api.ap-southeast-1.amazonaws.com/V1/rider_status_update

KEYS

KEY	TYPE	REQ	DESCRIPTION
app_key	string	required	
app_secret	string	required	
access_token	string	required	
order_id	integer	required	Unique third-party order id / Client Order ID
outlet_id	string	required	
status	enum	required	Rider status
rider_data	RiderData	required	
└ rider_name	string	required	Delivery executive name
└ rider_phone_number	string	required	Delivery executive phone number
external_order_id	string	optional	PetPooja Order Id (pass blank)

REQUEST

```
{
  "app_key": "xxxxxxxxxxxxxxxxxxxxxx",
  "app_secret": "xxxxxxxxxxxxxxxxxxxxxx",
  "access_token": "xxxxxxxxxxxxxxxxxxxxxx",
  "order_id": 101010527,
  "outlet_id": "xxxxx",
  "status": "rider-assigned",
  "rider_data": {
    "rider_name": "RIDER",
    "rider_phone_number": "9999999999"
  },
  "external_order_id": ""
}
```

RESPONSE & SCENARIOS

200 Rider status saved successfully

```
{
  "code": "200",
  "message": "Rider status saved successfully.",
  "success": "success"
}
```

400 Order not found or invalid rider status

```
{
  "code": "400",
  "message": "Order Id not found./Invalid Rider status.",
  "success": "failed"
}
```

Store

APIs for store status management

POST /get_store_status

Get Store Status

This API endpoint must be provided by the integration partner. The merchant at the restaurant can check the current status of the store at the integrator platform end.

KEYS

KEY	TYPE	REQ	DESCRIPTION
restID	string	required	Unique mapped Id for third party restaurant

REQUEST

```
{
  "restID": "xxxx"
}
```

RESPONSE & SCENARIOS

200 Store status fetched successfully

```
{
  "http_code": 200,
  "status": "success",
  "store_status": "1",
  "message": "Store Delivery Status fetched successfully"
}
```


POST /update_store_status

Update Store Status

This API endpoint must be provided by the integration partner. Used by the merchant to tell the integration partner to turn on/off the store for online orders within their set working hours.

KEYS

KEY	TYPE	REQ	DESCRIPTION
restID	string	required	Unique mapped Id for third party restaurant
store_status	integer	required	1=Open, 0=Closed
turn_on_time	string	required	Next opening time. Required when turning off the store.
reason	string	optional	Required when store_status=0

REQUEST

```
{
  "restID": "xxxx",
  "store_status": 0,
  "turn_on_time": "2023-02-17 00:00:00",
  "reason": ""
}
```

RESPONSE & SCENARIOS

200 Store status updated successfully

```
{
  "http_code": 200,
  "status": "success",
  "message": "Store Status updated successfully for store restID"
}
```