

GeeksforGeeks

A computer science portal for geeks



COURSES

HIRE WITH US

[Login](#)

Classifying data using Support Vector Machines(SVMs) in Python

Best Python libraries for Machine Learning

Neural Networks | A beginners guide

ML | Stochastic Gradient Descent (SGD)

DBMS | OLAP Operations

Generative Adversarial Network (GAN)

ML | Classification vs Regression

Game Playing in Artificial Intelligence

ML | Mini-Batch Gradient Descent with Python

Q-Learning in Python

Implement your own word2vec(skip-gram) model in Python

Python | Tokenize text using TextBlob

Deep Learning |



Introduction to
Long Short Term
Memory

ML | Using SVM to
perform
classification on a
non-linear dataset

ML | Locally
weighted Linear
Regression

ML | Monte Carlo
Tree Search
(MCTS)

Applying
Multinomial Naive
Bayes to NLP
Problems

Data Structure to
Design a special
social network

ML | Natural
Language
Processing using
Deep Learning

MATLAB | Display
histogram of a
grayscale Image

Audio processing
using Pydub and
Google
speechRecognition
API

LSB based Image
steganography
using MATLAB

Elasticsearch
Search Engine | An
introduction

Python | Speech
recognition on
large audio files

Draw Austria flag
using Matlab

Introduction to
Signals and

Systems:
Properties of
systems

Text extraction
from image using
LSB based
steganography

Draw Bangladesh
Flag Using Matlab

MATLAB | Convert
video into slow
motion

Image Resizing in
Matlab



Advertisement for GATECS 2020 Blended Course. The ad features a blue and yellow color scheme. At the top, it shows a price reduction from ₹27,000 to ₹20,999. The main text reads 'GATECS 2020 Blended Course'. Below this, it lists two key features: 'Learn from IISC/IIT's Alumni' and '2 LIVE sessions with 2 tests per week'. A prominent button at the bottom says 'TRY FREE VIDEOS'.



Advertisement for DSA Self-Paced Course. The ad has a dark purple background with circular elements. It mentions 'Starting from 1st July 2019' and 'DSA SELF-PACED COURSE'. A price tag shows ₹2,499 with a 'Register Now' button. The ad also includes a 'WEEK 10' indicator and a play button icon.

Naive Bayes Classifiers

This article discusses the theory behind the Naive Bayes classifiers and their implementation.

Naive Bayes classifiers are a collection of classification algorithms based on **Bayes' Theorem**. It is not a single algorithm but a family of algorithms where all of them share a common principle, i.e. every pair of features being classified is independent of each other.

To start with, let us consider a dataset.

Consider a fictional dataset that describes the weather conditions for playing a game of golf. Given the weather conditions, each tuple classifies the conditions as fit("Yes") or unfit("No") for playing golf.

Here is a tabular representation of our dataset.

	OUTLOOK	TEMPERATURE	HUMIDITY	WINDY	PLAY GOLF
0	Rainy	Hot	High	False	No
1	Rainy	Hot	High	True	No
2	Overcast	Hot	High	False	Yes
3	Sunny	Mild	High	False	Yes
4	Sunny	Cool	Normal	False	Yes
5	Sunny	Cool	Normal	True	No
6	Overcast	Cool	Normal	True	Yes
7	Rainy	Mild	High	False	No
8	Rainy	Cool	Normal	False	Yes
9	Sunny	Mild	Normal	False	Yes
10	Rainy	Mild	Normal	True	Yes
11	Overcast	Mild	High	True	Yes
12	Overcast	Hot	Normal	False	Yes
13	Sunny	Mild	High	True	No

The dataset is divided into two parts, namely, **feature matrix** and the **response vector**.

- Feature matrix contains all the vectors(rows) of dataset in which each vector consists of the value of **dependent features**. In above dataset, features are 'Outlook', 'Temperature', 'Humidity' and 'Windy'.
- Response vector contains the value of **class variable**(prediction or output) for each row of feature matrix. In above dataset, the class variable name is 'Play golf'.

Assumption:

The fundamental Naive Bayes assumption is that each feature makes an:

- independent
- equal

contribution to the outcome.

With relation to our dataset, this concept can be understood as:

- We assume that no pair of features are dependent. For example, the temperature being 'Hot' has nothing to do with the humidity or the outlook being 'Rainy' has no effect on the winds. Hence, the features are assumed to be **independent**.
- Secondly, each feature is given the same weight(or importance). For example, knowing only temperature and humidity alone can't predict the outcome accurately. None of the attributes is irrelevant and assumed to be contributing **equally** to the outcome.

Note: The assumptions made by Naive Bayes are not generally correct in real-world situations. In-fact, the independence assumption is never correct but often works well in practice.

Now, before moving to the formula for Naive Bayes, it is important to know about Bayes' theorem.

Bayes' Theorem

Bayes' Theorem finds the probability of an event occurring given the probability of another event that has already occurred. Bayes' theorem is stated mathematically as the following equation:

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$



where A and B are events and $P(B) \neq 0$.

- Basically, we are trying to find probability of event A, given the event B is true. Event B is also termed as **evidence**.
- $P(A)$ is the **priori** of A (the prior probability, i.e. Probability of event before evidence is seen). The evidence is an attribute value of an unknown instance(here, it is event B).
- $P(A|B)$ is a posteriori probability of B, i.e. probability of event after evidence is seen.

Now, with regards to our dataset, we can apply Bayes' theorem in following way:

$$P(y|X) = \frac{P(X|y)P(y)}{P(X)}$$

where, y is class variable and X is a dependent feature vector (of size n) where:

$$X = (x_1, x_2, x_3, \dots, x_n)$$

Just to clear, an example of a feature vector and corresponding class variable can be: (refer 1st row of dataset)

X = (Rainy, Hot, High, False)
y = No

So basically, $P(X|y)$ here means, the probability of "Not playing golf" given that the weather conditions are "Rainy outlook", "Temperature is hot", "high humidity" and "no wind".

Naive assumption

Now, its time to put a naive assumption to the Bayes' theorem, which is, **independence** among the features. So now, we split **evidence** into the independent parts.

Now, if any two events A and B are independent, then,



$$P(A, B) = P(A)P(B)$$

Hence, we reach to the result:

$$P(y|x_1, \dots, x_n) = \frac{P(x_1|y)P(x_2|y)\dots P(x_n|y)P(y)}{P(x_1)P(x_2)\dots P(x_n)}$$

which can be expressed as:

$$P(y|x_1, \dots, x_n) = \frac{P(y) \prod_{i=1}^n P(x_i|y)}{P(x_1)P(x_2)\dots P(x_n)}$$

Now, as the denominator remains constant for a given input, we can remove that term:

$$P(y|x_1, \dots, x_n) \propto P(y) \prod_{i=1}^n P(x_i|y)$$

Now, we need to create a classifier model. For this, we find the probability of given set of inputs for all possible values of the class variable y and pick up the output with maximum probability. This can be expressed mathematically as:

$$y = \operatorname{argmax}_y P(y) \prod_{i=1}^n P(x_i|y)$$

So, finally, we are left with the task of calculating $P(y)$ and $P(x_i|y)$.

Please note that $P(y)$ is also called **class probability** and $P(x_i|y)$ is called **conditional probability**.



GATECS 2020
Blended Course

> Learn from IISC/IIT's Alumni
> 2 LIVE sessions with 2 practice tests per week

The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i|y)$.

Let us try to apply the above formula manually on our weather dataset. For this, we need to do some precomputations on our dataset.

We need to find $P(x_i|y_j)$ for each x_i in X and y_j in y . All these calculations have been demonstrated in the tables below:

Outlook

	Yes	No	P(Yes)	P(no)
Sunny	2	3	2/9	3/5
Overcast	4	0	4/9	0/5
Rainy	3	2	3/9	2/5
Total	9	5	100%	100%

Temperature

	Yes	No	P(Yes)	P(no)
Hot	2	2	2/9	2/5
Mild	4	2	4/9	2/5
Cool	3	1	3/9	1/5
Total	9	5	100%	100%

Humidity

	Yes	No	P(Yes)	P(no)
High	3	4	3/9	4/5
Normal	6	1	6/9	1/5
Total	9	5	100%	100%

Wind

	Yes	No	P(Yes)	P(no)
False	6	2	6/9	2/5
True	3	3	3/9	3/5
Total	9	5	100%	100%

Play		P(Yes)/P(No)
Yes	9	9/14
No	5	5/14

Total	14	100%
-------	----	------

So, in the figure above, we have calculated $P(x_i | y_j)$ for each x_i in X and y_j in y manually in the tables 1-4. For example, probability of playing golf given that the temperature is cool, i.e $P(\text{temp.} = \text{cool} | \text{play golf} = \text{Yes}) = 3/9$.

Also, we need to find class probabilities ($P(y)$) which has been calculated in the table 5. For example, $P(\text{play golf} = \text{Yes}) = 9/14$.

So now, we are done with our pre-computations and the classifier is ready!

Let us test it on a new set of features (let us call it today):

```
today = (Sunny, Hot, Normal, False)
```

So, probability of playing golf is given by:

$$P(\text{Yes}|\text{today}) = \frac{P(\text{SunnyOutlook}|\text{Yes})P(\text{HotTemperature}|\text{Yes})P(\text{NormalHumidity}|\text{Yes})P(\text{NoWind}|\text{Yes})P(\text{Yes})}{P(\text{today})}$$

and probability to not play golf is given by:

$$P(\text{No}|\text{today}) = \frac{P(\text{SunnyOutlook}|\text{No})P(\text{HotTemperature}|\text{No})P(\text{NormalHumidity}|\text{No})P(\text{NoWind}|\text{No})P(\text{No})}{P(\text{today})}$$

Since, $P(\text{today})$ is common in both probabilities, we can ignore $P(\text{today})$ and find proportional probabilities as:

$$P(\text{Yes}|\text{today}) \propto \frac{2}{9} \cdot \frac{2}{9} \cdot \frac{6}{9} \cdot \frac{6}{9} \cdot \frac{9}{14} \approx 0.0141$$

and

$$P(\text{No}|\text{today}) \propto \frac{3}{5} \cdot \frac{2}{5} \cdot \frac{1}{5} \cdot \frac{2}{5} \cdot \frac{5}{14} \approx 0.0068$$

Now, since

$$P(\text{Yes}|\text{today}) + P(\text{No}|\text{today}) = 1$$

These numbers can be converted into a probability by making the sum equal to 1 (normalization):

$$P(\text{Yes}|\text{today}) = \frac{0.0141}{0.0141+0.0068} = 0.67$$

and

$$P(\text{No}|\text{today}) = \frac{0.0068}{0.0141+0.0068} = 0.33$$

Since

$$P(\text{Yes}|\text{today}) > P(\text{No}|\text{today})$$


So, prediction that golf would be played is 'Yes'.

The method that we discussed above is applicable for discrete data. In case of continuous data, we need to make some assumptions regarding the distribution of values of each feature. The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i | y)$.

Now, we discuss one of such classifiers here.

Gaussian Naive Bayes classifier

In Gaussian Naive Bayes, continuous values associated with each feature are assumed to be distributed according to a **Gaussian distribution**. A Gaussian distribution is also called **Normal distribution**. When plotted, it gives a bell shaped curve which is symmetric about the mean of the feature values as shown below:



The likelihood of the features is assumed to be Gaussian, hence, conditional probability is given by:

$$P(x_i|y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Now, we look at an implementation of Gaussian Naive Bayes classifier using scikit-learn.

```
# load the iris dataset
from sklearn.datasets import load_iris
iris = load_iris()

# store the feature matrix (X) and response vector (y)
X = iris.data
y = iris.target

# splitting X and y into training and testing sets
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.4, random_state=1)

# training the model on training set
from sklearn.naive_bayes import GaussianNB
gnb = GaussianNB()
gnb.fit(X_train, y_train)

# making predictions on the testing set
y_pred = gnb.predict(X_test)

# comparing actual response values (y_test) with predicted response values (y_pred)
from sklearn import metrics
print("Gaussian Naive Bayes model accuracy(in %):", metrics.accuracy_score(y_test, y_pred))
```

Output:

```
Gaussian Naive Bayes model accuracy(in %): 95.0
```

Other popular Naive Bayes classifiers are:

- **Multinomial Naive Bayes:** Feature vectors represent the frequencies with which certain events have been generated by a **multinomial distribution**. This is the event model typically used for document classification.
- **Bernoulli Naive Bayes:** In the multivariate Bernoulli event model, features are independent booleans (binary variables) describing inputs. Like the multinomial model, this model is popular for document classification tasks, where binary term occurrence(i.e. a word occurs in a document or not) features are used rather than term frequencies(i.e. frequency of a word in the document).

As we reach to the end of this article, here are some important points to ponder upon:

- In spite of their apparently over-simplified assumptions, naive Bayes classifiers have worked quite well in many real-world situations, famously document classification and spam filtering. They require a small amount of training data to estimate the necessary parameters.
- Naive Bayes learners and classifiers can be extremely fast compared to more sophisticated methods. The decou-


pling of the class conditional feature distributions means that each distribution can be independently estimated as a one dimensional distribution. This in turn helps to alleviate problems stemming from the curse of dimensionality.

References:

- https://en.wikipedia.org/wiki/Naive_Bayes_classifier
- http://gerardnico.com/wiki/data_mining/naive_bayes
- http://scikit-learn.org/stable/modules/naive_bayes.html

This blog is contributed by [Nikhil Kumar](#). If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

 **APPLIED COURSE**

GATECS 2020
Blended Course

[➤ Learn from IISC/IIT's Alumni](#)
[➤ 2 LIVE sessions with 2 practice tests per week](#)

Recommended Posts:

[Applying Multinomial Naive Bayes to NLP Problems](#)
[ML | Dummy classifiers using sklearn](#)
[Python | Blackman in numpy](#)
[Smart calculator in Python](#)
[Intesting Fact about Python Multi-line Comments](#)
[ML | Auto-Encoders](#)
[Explanation of Fundamental Functions involved in A3C algorithm](#)
[Data with Hadoop](#)
[Building an Auto-Encoder using Keras](#)
[Python | sympy.expand_pow_exp\(\) method](#)
[Pyhton | os.lseek\(\) method](#)
[Python | os.rename\(\) method](#)
[Crossover in Genetic Algorithm](#)
[Django Models | Set - 2](#)

Article Tags : [Advanced Computer Subject](#) [Machine Learning](#) [Python](#)

Practice Tags : [Machine Learning](#)



9

☐ To-do ☐ Done**2.5**

Based on 4 vote(s)

[Feedback/ Suggest Improvement](#)[Add Notes](#)[Improve Article](#)Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.[Load Comments](#)

GeeksforGeeks
A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

PRACTICE

Courses
Company-wise
Topic-wise
How to begin?

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved