


A computer science portal for geeks



COURSES

Login

HIRE WITH US

[Courses @
GeeksforGeeks](#)[Internships @
GeeksforGeeks](#)[Coding Practice](#)[How to write an
Interview
Experience?](#)[Must Do Coding
Questions
Company-wise](#)[Must Do Coding
Questions Topic-
wise](#)[Basic](#)[Easy](#)[Medium](#)[Hard](#)[Expert](#)[Step by Step
Preparation](#)[Company
Preparation](#)[Top Topics](#)[Company Specific
Practice](#)[Software Design
Patterns](#)[Placements
Preparation Course](#)

Python Numpy

Numpy is a general-purpose array-processing package. It provides a high-performance multidimensional array object, and tools for working with these arrays. It is the fundamental package for scientific computing with Python.

Besides its obvious scientific uses, Numpy can also be used as an efficient multi-dimensional container of generic data.

- Interview Corner
- Recent Interview Experiences
- GQ Home Page
- Quiz Corner
- LMNs
- What's New ?
- Leaderboard !!
- Topic-wise Practice
- Subjective Problems
- Difficulty Level - School
- Difficulty Level - Basic
- Difficulty Level - Easy
- Difficulty Level - Medium
- Difficulty Level - Hard
- Explore More...
- C
- C++
- Java
- Python
- SQL
- PHP
- JavaScript
- School Programming
- Operating Systems

DBMS

Computer
Networks

Engineering
Mathematics

Design Patterns

Common Interview
Puzzles

Web Technology

G-Facts

Computer Graphics

Image Processing

Project Ideas



**ENJOY THE
BIG BARGAIN
OF GEARBEST.**

UP TO 50% OFF
on Gearbest orders

**+
₹ 250 CASHBACK***
when you pay with PayPal
for \$ 20 or more

13th May - 30th June 2019

Shop Now

The banner features a wooden background with various electronic components like a camera lens, a small circuit board, and a USB cable.



Arrays in Numpy

Array in Numpy is a table of elements (usually numbers), all of the same type, indexed by a tuple of positive integers. In Numpy, number of dimensions of the array is called rank of the array. A tuple of integers giving the size of the array along each dimension is known as shape of the array. An array class in Numpy is called as **ndarray**. Elements in Numpy arrays are accessed by using square brackets and can be initialized by using nested Python Lists.



Creating a Numpy Array

Arrays in Numpy can be created by multiple ways, with various number of Ranks, defining the size of the Array. Arrays can also be created with the use of various data types such as lists, tuples, etc. The type of the resultant array is deduced from the type of the elements in the sequences.

Note: Type of array can be explicitly defined while creating the array.

```
# Python program for
# Creation of Arrays
import numpy as np

# Creating a rank 1 Array
arr = np.array([1, 2, 3])
print("Array with Rank 1: \n",arr)

# Creating a rank 2 Array
arr = np.array([[1, 2, 3],
                [4, 5, 6]])
print("Array with Rank 2: \n", arr)

# Creating an array from tuple
arr = np.array((1, 3, 2))
print("\nArray created using "
      "passed tuple:\n", arr)
```

[Run on IDE](#)

Output:

```
Array with Rank 1:
[1 2 3]
Array with Rank 2:
[[1 2 3]
 [4 5 6]]

Array created using passed tuple:
[1 3 2]
```

Accessing the array Index

In a numpy array, indexing or accessing the array index can be done in multiple ways. To print a range of an array, slicing is done. Slicing of an array is defining a range in a new array which is used to print a range of elements from the original array. Since, sliced array holds a range of elements of the original array, modifying content with the help of sliced array modifies the original array content.

```
# Python program to demonstrate
# indexing in numpy array
import numpy as np

# Initial Array
arr = np.array([[ -1, 2, 0, 4],
                [ 4, -0.5, 6, 0],
                [ 2.6, 0, 7, 8],
                [ 3, -7, 4, 2.0]])
print("Initial Array: ")
print(arr)

# Printing a range of Array
# with the use of slicing method
sliced_arr = arr[:2, ::2]
print ("Array with first 2 rows and"
       " alternate columns(0 and 2):\n", sliced_arr)

# Printing elements at
# specific Indices
Index_arr = arr[[1, 1, 0, 3],
                 [3, 2, 1, 0]]
print ("\nElements at indices (1, 3), "
       "(1, 2), (0, 1), (3, 0):\n", Index_arr)
```

[Run on IDE](#)

Output:

```
Initial Array:
[[-1.  2.  0.  4.]
 [ 4. -0.5 6.  0.]
 [ 2.6  0.  7.  8.]
 [ 3. -7.  4.  2.]]
Array with first 2 rows and alternate columns(0 and 2):
[[-1.  0.]
 [ 4.  6.]]

Elements at indices (1, 3), (1, 2), (0, 1), (3, 0):
[ 0. 54.  2.  3.]
```

Basic Array Operations

In numpy, arrays allow a wide range of operations which can be performed on a particular array or a combination of Arrays. These operation include some basic Mathematical operation as well as Unary and Binary operations.

```
# Python program to demonstrate
# basic operations on single array
import numpy as np

# Defining Array 1
a = np.array([[1, 2],
              [3, 4]])

# Defining Array 2
b = np.array([[4, 3],
              [2, 1]])

# Adding 1 to every element
print ("Adding 1 to every element:", a + 1)

# Subtracting 2 from each element
print ("\nSubtracting 2 from each element:", b - 2)
```

```
# sum of array elements
# Performing Unary operations
print ("\nSum of all array "
      "elements: ", a.sum())

# Adding two arrays
# Performing Binary operations
print ("\nArray sum:\n", a + b)
```

[Run on IDE](#)**Output:**

Adding 1 to every element:

```
[[2 3]
 [4 5]]
```

Subtracting 2 from each element:

```
[[ 2  1]
 [ 0 -1]]
```

Sum of all array elements: 10

Array sum:

```
[[5 5]
 [5 5]]
```

More on Numpy Arrays

- [Basic Array Operations in Numpy](#)
- [Advanced Array Operations in Numpy](#)
- [Basic Slicing and Advanced Indexing in NumPy Python](#)

Data Types in Numpy

Every Numpy array is a table of elements (usually numbers), all of the same type, indexed by a tuple of positive integers. Every ndarray has an associated data type (dtype) object. This data type object (dtype) provides information about the layout of the array. The values of an ndarray are stored in a buffer which can be thought of as a contiguous block of memory bytes which can be interpreted by the dtype object. Numpy provides a large set of numeric datatypes that can be used to construct arrays. At the time of Array creation, Numpy tries to guess a datatype, but functions that construct arrays usually also include an optional argument to explicitly specify the datatype.

Constructing a Datatype Object

In Numpy, datatypes of Arrays need not to be defined unless a specific datatype is required. Numpy tries to guess the datatype for Arrays which are not predefined in the constructor function.

```
# Python Program to create
# a data type object
import numpy as np

# Integer datatype
# guessed by Numpy
x = np.array([1, 2])
print("Integer Datatype: ")
print(x.dtype)

# Float datatype
# guessed by Numpy
x = np.array([1.0, 2.0])
print("\nFloat Datatype: ")
print(x.dtype)

# Forced Datatype
```

```
x = np.array([1, 2], dtype = np.int64)
print("\nForcing a Datatype: ")
print(x.dtype)
```

[Run on IDE](#)

Output:



Integer Datatype:
int64

Float Datatype:
float64

Forcing a Datatype:
int64

Math Operations on DataType array

In Numpy arrays, basic mathematical operations are performed element-wise on the array. These operations are applied both as operator overloads and as functions. Many useful functions are provided in Numpy for performing computations on Arrays such as **sum**: for addition of Array elements, **T**: for Transpose of elements, etc.

```
# Python Program to create
# a data type object
import numpy as np

# First Array
arr1 = np.array([[4, 7], [2, 6]],
                dtype = np.float64)

# Second Array
arr2 = np.array([[3, 6], [2, 8]],
                dtype = np.float64)

# Addition of two Arrays
Sum = np.add(arr1, arr2)
print("Addition of Two Arrays: ")
print(Sum)

# Addition of all Array elements
# using predefined sum method
Sum1 = np.sum(arr1)
print("\nAddition of Array elements: ")
print(Sum1)

# Square root of Array
Sqrt = np.sqrt(arr1)
print("\nSquare root of Array1 elements: ")
print(Sqrt)

# Transpose of Array
# using In-built function 'T'
Trans_arr = arr1.T
print("\nTranspose of Array: ")
print(Trans_arr)
```

[Run on IDE](#)

Output:

Addition of Two Arrays:

```
[[ 7. 13.]
 [ 4. 14.]]
```

Addition of Array elements:
19.0

Square root of Array1 elements:
[[2. 2.64575131]
 [1.41421356 2.44948974]]

Transpose of Array:
[[4. 2.]
 [7. 6.]]

More on Numpy Data Type

- [Data type Object \(dtype\) in NumPy](#)

Methods in Numpy

all()	arange()	dot()
any()	place()	vdot()
take()	extract()	trunc()
put()	compress()	divide()
apply_along_axis()	rot90()	floor_divide()
apply_over_axes()	tile()	true_divide()
argmin()	reshape()	random.rand()
argmax()	ravel()	random.randn()
nanargmin()	isinf()	ndarray.flat()
nanargmax()	isrealobj()	expm1()
amax()	isscalar()	bincount()
amin()	isneginf()	rint()
insert()	isposinf()	equal()
delete()	iscomplex()	not_equal()
append()	isnan()	less()
around()	iscomplexobj()	less_equal()
flip()	isreal()	greater()
fliplr()	isfinite()	greater_equal()
flipud()	isfortran()	prod()

<code>triu()</code>	<code>exp()</code>	<code>square()</code>
<code>tril()</code>	<code>exp2()</code>	<code>cbrt()</code>
<code>tri()</code>	<code>fix()</code>	<code>logical_or()</code>
<code>empty()</code>	<code>hypot()</code>	<code>logical_and()</code>
<code>empty_like()</code>	<code>absolute()</code>	<code>logical_not()</code>
<code>zeros()</code>	<code>ceil()</code>	<code>logical_xor()</code>
<code>zeros_like()</code>	<code>floor()</code>	<code>array_equal()</code>
<code>ones()</code>	<code>degrees()</code>	<code>array_equiv()</code>
<code>ones_like()</code>	<code>radians()</code>	<code>sin()</code>
<code>full_like()</code>	<code>npv()</code>	<code>cos()</code>
<code>diag()</code>	<code>fv()</code>	<code>tan()</code>
<code>diagflat()</code>	<code>pv()</code>	<code>sinh()</code>
<code>diag_indices()</code>	<code>power()</code>	<code>cosh()</code>
<code>asmatrix()</code>	<code>float_power()</code>	<code>tanh()</code>
<code>bmat()</code>	<code>log()</code>	<code>arcsin()</code>
<code>eye()</code>	<code>log1()</code>	<code>arccos()</code>
<code>roll()</code>	<code>log2()</code>	<code>arctan()</code>
<code>identity()</code>	<code>log10()</code>	<code>arctan2()</code>

Recent articles on Numpy

Programs on Numpy

- [Python | Check whether a list is empty or not](#)
- [Python | Get unique values from a list](#)
- [Python | Multiply all numbers in the list \(3 different ways\)](#)
- [Transpose a matrix in Single line in Python](#)
- [Multiplication of two Matrices in Single line using Numpy in Python](#)
- [Python program to print checkerboard pattern of nxn using numpy](#)
- [Graph Plotting in Python | Set 1, Set 2, Set 3](#)

Useful Numpy Articles

- [Matrix manipulation in Python](#)
- [Basic Slicing and Advanced Indexing in NumPy Python](#)
- [Differences between Flatten\(\) and Ravel\(\)](#)
- [rand vs normal in Numpy.random in Python](#)

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

1 Comment **GeeksforGeeks**

 Login ▾

 Recommend  Tweet  Share

Sort by Newest ▾



Join the discussion...

LOG IN WITH



OR SIGN UP WITH DISQUS 





Ram • 16 days ago

There's is a typo:

Elements at indices (1, 3), (1, 2), (0, 1), (3, 0): ***should be***
[0. 6. 2. 3.]

^ | ▾ • Reply • Share ▸

 Subscribe  Add Disqus to your siteAdd DisqusAdd

 [Disqus! Privacy Policy](#)[Privacy Policy](#)[Privacy Policy](#)

GeeksforGeeks
A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved