

A Term Report

Jinan (Dorothy) Hu, Peter Mitrano, Kacper Puczydowski, Nicolette Vere

October 3, 2017

1 Introduction

Knowing the position and orientation of a mobile robot is critical to many tasks. For robots designed for high-speed gameplay, knowing the position and orientation allows the robot to perform complex autonomous behaviors such as shooting and retrieving game objects. In this report, we describe a system for determining the pose (x, y, θ) of a mobile robot in a cluttered environment. The environment we are interested in is the FIRST Robotics Competition (FRC). FRC is a challenging environment because the robots make with rapid and aggressive maneuvers by human drivers for part of the time, and at other times are under complete autonomy. A localization system for FRC must handle up to six robots, occlusion from the playing field elements, and other unpredictable conditions. Our research suggests that there are at least four appropriate methods for localization: cameras and tags, radio and ultrasonic beacons, optical flow, and dead reckoning with encoders and an IMU. All of these methods have seen success in robot localization.

This report begins with a review of existing literature on indoor localization for mobile robots in the Related Work section. The strengths and weaknesses of these existing methods are described in the Evaluation of Localization Techniques section. The Experimental Results section contains information on experiments we conducted, and the Conclusion section details our plan moving forward.

2 Related Work

**Here we will go over all the papers we read and sources we talked to. Explain what if any of our approach is novel and what is built on existing approaches.

Beacon systems have been used many times with success in the literature. Generally, these systems use ultrasound and or radio as a medium and either signal strength, phase shift, or time to measure distance to the beacons. Among radio systems, the system in [3] identified the location of people moving around buildings using signal strength in the 2.4GHz band received at three or more beacons, and they report accuracy of a few meters with an update rate of at most four times per second. The systems described in [4] use passive RFID tags on the ceiling and an RFID transmitter on the robot, and report an accuracy of 4cm within a 5m². Another RFID system [8] also uses signal strength to RFID, and reports accuracies for various configurations ranging from 1cm to 3m. These RFID systems require readers that cost over \$500. There are also countless localization systems that use standard wireless networks. A comprehensive survey of these systems can be found in [7]. Systems that use signal strength in standard wireless LAN networks have achieved up to 10cm accuracy



Figure 1: Example figure.

and hundreds of updates per second. Another radio beacon solution is to substitute single-frequency radio with Ultra-wideband radio. These systems can achieve centimeter level accuracy, but they use obscure or custom made transmitters and receivers that cost in the hundreds of dollars [1] [2].

Many beacon systems use the speed difference between sound and electromagnetic waves to measure system. Systems like [9] [10] [6] send radio pulses followed by ultrasonic pulses. Nodes in the network use the difference in arrival time of these two signals to measure distance. Alternately, some systems use infrared pulses in place of radio [5] [11]. These systems are inexpensive, and report accuracy of between 2 and 14cm.

3 Evaluation of Localization Techniques

4 Experimental Results

****How did we test ArUco tags, IMUs, Optimal Flow. What results? Be specific. Include any relevant charts or equations.**

We demonstrated radio communication between two microcontrollers and tested the effect of distance and occlusion. The results can be seen in Figure 1.

5 Conclusion

Based on the extensive literature review and the few preliminary experiments we've conducted, we eliminated our initial list of possible techniques down to the following five:

1. Radio and ultrasonic beacons
2. IMU
3. Drive wheel encoders
4. Optical flow

5. Camera with matrix tags

We have found examples of each of these techniques being used successfully, and in many cases have verified that they satisfy our criteria for accuracy, precision, update rate, and accessibility criteria. We are confident that any combination of these methods would work. Nonetheless, it is unreasonable to attempt to use all of these methods in the time frame of this project, and therefore we have decided to use beacons, optical flow, and matrix tags in our solution. Optical flow gives us accurate angle measurements and fast updates that are relative to our current position. The camera also doubles as a sensor for matrix tags, which give us accurate position estimates in the global frame. This is complemented by beacons, which update more slowly, but are not effected by occlusion and is robust to vibration.

References

- [1] Dart Ultra Wideband UWB Technology | Zebra.
- [2] Pozyx - centimeter positioning for Arduino.
- [3] P. Bahl and V. N. Padmanabhan. RADAR: an in-building RF-based user location and tracking system. In *Proceedings IEEE INFOCOM 2000. Conference on Computer Communications. Nineteenth Annual Joint Conference of the IEEE Computer and Communications Societies (Cat. No.00CH37064)*, volume 2, pages 775–784 vol.2, 2000.
- [4] E. DiGiampaolo and F. Martinelli. Mobile Robot Localization Using the Phase of Passive UHF RFID Signals. *IEEE Transactions on Industrial Electronics*, 61(1):365–376, January 2014.
- [5] S. S. Ghidary, T. Tani, T. Takamori, and M. Hattori. A new home robot positioning system (HRPS) using IR switched multi ultrasonic sensors. In *1999 IEEE International Conference on Systems, Man, and Cybernetics, 1999. IEEE SMC '99 Conference Proceedings*, volume 4, pages 737–741 vol.4, 1999.
- [6] Hong-Shik Kim and Jong-Suk Choi. Advanced indoor localization using ultrasonic sensor and digital compass. In *2008 International Conference on Control, Automation and Systems*, pages 223–226, October 2008.
- [7] H. Liu, H. Darabi, P. Banerjee, and J. Liu. Survey of Wireless Indoor Positioning Techniques and Systems. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 37(6):1067–1080, November 2007.
- [8] S. S. Saab and Z. S. Nakad. A Standalone RFID Indoor Positioning System Using Passive Tags. *IEEE Transactions on Industrial Electronics*, 58(5):1961–1970, May 2011.
- [9] Adam Smith, Hari Balakrishnan, Michel Goraczko, and Nissanka Priyantha. Tracking Moving Devices with the Cricket Location System. In *Proceedings of the 2Nd International Conference on Mobile Systems, Applications, and Services, MobiSys '04*, pages 190–202, New York, NY, USA, 2004. ACM.
- [10] A. Ward, A. Jones, and A. Hopper. A new location technique for the active office. *IEEE Personal Communications*, 4(5):42–47, October 1997.

- [11] H. Yucel, R. Edizkan, T. Ozkir, and A. Yazici. Development of indoor positioning system with ultrasonic and infrared signals. In *2012 International Symposium on Innovations in Intelligent Systems and Applications*, pages 1–4, July 2012.