

Drush - annotation vs attributes

```
/**
 * @command xkcd:fetch
 * @param $search Optional argument to retrieve the cartoons matching an index number, keyword, or "random".
 * @option image-viewer Command to use to view images (e.g. xv, firefox).
 * @option google-custom-search-api-key Google Custom Search API Key.
 * @usage drush xkcd
 *   Retrieve and display the latest cartoon.
 * @usage drush xkcd sandwich
 *   Retrieve and display cartoons about sandwiches.
 * @aliases xkcd
 */
public function fetch($search = null, $options = ['image-viewer' => 'open', 'google-custom-search-api-key' => 'AIza']) {
    $this->doFetch($search, $options);
}
```

```

/**
 * Retrieve and display xkcd cartoons (attribute variant).
 */
#[
CLI\Command(name: 'xkcd:fetch-attributes', aliases: ['xkcd-attributes'])
#[CLI\Argument(
    name: 'search',
    description: 'Optional argument to retrieve the cartoons matching an index, keyword, or "random".',
)]
#[CLI\Option(
    name: 'image-viewer',
    description: 'Command to use to view images (e.g. xv, firefox).',
    suggestedValues: ['open', 'xv', 'firefox'],
)]
#[CLI\Option(
    name: 'google-custom-search-api-key',
    description: 'Google Custom Search API Key',
)]
#[CLI\Usage(
    name: 'drush xkcd',
    description: 'Retrieve and display the latest cartoon',
)]
#[CLI\Usage(
    name: 'drush xkcd sandwich',
    description: 'Retrieve and display cartoons about sandwiches.',
)]
public function fetch(
    $search = null,
    $options = [
        'image-viewer' => 'open',
        'google-custom-search-api-key' => 'AIza',
    ],
) {
    $this->doFetch($search, $options);
}

```