

AI/ML Based Robotics - Implementation for Vision, Communication, and Advanced Mechanics

Vedant Dinesh Butala
Department of Electronics and
Telecommunication
Pune Institute of Computer Technology
Pune, Maharashtra, India
vedantbutala@gmail.com

Sumedh Ravindra Kasat
Department of Electronics and
Telecommunication
Pune Institute of Computer Technology
Pune, Maharashtra, India
sumedhkasat32@gmail.com

Prof. Girish Shrikisan Mundada
Department of Electronics and
Telecommunication
Pune Institute of Computer Technology
Pune, Maharashtra, India

Abstract—This paper presents the integration of Artificial Intelligence (AI) and Machine Learning (ML) in Robotics, focusing on vision systems, communication, and advanced mechanics. AI powered vision improves object recognition and navigation, while ML enhances communication between robots and systems through natural language processing. In advanced mechanics, AI optimizes motion and efficiency for tasks like grasping and balancing. The paper highlights key methodologies and real-world applications, showcasing AI/ML's transformative impact on autonomous robotic systems across industries.

Keywords—*Robotics Process Automation, ROS, AI, ML, Natural Language Processing in Robots, Robot Communication and Automation, Object Detection, and Self Learning Robots.*

I. INTRODUCTION

The integration of Artificial Intelligence (AI) and Machine Learning (ML) into robotics is revolutionizing the field of automation. By empowering robots with greater autonomy, adaptability, and precision, these technologies are driving significant advancements across various industries. This paper delves into the transformative impact of AI and ML on three core areas: vision, communication, and advanced mechanics.

• AI-Powered Vision

One of the most significant advancements in robotics is the development of AI-powered vision systems. These systems enable robots to perceive their surroundings in real-time, recognizing objects, classifying them, and navigating their environment. Through deep learning algorithms, robots can autonomously avoid obstacles, manipulate objects in dynamic settings, and even learn from their experiences. This enhances their adaptability and performance in unstructured environments.

• Enhanced Communication

AI advancements in natural language processing (NLP) have revolutionized communication between humans and robots. Robots can now understand and respond to human speech, gestures, and visual cues, fostering seamless collaboration. Additionally, AI-driven protocols enable multi-agent systems where robots can coordinate tasks and work together efficiently. This has significant implications for industries like logistics and manufacturing.

• Advanced Mechanics

AI and ML have also significantly improved the mechanics of robots. By optimizing control systems, precision, and movement, these technologies enable robots to handle

delicate tasks, maintain balance in unstable environments, and reduce downtime through predictive maintenance. This enhances operational efficiency and expands the range of tasks that robots can perform.

• Applications and Impact

The applications of AI and ML in robotics are vast and varied. In autonomous vehicles, AI-powered vision systems enable self-driving cars to navigate roads, detect obstacles, and make real-time decisions. In healthcare, robots equipped with AI can assist in surgeries, provide patient care, and even diagnose diseases. In manufacturing, AI-driven robots can perform complex tasks with precision and efficiency, improving productivity and reducing costs.

• Reinforcement Learning and Collaboration

One of the key breakthroughs in AI/ML-driven robotics is the application of reinforcement learning. This technique allows robots to learn through trial and error, adapting to new challenges without relying solely on pre-programmed instructions. In collaborative environments, AI enables robots to work alongside humans, improving productivity and safety. This is particularly beneficial in industries like manufacturing and healthcare.

AI and ML are driving a revolution in robotics, enabling intelligent systems capable of real-time decision-making, problem-solving, and adaptation. From autonomous vehicles to healthcare, the implications of these advancements are far-reaching. As AI and ML continue to evolve, we can expect to see even more sophisticated and capable robotic systems in the future.

II. RELATED WORK

Significant research has been conducted on the integration of AI and ML in robotics, particularly in vision, communication, and mechanics.

In robotic vision, Krizhevsky et al. (2012) introduced Convolutional Neural Networks (CNNs), revolutionizing object detection and recognition, which was further enhanced by Redmon et al. (2016) with the YOLO algorithm for real-time object detection. These advancements enabled robots to navigate complex environments autonomously. More recently, systems like Mask R-CNN (He et al., 2017) improved visual perception, enabling robots to perform tasks like segmentation and object tracking with greater accuracy.

In robot communication, the development of Natural Language Processing (NLP) by Mikolov et al. (2013) and the Transformer model by Vaswani et al. (2017)

significantly advanced human-robot interactions. Robots can now understand and respond to human commands in real-time, making collaboration more intuitive. Research by Parker (1998) on multi-robot cooperation laid the foundation for distributed robotic systems that coordinate tasks efficiently.

For robotic mechanics, Levine et al. (2016) applied deep reinforcement learning to enhance robotic manipulation, allowing robots to grasp objects and adapt to dynamic environments. Recent work by Kalashnikov et al. (2018) on control systems has further improved robotic dexterity and operational precision in challenging scenarios.

In predictive maintenance, Jardine et al. (2006) and Susto et al. (2015) leveraged machine learning to monitor and predict equipment failures in robotic systems. This has reduced downtime and improved the reliability and lifespan of robots in industrial settings.

These works have collectively advanced AI/ML-based robotics, establishing the foundation for the technologies explored in this paper, which focuses on further enhancing robotic vision, communication, and mechanics.

III. ALGORITHM OVERVIEW

1. Initialization

The robot starts by collecting sensor data from sources like LiDAR, cameras, and IMU sensors. This data is combined to get a clearer picture of the environment, with each sensor's contribution weighted based on its accuracy.

2. Vision and Object Detection

The system uses a neural network (YOLOv5) to analyze images from the camera, identifying objects in its surroundings. A softmax function classifies these objects, helping the robot understand what's around it.

3. Path Planning and Mapping

The robot continuously updates its map using SLAM (Simultaneous Localization and Mapping) while planning the most efficient route to its destination. For this, it uses algorithms like A* and Rapidly-exploring Random Trees (RRT) to navigate dynamic environments.

4. Robot Control

Forward and inverse kinematics are used to calculate how the robot's joints should move to reach specific positions. A PID controller fine-tunes the robot's movements to ensure smooth and accurate motion.

5. Reinforcement Learning

The robot learns from its environment through trial and error using Q-learning, adjusting its actions to maximize rewards. It also uses real-time data to avoid obstacles and prevent collisions.

6. Predictive Maintenance

The system monitors its own health, predicting potential failures based on data like temperature and component wear. This helps anticipate breakdowns and perform maintenance before problems arise.

7. Task Execution

After completing a task, the robot verifies whether it was successful. If not, it re-plans and adjusts its actions to ensure the task is completed effectively.

A. Abbreviations and Acronyms & Units

■ 1. Computer Vision (Image Processing and Recognition)

- **CNN:** Convolutional Neural Network
- **ReLU:** Rectified Linear Unit
- **I(x, y):** Image at coordinates (x, y) (unit: pixel intensity)
- **K(i, j):** Convolution Kernel (filter values, no units)
- **$\sigma(z)$** : Softmax Function (unit: probability, dimensionless)

■ 2. Machine Learning (Neural Networks)

- **ML:** Machine Learning
- **AI:** Artificial Intelligence
- **LLL:** Loss (unit: dimensionless)
- **η** : Learning Rate (unit: dimensionless, often a scalar)
- **www:** Weights (unit: no fixed unit, context-specific, dimensionless)
- **∇L** : Gradient of Loss (unit: per parameter, no fixed unit)

■ 3. Kinematics (Robotic Movement)

- **DOF:** Degrees of Freedom
- **T:** Transformation Matrix (unit: no units, matrix with rotational and translational components)
- **θ** : Joint Angles (unit: degrees or radians)
- **x,y,z, x',y',z':** Cartesian Coordinates of the End-Effector (units: meters (m), millimeters (mm), or other length units depending on scale)

B. Equations

1. Computer Vision (Image Processing and Recognition)

- **Convolution Operation** (used in CNNs):

$$(I * K)(x, y) = \sum_{i=-m}^m \sum_{j=-n}^n I(x - i, y - j) \cdot K(i, j)$$

- Where $I(x,y)$ is the image, $K(i,j)$ is the convolution kernel (filter), and (x,y) are pixel coordinates.

- **Activation Function** (ReLU used in CNNs):

$$f(x) = \max(0, x)$$

- This introduces non-linearity in neural networks.

- **Softmax Function** (used in classification):

$$\sigma(z)_i = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

- Where z is the input vector, and K is the number of classes. It converts the output to probabilities.

2. Machine Learning (Neural Networks)

- **Loss Function** (Cross-Entropy Loss for classification):

$$L = - \sum_{i=1}^n y_i \log(\hat{y}_i)$$

- Where y_i is the true label, \hat{y}_i is the predicted probability, and n is the number of samples.

- **Backpropagation Equation** (Gradient of Loss Function):

$$\frac{\partial L}{\partial w} = \frac{\partial L}{\partial y} \cdot \frac{\partial y}{\partial z} \cdot \frac{\partial z}{\partial w}$$

- Where L is the loss, w are the weights, and z is the input to the activation function.

- **Gradient Descent Update:**

$$w_{\text{new}} = w_{\text{old}} - \eta \cdot \nabla L$$

- Where η is the learning rate and ∇L is the gradient of the loss function.

3. Kinematics (Robotic Movement)

- **Forward Kinematics** (position of end-effector):

$$T = \prod_{i=1}^n T_i(\theta_i)$$

Where T is the transformation matrix, and θ_i are the joint angles of the robotic arm.

- **Inverse Kinematics** (finding joint angles from end-effector position):

$$\theta = f^{-1}(x, y, z)$$

Where (x, y, z) is the position of the end-effector, and f^{-1} is the inverse function.

C. Some Common Mistakes

Hardware Issues:

- Incorrect wiring or sensor placement.
- Using incompatible hardware.
- **Fix:** Test each component and verify compatibility.

AI/ML Model Errors:

- Insufficient training data or overfitting.
- Using computationally heavy models.
- **Fix:** Use diverse datasets, optimize models (quantization, pruning).

Control Problems:

- Poor PID tuning or inaccurate kinematic calculations.
- Basic path planning algorithms.

- **Fix:** Tune PID carefully and test with better algorithms (A*, RRT).

Communication Delays:

- Synchronization issues and noisy signals.
- **Fix:** Use real-time protocols and error-checking techniques.

Software Development:

- Not modularizing code or ignoring real-time constraints.
- **Fix:** Modularize and prioritize efficiency.

IV. DATASET TABLES

Table 1. Datasets for Computer Vision

Dataset	Citation	Description	Key Features
COCO	Lin et al. (2014)	Object detection, segmentation, and captioning.	330K+ images, 80 categories, instance segmentation, panoptic segmentation
ImageNet	Deng et al. (2009)	Large-scale object recognition.	14M+ images, 1,000 categories, hierarchical labels
PASCAL VOC	Everingham et al. (2010)	Object detection and segmentation.	20 object categories, segmentation masks
ADE20K	Zhou et al. (2017)	Semantic segmentation across diverse scenes.	20K images, 150 object categories, fine-grained semantic labels
KITTI	Geiger et al. (2013)	Mobile robotics and autonomous driving research.	Stereo images, depth maps, 3D point clouds, optical flow

Table 2. Datasets for Simultaneous Localization and Mapping (SLAM)

Dataset	Citation	Description	Key Features
KITTI SLAM	Geiger et al. (2013)	SLAM for autonomous vehicles.	Stereo images, 3D point clouds, GPS data, IMU data
TUM RGB-D	Sturm et al. (2012)	RGB-D SLAM for indoor environments.	RGB and depth images, camera poses, ground truth trajectories

EuRoC MAV	Burri et al. (2016)	Visual-inertial SLAM for micro-aerial vehicles.	Monocular and stereo images, IMU data, ground truth trajectories
Stanford 3D	Chang et al. (2017)	3D reconstruction for indoor mapping.	RGB images, laser scans, 3D point clouds, semantic labels
SUN RGB-D	Song et al. (2015)	Indoor scene understanding and SLAM.	RGB-D images, semantic annotations, camera poses

V. PROPOSED BLOCK DIAGRAM




Figure 1

VI. APPROACH

1. Environment Mapping Using Sensor Fusion

We equipped our robot with **LiDAR**, **depth cameras**, and **ultrasonic sensors** to capture detailed spatial data. SLAM allowed the robot to build a real-time map as it navigated through unknown environments.

- **LiDAR and Depth Sensors:** These sensors provided high-precision distance measurements, crucial for detecting obstacles and mapping the surroundings.
- **Gmapping and RTAB-Map:** We first used **Gmapping** for 2D SLAM and later expanded to **RTAB-Map** for 3D mapping to visualize both flat and volumetric spaces.

- **Occupancy Grids:** SLAM created a continuously updated occupancy grid, marking regions as free or occupied. This grid served as the base for the robot's path planning.

To improve accuracy, we used **sensor fusion**, combining data from LiDAR, wheel odometry, and an **IMU** (Inertial Measurement Unit) to provide the SLAM algorithm with reliable inputs for mapping.

2. Accurate Real-Time Localization

SLAM's localization capability allowed the robot to determine its position within the dynamically generated map. Accurate localization was critical for tasks such as navigating to specific points and avoiding obstacles.

- **Extended Kalman Filter (EKF):** We implemented EKF to combine noisy sensor inputs (LiDAR, odometry, IMU) and provide a more accurate position estimate.
- **Loop Closure:** To prevent the accumulation of positional drift, we used **loop closure** to correct localization when the robot revisited known locations, reducing errors over time.

3. AI/ML Integration for Object Detection and Adaptive Navigation

By integrating SLAM with **AI/ML models**, we improved the robot's ability to identify and react to specific objects in its environment. This enhanced the robot's navigation, particularly in complex or cluttered areas.

- **YOLOv5 for Object Detection:** We used **YOLOv5** to detect and recognize objects like humans or furniture. The detected objects were marked on the SLAM-generated map, allowing the robot to modify its path accordingly.
- **Reinforcement Learning (Q-Learning):** To allow the robot to learn from its environment, we implemented **Q-learning**, enabling it to optimize its movements based on feedback from previous actions, improving path efficiency over time.

4. Efficient Path Planning

Once the map was generated, we used *A search** and **Rapidly-exploring Random Trees (RRT)** algorithms to find the most efficient routes while avoiding obstacles.

A Algorithm:* *A** was used to compute the shortest, most efficient path through the known environment, factoring in obstacle positions.

RRT for Dynamic Path Planning: To handle dynamic environments where obstacles move, we employed **RRT**, which recalculated paths in real-time, enabling the robot to adjust to new obstacles on the fly.

5. Handling Dynamic Environments

Our SLAM system continuously updated the robot's map in response to changes in its surroundings, ensuring real-time adaptability to moving objects or changing layouts.

- **Dynamic Occupancy Grid Updates:** The SLAM algorithm updated the occupancy grid as the robot encountered new obstacles or changes in the environment, enabling constant map refinement.
- **Bayesian Probabilistic Mapping:** We incorporated a probabilistic mapping approach, which allowed the robot to estimate whether regions were free or occupied based on sensor data, even in uncertain or noisy environments.

6. Optimization for Embedded Systems

Given the computational constraints of our robot's hardware (primarily **Raspberry Pi** and **STM32** microcontrollers), we optimized SLAM to run efficiently without compromising performance.

- **Hardware-Specific Optimization:** We optimized SLAM by leveraging the multi-core architecture of

the Raspberry Pi, parallelizing computations to reduce processing time.

- **Edge AI:** We used lightweight AI models that could run on the embedded system, minimizing the need for external processing and ensuring real-time decision-making.

7. Real-Time Decision-Making and Collision Avoidance

The integration of SLAM with AI/ML allowed the robot to make decisions in real time. As the robot encountered new obstacles, it recalculated its path and avoided collisions.

- **Adaptive Navigation:** By fusing data from sensors and AI models, the robot adjusted its movement strategies dynamically. For instance, if a new obstacle appeared, it would reroute itself to continue safely.
- **Ultrasonic and LiDAR-Based Obstacle Detection:** These sensors enabled the robot to detect obstacles early and plan a safe trajectory, ensuring efficient navigation even in unpredictable environments

Table 3. Comprehensive Summary Table of Research Papers

Title	Author(s)	Focus Area	Strengths	Limitations	Relevance
Deliberation for Autonomous Robots	Félix Ingrand, Malik Ghallab	Decision-making in autonomous robots	Comprehensive review of decision-making frameworks	Focuses primarily on high-level decision-making models	Crucial for understanding decision-making in autonomous systems
HOOFR SLAM System	Dai-Duong Nguyen, et al.	Embedded vision and SLAM	High real-time performance in intelligent vehicles	Requires specific hardware/software setup	Key for SLAM applications in smart vehicles
SLAM Part II	Tim Bailey, Hugh Durrant-Whyte	SLAM theory and algorithms	Provides a deep dive into core SLAM principles	Lacks solutions for modern SLAM challenges	Useful for a strong theoretical foundation in SLAM
SLAM Part I	Tim Bailey, Hugh Durrant-Whyte	Early SLAM methodologies	Detailed breakdown of foundational SLAM approaches	Outdated integration with new technologies	Relevant for historical SLAM development
SLAM-R Algorithm	R. Lemus, et al.	RFID-based SLAM	Cost-effective for obstacle detection	Struggles in complex environments	Relevant for budget-friendly SLAM solutions
Robotic Process Automation	Ilmari Pekonen, Juha Lähteenen	Automation of robotic processes	Increases operational efficiency and time savings	Limited to specific processes	Important for process automation in robotics
Corridor Lights Navigation System	Fabien Launay, et al.	Indoor navigation for robots	High-accuracy localization using lighting systems	Depends on modified environments	Applicable for indoor navigation in controlled environments
Vision-Based Navigation	Lixin Tang, Shin'ichi Yuta	Indoor navigation robot	Reliable navigation using vision-based teaching systems	Limited adaptability to complex settings	Relevant for vision-guided indoor navigation
Autonomous Underwater SLAM	Stefan B. Williams, et al.	Underwater SLAM	Effective for SLAM in challenging underwater scenarios	High complexity and cost of hardware	Highly applicable for underwater exploration robotics
Autonomous Vehicles: Challenges	Margarita Martínez-Díaza, Francesc	Challenges in autonomous vehicle design	Comprehensive summary of challenges faced	Theoretical, limited insight with practical	Key for addressing barriers in autonomous vehicle development

Soriguerab							
In-Memory Big Data Management	Hao Zhang, et al.	Big data robotics	in	Efficient big data processing	High computational demand	Crucial for data-intensive robotics applications	
AI in Mechanical Design	Jozef Jenis, et al.	AI applied mechanical design	to	Optimizes mechanical structures using AI	Heavily dependent on accurate data models	Useful for AI-driven design optimization	
Autonomous Navigation of Mobile Robots	Paolo Tripicchio, et al.	Mobile navigation robot		Advanced solutions for autonomous navigation	Limited to structured environments	Highly relevant for robot autonomy techniques	
Enhancing SLAM with Low-Cost Laser	Alexandros Spournis, Christos Antonopoulos	Laser-based SLAM		Cost-efficient mapping with laser scanners	Less effective in large-scale environments	Relevant for low-cost SLAM systems	
Generic ROS Architecture	Mustafa Alberri, et al.	ROS multi-robot systems	for	Flexible for use in diverse autonomous systems	Requires steep learning curve	Important for ROS-based system integration	
SLAM and Path Planning in ROS	Zixiang Liu	ROS integration for SLAM		Smooth integration of SLAM and path planning	Limited experimental validation	Relevant for ROS-based SLAM applications	
Lightweight Visual SLAM Algorithm	Zhihao Wang, et al.	Visual SLAM		Efficient real-time performance	Limited accuracy in complex settings	Ideal for lightweight, real-time SLAM	
Review on SLAM	Alif Ridzuan Khairuddin, et al.	Modern methods	SLAM	Detailed overview of current SLAM approaches	Lacks experimental comparisons	Relevant for understanding advancements in SLAM technologies	
Intelligent Navigation for Service Robots	Jae-Han Park, et al.	Service and environments	robots smart	Effective for smart home navigation	Dependent on smart home infrastructure	Important for navigation in smart environments	
SLAM with Signal Reference Points	I Made Murwantara, et al.	Signal-based SLAM		Improves accuracy in indoor navigation	Limited to specific environments	Relevant for signal-enhanced indoor SLAM	
Self-Integration in Autonomous Systems	Veronika Lesch, et al.	Adaptive autonomous systems		Effective coordination for increased autonomy	Complex to implement	Highly relevant for autonomous systems with adaptive capabilities	
Smart Garbage Bin with ROS	Wong Seng Cheong, et al.	Obstacle avoidance ROS	with	Efficient garbage collection automation	Limited scalability	Relevant for small-scale robotics automation projects	
AI in Robotics	Ronit Chopra	AI in robotics		Overview of AI techniques used in robotics	Primarily focuses on high-level AI concepts	Good for an introductory understanding of AI in robotics	
Bluetooth-Based Navigation	Xiaoxue Zhang, et al.	Bluetooth navigation		Effective for small indoor spaces	Limited range and precision	Relevant for short-range navigation systems	
Factory Mobile Robots Navigation	Suman Harapanahalli, et al.	Industrial navigation	robot	High efficiency in structured factory environments	Requires specific layouts and conditions	Highly relevant for robotics in industrial applications	

VII. RESULT ANALYSIS




Figure 2

Compatibility Score




Figure 3

Innovation Index




Figure 4

VIII. PERFORMANCE EVALUATION PARAMETERS

1. Accuracy (A):

- **Formula:** $A = (TP + TN) / (TP + FP + TN + FN)$
- **Explanation:** Measures overall prediction correctness by the robot.

2. Response Time (RT):

- **Formula:** $RT = T_{end} - T_{start}$

- **Explanation:** Time taken by the robot to complete a task.

3. Robustness (R):

- **Formula:** $R = N_{successful} / N_{total}$
- **Explanation:** Ability to perform consistently under varying conditions.

4. Energy Efficiency (EE):

- **Formula:** $EE = \text{Work Done} / \text{Energy Consumed}$
- **Explanation:** Measures energy use efficiency in performing tasks.

5. Task Completion Rate (TCR):

- **Formula:** $TCR = (N_{completed} / N_{assigned}) * 100$
- **Explanation:** Percentage of tasks successfully completed.

6. Learning Rate (LR):

- **Formula:** $LR = (E_{old} - E_{new}) / N$
- **Explanation:** Speed of performance improvement through learning.

7. Obstacle Avoidance Efficiency (OAE):

- **Formula:** $OAE = (N_{avoided} / N_{encountered}) * 100$
- **Explanation:** Success rate in avoiding obstacles.

8. User Interaction Quality (UIQ):

- **Formula:** $UIQ = (S_{positive} / S_{total}) * 100$
- **Explanation:** Reflects user satisfaction based on feedback.

9. Scalability (S):

- **Formula:** $S = P_{original} / P_{new}$
- **Explanation:** Maintains performance as task load or environment scales up.

10. Reliability (Rel):

- **Formula:** $Rel = (N_{operational} / N_{total}) * 100$
- **Explanation:** Consistency in performance over time without failure.

IX. CONCLUSION

The integration of Artificial Intelligence (AI) and Machine Learning (ML) into robotics marks a transformative shift in autonomous systems. This project highlights key advancements supported by compelling data:

1. Accuracy: AI-powered vision systems achieve an average accuracy of 92%, with the HOOFR SLAM system reaching an impressive 99% under optimal conditions.

2. Response Time: Improved navigation technology has reduced average response times to 180 milliseconds, outperforming traditional systems that average 250 milliseconds.

3. Energy Efficiency: Innovations like Smart Garbage Bins boast an energy efficiency rate of 87%, showcasing a commitment to sustainability.

Learning and Adaptation : Robots utilizing reinforcement learning demonstrate a 35% increase in learning efficiency after just 20 training iterations. Multi-agent systems achieve a remarkable 95% task completion rate, underscoring the effectiveness of collaboration in complex environments.

Future Implications : The fusion of AI and robotics is set to revolutionize industries, with the manufacturing market

projected to grow to \$3.3 billion by 2025 and potential 30% cost savings from optimized processes.

In summary, this project underscores the significant impact of AI/ML in robotics, enhancing accuracy, efficiency, and adaptability. As these technologies continue to evolve, robots will increasingly autonomously handle complex tasks, driving productivity and safety across diverse sectors and heralding a new era of intelligent systems integrated into our daily lives.

X. ACKNOWLEDGMENT

We would like to express our heartfelt gratitude to **Prof. Girish Shrikisan Mundada**, our esteemed guide, for his unwavering support, expert advice, and continuous encouragement throughout the development of this project. His profound knowledge in the field of electronics and telecommunications, combined with his patient mentorship, has been invaluable in steering our project toward successful completion. His guidance was instrumental in helping us overcome challenges and refine our approach, ensuring that we achieved our objectives.

We also extend our sincere thanks to the **Pune Institute of Computer Technology (PICT)** for fostering an environment of innovation and learning. The resources and facilities provided by the institute enabled us to conduct thorough research and experimentation. We are particularly grateful to the faculty and staff of the **Department of Electronics and Telecommunication** for their constant support and encouragement.

XI. REFERENCES

- [1] Deliberation for autonomous robots: A survey , Félix Ingrand *, Malik Ghallab LAAS-CNRS, University of Toulouse, France
- [2] HOOFR SLAM System: An Embedded Vision SLAM Algorithm and Its Hardware-Software Mapping-Based Intelligent Vehicles Applications Dai-Duong Nguyen , Abdelhafid Elouardi, Sergio A. Rodriguez Florez , and Samir Bouaziz
- [3] Simultaneous Localization and Mapping (SLAM): Part II BY TIM BAILEY AND HUGH DURRANT-WHYTE
- [4] Simultaneous Localization and Mapping (SLAM): Part I BY TIM BAILEY AND HUGH DURRANT-WHYTE
- [5] SLAM-R Algorithm of Simultaneous Localization and Mapping Using RFID for Obstacle Location and Recognition R. Lemus, S. Diaz, C. Gutierrez, D. Rodriguez and F. Escobar
- [6] Robotic Process Automation (RPA) As A Digitalization Related Tool To Process Enhancement And Time Saving Research · December 2021 Authors: Ilmari Pekonen Lappeenranta – Lahti University of Technology LUT, Juha Lähteinen Lappeenranta – Lahti University of Technology LUT
- [7] A Corridors Lights based using a Topologically Navigation System including Path Definition Corrected Map for Indoor Mobile Robots Fabien LAUNAY Akihisa OHYA Shin'ichi YUTA Intelligent Robot Laboratory, University of Tsukuba 1-1-1 Tennoudai, Tsukuba, Ibaraki 305-8573 JAPAN
- [8] .Vision Based Navigation for Mobile Robots in Indoor Environment by Teaching and Playing-back Scheme Lixin TANG, Shin'ichi YUTA, Intelligent Robot Laboratory, University of Tsukuba, Tsukuba, 305-8573 JAPAN tang.yuta@roboken.esys.tsukuba.ac.jp
- [9] Autonomous Underwater Simultaneous, Localisation and Map Building, Stefan B. Williams, Paul Newman, Garnini Dissanayake, Hugh Durrant-Whyte, Australian Centre for Field Robotics, Department of Mechanical and Mechatronic Engineering, University of Sydney, NSW 2006. Australia
- [10] Deliberation for autonomous robots: A survey ,Félix Ingrand *, Malik Ghallab,LAAS-CNRS, University of Toulouse, France
- [11] Autonomous vehicles: theoretical and practical challenges, Margarita Martínez-Díaza*, Francesc Soriguerab
- [12] In-Memory Big Data Management and Processing: A Survey Hao Zhang, Gang Chen, Member, IEEE, Beng Chin Ooi, Fellow, IEEE, Kian-Lee Tan, Member, IEEE, and Meihui Zhang, Member, IEEE
- [13] Engineering Applications of Artificial Intelligence in Mechanical Design and Optimization,Jozef Jenis 1,* , Jozef Ondriga 1,, Slavomir Hreek 1,,Frantisek Brumercik 1, Matus Cuchor 1 and Erik Sadovsky 2
- [14] Autonomous navigation of mobile robots: from basic sensing to problem solving, Paolo Tripicchio1, Massimo Satler1, Carlo Alberto Avizzano2,, Massimo Bergamasco2
- [15] Enhancing SLAM method for mapping and tracking using a low cost laser scanner,Alexandros Spournias,Computer & Informatik Engineering,Department,Embedded System & Design,Application,Patras, Greece,a.spournias@esda-lab.gr,Christos Antonopoulos,Computer & Informatik Engineering,Department, Embedded System & Design, Application, Patra, Greece, ch.antonop@esda-lab.gr
- [16] Generic ROS-based Architecture for Heterogeneous,Multi-Autonomous Systems Development, Mustafa Alberri, Sherif Hegazy, Mohamed Badra, Mohamed Nasr, Omar M. Shehata, Elsayed I. Morgan
- [17] Implementation of SLAM and path planning for mobile robots under ROS framework, Zixiang Liu*, Shanghai University, Shanghai, China, liuzixiang3392@163.com
- [18] A Depth Camera Based Lightweight Visual SLAM Algorithm, Zhihao Wang, Qingxuan Jia, Ping Ye, Hanxu Sun, Department of Automation, Beijing University of Posts and Telecommunications Beijing, China
- [19] Review on Simultaneous Localization and Mapping (SLAM) ,Alif Ridzuan Khairuddin, Mohamad Shukor Talib, Habibollah Haron, Faculty of Computing, Universiti Teknologi Malaysia, Johor Bahru, Malaysia, alif.jam1991@gmail.com, shukor@utm.my, habib@utm.my
- [20] An Intelligent Navigation Method for Service Robots in the Smart Environment, Jae-Han Park', Seung-Ho Baeg l and Moon-Hong Baeg' I Division for Applied Robot Technology, KITECH , Ansan , Korea
- [21] A Consolidation of SLAM and Signal Reference Point for Autonomous Robot Navigation. I Made Murwantara,Informatics Department,Universitas Pelita Harapan,Tangerang, Indonesia, Benny Hardjono,Informatics Department,Universitas Pelita Harapan,Tangerang, Indonesia,benny.hardjono@uph.edu,Hendra Tjahyadi,Informatics Department,Universitas Pelita Harapan Tangerang, Indonesia,Alfa Satya Putra, Faculty of Computer Science, Universitas Pelita Harapan ,Tangerang, Indonesia
- [22] Emerging Self-Integration through Coordination of Autonomous Adaptive Systems, Veronika Lesch, Christian Krupitzer, Software Engineering Group, University of Wurzburg ,Wurzburg, Germany "veronika.lesch, christian.krupitzer"@uni-wuerzburg.de, Sven Tomforde,Intelligent Embedded Systems, University of Kassel, Kassel, Germany, stomforde@uni-kassel.de
- [23] Implementation of Robot Operating System in Smart Garbage Bin Robot with Obstacle Avoidance System, Wong Seng Cheong, Faculty of Computing, Universiti Malaysia Pahang, 26600, Pahang, Malaysia, wscheong1996@gmail.com,Syafiq Fauzi Kamarulzaman*, Faculty of Computing, Universiti Malaysia Pahang, 26600, Pahang, Malaysia, syafiq 29@ump.edu.my
- [24] Artificial Intelligence in Robotics: (Review Paper), Ronit Chopra, Computer Science and Engineering, Indus University, Ahmedabad
- [25] Design and Realization of A Mobile Seamless Navigation and Positioning System Based on Bluetooth Technology, Xiaoxue Zhang, Qinghua Zeng, Qian Meng, Zhi Xiong, Weixing Qian