Universidad de Las Palmas de Gran Canaria

Grado en Ciencia e Ingeniería de Datos

Big Data: Search Engine Project

Stage 2: Building a Service-Oriented Architecture

Course: Big Data
Group: PIE data
Repository: https://github.com/PIE-data/stage_2

Group members

Marcela Nieto-Kuczyńska
Andrea Patruno
Ivan Colella
Manuel Muñoz Roca

Academic Year 2026/2027

Contents

1 Introduction and Objectives **1**

2 System Architecture **1**
2.1 Components and Responsibilities 3
2.2 Life of a Book 3
2.3 Storage and Shared State 4
2.4 Processes, Replicas, and Threads 4

3 API Design and Contracts **5**
3.1 Front-End-Facing API 5
3.2 Internal and Operational APIs 5
3.3 Non-HTTP Coordination Contract 6
3.4 Completion Semantics and Errors 6
3.5 Specification and Validation Evidence 6

4 Microservice Implementation **7**
4.1 Ingestion Service 7
4.2 Indexing Service 7
4.3 Search Service 7
4.4 Broker and Feeder 7
4.5 Readiness and Failure Handling 8

5 Design Decisions **8**
5.1 Reuse of Stage 1 Contracts and Oracles 8
5.2 Choreography Instead of a Central Control Module 8
5.3 At-Least-Once Delivery and Idempotency 8
5.4 Local Storage and SQLite 9
5.5 Replicas, Threads, and Single-Machine Deployment 9
5.6 Functional Validation Before Benchmarking 9

6 Benchmarks and Results **9**
6.1 Microbenchmarks (JMH) 9
6.2 Integration Benchmark: Dataset, Method, and Measures 11
6.3 Search Concurrency 12
6.4 Search Replicas and Gateway Cost 13
6.5 Indexing: Batch Size, Sessions, and Replicas 13
6.6 Per-Book Indexing Latency 15
6.7 Full Pipeline and Ingestion Replicas 16
6.8 Search and Indexing Interference 16
6.9 Coordination Cost and Resource Use 17
6.10 Results Compared with Expectations 18
6.11 Threats to Validity 18

7 Conclusions and Future Improvements **19**
7.1 Stage 3 Plan 20

1 Introduction and Objectives

Stage 2 continues the search engine project by turning the data layer developed in Stage 1 into a service-oriented system. The storage choices selected in the previous stage are reused, while Ingestion, Indexing, and Search now run as independent Java processes. The services communicate through HTTP interfaces and an ActiveMQ message broker, and several replicas of a service can run on the same Stage 2 host.

The Stage 1 result remains the storage foundation. Downloaded books are stored in the selected digit-prefix datalake layout, while metadata and the positional inverted index are stored in a SQLite datamart. The Ingestion Service downloads and splits books, the Indexing Service transforms them into searchable data, and the Search Service exposes the committed index through a read-only HTTP API. A Feeder starts ingestion runs and follows their progress, while nginx provides one front-end entry point for Search replicas.

A main objective of this stage is to keep the pipeline correct when several processes and threads work at the same time. This requires explicit rules for message delivery, retries, duplicate work, concurrent file access, SQLite writes, and process failure. The implementation therefore uses persistent broker messages, transacted JMS consumers, atomic file writes, per-book claims, and database transactions.

The second objective is to evaluate the behaviour of the complete system under concurrency. The integration benchmarks vary client concurrency, service threads, batch sizes, and replica counts for Search, Indexing, and Ingestion. Throughput, latency, queue time, CPU use, and memory use are measured so that the limits of the single-machine architecture can be identified.

The result of Stage 2 is a complete single-machine search system that can be built, started, tested, monitored, and stopped as one deployment. Its HTTP interfaces are described by a versioned OpenAPI specification, its broker messages have a separate event contract, and the complete pipeline is validated functionally and under load. These results also show which local assumptions must change in Stage 3, when the architecture moves to several machines.

2 System Architecture

Stage 1 implemented a sequential data pipeline. Stage 2 keeps the same logical order – download, split, index, query – but separates the work into autonomous services. There is no central controller that calls every stage in order. The pipeline is coordinated mainly by events: a service reacts to a message, commits its own work, and publishes the event that enables the next stage.

The front-end is deliberately separated from this internal coordination. It sends requests only to the gateway on port 8080. The gateway forwards them to Search replicas, which read the committed SQLite datamart. Ingestion and Indexing are never called by the front-end during the normal search path.




Figure 1: Stage 2 architecture on one host. The front-end reaches only the nginx gateway (public HTTP); Ingestion and Indexing are coordinated by broker queues and a topic; the dashed arrow is the only internal HTTP call of the pipeline. Each service runs as N replicas (two in the default configuration, ports separated by 10), and each process uses Jetty request threads or JMS consumer sessions internally (Table 3).

2.1 Components and Responsibilities

Table 1: Processes in the Stage 2 deployment.

Process	Port		Replicas	Responsibility
Broker	61616, (HTTP)	7000	1	Embedded ActiveMQ broker; persistent messages, queues, topic, and monitoring.
Feeder	7004		1	Chooses books from Stage 1 manifests, skips completed work, publishes ingestion requests, and reports progress.
Ingestion	7001, 7011, ...		1..N	Downloads and splits books, writes datalake files and receipts, publishes `books.downloaded`.
Indexing	7002, 7012, ...		1..N	Parses metadata, builds the positional index, writes the SQLite datamart, publishes `books.indexed`.
Search	7003, 7013, ...		1..N	Read-only front-end API over committed data.
Gateway	8080		1	nginx round-robin entry point in front of Search replicas.

All Java services are built as Maven modules and packaged as executable jars. Shared configuration, HTTP conventions, JSON models, messaging helpers, tokenizer logic, header parsing, and datamart code live in the `common` module. Configuration can be provided by defaults, an external properties file, environment variables, or JVM properties, with later layers overriding earlier ones.

2.2 Life of a Book

The order of the pipeline is encoded by durable state and messages rather than by one orchestration process. Table 2 shows the state transitions for one book.

Table 2: Life of one book in the Stage 2 pipeline.

Step	Owner	Effect	Durable state
1	Feeder / HTTP	Publish `IngestRequested`.	ActiveMQ broker store
2	Ingestion	Write cleaned header, body, and receipt.	Datalake and `control/ingestion/`
3	Ingestion	Publish `BookDownloaded`.	Broker queue
4	Indexing	Commit metadata and postings.	`datamart.db`
5	Search	New read transactions can see the book.	Same SQLite commit
6	Indexing	Publish `BookIndexed` for progress.	Topic notification

A book is never announced as downloaded before both datalake files and its receipt are complete. Likewise, Indexing publishes `BookIndexed` only after the SQLite commit. Search uses one read transaction per request, so the result count, ranking data, and returned page come from the same committed snapshot.

2.3 Storage and Shared State

Everything under the default workspace belongs to one machine:

```
data/
|-- datalake/<id6[0:2]>/<id6[2:4]>/<id>.header.txt
|-- datalake/<id6[0:2]>/<id6[2:4]>/<id>.body.txt
|-- control/ingestion/hash/<id>.json
|-- control/claims/<id>.lock
|-- control/failed_books.txt
|-- datamarts/datamart.db
`-- broker/
```

The datalake reuses the Stage 1 digit-prefix layout because Stage 2 always addresses books by id. The SQLite datamart combines metadata and the positional inverted index in one database so that a book becomes searchable atomically. ActiveMQ stores unacknowledged messages in KahaDB. These three stores solve different durability problems but are all local to the same host in Stage 2.

2.4 Processes, Replicas, and Threads

A replica is a separate process; a thread is concurrency inside one process. The distinction is important because the two mechanisms do not protect shared state in the same way.

Table 3: Replication, internal concurrency, and shared-state protection.

Service	**Replicas**	**Threads / sessions**	**Protection of shared state**
Ingestion	Competing consumers	Configurable JMS consumer sessions + HTTP threads	Per-book JVM lock + OS file lock; atomic rename.
Indexing	Competing consumers	Configurable JMS sessions; batches of messages	SQLite `BEGIN IMMEDIATE`, `busy_timeout`; one writer at a time.
Search	nginx upstreams	Jetty request threads	Read-only SQLite connections; no shared writes.
Feeder	Single process	Publisher + HTTP threads	Distinct-id progress set.
Broker	Single process	ActiveMQ internal threads	Persistent KahaDB store.

Broker queues distribute work between Ingestion and Indexing replicas with prefetch 1. nginx distributes HTTP requests between Search replicas. An in-process lock cannot protect two replicas, so cross-process rules use file locks, SQLite locking, or broker delivery instead.

3 API Design and Contracts

The HTTP API is documented separately from the broker messages. The implementation distinguishes the front-end-facing Search API from internal and operational endpoints. The complete HTTP contract is versioned in `api/openapi.yaml`, while `docs/API_INVENTORY.md` records the provider, consumer, and purpose of every route.

3.1 Front-End-Facing API

The front-end communicates with Search through the nginx gateway on port 8080. It does not read local files, access SQLite directly, or interact with the message broker.

Table 4: Front-end-facing Search endpoints.

Route	Provider / consumer	Purpose
`GET /search`	Search / front-end	Keyword search with optional author, language, and release-year filters plus pagination.
`GET /search/filters`	Search / front-end	Return the languages and release-year range available in the current datamart.
`GET /books/{book_id}`	Search / front-end	Return metadata for one indexed book.

The required query parameter is `q`. Optional filters are `author`, `language`, and `year`; pagination uses `offset` and `limit`. Multiple normalized query terms use AND semantics. Results are ranked with TF-IDF and then by book id. Invalid parameters return a documented HTTP 400 error, while a valid query with no matches returns HTTP 200 with an empty result list.

3.2 Internal and Operational APIs

Internal and operational routes are used by the Feeder, scripts, monitoring, and validation rather than by the front-end.

Table 5: Main internal and operational endpoints.

Route	Provider / consumer	Purpose
`POST /ingest/{book_id}`	Ingestion / operator, checks	Accept one ingestion request.
`GET /ingest/status/{book_id}`	Ingestion / scripts, checks	Report downloaded, failed, or not found.
`GET /ingest/list`	Ingestion / Feeder	Return completed ingestion ids so the Feeder can skip them.
`POST /index/update/{book_id}`	Indexing / operator, checks	Index or re-index one completed book.
`POST /index/rebuild`	Indexing / operator, checks	Rebuild the complete datamart.
`GET /index/status`	Indexing / monitoring	Return index counts and state.
`POST /feeder/run`	Feeder / operator, benchmarks	Start a run from a manifest.
`GET /feeder/status`	Feeder / monitoring	Report requested and indexed progress.
`GET /broker/stats`	Broker / monitoring, benchmarks	Return queue depth and timing statistics.
`GET /status`	Every service / scripts	Standard health endpoint.

3.3 Non-HTTP Coordination Contract

Most pipeline coordination does not use HTTP. It is defined in `docs/EVENTS.md` and carried by ActiveMQ.

Table 6: Broker destinations used by the pipeline.

Destination	Type	Producer	Meaning / consumer
`ingest.requests`	Queue	Feeder / Ingestion HTTP	Request one book; consumed by one Ingestion replica.
`books.downloaded`	Queue	Ingestion	Book files and receipt are complete; consumed by one Indexing replica.
`books.indexed`	Topic	Indexing	Book is committed and searchable; used for Feeder progress and monitoring.
`ActiveMQ.DLQ`	Queue	Broker	Messages that still fail after the configured redeliveries.

3.4 Completion Semantics and Errors

A new `POST /ingest/{book_id}` returns HTTP 202 after the request is published to ActiveMQ; this does not mean that the book has already been downloaded or indexed. If the book is already ingested, the endpoint returns HTTP 200. Indexing HTTP operations return HTTP 200 only after the datamart operation has completed.

The specification also records validation and error behaviour. Examples include HTTP 400 for invalid parameters, HTTP 404 for unknown resources, HTTP 409 for conflicting Indexing states, and HTTP 503 when an operation depends on an unavailable broker or busy datamart. Error responses use a common JSON shape with an error code and message.

3.5 Specification and Validation Evidence

The API work is delivered in four parts:

- `api/openapi.yaml`: the versioned HTTP contract, including parameters, schemas, defaults, status codes, examples, pagination, ordering, filtering, and completion semantics;
- `docs/API_INVENTORY.md`: the endpoint inventory with provider, consumer, and purpose;
- `api/api-checks.http`: runnable manual HTTP requests;
- `scripts/check-api.sh`: automated checks of the running deployment, including the event checks defined for broker coordination.

The final validation was run against the full deployment and returned **32 PASS, 0 FAIL, 0 SKIP**. This provides evidence that the running endpoints and the documented contract agree for the validated cases.

4 Microservice Implementation

The services are implemented in Java and built as a Maven multi-module project. The project uses Java 17 as the compilation target, Javalin 6.1.3 for HTTP services, Gson 2.11.0 for JSON handling, ActiveMQ Classic for broker coordination, and SQLite for the searchable datamart. Shared code is kept in the `common` module so that services use the same configuration, data models, tokenizer rules, event formats, and datamart code.

4.1 Ingestion Service

Ingestion receives a book id either from the `ingest.requests` queue or from its HTTP API. It downloads the Project Gutenberg text, finds the expected start and end markers, separates the header and body, cleans the text according to the Stage 1 specification, and writes the selected datalake layout.

Writes use a temporary `.part` file followed by an atomic move to the final path. A receipt marks a completely ingested book. To avoid two replicas processing the same book at the same time, Ingestion combines an in-process lock with an OS file lock on a per-book claim. Repeated requests are safe because an existing receipt is detected before new work is performed. The 20 golden books are used to verify compatibility with Stage 1.

4.2 Indexing Service

Indexing consumes `BookDownloaded` events and can also be called through administrative HTTP routes. It reads the completed header and body, parses metadata, tokenizes the text, builds the positional inverted index, and writes metadata, terms, and postings into `data/datamarts/datamart.db`.

SQLite uses WAL mode. Indexing is the logical writer and Search is read-only. Re-indexing replaces the existing rows for a book instead of creating duplicates. Broker messages can be processed in batches; the default batch size is 20 with a 200 ms batch wait. The canonical export for the golden dataset is checked against the Stage 1 SHA-256 oracle.

4.3 Search Service

Search exposes the front-end HTTP API and never modifies the datamart. Each request uses a read-only SQLite connection and one read transaction. Query terms are normalized with the Stage 1 tokenizer. Multiple terms use AND semantics, and the optional filters are author, language, and Gutenberg release year.

Ranking uses TF-IDF:

$$\text{score}(d) = \sum_{t \in q} tf(t, d) \, \ln\left(\frac{N}{df(t)}\right).$$

Results are ordered by decreasing score and then increasing book id. Search can run as several replicas on different ports, with nginx providing one public gateway.

4.4 Broker and Feeder

The broker runs as its own Java process with persistent KahaDB storage. It provides the two work queues, the indexed topic, and the Dead Letter Queue. Consumers use transacted

JMS sessions, and the failover transport reconnects clients after a broker restart.

The Feeder starts pipeline work from the Stage 1 corpus manifests. Before publishing new requests, it checks the completed ingestion ids and skips books that are already present. It listens to `books.indexed` to report progress through `/feeder/status`.

4.5 Readiness and Failure Handling

Every HTTP service exposes `GET /status`. The deployment scripts start services in order and wait for their readiness endpoints before continuing. A crashed service is not automatically restarted by the process manager; unacknowledged broker work can instead be redelivered to a remaining consumer replica.

Transient consumer failures cause the JMS transaction to roll back and the message to be redelivered. Permanent ingestion failures such as a missing Gutenberg book are recorded and completed without repeated retries. Malformed messages that still fail after the configured redeliveries end in `ActiveMQ.DLQ`.

5 Design Decisions

5.1 Reuse of Stage 1 Contracts and Oracles

Stage 2 changes the execution architecture without intentionally changing the meaning of the data. The Java tokenizer is checked against the frozen Stage 1 token oracle, the metadata parser against the golden metadata records, and the datamart writer against the same canonical SHA-256 export. This gives a correctness reference while the implementation moves from one pipeline to independent services.

5.2 Choreography Instead of a Central Control Module

The project uses choreography with ActiveMQ rather than a central orchestrator. Each service owns one responsibility and reacts to events. The Feeder publishes an ingestion request, Ingestion publishes `BookDownloaded` when the files are complete, and Indexing publishes `BookIndexed` after the database commit.

This choice lets replicas become competing consumers without changing the workflow logic. It also buffers temporary differences in service speed: if Ingestion is faster than Indexing, completed books wait in `books.downloaded` rather than blocking the Ingestion process.

5.3 At-Least-Once Delivery and Idempotency

The messaging model is at least once, so duplicate delivery is possible. The project therefore makes consumers idempotent instead of assuming exactly-once delivery. Ingestion skips a book with an existing receipt, Indexing replaces the previous rows for the same book, and the Feeder counts distinct ids.

Broker consumers use transacted JMS sessions. The general sequence is:

```
receive -> do work -> commit storage
-> send next event -> session.commit()
```

If the transaction is not committed, the input message can be redelivered. The redelivery policy uses up to five redeliveries with delays of 1, 2, 4, 8, and 16 seconds before a repeatedly failing message reaches the DLQ.

5.4 Local Storage and SQLite

The Stage 1 datalake layout is kept because Stage 2 reads books by id. SQLite is kept for the searchable datamart because it provides transactions, a simple single-file deployment, and WAL mode for concurrent readers. The important limitation is that the database has one writer at a time. This is acceptable for Stage 2 but becomes a measured bottleneck when several Indexing replicas share the same file.

Atomic file writes and per-book claims protect Ingestion on the same host. These mechanisms depend on one local filesystem and one kernel, so they are assumptions that must change for Stage 3.

5.5 Replicas, Threads, and Single-Machine Deployment

Replicas and threads are treated as different forms of concurrency. Replicas are separate service processes; threads or JMS sessions add concurrency inside one process. On the Stage 2 host they all share the same physical resources, so adding workers may increase contention rather than throughput.

nginx is used as a round-robin gateway for Search replicas. The deployment scripts keep ports, replica counts, data paths, thread settings, JVM heap, and Indexing batch settings in one configuration so that the complete single-machine setup can be reproduced.

5.6 Functional Validation Before Benchmarking

A 20-book full-pipeline smoke test completed all 20 books, retrieved every id through the gateway, drained both work queues, and left the DLQ empty. A second test requested 100 books with two replicas of Ingestion, Indexing, and Search. One Indexing replica was killed after 70 books had been observed as indexed; the remaining replica completed all 100 books and the final queues were empty. These tests show that the event and replica design continues processing after a replica is lost.

6 Benchmarks and Results

Benchmarks are run at two levels. JMH microbenchmarks measure single components in one JVM (Section 6.1); integration benchmarks measure the deployed services and the broker together (Sections 6.2–6.8). Both run on the same host.

6.1 Microbenchmarks (JMH)

The component level is measured with JMH 1.37 before the integration experiments. Benchmark classes live under `src/test/java/.../benchmark` of each module, so they are not part of the deployed jars. Every benchmark uses 5 warm-up and 10 measurement iterations, one fork and a fixed heap (`-Xms4G -Xmx4G`); results are exported as CSV to `results/jmh/`. The host is the same laptop described in Table 10. Indexing benchmarks

were run on 28 October 2026 (commit `05bcfec`, `results/jmh/20261028-1138`) and the Search benchmark on 29 October 2026; the measured code (tokenizer, header parser, datamart writer, Indexing service and Search queries) has not changed since. Values are means with the JMH 99.9% error margin. Two golden books show the effect of size: book 8708 (about 2.7 k tokens) and book 36020 (about 129 k tokens, the largest golden book).

Table 7: JMH: cost of one book in the Indexing path (ms per book, single thread).

Operation	**Book 8708**	**Book 36020**
Parse header, tokenize, group positions, hash (no disk)	0.44 ± 0.01	23.7 ± 0.2
SQLite write of a new book, 1,000-book datamart	7.38 ± 0.20	85.6 ± 2.5
SQLite re-index (delete + write), 1,000-book datamart	13.3 ± 1.0	153.7 ± 39.9
SQLite re-index, 20-book datamart	5.05 ± 0.27	57.6 ± 0.6
SQLite re-index, 1,000-book datamart, 2 MiB page cache	16.4 ± 0.4	160.5 ± 2.3

Table 8: JMH: transaction batching and threads in one Indexing process.

Benchmark	**1 thread**	**2 threads**	**4 threads**	**8 threads**
Re-index, one transaction per book (books/s)	4.67 ± 0.66	4.89 ± 0.83	4.65 ± 0.89	4.77 ± 1.19
Re-index, batches of 20 books (books/s)	11.02 ± 1.18	11.22 ± 1.37	11.42 ± 0.94	10.92 ± 2.43

Table 9: JMH: Search query cost on the 1,000-book datamart (one thread, offset 0, limit 20).

Workload	**Query**	**ms/query**
single	`sea`	4.43 ± 0.72
multi	`sea ship`	5.26 ± 0.63
filtered	`sea ship`, author Stacpoole, language `en`, year 2017	3.40 ± 0.28

The microbenchmarks locate the cost of Indexing before any service runs. Writing to SQLite, not text processing, dominates: for the large book the write of a new book takes 85.6 ms against 23.7 ms of parsing and tokenization (about 78% of the work), and for the small book more than 90%. A re-index costs about 1.8 times a first insertion, because the previous rows of the book must be removed and the document frequencies corrected, and the write cost grows with the size of the index (57.6 ms with 20 books, 153.7 ms with 1,000 books for the same book). The larger page cache gives a modest gain (4–19%).

Batching is the effective optimisation: writing the 20 golden books as new books in one transaction costs 18.1 ± 0.2 ms per book against 27.2 ± 0.5 ms with one transaction per book (-34%), and the full Indexing path in one process re-indexes about 11 books/s in batches against 4.7 books/s with one transaction per book ($2.4\times$). Threads give no gain: 1 to 8 threads stay within the error margins, because the SQLite writer admits one transaction at a time and the write is most of the work, so the parallel part is small. These component results predict the integration results: I1 shows the same batching gain and I2

the same flat behaviour of consumer sessions. The JMH throughput benchmark re-indexes books that are already in the datamart, so its 11 books/s compares with the X0 re-index through the broker (10.0 books/s, Section 6.8): the message-driven path adds little to the cost of the work itself.

A single Search query costs 3–5 ms on one thread. These workloads differ in terms and selectivity, so they do not isolate the cost of one filter; the filtered query is probably cheaper because the filters reduce the candidate books to rank. Under concurrent HTTP load (Section 6.3) the mean latency is lower, mainly because the integration query set contains many low-frequency terms.

6.2 Integration Benchmark: Dataset, Method, and Measures

The integration benchmark uses the delivered Stage 2 code and a tier-1000 workspace. Every configuration is repeated three times and reported as mean ± standard deviation unless stated otherwise. The client, broker, services, and monitor all run on the same WSL machine. Before a run, state that could affect the experiment is reset; runs are rejected if a book is lost, an error is reported, a pipeline book is skipped as already ingested, or a message reaches the DLQ.

Table 10: Integration benchmark environment and baseline.

Item	**Value**
Host	Intel Core i7-1255U laptop, 12 logical CPUs visible to WSL, Windows + WSL 2 Ubuntu, 10 GiB WSL RAM.
Storage	WSL 2 ext4 virtual disk (1 TB) on the laptop's internal drive; datalake, datamart and broker store all on this disk.
Runtime	OpenJDK 21.0.12, code compiled for Java 17; nginx 1.28.3; 64–512 MiB JVM heap.
Code	Benchmark commit `19e2b1b`, 4 November 2026.
Data	1,000 Gutenberg books; 1,000-book datamart with 366,187 distinct terms.
Search workload	300 fixed queries from three document-frequency groups; 70% one term, 30% two terms; 22.7% empty answers.
Baseline	One replica per service; Indexing two consumer sessions, batch 20, 200 ms batch wait; HTTP threads 8–64; one nginx worker.
Search runs	Closed loop; 10 s warm-up; 60 s measured (X1 uses 5 s + 30 s).
Indexing runs	I1–I3 send 1,000 messages at once; I4 sends 200 books at controlled rates.

The main questions are whether Search scales with client concurrency and replicas, whether Indexing benefits from larger batches, more consumer sessions, or more replicas, whether Ingestion replicas increase end-to-end throughput, and how much Search and Indexing interfere when they share one machine.

6.3 Search Concurrency

Table 11: S1: one Search replica, direct port, increasing client concurrency.

Clients	Queries/s	Mean ms	p95 ms	p99 ms
1	1017 ± 4	0.98 ± 0.01	1.74 ± 0.04	2.37 ± 0.07
2	1829 ± 55	1.09 ± 0.04	2.09 ± 0.05	2.61 ± 0.14
4	3037 ± 149	1.31 ± 0.07	2.38 ± 0.09	3.09 ± 0.15
8	4373 ± 674	1.86 ± 0.31	3.66 ± 0.90	6.27 ± 3.00
16	6101 ± 177	2.62 ± 0.08	5.21 ± 0.20	7.88 ± 0.66
32	7875 ± 208	4.06 ± 0.11	8.64 ± 0.26	12.69 ± 0.43




Figure 2: Search throughput as client concurrency increases. Error bars show one standard deviation.




Figure 3: Search mean and p95 latency as client concurrency increases.

Throughput grows almost linearly only at the beginning. From 16 to 32 clients the number of clients doubles, but throughput grows by 29% while p95 latency grows by 66%. At 32 clients the Search process uses about seven logical CPUs at p90 and the WSL host is already heavily loaded. Search has no writer lock in this experiment, so the observed saturation is a CPU limit rather than a database serialization limit.

6.4 Search Replicas and Gateway Cost

Table 12: S2: Search replicas behind nginx.

Replicas	16 clients q/s	p95 ms	32 clients q/s	p95 ms
1	4353 ± 44	6.10 ± 0.10	5147 ± 102	10.54 ± 0.37
2	4019 ± 38	6.74 ± 0.08	4428 ± 192	12.86 ± 0.99
3	3647 ± 75	7.78 ± 0.28	4074 ± 125	14.46 ± 1.18




Figure 4: Search throughput behind nginx as replicas are added.

The gateway has a measurable cost on one host. With one replica and 16 clients, throughput drops from 6101 q/s on the direct port to 4353 q/s through nginx. More Search replicas reduce throughput further. The replicas share the same cores, so the additional JVMs, context switches, and per-process caches add work without adding CPU capacity. Replication is still useful for availability – the failure tests show that – but it is not a speedup mechanism on this machine.

6.5 Indexing: Batch Size, Sessions, and Replicas

Table 13: I1–I3: Indexing throughput at saturation.

Experiment	Throughput (books/s) per configuration			
I1 batch size	1: 6.08 ± 0.28	5: 11.23 ± 0.29	20: 18.37 ± 0.27	50: 22.30 ± 0.11
I2 consumer sessions	1: 17.69 ± 1.00	2: 18.39 ± 0.53	4: 16.19 ± 1.61	
I3 replicas	1: 17.92 ± 0.68	2: 14.51 ± 3.19	3: 10.10 ± 1.55	




Figure 5: Indexing throughput versus transaction batch size.




Figure 6: Indexing throughput versus consumer sessions in one process.




Figure 7: Indexing throughput versus Indexing replicas sharing one SQLite datamart.

Batching is the factor that clearly helps. Increasing the batch from 1 to 50 messages raises throughput by about 3.7 times because one transaction can commit many books and document-frequency updates are aggregated. More consumer sessions do not improve throughput, and more Indexing replicas make it worse. Three replicas achieve only about 56% of the throughput of one replica. The host is not CPU-saturated in this case: the replicas compete for the same SQLite writer and spend more time waiting for access to the shared database. This identifies the single datamart writer as the main pipeline bottleneck.

The very large request-to-completion latency in the saturated I1–I3 runs is mostly backlog time in the `books.downloaded` queue. It should not be interpreted as the processing cost of one book. That cost is measured separately below saturation.

6.6 Per-Book Indexing Latency

Table 14: I4: Indexing latency below saturation, batch size 20.

Sent b/s	Indexed b/s	Median ms	Mean ms	p95 ms	Queue ms
2	2.02 ± 0.01	366 ± 15	436 ± 44	937 ± 312	2 ± 1
5	5.02 ± 0.05	337 ± 5	446 ± 44	1162 ± 370	4 ± 3
10	10.08 ± 0.07	473 ± 32	690 ± 166	1695 ± 606	27 ± 16




Figure 8: Median, mean, and p95 per-book Indexing latency below saturation.

At low and moderate input rates the median is roughly 0.35 s per book. The configured 200 ms batch wait contributes to latency when traffic is too low to fill a batch immediately. Reducing that wait could improve low-load latency, while larger batches are better for throughput. The longer p95 tail varies with book size and runtime behaviour, but this experiment does not isolate one dominant cause.

6.7 Full Pipeline and Ingestion Replicas

Table 15: P1: full pipeline with a local Gutenberg mirror.

Ingestion replicas	Ingestion b/s	End-to-end b/s	Mean latency s	p95 s
1	27.67 ± 1.55	16.16 ± 0.41	12.7 ± 1.2	25.3 ± 1.1
2	30.71 ± 0.57	15.46 ± 0.09	15.8 ± 0.6	31.4 ± 0.3
4	35.14 ± 5.29	14.39 ± 0.71	19.5 ± 0.8	39.5 ± 1.1




Figure 9: Ingestion throughput and end-to-end searchable throughput as Ingestion replicas increase.

Ingestion itself improves modestly with more replicas: four replicas download and split about 27% more books per second than one. The complete pipeline does not improve. Books become searchable at roughly the speed at which Indexing can commit them, while the extra downloaded books wait in `books.downloaded`. The average broker time in that queue increases from about 10 to 17 seconds. The additional Ingestion JVMs also take CPU from Indexing, so end-to-end throughput falls slightly as more Ingestion replicas are added.

6.8 Search and Indexing Interference

Table 16: X1: Search under load while one Indexing replica re-indexes the 1,000 books of the full datamart (`BookDownloaded` events); X0: the same re-index without Search load.

	Search q/s	Search p95 ms	Search p99 ms	Indexing b/s
Search idle	6555 ± 417	4.96 ± 0.35	7.38 ± 0.65	–
Re-index only (X0)	–	–	–	10.01 ± 1.20
During re-index	4696 ± 247	8.23 ± 0.47	15.16 ± 1.09	9.08 ± 0.17




Figure 10: Search throughput with and without concurrent re-indexing.




Figure 11: Search p95 latency with and without concurrent re-indexing.

Concurrent Indexing lowers Search throughput by 28% and increases p95 by 66%. The effect in the other direction is small. The same re-index without Search load (X0) runs at 10.0 ± 1.2 books/s, against 9.1 ± 0.2 books/s under Search load: about 9% lower, which is within the run-to-run variation of X0. The I1 throughput (18.4 books/s) is not a valid baseline here: I1 inserts new books into an empty datamart, while a re-index first removes the existing rows of every book and is therefore slower. X0 was measured on 8 November 2026 on the same host and with the same service code; only the benchmark script changed. WAL mode lets readers and the writer operate concurrently, while the CPU measurements show strong competition for the same host resources: Search uses about 5.5 logical CPUs at p90 and Indexing about 3.3. Search is therefore the side that pays most of the cost of sharing the machine.

6.9 Coordination Cost and Resource Use

Below saturation, broker queue time is small compared with the work itself. In I4 a message waits about 2–27 ms in the broker, while one book needs roughly 350 ms from

publication to commit (median, including the 200 ms batch wait). In the full pipeline, `ingest.requests` waits about 1–2 ms. When the system is saturated, large queue times are a symptom of the downstream bottleneck rather than an expensive broker operation.

Table 17: Selected resource measurements, run 1 of each configuration; CPU p90 where applicable.

Configuration	Host CPU mean / p90	Main process CPU p90	Max RSS
S1, 32 clients	78% / 87%	Search 703%	Search 265 MiB
S2, 1 replica	72% / 80%	Search 646%, nginx worker 79%	Search 258 MiB
S2, 3 replicas	79% / 93%	Search 314 + 291 + 275%, nginx 75%	3 × about 240 MiB
I1, batch 20	24% / 34%	Indexing 380%, broker 43%	Indexing 1.0 GiB
I3, 3 replicas	26% / 57%	Indexing 301 + 266 + 291%	3 × about 1.0 GiB
P1, 4 Ingestion replicas	31% / 50%	Indexing 360%, Ingestion about 4 × 50%	Indexing 1.0 GiB; Ingestion about 4 × 320 MiB
X1 during re-index	37% / 78%	Search 547%, Indexing 326%	Indexing 958 MiB

The memory result reinforces the Indexing replica conclusion. One Indexing process can use about 1 GiB when the JVM heap and 256 MiB SQLite page cache are included. Three replicas therefore spend about 3 GiB while still reducing throughput.

6.10 Results Compared with Expectations

The central expectation in the architecture document was that SQLite's single writer would limit Indexing. The measurements confirm it more strongly than the initial design discussion suggested. Batching improves throughput substantially, but additional consumer sessions barely help and additional Indexing replicas make the result worse. The bottleneck is therefore not a shortage of workers; it is serialization on one shared database file.

The Ingestion result is also consistent with the architecture. Several replicas can increase the rate at which books are prepared, but that extra capacity is not useful while Indexing is slower. The broker makes this imbalance visible as queue growth without blocking Ingestion itself.

The Search result is less intuitive if replication is treated automatically as a performance optimization. One Search process already uses most of the available CPU at high client concurrency. Adding two more processes on the same cores therefore adds overhead and lowers throughput. This is an important distinction for Stage 3: replication can scale Search only if it also adds physical CPU capacity, which requires separate machines or nodes.

Finally, the event broker is not the observed bottleneck. At non-saturated rates its queue delay is a small fraction of one book's processing time, and its CPU use is about half of one logical CPU at the measured Indexing rate. At saturation, long queue times indicate that work is waiting for Indexing rather than that ActiveMQ is slow.

6.11 Threats to Validity

All integration measurements were collected on one laptop under WSL 2. Replicas therefore share the same physical CPU, memory, and disk. This is the intended Stage 2 environment, but it means the replication results cannot be generalized to a cluster where every replica

has independent hardware. In particular, the conclusion that Search replicas reduce throughput applies to this single-host experiment, not to multi-node Search.

The benchmark client also runs on the same machine as the services. Its CPU consumption is included in host load and can reduce the capacity available to the system being measured. CPU frequency and thermal behaviour of the hybrid laptop processor add run-to-run variability. Every configuration is repeated three times, but three repetitions are still a modest sample.

The local Project Gutenberg mirror removes WAN latency and server rate limiting. This is necessary for a reproducible Ingestion experiment, but the measured Ingestion throughput describes local CPU, parsing, and disk work rather than real Internet download speed.

The resource monitor reads Linux `/proc`. Under WSL it does not include all Windows host activity, so the CPU and memory tables describe the Linux environment visible to the processes. The load client itself is not shown as a separate row in the summary table even though its CPU use is part of the host figures.

Some causes remain grouped together. The long I4 p95 tail may come from large books, garbage collection, or SQLite checkpoints; the benchmark does not separate them. Likewise, WAL growth was not measured independently during the Search/Indexing interference experiment. The gateway was measured with one nginx worker, so no conclusion is made about a different gateway configuration.

7 Conclusions and Future Improvements

Stage 2 transforms the Stage 1 storage layer into a service-oriented search system while preserving the same data semantics. Ingestion, Indexing, Search, the Feeder, and the broker are independent processes, and the complete system can run with several replicas on one machine. The shared contracts and Stage 1 oracles make it possible to add this concurrency without changing the meaning of the tokenizer, metadata, or positional index.

The event-driven design works as intended for failure handling. Transacted acknowledgements, persistent broker messages, idempotent consumers, atomic datalake writes, and SQLite transactions allow work to be repeated safely. Functional tests show that the full pipeline completes after an Indexing replica is killed, and the final combined API/event validation passes all 32 checks.

The performance results identify one clear limit. **Indexing is the bottleneck of the current pipeline, and the bottleneck inside Indexing is the single SQLite writer.** The JMH microbenchmarks show why: writing to SQLite is 78–94% of the cost of one book, and threads inside one process do not change throughput. Batching improves throughput from about 6 to 22 books/s, but more Indexing replicas reduce it. Ingestion can prepare books faster than Indexing can publish them, so extra Ingestion replicas only build a longer queue. Search reaches several thousand queries per second, but on one host additional Search replicas do not create new compute capacity and therefore do not improve throughput.

The Stage 2 results also show that replication has two different purposes. On one machine it gives fault tolerance: a remaining replica can continue after another process dies. It

does not necessarily give performance. Performance scaling requires removing the shared resource that serializes the work or adding hardware resources that replicas can actually use independently.

7.1 Stage 3 Plan

Stage 3 should preserve the logical pipeline and contracts but remove assumptions that are valid only because all processes currently share one host.

Table 18: Single-machine assumptions that must change in Stage 3.

Stage 2 assumption	**Why it works now**	**Stage 3 direction**
`localhost` service addresses	Every process runs inside one machine.	Real node addresses plus service discovery or explicit deployment configuration.
Shared local datalake	Indexing can open files written by any Ingestion replica.	Shared/distributed storage, or transfer/ownership rules that make book data reachable across nodes.
OS file locks	All Ingestion replicas share one kernel and filesystem.	Distributed ownership/partitioning or another cross-node coordination mechanism.
One SQLite datamart file	One host can share one WAL database between writer and readers.	Partitioned index or database service that supports parallel writers and remote readers.
Embedded single broker	One local broker is sufficient for Stage 2.	Network-reachable broker deployment with failure and unavailable-node handling.
One nginx gateway	All Search replicas are local upstreams.	Gateway/load balancer that routes to Search replicas on different nodes and handles unavailable nodes.
Local process manager	PIDs and `/proc` describe every component.	Cross-machine deployment, health checks, and monitoring with node identity.

Task distribution should also become explicit at cluster level. The current ActiveMQ queues already provide competing-consumer distribution for Ingestion and Indexing, so their logical interface can remain similar, but the storage behind them cannot rely on one local directory. Search is the simpler case: replicas are read-only, so placing them on separate machines would directly add CPU capacity once they can access a suitable distributed or replicated index.

Unavailable nodes must be treated as a normal operating condition rather than as a special test. The Stage 2 event rules already cover redelivery after a consumer disappears; Stage 3 should extend that idea to node discovery, storage access, gateway routing, and broker availability. The main architectural change is therefore not the sequence of the search pipeline. It is the removal of single-host shared state – especially the local datalake, the SQLite single file, and the embedded broker – that currently prevents the measured replicas from becoming true distributed capacity.