

SAMPLE DOCUMENT - FICTITIOUS DATA FOR DEMONSTRATION ONLY

Process Datasheet - Separator V-101

Project: Demo Gas Plant Expansion (fictitious). Document PDS-V-101 Rev B.

Item / Tag No.	V-101
Service	HP Gas/Condensate Separator
Fluid	Natural gas, hydrocarbon condensate, produced water
Lethal service	No
Corrosive service	Yes (wet CO ₂)
Specific gravity	0.72
Normal liquid level	900 mm from bottom tangent

Operating conditions

Case 1 minimum operating pressure	8 barg
Case 1 maximum operating pressure	12 barg
Case 1 minimum operating temperature	5 °C
Case 1 maximum operating temperature	85 °C
Case 2 minimum operating pressure	0 barg
Case 2 maximum operating pressure	3 barg
Case 2 minimum operating temperature	-20 °C
Case 2 maximum operating temperature	40 °C

Design conditions

Internal design pressure	15 barg
Design temperature	120 °C
External design pressure	Full vacuum
Temperature at external design pressure	120 °C
MDMT	-29 °C
MDMT coincident pressure	15 barg
MDMT due to	Ambient temperature

Overpressure protection: pressure relief valve PSV-101 set at design pressure.

Note: depressurisation case 2 is the start-up after blowdown.