


# Module 11

## Principal Component Analysis (PCA)

---



Prof. Pedram Jahangiry






# Class Modules


- Module 1- Introduction to Machine Learning
- Module 2- Setting up Machine Learning Environment
- Module 3- Linear Regression (Econometrics approach)
- Module 4- Machine Learning Fundamentals
- Module 5- Linear Regression (Machine Learning approach)
- Module 6- Penalized Regression (Ridge, LASSO, Elastic Net)
- Module 7- Logistic Regression
- Module 8- K-Nearest Neighbors (KNN)
- Module 9- Classification and Regression Trees (CART)
- Module 10- Bagging and Boosting
- **Module 11- Dimensionality Reduction (PCA)**
- Module 12- Clustering (KMeans – Hierarchical)





# Road map





# Topics

## Part I



1. Unsupervised Machine Learning
2. Principal Component terminology

## Part II

1. Principal Components Analysis (PC)
2. Scree plot

## Part III

1. Why PCA? Pros and Cons!
2. Kernel PCA
3. Applications of PCA





# Part I

1. Unsupervised Machine Learning
2. PC terminology

# → Unsupervised Learning


- **Unsupervised learning** is a type of machine learning where the algorithm is **not given any labeled** training data.
- The goal is to discover the **underlying patterns** and find groups of samples that behave similarly. **Find something interesting!**
- The two main types of unsupervised learning algorithms are:
  - 1) **Dimension reduction algorithm**
    - Principal Component Analysis
  - 2) **Clustering: group similar data**
    - K-Mean
    - Hierarchical





# Motivation

- 1) Dimension reduction algorithm: Principal Component Analysis
- 2) Clustering techniques: K-Mean for example









# Eigen things!


- **Eigenvector** does not change direction in a transformation.
- In this mapping, the **blue arrow** is eigenvector (why?)
- Its **eigenvalue** = 1 (why?)
- For a square matrix A, an Eigenvector and Eigenvalue are defined as follow:




Transformation  
matrix      Eigenvalue

$$\vec{A}\vec{v} = \lambda\vec{v}$$

Eigenvector



What is a transformation matrix?









# PC terminology (connecting PC and Eigenthings)

- The **eigenvectors** and **eigenvalues** of a **covariance matrix** represent the “core” of a PCA
- Consider the following data points:



If you want to reduce the dimension of the data to 1, which PC would you drop?



- We want to find a **direction(s)** in the data set that **explain the most variation**. So, our transformation matrix will be the **covariance matrix**.
- The **principal components** (**eigenvectors** of the covariance matrix) determine the **directions** of the new feature space, and the **eigenvalues** determine their **magnitude**. In other words, the eigenvalues explain the variance of the data **along the new feature axes**.

# → PC terminology (PC definition)

In summary:

- **Principal components** are vectors that define a **new coordinate system** in which the first axis goes in the direction of the highest variance in the data.
- The second axis is orthogonal to the first one and goes in the direction of the second highest variance in the data.







Figure 9.7: PCA: (a) the original data; (b) two principal components displayed as vectors; (c) the data projected on the first principal component. | Source: [The hundred-page machine learning book](#)




# PC terminology (the objective function)

- **Projection errors:** The perpendicular distance (Euclidian) between the data point and a Principal Component.
- **Spread:** Variation of the data along Principal component.
- In PCA the goal is to **minimize the projection errors** (or equivalently maximize the spreads)




## Part II


1. Principal Component Analysis (PCA)
2. Proportion Variance Explained
3. Scree plot



# Principal Component Analysis (PCA)

- **Dimension reduction** aims to represent a dataset with many typically correlated features by a smaller set of features that still does well in describing the data.
- When **many features** in a dataset, **visualizing** the data or **fitting models** to the data may become extremely complex and “noisy”.
- **Principal components analysis (PCA)** is used to summarize or transform highly correlated features of data into a few main, **uncorrelated components**.
- The PCA algorithm **orders the eigenvectors from highest to lowest** according to their **usefulness** in explaining the **total variance** in the initial data (i.e., eigenvalues)





# PCA details

- The PC1 of a set of features  $X_1, X_2, \dots, X_p$  is the **normalized** linear combination of the features that has **the largest variance**.

$$PC_1 = \phi_{11}X_1 + \phi_{21}X_2 + \dots + \phi_{p1}X_p \quad \text{where } \sum_{j=1}^p \phi_{j1}^2 = 1$$

- The elements  $\phi_{11}, \dots, \phi_{p1}$  are referred to as **loadings** of PC1.
- Note that the X features are **standardized (why?)**
- The loading vector  $\phi_1$  defines a direction in feature space along which the data vary the most i.e., maximizing the variance in that direction!

$$\underset{\phi_{11}, \dots, \phi_{p1}}{\text{maximize}} \frac{1}{n} \sum_{i=1}^n \left( \sum_{j=1}^p \phi_{j1} x_{ij} \right)^2 \quad \text{subject to } \sum_{j=1}^p \phi_{j1}^2 = 1$$

# USA arrests data: Biplot


- USA arrests data contains the number of arrests per 100k residents for each of the 50 states.
- The **features** are murder, assault, rape and urban population.
- PCA was performed after **standardizing** each feature! The loadings are as follow:

	PC1	PC2
Murder	0.5358995	-0.4181809
Assault	0.5831836	-0.1879856
UrbanPop	0.2781909	0.8728062
Rape	0.5434321	0.1673186

- Biplot** displays both the PC **scores** and PC **loadings**.

Source: ISLR first edition



	Murder	Assault	UrbanPop	Rape
California	0.2782682	1.262814	1.7589234	2.067820
Florida	1.7476714	1.970778	0.9989801	1.138967
New Hampshire	-1.3059321	-1.365049	-0.6590781	-1.252564





# ➔ Another interpretation of PCA


- PCA find the **hyperplane closest** to the observations!
- What is the difference between **PCA** and linear regression then?





# Scree plot

- **Scree plot** shows the proportion of total variance in the data explained by each principal component. This is also called **Proportion Variance Explained (PVE)**
- The **PVEs sum to one**. Sometimes they are displayed as **cumulative PVEs**.



- What is the **optimal number of PCs** here?

# Part III

Why PCA? Pros and cons!

Kernel PCA

Applications of PCA



# PCA's Pros and Cons

---

## Pros:

- Reducing the number of features to the **most relevant predictors** is very useful in general.
- Dimension reduction **facilitates** the data visualization in two or three dimensions.
- **Before** training another supervised or unsupervised learning model, it can be performed as part of EDA to **identify patterns** and detect **correlations**.
- Machine learning models are **quicker to train**, tend to reduce overfitting (by avoiding the curse of dimensionality), and are easier to visualized if provided with lower-dimensional datasets.




## Cons:

- Hard to interpret!
- Standard PCA is limited to linear transformations and may not capture the intrinsic structure of non-linear data.




# Kernel Trick!

- Non-linearly separable data
- We need a non-linear decision boundary!
- Mapping to higher dimensional space, finding the hyper plane and projecting it back to low dimensional space can be computationally expensive.
- Solution: Kernel Trick!






# The Gaussian RBF Kernel (Radial Basis Function)




# ➔ Most common types of Kernel


Linear Kernel




The Gaussian RBF Kernel



Polynomial Kernel



Sigmoid Kernel








# Kernel PCA

- **Kernel PCA** is an advanced form of PCA that utilizes kernel methods to enable effective dimensionality reduction in datasets with **complex, non-linear structures**.
- Process:
  - **Kernel Transformation:** Apply a kernel function (e.g., RBF, polynomial, sigmoid) to the original data, creating a kernel matrix that represents similarities between all data points.
  - **Dimensionality Reduction:** Perform PCA on the kernel matrix to extract principal components in the transformed feature space, capturing major variance in data according to non-linear relationships.



# ➔ Applications of PCA



- Consider a hypothetical Diversified Large Cap (**DLC**) 500 and Very Large Cap (**VLC**) 30:
  - DLC 500 can be thought of as a diversified index of **500 large-cap companies** covering all economic sectors
  - VLC 30 is a more concentrated index of the **30 largest publicly traded companies**.
- The dataset consists of index prices and more than **2,000** fundamental and technical **features**
- **Multi-collinearity** among the features is **inevitable!**
- To mitigate the problem, PCA can be used to capture the information and **variance** in the data.

## THE FACTOR ZOO



# ➔ Applications of PCA



- The following **scree plots** show that of the **20 principal components** generated, **the first 3 together** explain about 90% of the variance of DLC 500 and 86% of the VLC 30.





# Applications of PCA (Data visualization)



- PCA can be **fed into** other **unsupervised or supervised learning models!**
- Using PCA with an unsupervised model like K-Mean **clustering**:





# Applications of PCA (Kernel PCA)

- What if we want to use a linear classifier (regressor) but the data is **non-linearly separable**?
- Solution: **Kernel PCA**
- Kernel PCA uses a kernel function to project dataset into a higher dimensional feature space, where it is **linearly separable**. (without explicitly going to higher dimensions)
- Using PCA with a supervised learning model like logistic regression:





# Class Modules

- ✓ Module 1- Introduction to Deep Learning
- ✓ Module 2- Setting up Machine Learning Environment
- ✓ Module 3- Linear Regression (Econometrics approach)
- ✓ Module 4- Machine Learning Fundamentals
- ✓ Module 5- Linear Regression (Machine Learning approach)
- ✓ Module 6- Penalized Regression (Ridge, LASSO, Elastic Net)
- ✓ Module 7- Logistic Regression
- ✓ Module 8- K-Nearest Neighbors (KNN)
- ✓ Module 9- Classification and Regression Trees (CART)
- ✓ Module 10- Bagging and Boosting
- ✓ Module 11- Dimensionality Reduction (PCA)
- Module 12- Clustering (KMeans – Hierarchical)

