北京大学
PEKING UNIVERSITY

Deep Research Agent：

Data + loop/context + training + eval/reward

王一米

2026.9.23

研究的问题

北京大学 PEKING UNIVERSITY

1.任务和数据构建

2.训练范式

3.Agent loop设计和上下文管理

4.评测和奖励

数据构造：什么样的数据能训练出复杂搜索能力？

北京大学 PEKING UNIVERSITY

WebSailor: Navigating Super-human Reasoning for Web Agent

ReAct框架；Search+vist两种工具

$$\mathcal{H}_T = (\tau_0, a_0, o_0, \ldots, \tau_i, a_i, o_i, \ldots, \tau_T, a_T),$$


Tongyi Lab, Alibaba Group

种子实体 → 搜索+浏览发现相关实体并抽取关系 → 建知识图谱（wikipedia）

抽取局部子图 → 判断子图是否同构，并收集不同构的子图（链式、多分支、环状等）

按节点结构角色均匀出题：中心节点、链条端点、连接两分支的节点——不同角色对应不同推理任务

注入不确定性提高难度：把实体名/日期/数值替换成间接模糊描述，迫使解题者消歧→假设→搜索→交叉验证




数据构造：什么样的数据能训练出复杂搜索能力?

北京大学 PEKING UNIVERSITY

WebSailor: Navigating Super-human Reasoning for Web Agent

Tongyi Lab , Alibaba Group



Examples of Generated Questions

Question: *There was an early Christian poetic hymn composed by a late antique writer who passed away around the mid-5th century. The year of this writer's death coincides with the last year of a scientific chronology that reconstructs environmental conditions from several centuries before the modern era. What is the name of this chronology?*

Answer: *Estimated Tree-Ring Chronology: 300-450 A.D.*

Question: *A musical piece closely associated with a prominent South American capital features lyrics written by a notable figure who was later recognized with a distinguished local civic honor in the early 21st century. The composition's melody was created by a musician who received formal training at a respected arts institution in western Colombia. What is the name of this musical piece?*

Answer: *the Rue de Rivoli*

数据构造：什么样的数据能训练出复杂搜索能力?

北京大学 PEKING UNIVERSITY


REDSearcher: A Scalable and Cost-Efficient Framework for Long-Horizon Search Agents

REDSearcher Team
Project Page: redsearchagent.github.io


搜索任务的难度不能简单用hop数衡量，而是通过两种指标量化问题的复杂度：

推理结构复杂度（通过tree width控制）+ 证据分散程度（解决问题的信息分布在最少多少个文档）


将关键事实改写为工具可解析的约束条件（这些约束无法仅通过文本检索满足），例如将地名转换为地图工具可解析的路径/距离约束，或将命名实体替换为需要图像理解能力的视觉线索



Question: If D represents David, who is A?



Question: In which 1990 gangster film did the director cast his own daughter as the main character's daughter?



Identify Person A: A tech co-founder ousted in a mid-80s power struggle, he launched a new venture whose core technology was later bought out by his original company. This acquisition became the key to his regaining total control of the firm.

训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Scaling Agents via Continual Pre-training


Tongyi Lab , Alibaba Group

传统的后训练承担两个职责：

- 建立能力：学会规划、调用工具、处理环境反馈。
- 规范行为：按照高质量示范或奖励要求完成任务。

轨迹很长+很贵，sft很难覆盖巨大的action space，rl可以探索但是只有trajectory-level稀疏反馈

先把普通 base model 变成 agentic base model，再进行 agent alignment



训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Scaling Agents via Continual Pre-training

Tongyi Lab , Alibaba Group

低成本、大规模制造适合pretraining 的 agent 数据【1】


First-order Action Synthesis（FAS）


- 历史搜索/网页访问结果、Wikipedia，以及以前 RL/SFT 过程中废弃的 trajectory
- 得到 {entity + 大量与这个 entity 有关的 knowledge statements}（不同于websailor的显式建构graph）
- 合成两类action数据：**Planning Action Synthesis** + **Reasoning Action Synthesis**

Question → reasoning / planning → next tool call（不执行）

Q → 不给证据，让模型先拆问题、猜测和推理 → A_1

Q + 真正需要的 knowledge → 修正 A_1 → A2





训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Scaling Agents via Continual Pre-training

Tongyi Lab, Alibaba Group




Figure 5: Comparison of high-orider action synthesis data and the original trajectory.

低成本、大规模制造适合pretraining 的 agent 数据【2】

Higher-order Action Synthesis（HAS）

在每一个 state C_k上，模型额外生成 N个可能的下一步 action，于是每一步从“唯一正确轨迹”变成：

当前 state 下有 N+1 个可能 action

→ 比较这些 action

→ 选择原 trajectory 的 action

→ 接收真实environment response

思想自由 兼容并包

训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Scaling Agents via Continual Pre-training

Tongyi Lab , Alibaba Group

Base Model	SFT Data	BrowseComp-en	BrowseComp-zh	GAIA	HLE
Qwen3-30B-A3B-Base	SFT-A	26.9	29.8	67.0	23.5
AgentFounder-30B-Base	SFT-A	**31.4**	**35.6**	**72.8**	**30.4**
Relative Δ	SFT-A	+4.5	+5.8	+5.8	+6.9
Qwen3-30B-A3B-Base	SFT-B	28.6	35.6	71.8	27.0
AgentFounder-30B-Base	SFT-B	**39.9**	**43.3**	**72.8**	**31.5**
Relative Δ	SFT-B	+11.3	+7.7	+1.0	+4.5
Qwen3-30B-A3B-Base	SFT-C	24.5	36.7	68.9	27.9
AgentFounder-30B-Base	SFT-C	**38.8**	**44.3**	**71.8**	**28.9**
Relative Δ	SFT-C	+14.3	+7.6	+2.9	+1.0

AgentFounder Base 在 A/B/C 三种 SFT 配方下基本都更好：

先cpt再sft+rl，效果好于仅sft+rl

训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Scaling Agents via Continual Pre-training

Tongyi Lab, Alibaba Group

Strategy	BrowseComp-en		BrowseComp-zh		GAIA	
	Pass@1	Pass@3	Pass@1	Pass@3	Pass@1	Pass@3
AgentFounder Stage 1 Only	31.4	49.9	34.3	50.5	69.9	81.6
AgentFounder Stage 1 & 2	35.5	52.0	37.2	58.5	72.8	82.5
Relative Δ	**+4.1**	**+2.1**	**+2.9**	**+8.0**	**+2.9**	**+0.9**

Table 4: Evaluation of the effectiveness of the two-stage AgentFounder training strategy.

Data	Tokens	BrowseComp-en		BrowseComp-zh		GAIA	
		Pass@1	Pass@3	Pass@1	Pass@3	Pass@1	Pass@3
Non CPT	0B	26.9	38.0	29.8	45.3	67.0	75.7
FAS	50B	31.4	49.9	37.0	54.3	72.8	80.6
FAS+HAS	50B	31.4	50.1	40.1	54.7	69.9	82.5
Relative Δ	/	0.0	**+0.2**	**+3.1**	**+0.4**	**-2.9**	**+1.9**

消融：

32k+128k效果更好

Cpt的主要提升来自FAS

训练方法：CPT+SFT+RL

Scaling Agents via Continual Pre-training

Tongyi Lab , Alibaba Group




Figure 6: Scaling Law Exploration for Agentic Capabilities. (a) Performance across model sizes ranging from 1B to 30B-A3B parameters. (b) Impact of training data volume from 0B to 315B samples on task performance. Both axes are in log scale.

Scaling：

模型越大，Agentic CPT 带来的 agent 能力越强

Agentic CPT 数据量继续增加时，性能仍然持续提升，而且呈近似对数型增长

训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

REDSearcher: A Scalable and Cost-Efficient Framework for Long-Horizon Search Agents

REDSearcher Team
Project Page: redsearchagent.github.io



Stage I，32K context：先训练 atomic capabilities

Intent-anchored Grounding：给很多相关和不相关网页，让模型根据 search intent 从噪声里找真正需要的信息；

Hierarchical Planning：区分可以明确解决的 concrete goal，和模糊、需要后续逐渐缩小范围的goal。


Stage II，128K context：再学真正的 Agent interaction（模拟工具、本地搜索环境）

训练方法：CPT+SFT+RL

北京大学 PEKING UNIVERSITY

Iris: Climbing to the Search Frontier

AllSpark Team




思考 → （工具1）搜索/抓网页 → （工具2）摘要后的结果 → 再思考”，一直到最终答案
Sft起点：trajectory-level 的 coarse filtering，要求最终答案正确、没有退化行为，而且搜索深度足够
Sft起点：turn-level fine filtering，用 LLM judge 给每个 assistant turn 打 KEEP/MASK，

SFT1→RL1→SFT2→RL2→...
选择rl中的稀有成功轨迹（0，0.5）中长度最短的用于下一轮sft

Agent Loop：从预算控制到状态维护

AgentFold: Long-Horizon Web Agents with Proactive Context Management



每次把历史全部追加，网页内容/失败搜索/重复信息越来越多

每次都重新总结，压缩内容导致容易丢失细节

保留不同粒度的summary：模型决定信息保留到多细

Agent Loop：从预算控制到状态维护

AgentFold: Long-Horizon Web Agents with Proactive Context Management

Tongyi Lab , Alibaba Group

每轮：

- 输入第t步的上下文： $C_t = (Q, T, S_{t-2}, I_{t-1})$ ，表示问题+工具+覆盖「1，t-2」步的摘要序列+第t-1步的完整交互记录


  这里摘要 $S_{t-2} = (s_{x_1,y_1}, s_{x_2,y_2}...)$ 共同覆盖第一步到第t-2步的交互历史，注意一个摘要可以覆盖多步也可以覆盖单步，

  $I_{t-1} = (e_{t-1}, a_{t-1}, o_{t-1})$ 表示上一步动作执行的内容

- 折叠和行动： $R_t = (th_t, f_t, e_t, a_t)$ ：思考，折叠指令，简短解释，行动

- 把t-k步～t-1步的合并成summary；或者将最近交互与此前的一串摘要共同合并，替换为一个新的粗粒度摘要；或者仍然保留t-1步的完整交互以待后续合并。

训练：sft，数据是 $D = \{(C_t, R_t^*\}^N$ ，即多个"看到这样的任务状态，应该如何共同产生折叠决策和下一步行动。"



Agent Loop：从预算控制到状态维护

北京大学 PEKING UNIVERSITY

AgentFold: Long-Horizon Web Agents with Proactive Context Management

Tongyi Lab , Alibaba Group

Question
I am looking for a specialty food shop that has at least one location in both Mexico and California as of December 1, 2023. One of the locations in Mexico is a 7.8-kilometer walk from a McDonald's located at Anillo Perif. 137, Polanco, Polanco I Secc, Miguel Hidalgo, 11510 Ciudad de México, CDMX, Mexico as of December 1, 2023. The location in California is located within a market that held a Thanksgiving Floral Arrangement Class event in November 2023 as of December 1, 2023. What is the name of the specialty food shop?

Previous Steps
[Compressed Step 0] <Compressed summary omitted for visualization>
[Compressed Step 1 to 2] <Compressed summary omitted for visualization>
[Compressed Step 3] <Compressed summary omitted for visualization>
[Compressed Step 4] <Compressed summary omitted for visualization>
[Compressed Step 5] <Compressed summary omitted for visualization>
[Compressed Step 6 to 8] Steps 6-8 focused on obtaining GPS coordinates for the McDonald's at Blvd. Manuel Ávila Camacho 137 in Polanco, Mexico City, to define the 7.8 km radius around it. <Compressed summary omitted for visualization> **The coordinates remain unknown, and the cross-border shop investigation is preliminary.**
[Compressed Step 9] <Compressed summary omitted for visualization>
[Compressed Step 10] <Compressed summary omitted for visualization>
[Compressed Step 11] <Compressed summary omitted for visualization>
[Compressed Step 12] <Compressed summary omitted for visualization>
[Compressed Step 13] <Compressed summary omitted for visualization>
[Compressed Step 14] <Compressed summary omitted for visualization>
[Compressed Step 15] <Compressed summary omitted for visualization>
[Step 16] <lengthy web page content omitted for visualization>

<think> <omitted for visualization> </think>
<folding>
{"range": [6, 16], "summary": "**Multiple attempts (Steps 6-16)** to obtain GPS coordinates for the McDonald's at Blvd. Manuel Ávila Camacho 137, Polanco, Mexico City, via searches and visiting Infobelpro, Yelp, and TripAdvisor pages were unsuccessful. **No coordinates were found, hindering identification of the 7.8 km radius around the McDonald's.**"}
</folding>

Intermediate steps are folded into one conclusion

<motivation>
Since direct methods to retrieve the GPS coordinates have failed, I am **shifting focus to identifying the specialty food shop by searching for potential candidates that operate in both Mexico and California**. This includes verifying if known candidates like Bazaar del Mundo have a Mexican location, and checking specific Polanco shops (e.g., Amado Pasteleria, Le Fromager) for California presence, as well as exploring concepts linking Northgate Market to cross-border operations.
</motivation>

Dynamically switch to other search directions

<tool_call>
{"name": "search", "arguments": {"query": ["Bazaar del Mundo Mexico location", "specialty food shop Polanco Mexico California locations", "Northgate Market specialty food shop California Mexico", "Amado Pasteleria California", "Le Fromager California"]}}
</tool_call>

Agent Loop：从预算控制到状态维护


北京大学 PEKING UNIVERSITY

AgentFold: Long-Horizon Web Agents with Proactive Context Management


Tongyi Lab, Alibaba Group

Agent	BrowseComp	BrowseComp-ZH	WideSearch	GAIA
Proprietary Agents				
Claude-4-Sonnet	14.7	22.5	**62.0**	68.3
Claude-4-Opus (anthropic, 2025)	18.8	37.4	-	-
OpenAI-o4-mini (OpenAI, 2025b)	28.3	44.3	-	-
OpenAI-o3 (OpenAI, 2025b)	49.7	**58.1**	60.0	**70.5**
OpenAI Deep Research (OpenAI, 2025a)	**51.5**	42.9	-	67.4
Open-Source Agents				
WebThinker-32B Li et al. (2025c)	2.8	7.3	-	48.5
WebDancer-32B (Wu et al., 2025)	3.8	18.0	-	51.5
WebSailor-32B (Li et al., 2025b)	10.5	25.5	-	53.2
WebSailor-72B (Li et al., 2025b)	12.0	30.1	-	55.4
ASearcher-Web-32B (Gao et al., 2025)	5.2	15.6	-	52.8
MiroThinker-32B-DPO-v0.2 (MiroMind AI Team, 2025)	13.0	17.0	-	64.1
WebExplorer-8B (Liu et al., 2025)	15.7	32.0	-	50.0
DeepDive-32B (Lu et al., 2025)	14.8	25.6	-	-
DeepDiver-V2-38B (OpenPangu Team, 2025)	13.4	34.6	-	-
Kimi-K2-Instruct-1T (Team et al., 2025)	14.1	28.8	59.9	57.3
GLM-4.5-355B-A32B (Zeng et al., 2025)	26.4	37.5	-	66.0
DeepSeek-V3.1-671B-A37B (DeepSeek Team, 2025)	30.0	**49.2**	-	63.1
AgentFold-30B-A3B (Ours)	**36.2**	47.3	**62.1**	**67.0**


Sub-linear growth



(a) Growth curve of AgentFold's context



(b) Number of blocks in AgentFold's context



Sub-linear growth

Agent Loop：从预算控制到状态维护

北京大学 PEKING UNIVERSITY


AREX: Towards a Recursively Self-Improving Agent for Deep Research

AREX Team

Beijing Academy of Artificial Intelligence (BAAI)

上下文不是要压缩的对象"，是研究状态的数据结构

- 内层循环解题+整合证据+判下一步；
- 外层循环判断结构化结果相对原问题是否解决，决定 finish / refine（更新剩余问题）/ restart。
- 状态里显式维护：已验证发现及来源、当前候选、负面证据、否决的内容。



Agent Loop：从预算控制到状态维护


AREX: Towards a Recursively Self-Improving Agent for Deep Research

research state 的递归自我改进。
上下文不是要压缩的对象"，是研究状态的数据结构

AREX Team

Beijing Academy of Artificial Intelligence (BAAI)

- 内层循环解题+整合证据+判下一步；
- 外层循环判断结构化结果相对原问题是否解决，决定 finish / refine（更新剩余问题）/ restart。
- 状态里显式维护：已验证发现及来源、当前候选、负面证据、否决的内容。



Agent Loop：从预算控制到状态维护

北京大学 PEKING UNIVERSITY

AREX: Towards a Recursively Self-Improving Agent for Deep Research

research state 的递归自我改进。
上下文不是要压缩的对象"，研究状态的数据结构是

AREX Team

Beijing Academy of Artificial Intelligence (BAAI)



- 内层自主决定压缩为结构化research state
- 80%主动压缩，中位数25k远小于128k
- 触发原因主要是revise search strategy
- 压缩更新最多：Unresolved constraints，next-plan，Rejected candidates

Update usage		Call trigger		Update content	
Metric	**Value**	**Category**	**Share**	**Category**	**Share**
Cases w/ update	80.3%	Revise search strategy	66.9%	Verified findings	72.1%
Upper bound	128,000	Reject candidate	13.6%	Current candidates	39.2%
Min. context tokens	3,788	Verify evidence/answer	5.3%	Unresolved constraints	95.5%
Mean context tokens	25,721	Identify new lead	7.2%	Validity concerns	14.1%
Median context tokens	25,386	Summarize progress	6.4%	Rejected candidates	81.5%
Max. context tokens	128,591	Other	0.6%	Next-step plan	96.4%

先mid-training形成稳定的agentic behavior
再逐步增加 reasoning提升复杂推理能力
Sft和rl都给key step更多loss/奖励

Training setting	Accuracy
Replace multi-round capability training by mixed training	77.5
Replace key-step focused supervision by random-step replay	74.1
Replace step-aware RL by standard GRPO	79.4
Full AREX	82.5

Agent Loop：从预算控制到状态维护

北京大学 PEKING UNIVERSITY

AREX: Towards a Recursively Self-Improving Agent for Deep Research

research state 的递归自我改进。
上下文不是要压缩的对象"，研究状态的数据结构是

AREX Team

Beijing Academy of Artificial Intelligence (BAAI)

两个机制共同作用：acu上下文update + 外层循环

Method	Setting	Acc.
AREX w/o ACU	w/o outer loop	59.6
	w/ outer loop	69.8
AREX w/ ACU	w/o outer loop	71.4
	w/ outer loop	82.5


Table 3: Effect of ACU in the inner research loop and the outer self-improvement loop. Accuracy is measured on BrowseComp.

评测和奖励

北京大学 PEKING UNIVERSITY

DR Tulu: Reinforcement Learning with Evolving Rubrics for Deep Research

- 给验证者特权信息制造生成-验证鸿沟：多次搜索 rollout 检索回的外部知识（支撑事实核查）+ 同题多个独立采样回答（提供相对质量对比）。
- 用方差管理 rubric buffer：每步给所有 rollout 打分后，方差为 0 的条目直接删（对 GRPO 组内相对优势零贡献），按标准差降序留 top-5，定长 buffer 同时解决评估成本和信号质量。




评测和奖励

DR Tulu: Reinforcement Learning with Evolving Rubrics for Deep Research

- Initial rubrics only 已经明显优于不做 RL；
- 加入 **evolving rubrics** 后还能继续提高，
- 随着训练进行，两者差距会逐渐扩大

RLER 的效果并不主要来自强模型 teacher 给弱模型传知识
换成qwen3-8b，有comparable的效果



	SQAv2	HealthBench	ResearchQA	DRB	Average
Qwen3-8B + Our Search	57.2	5.9	46.3	18.2	31.9
+ SFT	72.3	38.1	68.5	39.0	53.9
+ RL (1000 steps, GPT-judge)	**85.8**	**42.2**	**70.2**	**40.1**	**59.6**
+ RL (1000 steps, Qwen3-8B-judge)	85.3	39.7	69.2	39.1	58.3


Table 4. **Comparing using GPT-4.1 and Qwen3-8B as a judge model and rubric generator.** For GPT-judge, we use GPT-4.1-mini as the judge, and GPT-4.1 as the rubric generator. For Qwen3-8B-judge, we use Qwen3-8B as both judge and generator. Using Qwen3-8B only underperforms using GPT models by 1.3 points, while still outperforming the SFT baseline by 4.4 points.

评测和奖励

北京大学 PEKING UNIVERSITY

QUEST: Training Frontier Deep Research Agents with Fully Synthetic Tasks

[1]The Ohio State University [2]Amazon AGI SF Lab



(a) Rubric tree of an objective task **(b)** Rubric tree of an open-ended task

网上找主题
→ 自动探索网页
→ 从信息中抽出答案应满足的约束
→ 组成 Rubric Tree
→ 再反过来生成问题
→ 自动生成评价器。

北京大学
PEKING UNIVERSITY

请批评指正