

September 12, 2018 题目 :

354,493,417,667,360,819,796,763,512,757,466,669

354

1. LIS 完全相同的思路 :

```
class Solution {
    typedef pair<int, int> ii;
public:
    int maxEnvelopes(vector<pair<int, int>>& E) {
        if(E.empty()) return 0;
        sort(E.begin(), E.end(), [](const ii&x, const ii&y){
            if(x.first == y.first) return x.second > y.second;
            return x.first < y.first;
        });
        vector<int> res;
        for(auto p: E){
            if(res.empty() || p.second > res.back()){
                res.push_back(p.second);
            }
            else{
                int l = -1, r = res.size();
                while(l < r-1){
                    int c = (l+r)/2;
                    if(res[c] < p.second) l = c;
                    else r = c;
                }
                res[r] = p.second;
            }
        }
    }
};
```

```

    }
    return res.size();
}
};

```

493

1. Segment Tree 注意细节，over flow的情况很烦的:

```

class Solution {
    vector<long> SEG;
    int N;
    int dfs(int l, int r, int i, int j, int k){
        if(j<=l || i>=r) return 0;
        if(i<=l && j>=r) return SEG[k];
        return dfs(l, (l+r)/2, i, j, 2*k+1) + dfs((l+r)/2, r,
i, j, 2*k+2);
    }
    void updateSeg(int i, long val){
        int k = N - 1 + i;
        SEG[k] += val;
        do{
            k = (k-1)/2;
            SEG[k] += val;
        }while(k);
    }
    typedef pair<long, int> ii;
public:
    int reversePairs(vector<int>& nums) {
        int n = nums.size(), ans = 0;
        if(n<=1) return 0;
        vector<ii> reorder;

```

```

        for(int i=0; i<n; ++i) reorder.push_back(ii(long(nums
[i])), i));
        sort(reorder.begin(), reorder.end());
        // for(auto p: reorder) cout<<p.first<<' '<<p.second<<
endl;
        N = 1;
        while(N<n) N *= 2;
        SEG = vector<long>(2*N, 0);
        for(int i=n-1, j=n-1; i>=0; --i){
            while(j>=0 && reorder[j].first > 2*reorder[i].firs
t) {
                updateSeg(reorder[j].second, 1);
                --j;
            }
            // for(int k: SEG) cout<<k <<' ';
            // cout<<endl;
            ans += dfs(0, N, 0, reorder[i].second, 0);
        }
        return ans;
    }
};

```

2. MergeSort 确实过了：

```

class Solution {
    int res;
    vector<long> A;
    void mergeSort(int l, int r){
        if(l >= r-1) return;
        int m = (l+r)/2;
        mergeSort(l, m);
        mergeSort(m, r);
        vector<long> B;
    }
};

```

```

        int i=l, j=m;
        while(i<m || j<r){
            if(j==r || (i<m && A[i] <= A[j])) B.push_back(A[i+
+]);
            else{
                int left = l-1, right = m;
                while(left < right-1){
                    int mid = (left + right)/2;
                    if(A[mid] > 2*A[j]) right = mid;
                    else left = mid;
                }
                res += m - right;
                B.push_back(A[j++]);
            }
        }
        copy(B.begin(), B.end(), A.begin() + l);
    }
public:
    int reversePairs(vector<int>& nums) {
        for(int k: nums) A.push_back(long(k));
        res = 0;
        mergeSort(0, (int)A.size());
        return res;
    }
};

```

417

1. 有一点逆向思维

```

class Solution {
    final int[] dx = {1, -1, 0, 0};
    final int[] dy = {0, 0, -1, 1};

```

```
public List<int[]> pacificAtlantic(int[][] matrix) {
    List<int[]> res = new ArrayList<>();
    if (matrix == null || matrix.length == 0) {
        return res;
    }
    Queue<int[]> leftTop = new LinkedList<>();
    Queue<int[]> rightBottom = new LinkedList<>();
    int m = matrix.length, n = matrix[0].length;
    boolean[][] pVisited = new boolean[m][n];
    boolean[][] aVisited = new boolean[m][n];

    for (int i = 0; i < n; i++) {
        leftTop.offer(new int[]{0, i});
        rightBottom.offer(new int[]{m - 1, i});
        pVisited[0][i] = true;
        aVisited[m - 1][i] = true;
    }

    for (int i = 0; i < m; i++) {
        leftTop.offer(new int[]{i, 0});
        rightBottom.offer(new int[]{i, n - 1});
        pVisited[i][0] = true;
        aVisited[i][n - 1] = true;
    }

    helper(leftTop, pVisited, matrix, m, n);
    helper(rightBottom, aVisited, matrix, m, n);

    for (int i = 0; i < m; i++) {
        for (int j = 0; j < n; j++) {
```

```

        if (pVisited[i][j] && aVisited[i][j]) {
            res.add(new int[]{i, j});
        }
    }
}

return res;
}

public void helper(Queue<int[]> q, boolean[][] visited, int
t[][] matrix, int m, int n) {
    while (!q.isEmpty()) {
        int[] cur = q.poll();
        for (int k = 0; k < 4; k++) {
            int ux = cur[0] + dx[k];
            int uy = cur[1] + dy[k];
            if (ux < 0 || uy < 0 || ux >= m || uy >= n ||
visited[ux][uy] || matrix[ux][uy] < matrix[cur[0]][cur[1]]) {
                continue;
            }
            visited[ux][uy] = true;
            q.offer(new int[]{ux, uy});
        }
    }
}
}
}

```

2. BFS记Frontier :

```

class Solution {
    typedef pair<int, int> ii;
    int d[4] = {1, -1, 0, 0}, n, m;
    void bfs(unordered_set<int> &S, vector<vector<int>>& M){
        queue<int> Q;
    }
}

```

```

        for(int k: S) Q.push(k);
        while(!Q.empty()){
            int i = Q.front()/m, j = Q.front()%m;
            Q.pop();
            for(int k=0; k<4; ++k){
                int x = i + d[k], y = j + d[3-k];
                if(x>=0 && x<n && y>=0 && y<m && !S.count(x*m+
y) && M[x][y]>=M[i][j]){
                    S.insert(x*m + y);
                    Q.push(x*m + y);
                }
            }
        }
    }

public:
    vector<pair<int, int>> pacificAtlantic(vector<vector<int>>
& matrix) {
        vector<pair<int, int>> ans;
        if(matrix.empty() || matrix[0].empty()) return ans;
        n = matrix.size();
        m = matrix[0].size();
        unordered_set<int> P, A;
        for(int i=0; i<n; ++i){
            P.insert(i*m + 0);
            A.insert(i*m + m - 1);
        }
        for(int j=0; j<m; ++j){
            P.insert(0 + j);
            A.insert((n-1)*m + j);
        }
    }

```

```

        bfs(P, matrix);
        bfs(A, matrix);
        for(int k: P) if(A.count(k)) ans.push_back(ii(k/m, k%
m));
        return ans;
    }
};

```

667

1.

```

class Solution {
    public int[] constructArray(int n, int k) {
        // 1, n - 1, 2, n - 2, 3, n - 3, ...
        int[] res = new int[n];
        int lo = 1, high = n;
        int i = 0;
        while (i < k) {
            res[i++] = lo++;
            if (i < k) {
                res[i++] = high--;
            }
        }
        if (k % 2 == 0) {
            while (i < n) {
                res[i++] = high--;
            }
        } else {
            while (i < n) {
                res[i++] = lo++;
            }
        }
    }
}

```



```

        return res;
    }
}

```

2. 做过，折叠：

```

class Solution {
public:
    vector<int> constructArray(int n, int k) {
        vector<int> ans;
        int l = 1, r = n, f = 0;
        while(k){
            if(f) ans.push_back(r--);
            else ans.push_back(l++);
            f = 1-f;
            --k;
        }
        if(ans.back() == l-1) for(;l<=r;++l) ans.push_back(l);
        else for(; r>=l;--r) ans.push_back(r);
        return ans;
    }
};

```

360

1. 先找最小值点，然后向两边延伸：

```

class Solution {
public:
    vector<int> sortTransformedArray(vector<int>& nums, int a,
int b, int c) {
        if(!a){
            bool rev = (b < 0);
            for(auto &n: nums) n = b*n + c;
            if(rev) reverse(nums.begin(), nums.end());

```

```

        return nums;
    }
    bool rev = (a < 0);
    int l=-1, r=nums.size(), n=nums.size();
    double center = -double(b)/2./a;
    while(l < r-1){
        int c = (l+r)/2;
        if(double(nums[c]) < center) l = c;
        else r = c;
    }
    vector<int> ans;
    for(int i=0; i<n; ++i){
        if(l<0) {
            ans.push_back(a * nums[r] * nums[r] + b * nums
[r] + c);
            ++r;
        }
        else if(r>=n) {
            ans.push_back(a * nums[l] * nums[l] + b * nums
[l] + c);
            --l;
        }
        else if(nums[r]-center < center-nums[l]){
            ans.push_back(a * nums[r] * nums[r] + b * nums
[r] + c);
            ++r;
        }
        else{
            ans.push_back(a * nums[l] * nums[l] + b * nums
[l] + c);
            --l;
        }
    }
}

```

```

        }
    }
    if(rev) reverse(ans.begin(), ans.end());
    return ans;
}
};

```

819

1. 最后一个case应该是这几天新加上去的, "a, a, a, a, b,b,b,c, c" => ["a"] 不知道咋改

```

class Solution {
    public String mostCommonWord(String paragraph, String[] banned) {
        String[] strs = paragraph.toLowerCase().split("\\W+");
        //System.out.println(Arrays.toString(strs));
        Map<String, Integer> map = new HashMap<>();
        for (String str : strs) {
            map.put(str, map.getOrDefault(str, 0) + 1);
        }

        for (String s : banned) {
            map.remove(s);
        }

        int max = 0;
        String res = "";
        for (String s : map.keySet()) {
            if (map.get(s) > max) {
                max = map.get(s);
                res = s;
            }
        }
    }
}

```

```

        return res;
    }
}

```

2. 一道Easy 费了我九牛二虎之力：

```

class Solution:
    def _process(self, s):
        return s.strip('!?\',;.\\n').lower()
    def mostCommonWord(self, s, banned):
        banned = [w.lower() for w in banned]
        pool = [self._process(w) for w in s.split(' ')]
        pool = [w for w in pool if w and w not in banned]
        print(pool, banned)
        cnt = {}
        res = pool[0]
        for w in pool:
            if w not in cnt:
                cnt[w] = 1
            else:
                cnt[w] += 1
        for w in cnt:
            if cnt[w] > cnt[res]:
                res = w
        return res

```

796

1. 厉害了。。好像还有一道题也是类似的解法，想不起来了

```

class Solution {
    public boolean rotateString(String A, String B) {
        return A.length() == B.length() && (A + A).contains
(B);
    }
}

```

```
}
```

2. 楼上解法神了!!! @Tongtong X:

```
class Solution {
public:
    bool rotateString(string A, string B) {
        if(A.size() != B.size()) return false;
        if(A.empty() && B.empty()) return true;
        for(int i=0, n=A.size(); i<n; ++i){
            bool ok = true;
            for(int j=0; j<n && ok; ++j) if(A[(i+j)%n] != B[j]) ok = false;
            if(ok) return true;
        }
        return false;
    }
};
```

763

1.

```
class Solution {
    public List<Integer> partitionLabels(String S) {
        int[] chs = new int[26];
        List<Integer> list = new ArrayList<>();
        int start = 0;
        int end = 0;
        for (int i = 0; i < S.length(); i++) {
            chs[S.charAt(i) - 'a'] = i;
        }

        for (int i = 0; i < S.length(); i++) {
            end = Math.max(end, chs[S.charAt(i) - 'a']);
        }
    }
}
```

```

        if (end == i) {
            list.add(end - start + 1);
            start = end + 1;
        }
    }
    return list;
}
}

```

2. n 方 solution :

```

class Solution {
    bool inter(unordered_map<char, int> &m1, unordered_map<char, int> &m2){
        for(auto p: m1) if(m2.count(p.first)) return true;
        return false;
    }
public:
    vector<int> partitionLabels(string S) {
        int head = -1;
        vector<int> ans;
        unordered_map<char, int> m1, m2;
        for(char c: S) ++m2[c];
        for(int i=0; i<S.size(); ++i){
            m2[S[i]]--;
            if(!m2[S[i]]) m2.erase(S[i]);
            m1[S[i]]++;
            if(!inter(m1, m2)){
                ans.push_back(i-head);
                head = i;
            }
        }
    }
}

```

```

        return ans;
    }
};

```

3. 好方法：

```

class Solution {
    #define CI(c) int((c) - 'a')
public:
    vector<int> partitionLabels(string S) {
        vector<int> pos(26, 0), ans;
        for(int i=0; i<S.size(); ++i) pos[CI(S[i])] = i;
        int head = -1;
        for(int i=0, tmp=pos[CI(S[0])]; i<S.size(); ++i){
            tmp = max(tmp, pos[CI(S[i])]);
            if(i == tmp){
                ans.push_back(i-head);
                head = i;
            }
        }
        return ans;
    }
};

```

512没有题

757

1. n方非常慢的solution：

```

class Solution {
    typedef pair<int, int> ii;
public:
    int intersectionSizeTwo(vector<vector<int>>& intervals) {
        map<int, int> I, R;
    }
};

```

```

for(auto p: intervals){
    if(!I.count(p[0])) I[p[0]] = p[1];
    else I[p[0]] = min(I[p[0]], p[1]);
    R[p[0]] = 2;
}
int ans = 0;
while(!I.empty()){
    int start = INT_MAX, l = 0;
    for(auto p: R){
        if(I[p.first] - p.second + 1 < start){
            start = I[p.first] - p.second + 1;
            l = p.second;
        }
        else if(I[p.first] - p.second + 1 == start &&
p.second > l){
            l = p.second;
        }
    }
    int end = start + l - 1;
    ans += l;
    for(auto it=I.begin(); it!=I.end() && it->first <=
end; ){
        int x = max(it->first, start), y = min(it->sec
ond, end);

        int d = y - x + 1;
        R[it->first] -= d;
        if(R[it->first] <= 0) {
            R.erase(it->first);
            it = I.erase(it);
        }
        else ++it;
    }
}

```



```

        }
    }
    return ans;
}
};

```

2. 改进 $n \log n$:

```

class Solution {
public:
    int intersectionSizeTwo(vector<vector<int>>& intervals) {
        map<int, int> LR, RL, RT;
        for(auto p: intervals){
            if(!RL.count(p[1])) RL[p[1]] = p[0];
            else RL[p[1]] = max(RL[p[1]], p[0]);
        }
        for(auto p: RL){
            if(!LR.count(p.second)) LR[p.second] = p.first;
            else LR[p.second] = min(LR[p.second], p.first);
        }
        for(auto p: LR){
            RT[p.second] = 2;
        }
        int ans = 0;
        while(!LR.empty()){
            int end = RT.begin()->first, l = RT.begin()->second;

            int start = end - l + 1;
            ans += l;
            for(auto it=LR.begin(); it!=LR.end() && it->first<
=end;){
                int x = max(it->first, start), y = min(it->second, end);
            }
        }
    }
};

```

```

        int d = y-x+1;
        RT[it->second] -= d;
        if(RT[it->second] <= 0) {
            RT.erase(it->second);
            it = LR.erase(it);
        }
        else ++it;
    }
}
return ans;
}
};

```

3. 精妙的方法：

```

class Solution {
public:
    int intersectionSizeTwo(vector<vector<int>>& intervals) {
        int ans = 0, x=-1, y=-1;
        sort(intervals.begin(), intervals.end(), [](vector<int>&a, vector<int>&b){
            return (a[1] < b[1]) || (a[1] == b[1] && a[0] > b[0]);
        });
        for(auto v: intervals) if(v[0] > x){
            if(v[0] <= y){
                ++ans;
                x = y;
                y = v[1];
            }
            else{
                ans += 2;
                y = v[1];
            }
        }
    }
};

```

```

        x = y-1;
    }
}
return ans;
}
};

```

466

1. 找循环节，非常Ugly地做对了：

```

class Solution {
    typedef pair<int, int> ii;
    unordered_map<char, set<int>> pos;
    vector<ii> trans, transM;
public:
    int getMaxRepetitions(string s1, int n1, string s2, int n
2) {
        int l1 = s1.size(), l2 = s2.size();
        for(int i=0; i<l1; ++i) pos[s1[i]].insert(i);
        for(char c: s2) if(!pos.count(c)) return 0;
        if(!n1) return 0;
        trans.resize(l1);
        transM.resize(l1);
        for(int i=l1-1; i>=0; --i){
            if(i<l1-1 && s1[i] != s2[0]) trans[i] = trans[i+
1];
            else{
                int cnt = 0;
                int j = i;
                for(char c: s2){
                    auto it = pos[c].lower_bound(j);
                    if(it == pos[c].end()){

```

```

        ++cnt;
        it = pos[c].lower_bound(0);
    }
    j = (*it) + 1;
    if(j==l1){
        ++cnt;
        j = 0;
    }
}
trans[i] = ii(j, cnt);
}
}
for(int i=l1-1; i>=0; --i){
    if(i<l1-1 && s1[i] != s2[0]) transM[i] = transM[i+
1];
    else{
        int j = i, cnt = 0, k=0;
        unordered_map<int, int> cnts, T;
        T[j] = 0;
        cnts[0] = 0;
        while(k < n2){
            cnt += trans[j].second;
            j = trans[j].first;
            ++k;
            if(T.count(j)) break;
            T[j] = k;
            cnts[k] = cnt;
        }
        if(k < n2) {
            int start = T[j], end = k;

```

```

        int delta_cnt = cnt - cnts[start];
        int delta_k = end - start;
        int loop = (n2 - k)/ delta_k;
        k += loop * delta_k;
        cnt += loop * delta_cnt;
        while(k < n2){
            cnt += trans[j].second;
            j = trans[j].first;
            ++k;
        }
    }
    transM[i] = ii(j, cnt);
}
cout<<i<<"shaocong"<<endl;
}
int j = 0, cnt = 0, k = 0;
unordered_map<int, int> cnts, T;
for(auto p: transM) cout<<p.first<<' '<<p.second<<endl;

cnts[0] = 0;
T[0] = 0;
while(cnt<n1) {
    cnt += transM[j].second;
    j = transM[j].first;
    if(cnt >= n1){
        if(cnt==n1 && j==0) return k+1;
        else return k;
    }
    ++k;
    if(T.count(j)) break;
}

```

```

        T[j] = k;
        cnts[k] = cnt;
    }
    int delta_k = k - T[j];
    int delta_cnt = cnt - cnts[T[j]];
    int loop = (n1 - 1 - cnt)/delta_cnt;
    cout<<loop<<endl;
    cnt += loop * delta_cnt;
    k += delta_k * loop;
    while(cnt<n1) {
        cnt += transM[j].second;
        j = transM[j].first;
        if(cnt >= n1){
            if(cnt==n1 && j==0) return k+1;
            else return k;
        }
        ++k;
    }
    return k;
}

};

```

669

1.

```

class Solution {
    public TreeNode trimBST(TreeNode root, int L, int R) {
        if (root == null) {
            return null;
        }
        if (root.val < L) {

```

```

        return trimBST(root.right, L, R);
    }
    if (root.val > R) {
        return trimBST(root.left, L, R);
    }

    root.left = trimBST(root.left, L, R);
    root.right = trimBST(root.right, L, R);
    return root;
}
}

```

2. 单纯recursion :

```

class Solution {
public:
    TreeNode* trimBST(TreeNode* root, int L, int R) {
        if(!root) return NULL;
        if(root->val > R) return trimBST(root->left, L, R);
        if(root->val < L) return trimBST(root->right, L, R);
        root->left = trimBST(root->left, L, R);
        root->right = trimBST(root->right, L, R);
        return root;
    }
};

```