

HW2_Julia_Bright

This file available at: https://github.com/JBrighttt/plan372_hmks/tree/main

Question 1


```
unique(ri$SCORE)
```

```
[1] 97.0 96.0 98.5 90.5 97.5 98.0 100.0 99.5 95.0 88.0 90.0 96.5  
[13] 91.0 91.5 94.0 93.5 99.0 94.5 92.5 95.5 93.0 92.0 89.5 88.5  
[25] 84.5 89.0 85.0 87.0 85.5 80.5 87.5 86.5 0.0 84.0
```


```
table(ri$SCORE) #i see there is only a single 0 score
```

```
0 80.5 84 84.5 85 85.5 86.5 87 87.5 88 88.5 89 89.5 90 90.5 91  
1 1 1 3 2 1 1 2 1 3 5 4 1 34 35 48  
91.5 92 92.5 93 93.5 94 94.5 95 95.5 96 96.5 97 97.5 98 98.5 99  
49 47 35 83 76 82 135 177 152 247 258 305 284 402 433 330  
99.5 100  
310 327
```

```
ggplot(data=ri, aes(x=SCORE)) + geom_histogram()
```




```
#would be useful to set xlim to see a more visually instructive distribution  
ggplot(data=ri, aes(x=SCORE)) + geom_histogram() + xlim(80,100) +  
  ↪ xlab("Inspection Scores")
```



Question 2


```
ri$RESTAURANTOPENDATE <- as.Date(ri$RESTAURANTOPENDATE, format = "%Y/%m/%d")
  ↳ #formatted the open date column to function as date values

fit1 <- lm(SCORE~RESTAURANTOPENDATE, data = ri) #created linear regression of
  ↳ inspection scores as a function of open date
ggplot(data=fit1, aes(x=RESTAURANTOPENDATE, y=SCORE)) + geom_point() +
  ↳ geom_smooth(method="lm") + labs(x="Restaurant Open Date", y="Inspection
  ↳ Score") #plotted linear regression, no apparent relationship between
  ↳ restaurant open date and inspection scores
```



```
#let's check age instead of open date
ri$DATE_ <- as.Date(ri$DATE_, format = "%Y/%m/%d") #formatted inspection date
  ↳ column

ri$age_to_inspection <- ri$DATE_ - ri$RESTAURANTOPENDATE # create new
  ↳ variable determining the age of facility at date of inspection
ri$age_to_inspection <- as.numeric(ri$age_to_inspection) #format it as
  ↳ numeric to function properly in linear model
fit2 <- lm(SCORE~age_to_inspection, data=ri)
ggplot(data=fit2, aes(x=age_to_inspection, y=SCORE)) + geom_point() +
  ↳ geom_smooth(method="lm") + labs(x="Age at Inspection", y="Inspection
  ↳ Score") #basically the same but flipped due to taking the age rather than
  ↳ open date. No discernable relationship.
```



Question 3

```
unique(ri$CITY)
```

[1] "CARY"	"RALEIGH"	"KNIGHTDALE"
[4] "CLAYTON"	"FUQUAY VARINA"	NA
[7] "GARNER"	"MORRISVILLE"	"RESEARCH TRIANGLE PARK"
[10] "RTP"	"WENDELL"	"Cary"
[13] "APEX"	"Apex"	"WILLOW SPRING"
[16] "HOLLY SPRINGS"	"ROLESVILLE"	"ZEBULON"
[19] "Raleigh"	"WAKE FOREST"	"NEW HILL"
[22] "FUQUAY-VARINA"	"Zebulon"	"Morrisville"
[25] "Wake Forest"	"Holly Springs"	"ANGIER"
[28] "Fuquay Varina"	"NORTH CAROLINA"	"MORRISVILE"
[31] "Fuquay-Varina"	"HOLLY SPRING"	"Garner"

```
ri$CITY <- str_to_upper(ri$CITY) #converted all to upper case, removes 10 of
  ↳ the duplicates
unique(ri$CITY)
```

```
[1] "CARY"           "RALEIGH"         "KNIGHTDALE"
[4] "CLAYTON"        "FUQUAY VARINA"   NA
[7] "GARNER"         "MORRISVILLE"   "RESEARCH TRIANGLE PARK"
[10] "RTP"           "WENDELL"         "APEX"
[13] "WILLOW SPRING"  "HOLLY SPRINGS"   "ROLESVILLE"
[16] "ZEBULON"        "WAKE FOREST"     "NEW HILL"
[19] "FUQUAY-VARINA" "ANGIER"          "NORTH CAROLINA"
[22] "MORRISVILE"     "HOLLY SPRING"
```

```
ri$CityNames <- case_match(ri$CITY, "CARY"~"CARY", "RALEIGH"~"RALEIGH",
  ↳ "KNIGHTDALE"~"KNIGHTDALE", "CLAYTON"~"CLAYTON", "FUQUAY
  ↳ VARINA"~"FUQUAY-VARINA", "FUQUAY-VARINA"~"FUQUAY-VARINA",
  "GARNER"~"GARNER", "MORRISVILLE"~"MORRISVILLE",
  ↳ "MORRISVILLE"~"MORRISVILLE", "RESEARCH TRIANGLE
  ↳ PARK"~"RTP", "RTP"~"RTP",
  "WENDELL"~"WENDELL", "APEX"~"APEX", "WILLOW
  ↳ SPRING"~"WILLOW SPRING", "HOLLY
  ↳ SPRINGS"~"HOLLY SPRINGS", "HOLLY
  ↳ SPRING"~"HOLLY SPRINGS",
  "ROLESVILLE"~"ROLESVILLE", "ZEBULON"~"ZEBULON",
  ↳ "WAKE FOREST"~"WAKE FOREST", "NEW HILL"~"NEW
  ↳ HILL", "ANGIER"~"ANGIER", "NORTH
  ↳ CAROLINA"~"NORTH CAROLINA")
```


```
#used the case match command from the sfpark exercise. wow that sucked I hope
  ↳ there's a better way to do it. I noticed that if I did only the ones that
  ↳ needed changing it would convert all others to NA so it's like you have
  ↳ to type out each one to preserve it.
```

```
scorebycity <- ri %>%
  group_by(CityNames) %>%
  summarize(meanscore = mean(SCORE))
```

```
#created new dataframe to average the inspection scores for each city. There
  ↳ are two that don't make much sense, "north carolina" and NA
```

```
ggplot(data=scorebycity, aes(x=CityNames, y=meanscore)) + geom_point() +
  ↳ theme(axis.title = element_text(size=10),
  axis.text = element_text(size=6),
```

```
axis.text.x = element_text(angle=90))
```




#There are differences between cities. I cannot find a way to order the
 ↳ scatterplot in ascending or descending order of scores, but it would be
 ↳ visually helpful. The top 3 are New Hill, Research Triangle Park, and
 ↳ Holly Springs, the only 3 to average a score above 98. Angier and Zebulon
 ↳ are the lowest, scoring below 95.

Question 4

```
scorebyinspector <- ri %>%
  group_by(INSPECTOR) %>%
  summarize(meanscore = mean(SCORE))
#made new dataframe to average the inspection scores for each inspector

ggplot(data=scorebyinspector, aes(x=INSPECTOR, y=meanscore)) + geom_point() +
  ↳ theme(axis.title = element_text(size=10),
    axis.text = element_text(size=6),
    axis.text.x = element_text(angle=90))
```



```
#Thomas Jumalon scores much lower than the rest
```

Question 5

```
ri$SCORE[ri$INSPECTOR=="Thomas Jumalon"] #Thomas has only 3 recorded
↪ inspections of 91, 91, and 85.
```

```
[1] 91 91 85
```

```
sampleinspector <- ri %>%
  group_by(INSPECTOR) %>%
  summarize(totalentries = length(SCORE))
#Many of the inspectors have single digit inspections logged, but Mr. Jumalon
↪ is the only one that stands out to an extreme degree in the scores given.
↪


samplecity <- ri %>%
  group_by(CityNames) %>%
  summarize(totalentries = length(SCORE))
#Angier, New Hill, Willow Spring, Clayton, and RTP all have very low sample
↪ sizes, each less than 4. This could explain Angier's low score, with only
↪ 1 inspection recorded. Conversely, New Hill and RTP are at the top each
↪ with only 2 inspections recorded.
```

Question 6


```
scorebyfacility <- ri %>%  
  group_by(FACILITYTYPE) %>%  
  summarize(meanscore=mean(SCORE))  
#Restaurants score lowest out of all categories. Yikes
```

Question 7

```
restonly <- ri %>%  
  filter(FACILITYTYPE=="Restaurant")  
#Created a dataset excluding any facility other than restaurants to do  
  ↳ analysis on restaurants only  
  
ggplot(data=restonly, aes(x=SCORE)) + geom_histogram()
```





```
#there is a single "0" score, but would be useful to set xlim to see a more
↳ visually instructive distribution
ggplot(data=restonly, aes(x=SCORE)) + geom_histogram() + xlim(80,100) +
↳ xlab("Inspection Scores")
```



```
#visualized inspection scores with histogram
```


```
fit3 <- lm(SCORE~age_to_inspection, data=restonly)
ggplot(data=fit3, aes(x=age_to_inspection, y=SCORE)) + geom_point() +
↳ geom_smooth(method="lm") + labs(x="Age at Inspection", y="Inspection
↳ Score", title="Restaurant Inspection Scores by Age")
```



```
#No discernable relationship, there are simply more young restaurants than
↪ old ones

restbycity <- restonly %>%
  group_by(CityNames) %>%
  summarize(meanscore = mean(SCORE))
#fairly significant difference in scores, but we already know that several of
↪ those are due to low sample size


ggplot(data=restbycity, aes(x=CityNames, y=meanscore)) + geom_point() +
↪ theme(axis.title = element_text(size=10),
        axis.text = element_text(size=6),
        axis.text.x = element_text(angle=90))
```



```
#plot of restaurant scores by city

restbyinspector <- restonly %>%
  group_by(INSPECTOR) %>%
  summarize(meanscore = mean(SCORE))
#Thomas must've seen some nasty stuff.

ggplot(data=restbyinspector, aes(x=INSPECTOR, y=meanscore)) + geom_point() +
  ↪ theme(axis.title = element_text(size=10),
        axis.text = element_text(size=6),
        axis.text.x = element_text(angle=90))
```



```
#Data similar, scores are a bit lower. To be expected after seeing that
↪ restaurants as a category score the lowest.

samplerestinspector <- restonly %>%
  group_by(INSPECTOR) %>%
  summarize(totalentries = length(SCORE))
#Six with single digit inspections recorded. James Smith, Greta Welch,
↪ Brittany Thomas, three of the top four by rating and also the three least
↪ voluminous in sample size.

samplerestcity <- restonly %>%
  group_by(CityNames) %>%
  summarize(totalentries = length(SCORE))
#Many of the highest and lowest scores are the lowest sample size
```