ISSUE 日本語解説資料

Issue #120 SNS auth-error contract command implementation split を整理する

GitHub で closed になっている issue 記録を、そのまま参照用 PDF に変換したもの。

Issue #120　更新: 2026/03/12

ソース: docs/portal/issues/issue-120-sns-auth-error-contract-command-implementation-split.md

GitHub: https://github.com/PLAYER1-r7/MultiCloudProject/issues/120

計画　セキュリティ　テスト　SNS

この ISSUE の要点

Issue 115 で contract regression command baseline は request-response compatibility と auth-error mapping に分離できたが、guest/member/operator permission mapping と write-failure error visibility を 1 つの repeatable implementation unit としてどう切るかは未固定のままである。このままだと shared auth abstraction や error mapping 変更時に auth/error evidence の実装粒度が揺れやすい。

目標

SNS auth-error contract command implementation split を整理し、auth-to-post permission mapping と write failure error visibility を一貫した command implementation unit として固定する。

完了状態

CLOSED

1. この Issue が扱っていたこと

まず Summary と Goal から、この Issue が何を決めるためのものだったかを短く押さえる。

Issue 115 で contract regression command baseline は request-response compatibility と auth-error mapping に分離できたが、guest/member/operator permission mapping と write-failure error visibility を 1 つの repeatable implementation unit としてどう切るかは未固定のままである。このままだと shared auth abstraction や error mapping 変更時に auth/error evidence の実装粒度が揺れやすい。

目標

SNS auth-error contract command implementation split を整理し、auth-to-post permission mapping と write failure error visibility を一貫した command implementation unit として固定する。

2. 完了判断の見方

Tasks、Definition of Done、Current Status の記述から、どこまで完了済みとして扱っているかを先に読む。

TASKS

Tasks セクションの有無は原文側で確認する。

DEFINITION OF DONE

Definition of Done セクションの有無は原文側で確認する。

> CLOSED / GitHub Issue: #120 / GitHub URL: https://github.com/PLAYER1-r7/MultiCloudProject/issues/120 / Sync Status: local body updated for closure sync

3. 依存関係と読み進め方

Dependencies や前提 Issue がある場合は、ここで関連先を先に把握しておくと読みやすい。

依存関係

- docs/portal/issues/issue-115-sns-contract-regression-test-command-baseline.md

読み方の注意

この解説書は原文の意思決定や完了状態を読みやすくするための補助資料である。最終的な正本は原文 Issue にあり、判断変更時は原文側を先に更新する。

4. 用語集

原文に残る英語や実務用語のうち、訳し切らずに補助説明を付けた方が読みやすい語をここにまとめる。

原語	日本語の扱い	補足
baseline	基準線	後続作業が参照する最小限の判断・実装・検証の出発点。
operator	運用担当者	監視、承認、非表示、切り戻しなどの運用行為を担う役割。
workflow	ワークフロー	GitHub Actions などで定義された自動処理の流れ。

原語	日本語の扱い	補足
owner	責任者	意思決定または更新責任を持つ担当者。文脈により product owner などを含む。
evidence	証跡	判断や完了状態の根拠になるログ、表、文書、出力結果。
mapping	対応付け	チェック項目とその根拠を結び付けて整理すること。
current status	現在の状態	Issue 文書時点での完了度合いや同期状況を示す節。
task contract	タスク契約	対象、目的、スコープ、検証計画、リスクを明文化した作業契約。

5. 原文

以下に Issue 原文をそのまま掲載する。詳細な根拠、証跡、チェックリストはこの原文を参照する。

概要

Issue 115 で contract regression command baseline は request-response compatibility と auth-error mapping に分離できたが、guest/member/operator permission mapping と write-failure error visibility を 1 つの repeatable implementation unit としてどう切るかは未固定のままである。このままだと shared auth abstraction や error mapping 変更時に auth/error evidence の実装粒度が揺れやすい。

目標

SNS auth-error contract command implementation split を整理し、auth-to-post permission mapping と write failure error visibility を一貫した command implementation unit として固定する。

タスク契約

```
Task Contract

Metadata
- Task ID: ISSUE-120
- Title: SNS auth-error contract command implementation split を整理する
- Requester: repository owner
- Target App: portal-web and future SNS service layer
- Environment: planning
- Priority: high
- Predecessor: Issue 115 (baseline; closed)

Objective
- Problem to solve: auth-error mapping grouping は fixed したが、permission boundary と write
failure visibility をどの single implementation unit で実装するかが未固定である
- Expected value: shared auth / error mapping change 時に必要な auth-error contract evidence を
repeatable command implementation issue へ落とせる

Scope
- In scope: auth-error command scope、target-to-command mapping、evidence shape、fallback
direction、non-goals
- Out of scope: actual test code implementation、request-response command implementation、CI
wiring、integration suite implementation
- Editable paths: docs/portal/issues/issue-120-sns-auth-error-contract-command-implementation-
split.md, docs/portal/issues/issue-115-sns-contract-regression-test-command-baseline.md
- Restricted paths: apps/, infra/, .github/workflows/

Acceptance Criteria
- [x] AC-1: auth-error command scope が読める
- [x] AC-2: guest/member/operator permission mapping と write failure visibility coverage が読める
- [x] AC-3: evidence shape と fallback direction が整理されている
- [x] AC-4: actual test implementation を含まない split issue に留まっている
```

Implementation Unit

- one command unit covers guest/member/operator auth-to-post mapping
- the same unit covers write failure error visibility to SNS client surface

Implementation rule:

- auth boundary drift と silent failure drift を同一 evidence 系統で残せる unit とする
- shared auth abstraction or error mapping change ではこの unit を省略しない
- request/response schema compatibility は本 issue に含めない

Evidence Shape

- command output for guest/member/operator permission mapping
- command output for write failure error visibility

Current Codebase Fit

- current portal-web keeps repeatable CLI validation in apps/portal-web/src/main.ts and script wiring in apps/portal-web/package.json
- there is no dedicated auth policy or error mapping module yet, so auth/error command placement should be explicit before implementation starts
- browser verification already has a separate home in apps/portal-web/scripts/verify-public-variants.mjs, which is not the right place for permission and error contract checks

Candidate Target Files

- primary support-module candidate: apps/portal-web/src/main.ts
- preferred extraction candidate once SNS auth/error contract logic exists: `apps/portal-web/src/sns-auth-error-contract.ts`
- package wiring candidate: apps/portal-web/package.json

Target-file rule:

- keep guest/member/operator mapping and write-failure visibility in one contract-oriented unit
- use apps/portal-web/src/main.ts only as temporary CLI entry if a dedicated auth/error contract module is introduced
- avoid coupling auth/error contract checks to browser runtime files or public variant scripts

Test Placement Candidates

- first-fit command entry candidate: extend apps/portal-web/src/main.ts with a dedicated CLI flag for auth/error contract validation
- second candidate if command entry needs isolation: `apps/portal-web/src/sns-auth-error-contract-cli.ts`
- npm script candidate in apps/portal-web/package.json: `test:sns-auth-error-contract`

Placement rule:

- this issue should follow the same Node CLI pattern already used by `test:routes`
- stdout evidence should remain command-oriented and not depend on browser rendering
- do not merge auth/error contract evidence into request/response command output unless a higher-level baseline issue explicitly asks for that combination

Preferred Command Contract

- CLI flag candidate: `--validate-sns-auth-error-contract`
- npm script candidate in apps/portal-web/package.json: `test:sns-auth-error-contract`
- first command shape candidate: `node --experimental-strip-types ./src/main.ts --validate-sns-auth-error-contract`

Contract rule:

- the first implementation pass should reuse the same Node invocation pattern already used by `test:routes`
- if the command body outgrows apps/portal-web/src/main.ts, move validator logic first and keep the CLI surface stable

Expected Stdout Shape

preferred stdout shape should stay aligned with the existing route validation report style.

```
SNS auth-error contract baseline
- Command: validate-sns-auth-error-contract
- Guest/member/operator permission mapping: passed | failed
- Write failure error visibility: passed | failed
- Result: passed | failed
- Issues: none | detailed issue list
```

Output rule:

- stdout should be short, deterministic, and readable beside the current route validation report
- failures should enumerate concrete issue lines rather than broad `auth-error contract failed` wording
- success output should still mention both covered surfaces so permission mapping and error visibility remain visibly in scope

Exit And Failure Contract

- exit code `0` only when permission mapping and write-failure visibility both pass
- exit code `1` when guest/member/operator permission behavior or write-failure visibility fails
- partial evidence should not downgrade to warning-only success

Failure rule:

- silent write-failure handling should fail closed rather than being treated as a soft regression
- this command should not absorb request/response coverage just to avoid failure; that remains Issue 119 scope

Recommended Implementation Sequence

1. add a stable CLI flag branch in apps/portal-web/src/main.ts that is parallel to `--validate-routes` rather than mixed into browser runtime logic
2. define a report-builder function whose output shape stays parallel to the current route validation report before extracting SNS-specific helper code
3. extract auth and error contract checks into a dedicated support module once the report shape is stable enough to preserve
4. add the package script in apps/portal-web/package.json only after the CLI flag and stdout contract are fixed

Sequence rule:

- first lock the command surface and report shape, then lock helper extraction
- avoid starting with package-script naming alone before the CLI branch and output contract are settled

Cross-Issue Execution Order

overall preferred execution order across the active SNS implementation chain is:

1. Issue 119
2. Issue 120
3. Issue 122
4. Issue 121

Order meaning:

- Issue 120 is the second execution target and should reuse the CLI branch, package-script shape, and stdout contract pattern established by Issue 119
- this issue should not start before Issue 119 settles the first SNS command-entry pattern on the non-browser side
- this issue should still complete before browser suites begin, so auth/error contract drift is not hidden behind browser-only evidence
- if Issue 119 changes command-surface naming or report format, this issue should follow the stabilized pattern rather than inventing a parallel one

Fallback Direction

- auth-error command が未整備でも request-response command へ吸収しない
- temporary broader evidence を使う場合は auth/error coverage を代替したことを明示する

Non-Goals

- actual test code implementation
- request-response command implementation
- CI workflow integration
- integration suite implementation

Resolution

- Added the auth-error contract validator entry on the existing Node CLI path in apps/portal-web/src/main.ts and kept the command surface fixed as `--validate-sns-auth-error-contract`
- Added the dedicated validator/report module in apps/portal-web/src/snsAuthErrorContract.ts and reused shared support in apps/portal-web/src/snsContractShared.ts
- Added package wiring in apps/portal-web/package.json as `test:sns-auth-error-contract`
- Validation result: `node --experimental-strip-types ./src/main.ts --validate-sns-auth-error-contract` returned passed for guest/member/operator permission mapping and write failure error visibility

現在の状態

- CLOSED
- GitHub Issue: #120
- GitHub URL: https://github.com/PLAYER1-r7/MultiCloudProject/issues/120
- Sync Status: local body updated for closure sync

依存関係

- docs/portal/issues/issue-115-sns-contract-regression-test-command-baseline.md