```
No.     Time           Source                Destination           Protocol Length Info
      1 0.000000       host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 1: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309536000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309536000 UTC
    Epoch Arrival Time: 1775345253.309536000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
    Frame Number: 1
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 2]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
      2 0.000029       3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 2: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309565000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309565000 UTC
    Epoch Arrival Time: 1775345253.309565000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000029000 seconds]
    [Time delta from previous displayed frame: 0.000029000 seconds]
    [Time since reference or first frame: 0.000029000 seconds]
    Frame Number: 2
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 1]
    [Time from request: 0.000029000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
      3 0.000032       host                  3.3.0                 USB      36     GET DESCRIPTOR Request CONFIGURATION
Frame 3: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309568000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309568000 UTC
    Epoch Arrival Time: 1775345253.309568000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000003000 seconds]
    [Time delta from previous displayed frame: 0.000003000 seconds]
    [Time since reference or first frame: 0.000032000 seconds]
    Frame Number: 3
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 4]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: CONFIGURATION (0x02)
    Language Id: no language specified (0x0000)
    wLength: 9
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 02   ................
0020  00 00 09 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
      4 0.000034       3.3.0                 host                  USB      37     GET DESCRIPTOR Response CONFIGURATION
Frame 4: 37 bytes on wire (296 bits), 37 bytes captured (296 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309570000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309570000 UTC
    Epoch Arrival Time: 1775345253.309570000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000002000 seconds]
    [Time delta from previous displayed frame: 0.000002000 seconds]
    [Time since reference or first frame: 0.000034000 seconds]
    Frame Number: 4
    Frame Length: 37 bytes (296 bits)
    Capture Length: 37 bytes (296 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 9
    [Request in: 3]
    [Time from request: 0.000002000 seconds]
    Control transfer stage: Complete (3)
CONFIGURATION DESCRIPTOR
    bLength: 9
    bDescriptorType: 0x02 (CONFIGURATION)
    wTotalLength: 32
    bNumInterfaces: 1
    bConfigurationValue: 1
    iConfiguration: 0
    Configuration bmAttributes: 0x80  NOT SELF-POWERED  NO REMOTE-WAKEUP
        1... .... = Must be 1: Must be 1 for USB 1.1 and higher
        .0.. .... = Self-Powered: This device is powered from the USB bus
        ..0. .... = Remote Wakeup: This device does NOT support remote wakeup
    bMaxPower: 50  (100mA)
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  01 03 00 03 00 80 02 09 00 00 00 03 09 02 20 00   ............. .
0020  01 01 00 80 32                                    ....2
```

```
No.     Time           Source                Destination           Protocol Length Info
      5 0.000036       host                  3.3.0                 USB      36     GET DESCRIPTOR Request CONFIGURATION
Frame 5: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309572000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309572000 UTC
    Epoch Arrival Time: 1775345253.309572000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000002000 seconds]
    [Time delta from previous displayed frame: 0.000002000 seconds]
    [Time since reference or first frame: 0.000036000 seconds]
    Frame Number: 5
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 6]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: CONFIGURATION (0x02)
    Language Id: no language specified (0x0000)
    wLength: 32
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 02   ................
0020  00 00 20 00                                        .. .
```

```
No.     Time           Source                Destination           Protocol Length Info
      6 0.000037       3.3.0                 host                  USB      60     GET DESCRIPTOR Response CONFIGURATION
Frame 6: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309573000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309573000 UTC
    Epoch Arrival Time: 1775345253.309573000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000001000 seconds]
    [Time delta from previous displayed frame: 0.000001000 seconds]
    [Time since reference or first frame: 0.000037000 seconds]
    Frame Number: 6
    Frame Length: 60 bytes (480 bits)
    Capture Length: 60 bytes (480 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 32
    [Request in: 5]
    [Time from request: 0.000001000 seconds]
    Control transfer stage: Complete (3)
CONFIGURATION DESCRIPTOR
    bLength: 9
    bDescriptorType: 0x02 (CONFIGURATION)
    wTotalLength: 32
    bNumInterfaces: 1
    bConfigurationValue: 1
    iConfiguration: 0
    Configuration bmAttributes: 0x80  NOT SELF-POWERED  NO REMOTE-WAKEUP
        1... .... = Must be 1: Must be 1 for USB 1.1 and higher
        .0.. .... = Self-Powered: This device is powered from the USB bus
        ..0. .... = Remote Wakeup: This device does NOT support remote wakeup
    bMaxPower: 50  (100mA)
INTERFACE DESCRIPTOR (0.0): class Vendor Specific
    bLength: 9
    bDescriptorType: 0x04 (INTERFACE)
    bInterfaceNumber: 0
    bAlternateSetting: 0
    bNumEndpoints: 2
    bInterfaceClass: Vendor Specific (0xff)
    bInterfaceSubClass: 0x00
    bInterfaceProtocol: 0x00
    iInterface: 0
ENDPOINT DESCRIPTOR
    bLength: 7
    bDescriptorType: 0x05 (ENDPOINT)
    bEndpointAddress: 0x01  OUT  Endpoint:1
        0... .... = Direction: OUT Endpoint
        .... 0001 = Endpoint Number: 0x1
    bmAttributes: 0x02
        .... ..10 = Transfertype: Bulk-Transfer (0x2)
    wMaxPacketSize: 512
        .... .010 0000 0000 = Maximum Packet Size: 512
    bInterval: 0
ENDPOINT DESCRIPTOR
    bLength: 7
    bDescriptorType: 0x05 (ENDPOINT)
    bEndpointAddress: 0x81  IN  Endpoint:1
        1... .... = Direction: IN Endpoint
        .... 0001 = Endpoint Number: 0x1
    bmAttributes: 0x02
        .... ..10 = Transfertype: Bulk-Transfer (0x2)
    wMaxPacketSize: 512
        .... .010 0000 0000 = Maximum Packet Size: 512
    bInterval: 0
```

```
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J..........
0010  01 03 00 03 00 80 02 20 00 00 00 03 09 02 20 00   ....... ...... .
0020  01 01 00 80 32 09 04 00 00 02 ff 00 00 00 07 05   ....2..........
0030  01 02 00 02 00 07 05 81 02 00 02 00               ............
```

```
No.     Time           Source                Destination           Protocol Length Info
      7 0.000039       host                  3.3.0                 USB      36     GET STATUS Request
Frame 7: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309575000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309575000 UTC
    Epoch Arrival Time: 1775345253.309575000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000002000 seconds]
    [Time delta from previous displayed frame: 0.000002000 seconds]
    [Time since reference or first frame: 0.000039000 seconds]
    Frame Number: 7
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_STATUS_FROM_DEVICE (0x0013)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 8]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET STATUS (0)
    wValue: 0x0000
    wIndex: 0 (0x0000)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 13 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 00 00 00   ................
0020  00 00 02 00                                       ....
```

```
No.     Time           Source                Destination           Protocol Length Info
      8 0.000133       3.3.0                 host                  USB      30     GET STATUS Response
Frame 8: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309669000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309669000 UTC
    Epoch Arrival Time: 1775345253.309669000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000094000 seconds]
    [Time delta from previous displayed frame: 0.000094000 seconds]
    [Time since reference or first frame: 0.000133000 seconds]
    Frame Number: 8
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 7]
    [Time from request: 0.000094000 seconds]
    Control transfer stage: Complete (3)
wStatus: 0x0000
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 00 00         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
      9 0.000159       host                  3.3.0                 USB      36     SET CONFIGURATION Request
Frame 9: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.309695000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.309695000 UTC
    Epoch Arrival Time: 1775345253.309695000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000026000 seconds]
    [Time delta from previous displayed frame: 0.000026000 seconds]
    [Time since reference or first frame: 0.000159000 seconds]
    Frame Number: 9
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_SELECT_CONFIGURATION (0x0000)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x00, Direction: OUT
        0... .... = Direction: OUT (0)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 10]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x00
        0... .... = Direction: Host-to-device
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: SET CONFIGURATION (9)
    bConfigurationValue: 1
    wIndex: 0 (0x0000)
    wLength: 0
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 00 00   .. .J..........
0010  00 03 00 03 00 00 02 08 00 00 00 00 00 00 09 01 00   ................
0020  00 00 00 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     10 0.001490       3.3.0                 host                  USB      28     SET CONFIGURATION Response
Frame 10: 28 bytes on wire (224 bits), 28 bytes captured (224 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:33.311026000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:33.311026000 UTC
    Epoch Arrival Time: 1775345253.311026000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.001331000 seconds]
    [Time delta from previous displayed frame: 0.001331000 seconds]
    [Time since reference or first frame: 0.001490000 seconds]
    Frame Number: 10
    Frame Length: 28 bytes (224 bits)
    Capture Length: 28 bytes (224 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_SELECT_CONFIGURATION (0x0000)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x00, Direction: OUT
        0... .... = Direction: OUT (0)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 0
    [Request in: 9]
    [Time from request: 0.001331000 seconds]
    Control transfer stage: Complete (3)
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 00 00   .. .J..........
0010  01 03 00 03 00 00 02 00 00 00 00 03               ............
```

```
No.     Time           Source                Destination           Protocol Length Info
     11 7.273755       host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 11: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.583291000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.583291000 UTC
    Epoch Arrival Time: 1775345260.583291000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 7.272265000 seconds]
    [Time delta from previous displayed frame: 7.272265000 seconds]
    [Time since reference or first frame: 7.273755000 seconds]
    Frame Number: 11
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 12]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     12 7.284904       3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 12: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.594440000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.594440000 UTC
    Epoch Arrival Time: 1775345260.594440000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011149000 seconds]
    [Time delta from previous displayed frame: 0.011149000 seconds]
    [Time since reference or first frame: 7.284904000 seconds]
    Frame Number: 12
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 11]
    [Time from request: 0.011149000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
     13 7.285041       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 13: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.594577000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.594577000 UTC
    Epoch Arrival Time: 1775345260.594577000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000137000 seconds]
    [Time delta from previous displayed frame: 0.000137000 seconds]
    [Time since reference or first frame: 7.285041000 seconds]
    Frame Number: 13
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 14]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     14 7.296109       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 14: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.605645000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.605645000 UTC
    Epoch Arrival Time: 1775345260.605645000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011068000 seconds]
    [Time delta from previous displayed frame: 0.011068000 seconds]
    [Time since reference or first frame: 7.296109000 seconds]
    Frame Number: 14
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 13]
    [Time from request: 0.011068000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     15 7.296191       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 15: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.605727000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.605727000 UTC
    Epoch Arrival Time: 1775345260.605727000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000082000 seconds]
    [Time delta from previous displayed frame: 0.000082000 seconds]
    [Time since reference or first frame: 7.296191000 seconds]
    Frame Number: 15
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 16]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     16 7.307236       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 16: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.616772000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.616772000 UTC
    Epoch Arrival Time: 1775345260.616772000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011045000 seconds]
    [Time delta from previous displayed frame: 0.011045000 seconds]
    [Time since reference or first frame: 7.307236000 seconds]
    Frame Number: 16
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 15]
    [Time from request: 0.011045000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     17 7.307305       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 17: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.616841000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.616841000 UTC
    Epoch Arrival Time: 1775345260.616841000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000069000 seconds]
    [Time delta from previous displayed frame: 0.000069000 seconds]
    [Time since reference or first frame: 7.307305000 seconds]
    Frame Number: 17
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 18]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     18 7.318387       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 18: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.627923000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.627923000 UTC
    Epoch Arrival Time: 1775345260.627923000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011082000 seconds]
    [Time delta from previous displayed frame: 0.011082000 seconds]
    [Time since reference or first frame: 7.318387000 seconds]
    Frame Number: 18
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 17]
    [Time from request: 0.011082000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     19 7.318466       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 19: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.628002000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.628002000 UTC
    Epoch Arrival Time: 1775345260.628002000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000079000 seconds]
    [Time delta from previous displayed frame: 0.000079000 seconds]
    [Time since reference or first frame: 7.318466000 seconds]
    Frame Number: 19
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 20]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     20 7.329542       3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 20: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.639078000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.639078000 UTC
    Epoch Arrival Time: 1775345260.639078000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011076000 seconds]
    [Time delta from previous displayed frame: 0.011076000 seconds]
    [Time since reference or first frame: 7.329542000 seconds]
    Frame Number: 20
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 19]
    [Time from request: 0.011076000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
     21 7.329620       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 21: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.639156000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.639156000 UTC
    Epoch Arrival Time: 1775345260.639156000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000078000 seconds]
    [Time delta from previous displayed frame: 0.000078000 seconds]
    [Time since reference or first frame: 7.329620000 seconds]
    Frame Number: 21
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 22]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     22 7.340662       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 22: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.650198000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.650198000 UTC
    Epoch Arrival Time: 1775345260.650198000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011042000 seconds]
    [Time delta from previous displayed frame: 0.011042000 seconds]
    [Time since reference or first frame: 7.340662000 seconds]
    Frame Number: 22
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 21]
    [Time from request: 0.011042000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     23 7.340730       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 23: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.650266000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.650266000 UTC
    Epoch Arrival Time: 1775345260.650266000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000068000 seconds]
    [Time delta from previous displayed frame: 0.000068000 seconds]
    [Time since reference or first frame: 7.340730000 seconds]
    Frame Number: 23
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 24]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     24 7.351794       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 24: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.661330000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.661330000 UTC
    Epoch Arrival Time: 1775345260.661330000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011064000 seconds]
    [Time delta from previous displayed frame: 0.011064000 seconds]
    [Time since reference or first frame: 7.351794000 seconds]
    Frame Number: 24
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 23]
    [Time from request: 0.011064000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     25 7.351887       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 25: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.661423000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.661423000 UTC
    Epoch Arrival Time: 1775345260.661423000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000093000 seconds]
    [Time delta from previous displayed frame: 0.000093000 seconds]
    [Time since reference or first frame: 7.351887000 seconds]
    Frame Number: 25
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 26]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     26 7.362962       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 26: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.672498000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.672498000 UTC
    Epoch Arrival Time: 1775345260.672498000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011075000 seconds]
    [Time delta from previous displayed frame: 0.011075000 seconds]
    [Time since reference or first frame: 7.362962000 seconds]
    Frame Number: 26
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 25]
    [Time from request: 0.011075000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     27 7.363061       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 27: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.672597000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.672597000 UTC
    Epoch Arrival Time: 1775345260.672597000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000099000 seconds]
    [Time delta from previous displayed frame: 0.000099000 seconds]
    [Time since reference or first frame: 7.363061000 seconds]
    Frame Number: 27
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 28]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     28 7.374107       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 28: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.683643000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.683643000 UTC
    Epoch Arrival Time: 1775345260.683643000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011046000 seconds]
    [Time delta from previous displayed frame: 0.011046000 seconds]
    [Time since reference or first frame: 7.374107000 seconds]
    Frame Number: 28
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 27]
    [Time from request: 0.011046000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     29 7.374205       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 29: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.683741000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.683741000 UTC
    Epoch Arrival Time: 1775345260.683741000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 7.374205000 seconds]
    Frame Number: 29
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499c589a0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 30]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 a0 89 c5 99 04 c7 ff ff 00 00 00 00 0b 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     30 7.385272       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 30: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.694808000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.694808000 UTC
    Epoch Arrival Time: 1775345260.694808000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011067000 seconds]
    [Time delta from previous displayed frame: 0.011067000 seconds]
    [Time since reference or first frame: 7.385272000 seconds]
    Frame Number: 30
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499c589a0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 29]
    [Time from request: 0.011067000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 a0 89 c5 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     31 7.385331       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 31: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.694867000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.694867000 UTC
    Epoch Arrival Time: 1775345260.694867000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000059000 seconds]
    [Time delta from previous displayed frame: 0.000059000 seconds]
    [Time since reference or first frame: 7.385331000 seconds]
    Frame Number: 31
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499c589a0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 32]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 a0 89 c5 99 04 c7 ff ff 00 00 00 00 0b 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     32 7.396414       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 32: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.705950000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.705950000 UTC
    Epoch Arrival Time: 1775345260.705950000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011083000 seconds]
    [Time delta from previous displayed frame: 0.011083000 seconds]
    [Time since reference or first frame: 7.396414000 seconds]
    Frame Number: 32
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499c589a0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 31]
    [Time from request: 0.011083000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 a0 89 c5 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                        X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     33 7.398856       host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 33: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.708392000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.708392000 UTC
    Epoch Arrival Time: 1775345260.708392000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.002442000 seconds]
    [Time delta from previous displayed frame: 0.002442000 seconds]
    [Time since reference or first frame: 7.398856000 seconds]
    Frame Number: 33
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 34]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     34 7.409988       3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 34: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.719524000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.719524000 UTC
    Epoch Arrival Time: 1775345260.719524000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011132000 seconds]
    [Time delta from previous displayed frame: 0.011132000 seconds]
    [Time since reference or first frame: 7.409988000 seconds]
    Frame Number: 34
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 33]
    [Time from request: 0.011132000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
     35 7.410060       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 35: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.719596000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.719596000 UTC
    Epoch Arrival Time: 1775345260.719596000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000072000 seconds]
    [Time delta from previous displayed frame: 0.000072000 seconds]
    [Time since reference or first frame: 7.410060000 seconds]
    Frame Number: 35
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 36]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     36 7.421112       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 36: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.730648000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.730648000 UTC
    Epoch Arrival Time: 1775345260.730648000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011052000 seconds]
    [Time delta from previous displayed frame: 0.011052000 seconds]
    [Time since reference or first frame: 7.421112000 seconds]
    Frame Number: 36
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 35]
    [Time from request: 0.011052000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     37 7.421174       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 37: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.730710000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.730710000 UTC
    Epoch Arrival Time: 1775345260.730710000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000062000 seconds]
    [Time delta from previous displayed frame: 0.000062000 seconds]
    [Time since reference or first frame: 7.421174000 seconds]
    Frame Number: 37
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 38]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     38 7.432253       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 38: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.741789000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.741789000 UTC
    Epoch Arrival Time: 1775345260.741789000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011079000 seconds]
    [Time delta from previous displayed frame: 0.011079000 seconds]
    [Time since reference or first frame: 7.432253000 seconds]
    Frame Number: 38
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 37]
    [Time from request: 0.011079000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     39 7.432319       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 39: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.741855000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.741855000 UTC
    Epoch Arrival Time: 1775345260.741855000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000066000 seconds]
    [Time delta from previous displayed frame: 0.000066000 seconds]
    [Time since reference or first frame: 7.432319000 seconds]
    Frame Number: 39
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 40]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     40 7.443399       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 40: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.752935000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.752935000 UTC
    Epoch Arrival Time: 1775345260.752935000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011080000 seconds]
    [Time delta from previous displayed frame: 0.011080000 seconds]
    [Time since reference or first frame: 7.443399000 seconds]
    Frame Number: 40
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 39]
    [Time from request: 0.011080000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     41 7.443472       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 41: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.753008000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.753008000 UTC
    Epoch Arrival Time: 1775345260.753008000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000073000 seconds]
    [Time delta from previous displayed frame: 0.000073000 seconds]
    [Time since reference or first frame: 7.443472000 seconds]
    Frame Number: 41
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 42]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     42 7.454529       3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 42: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.764065000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.764065000 UTC
    Epoch Arrival Time: 1775345260.764065000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011057000 seconds]
    [Time delta from previous displayed frame: 0.011057000 seconds]
    [Time since reference or first frame: 7.454529000 seconds]
    Frame Number: 42
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 41]
    [Time from request: 0.011057000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
     43 7.454614       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 43: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.764150000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.764150000 UTC
    Epoch Arrival Time: 1775345260.764150000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000085000 seconds]
    [Time delta from previous displayed frame: 0.000085000 seconds]
    [Time since reference or first frame: 7.454614000 seconds]
    Frame Number: 43
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 44]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     44 7.465657       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 44: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.775193000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.775193000 UTC
    Epoch Arrival Time: 1775345260.775193000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011043000 seconds]
    [Time delta from previous displayed frame: 0.011043000 seconds]
    [Time since reference or first frame: 7.465657000 seconds]
    Frame Number: 44
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 43]
    [Time from request: 0.011043000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     45 7.465751       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 45: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.775287000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.775287000 UTC
    Epoch Arrival Time: 1775345260.775287000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000094000 seconds]
    [Time delta from previous displayed frame: 0.000094000 seconds]
    [Time since reference or first frame: 7.465751000 seconds]
    Frame Number: 45
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 46]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     46 7.476818       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 46: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.786354000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.786354000 UTC
    Epoch Arrival Time: 1775345260.786354000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011067000 seconds]
    [Time delta from previous displayed frame: 0.011067000 seconds]
    [Time since reference or first frame: 7.476818000 seconds]
    Frame Number: 46
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 45]
    [Time from request: 0.011067000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     47 7.476901       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 47: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.786437000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.786437000 UTC
    Epoch Arrival Time: 1775345260.786437000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000083000 seconds]
    [Time delta from previous displayed frame: 0.000083000 seconds]
    [Time since reference or first frame: 7.476901000 seconds]
    Frame Number: 47
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 48]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     48 7.487965       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 48: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.797501000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.797501000 UTC
    Epoch Arrival Time: 1775345260.797501000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011064000 seconds]
    [Time delta from previous displayed frame: 0.011064000 seconds]
    [Time since reference or first frame: 7.487965000 seconds]
    Frame Number: 48
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 47]
    [Time from request: 0.011064000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     49 7.488056       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 49: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.797592000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.797592000 UTC
    Epoch Arrival Time: 1775345260.797592000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000091000 seconds]
    [Time delta from previous displayed frame: 0.000091000 seconds]
    [Time since reference or first frame: 7.488056000 seconds]
    Frame Number: 49
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 50]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     50 7.499119       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 50: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.808655000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.808655000 UTC
    Epoch Arrival Time: 1775345260.808655000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011063000 seconds]
    [Time delta from previous displayed frame: 0.011063000 seconds]
    [Time since reference or first frame: 7.499119000 seconds]
    Frame Number: 50
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 49]
    [Time from request: 0.011063000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     51 7.499217       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 51: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.808753000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.808753000 UTC
    Epoch Arrival Time: 1775345260.808753000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 7.499217000 seconds]
    Frame Number: 51
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 52]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 0b 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     52 7.510302       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 52: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.819838000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.819838000 UTC
    Epoch Arrival Time: 1775345260.819838000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011085000 seconds]
    [Time delta from previous displayed frame: 0.011085000 seconds]
    [Time since reference or first frame: 7.510302000 seconds]
    Frame Number: 52
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 51]
    [Time from request: 0.011085000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     53 7.510338       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 53: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.819874000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.819874000 UTC
    Epoch Arrival Time: 1775345260.819874000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000036000 seconds]
    [Time delta from previous displayed frame: 0.000036000 seconds]
    [Time since reference or first frame: 7.510338000 seconds]
    Frame Number: 53
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 54]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 0b 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     54 7.521403       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 54: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.830939000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.830939000 UTC
    Epoch Arrival Time: 1775345260.830939000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011065000 seconds]
    [Time delta from previous displayed frame: 0.011065000 seconds]
    [Time since reference or first frame: 7.521403000 seconds]
    Frame Number: 54
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 53]
    [Time from request: 0.011065000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     55 7.563528       host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 55: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.873064000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.873064000 UTC
    Epoch Arrival Time: 1775345260.873064000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.042125000 seconds]
    [Time delta from previous displayed frame: 0.042125000 seconds]
    [Time since reference or first frame: 7.563528000 seconds]
    Frame Number: 55
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 56]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     56 7.574671       3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 56: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.884207000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.884207000 UTC
    Epoch Arrival Time: 1775345260.884207000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011143000 seconds]
    [Time delta from previous displayed frame: 0.011143000 seconds]
    [Time since reference or first frame: 7.574671000 seconds]
    Frame Number: 56
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 55]
    [Time from request: 0.011143000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
     57 7.574782       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 57: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.884318000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.884318000 UTC
    Epoch Arrival Time: 1775345260.884318000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000111000 seconds]
    [Time delta from previous displayed frame: 0.000111000 seconds]
    [Time since reference or first frame: 7.574782000 seconds]
    Frame Number: 57
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 58]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     58 7.585849       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 58: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.895385000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.895385000 UTC
    Epoch Arrival Time: 1775345260.895385000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011067000 seconds]
    [Time delta from previous displayed frame: 0.011067000 seconds]
    [Time since reference or first frame: 7.585849000 seconds]
    Frame Number: 58
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 57]
    [Time from request: 0.011067000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     59 7.585916       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 59: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.895452000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.895452000 UTC
    Epoch Arrival Time: 1775345260.895452000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000067000 seconds]
    [Time delta from previous displayed frame: 0.000067000 seconds]
    [Time since reference or first frame: 7.585916000 seconds]
    Frame Number: 59
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 60]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     60 7.596970       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 60: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.906506000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.906506000 UTC
    Epoch Arrival Time: 1775345260.906506000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011054000 seconds]
    [Time delta from previous displayed frame: 0.011054000 seconds]
    [Time since reference or first frame: 7.596970000 seconds]
    Frame Number: 60
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 59]
    [Time from request: 0.011054000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     61 7.597041       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 61: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.906577000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.906577000 UTC
    Epoch Arrival Time: 1775345260.906577000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000071000 seconds]
    [Time delta from previous displayed frame: 0.000071000 seconds]
    [Time since reference or first frame: 7.597041000 seconds]
    Frame Number: 61
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 62]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     62 7.608130       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 62: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.917666000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.917666000 UTC
    Epoch Arrival Time: 1775345260.917666000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011089000 seconds]
    [Time delta from previous displayed frame: 0.011089000 seconds]
    [Time since reference or first frame: 7.608130000 seconds]
    Frame Number: 62
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 61]
    [Time from request: 0.011089000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     63 7.608216       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 63: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.917752000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.917752000 UTC
    Epoch Arrival Time: 1775345260.917752000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000086000 seconds]
    [Time delta from previous displayed frame: 0.000086000 seconds]
    [Time since reference or first frame: 7.608216000 seconds]
    Frame Number: 63
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 64]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     64 7.619298       3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 64: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.928834000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.928834000 UTC
    Epoch Arrival Time: 1775345260.928834000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011082000 seconds]
    [Time delta from previous displayed frame: 0.011082000 seconds]
    [Time since reference or first frame: 7.619298000 seconds]
    Frame Number: 64
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 63]
    [Time from request: 0.011082000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
     65 7.619360       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 65: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.928896000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.928896000 UTC
    Epoch Arrival Time: 1775345260.928896000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000062000 seconds]
    [Time delta from previous displayed frame: 0.000062000 seconds]
    [Time since reference or first frame: 7.619360000 seconds]
    Frame Number: 65
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 66]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     66 7.630423       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 66: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.939959000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.939959000 UTC
    Epoch Arrival Time: 1775345260.939959000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011063000 seconds]
    [Time delta from previous displayed frame: 0.011063000 seconds]
    [Time since reference or first frame: 7.630423000 seconds]
    Frame Number: 66
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 65]
    [Time from request: 0.011063000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     67 7.630487       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 67: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.940023000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.940023000 UTC
    Epoch Arrival Time: 1775345260.940023000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000064000 seconds]
    [Time delta from previous displayed frame: 0.000064000 seconds]
    [Time since reference or first frame: 7.630487000 seconds]
    Frame Number: 67
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 68]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     68 7.641549       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 68: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.951085000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.951085000 UTC
    Epoch Arrival Time: 1775345260.951085000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011062000 seconds]
    [Time delta from previous displayed frame: 0.011062000 seconds]
    [Time since reference or first frame: 7.641549000 seconds]
    Frame Number: 68
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 67]
    [Time from request: 0.011062000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     69 7.641610       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 69: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.951146000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.951146000 UTC
    Epoch Arrival Time: 1775345260.951146000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000061000 seconds]
    [Time delta from previous displayed frame: 0.000061000 seconds]
    [Time since reference or first frame: 7.641610000 seconds]
    Frame Number: 69
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 70]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     70 7.652693       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 70: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.962229000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.962229000 UTC
    Epoch Arrival Time: 1775345260.962229000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011083000 seconds]
    [Time delta from previous displayed frame: 0.011083000 seconds]
    [Time since reference or first frame: 7.652693000 seconds]
    Frame Number: 70
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 69]
    [Time from request: 0.011083000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     71 7.652756       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 71: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.962292000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.962292000 UTC
    Epoch Arrival Time: 1775345260.962292000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000063000 seconds]
    [Time delta from previous displayed frame: 0.000063000 seconds]
    [Time since reference or first frame: 7.652756000 seconds]
    Frame Number: 71
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 72]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     72 7.663801       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 72: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.973337000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.973337000 UTC
    Epoch Arrival Time: 1775345260.973337000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011045000 seconds]
    [Time delta from previous displayed frame: 0.011045000 seconds]
    [Time since reference or first frame: 7.663801000 seconds]
    Frame Number: 72
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 71]
    [Time from request: 0.011045000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     73 7.663962       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 73: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.973498000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.973498000 UTC
    Epoch Arrival Time: 1775345260.973498000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000161000 seconds]
    [Time delta from previous displayed frame: 0.000161000 seconds]
    [Time since reference or first frame: 7.663962000 seconds]
    Frame Number: 73
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70495895010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 74]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 50 89 95 04 c7 ff ff 00 00 00 00 0b 00   ...P............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     74 7.675028       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 74: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.984564000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.984564000 UTC
    Epoch Arrival Time: 1775345260.984564000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011066000 seconds]
    [Time delta from previous displayed frame: 0.011066000 seconds]
    [Time since reference or first frame: 7.675028000 seconds]
    Frame Number: 74
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70495895010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 73]
    [Time from request: 0.011066000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 50 89 95 04 c7 ff ff 00 00 00 00 08 00   ...P............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     75 7.675090       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 75: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.984626000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.984626000 UTC
    Epoch Arrival Time: 1775345260.984626000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000062000 seconds]
    [Time delta from previous displayed frame: 0.000062000 seconds]
    [Time since reference or first frame: 7.675090000 seconds]
    Frame Number: 75
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 76]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 0b 00   .. .J...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     76 7.686156       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 76: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.995692000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.995692000 UTC
    Epoch Arrival Time: 1775345260.995692000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011066000 seconds]
    [Time delta from previous displayed frame: 0.011066000 seconds]
    [Time since reference or first frame: 7.686156000 seconds]
    Frame Number: 76
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704974ada20
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 75]
    [Time from request: 0.011066000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 20 da 4a 97 04 c7 ff ff 00 00 00 00 08 00   .. .J..........
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     77 7.687668       host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 77: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:40.997204000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:40.997204000 UTC
    Epoch Arrival Time: 1775345260.997204000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.001512000 seconds]
    [Time delta from previous displayed frame: 0.001512000 seconds]
    [Time since reference or first frame: 7.687668000 seconds]
    Frame Number: 77
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 78]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     78 7.698774       3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 78: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.008310000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.008310000 UTC
    Epoch Arrival Time: 1775345261.008310000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011106000 seconds]
    [Time delta from previous displayed frame: 0.011106000 seconds]
    [Time since reference or first frame: 7.698774000 seconds]
    Frame Number: 78
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 77]
    [Time from request: 0.011106000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
     79 7.698832       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 79: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.008368000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.008368000 UTC
    Epoch Arrival Time: 1775345261.008368000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000058000 seconds]
    [Time delta from previous displayed frame: 0.000058000 seconds]
    [Time since reference or first frame: 7.698832000 seconds]
    Frame Number: 79
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 80]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     80 7.709894       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 80: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.019430000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.019430000 UTC
    Epoch Arrival Time: 1775345261.019430000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011062000 seconds]
    [Time delta from previous displayed frame: 0.011062000 seconds]
    [Time since reference or first frame: 7.709894000 seconds]
    Frame Number: 80
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 79]
    [Time from request: 0.011062000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     81 7.709931       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 81: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.019467000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.019467000 UTC
    Epoch Arrival Time: 1775345261.019467000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000037000 seconds]
    [Time delta from previous displayed frame: 0.000037000 seconds]
    [Time since reference or first frame: 7.709931000 seconds]
    Frame Number: 81
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 82]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     82 7.720985       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 82: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.030521000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.030521000 UTC
    Epoch Arrival Time: 1775345261.030521000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011054000 seconds]
    [Time delta from previous displayed frame: 0.011054000 seconds]
    [Time since reference or first frame: 7.720985000 seconds]
    Frame Number: 82
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 81]
    [Time from request: 0.011054000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     83 7.721045       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 83: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.030581000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.030581000 UTC
    Epoch Arrival Time: 1775345261.030581000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000060000 seconds]
    [Time delta from previous displayed frame: 0.000060000 seconds]
    [Time since reference or first frame: 7.721045000 seconds]
    Frame Number: 83
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 84]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     84 7.732104       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 84: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.041640000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.041640000 UTC
    Epoch Arrival Time: 1775345261.041640000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011059000 seconds]
    [Time delta from previous displayed frame: 0.011059000 seconds]
    [Time since reference or first frame: 7.732104000 seconds]
    Frame Number: 84
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 83]
    [Time from request: 0.011059000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     85 7.732149       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 85: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.041685000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.041685000 UTC
    Epoch Arrival Time: 1775345261.041685000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000045000 seconds]
    [Time delta from previous displayed frame: 0.000045000 seconds]
    [Time since reference or first frame: 7.732149000 seconds]
    Frame Number: 85
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 86]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     86 7.743205       3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 86: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.052741000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.052741000 UTC
    Epoch Arrival Time: 1775345261.052741000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011056000 seconds]
    [Time delta from previous displayed frame: 0.011056000 seconds]
    [Time since reference or first frame: 7.743205000 seconds]
    Frame Number: 86
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 85]
    [Time from request: 0.011056000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
     87 7.743245       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 87: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.052781000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.052781000 UTC
    Epoch Arrival Time: 1775345261.052781000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000040000 seconds]
    [Time delta from previous displayed frame: 0.000040000 seconds]
    [Time since reference or first frame: 7.743245000 seconds]
    Frame Number: 87
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 88]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     88 7.754298       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 88: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.063834000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.063834000 UTC
    Epoch Arrival Time: 1775345261.063834000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011053000 seconds]
    [Time delta from previous displayed frame: 0.011053000 seconds]
    [Time since reference or first frame: 7.754298000 seconds]
    Frame Number: 88
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 87]
    [Time from request: 0.011053000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     89 7.754349       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 89: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.063885000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.063885000 UTC
    Epoch Arrival Time: 1775345261.063885000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000051000 seconds]
    [Time delta from previous displayed frame: 0.000051000 seconds]
    [Time since reference or first frame: 7.754349000 seconds]
    Frame Number: 89
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 90]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     90 7.765408       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 90: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.074944000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.074944000 UTC
    Epoch Arrival Time: 1775345261.074944000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011059000 seconds]
    [Time delta from previous displayed frame: 0.011059000 seconds]
    [Time since reference or first frame: 7.765408000 seconds]
    Frame Number: 90
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 89]
    [Time from request: 0.011059000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     91 7.765465       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 91: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.075001000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.075001000 UTC
    Epoch Arrival Time: 1775345261.075001000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000057000 seconds]
    [Time delta from previous displayed frame: 0.000057000 seconds]
    [Time since reference or first frame: 7.765465000 seconds]
    Frame Number: 91
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 92]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     92 7.776547       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 92: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.086083000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.086083000 UTC
    Epoch Arrival Time: 1775345261.086083000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011082000 seconds]
    [Time delta from previous displayed frame: 0.011082000 seconds]
    [Time since reference or first frame: 7.776547000 seconds]
    Frame Number: 92
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 91]
    [Time from request: 0.011082000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     93 7.776671       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 93: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.086207000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.086207000 UTC
    Epoch Arrival Time: 1775345261.086207000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000124000 seconds]
    [Time delta from previous displayed frame: 0.000124000 seconds]
    [Time since reference or first frame: 7.776671000 seconds]
    Frame Number: 93
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 94]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     94 7.787761       3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 94: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.097297000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.097297000 UTC
    Epoch Arrival Time: 1775345261.097297000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011090000 seconds]
    [Time delta from previous displayed frame: 0.011090000 seconds]
    [Time since reference or first frame: 7.787761000 seconds]
    Frame Number: 94
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 93]
    [Time from request: 0.011090000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
     95 7.787881       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 95: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.097417000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.097417000 UTC
    Epoch Arrival Time: 1775345261.097417000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000120000 seconds]
    [Time delta from previous displayed frame: 0.000120000 seconds]
    [Time since reference or first frame: 7.787881000 seconds]
    Frame Number: 95
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 96]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 0b 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     96 7.798990       3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 96: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.108526000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.108526000 UTC
    Epoch Arrival Time: 1775345261.108526000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011109000 seconds]
    [Time delta from previous displayed frame: 0.011109000 seconds]
    [Time since reference or first frame: 7.798990000 seconds]
    Frame Number: 96
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 95]
    [Time from request: 0.011109000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
     97 7.799037       host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 97: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.108573000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.108573000 UTC
    Epoch Arrival Time: 1775345261.108573000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000047000 seconds]
    [Time delta from previous displayed frame: 0.000047000 seconds]
    [Time since reference or first frame: 7.799037000 seconds]
    Frame Number: 97
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 98]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 0b 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
     98 7.810148       3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 98: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:41.119684000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:41.119684000 UTC
    Epoch Arrival Time: 1775345261.119684000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011111000 seconds]
    [Time delta from previous displayed frame: 0.011111000 seconds]
    [Time since reference or first frame: 7.810148000 seconds]
    Frame Number: 98
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 97]
    [Time from request: 0.011111000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
     99 11.254714      host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 99: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.564250000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.564250000 UTC
    Epoch Arrival Time: 1775345264.564250000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 3.444566000 seconds]
    [Time delta from previous displayed frame: 3.444566000 seconds]
    [Time since reference or first frame: 11.254714000 seconds]
    Frame Number: 99
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 100]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    100 11.265926      3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 100: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.575462000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.575462000 UTC
    Epoch Arrival Time: 1775345264.575462000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011212000 seconds]
    [Time delta from previous displayed frame: 0.011212000 seconds]
    [Time since reference or first frame: 11.265926000 seconds]
    Frame Number: 100
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 99]
    [Time from request: 0.011212000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
    101 11.266024      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 101: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.575560000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.575560000 UTC
    Epoch Arrival Time: 1775345264.575560000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 11.266024000 seconds]
    Frame Number: 101
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 102]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    102 11.277175      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 102: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.586711000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.586711000 UTC
    Epoch Arrival Time: 1775345264.586711000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011151000 seconds]
    [Time delta from previous displayed frame: 0.011151000 seconds]
    [Time since reference or first frame: 11.277175000 seconds]
    Frame Number: 102
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 101]
    [Time from request: 0.011151000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    103 11.277268      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 103: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.586804000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.586804000 UTC
    Epoch Arrival Time: 1775345264.586804000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000093000 seconds]
    [Time delta from previous displayed frame: 0.000093000 seconds]
    [Time since reference or first frame: 11.277268000 seconds]
    Frame Number: 103
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 104]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    104 11.288427      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 104: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.597963000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.597963000 UTC
    Epoch Arrival Time: 1775345264.597963000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011159000 seconds]
    [Time delta from previous displayed frame: 0.011159000 seconds]
    [Time since reference or first frame: 11.288427000 seconds]
    Frame Number: 104
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 103]
    [Time from request: 0.011159000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    105 11.288525      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 105: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.598061000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.598061000 UTC
    Epoch Arrival Time: 1775345264.598061000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 11.288525000 seconds]
    Frame Number: 105
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 106]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    106 11.299673      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 106: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.609209000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.609209000 UTC
    Epoch Arrival Time: 1775345264.609209000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011148000 seconds]
    [Time delta from previous displayed frame: 0.011148000 seconds]
    [Time since reference or first frame: 11.299673000 seconds]
    Frame Number: 106
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 105]
    [Time from request: 0.011148000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    107 11.299766      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 107: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.609302000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.609302000 UTC
    Epoch Arrival Time: 1775345264.609302000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000093000 seconds]
    [Time delta from previous displayed frame: 0.000093000 seconds]
    [Time since reference or first frame: 11.299766000 seconds]
    Frame Number: 107
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 108]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    108 11.310924      3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 108: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.620460000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.620460000 UTC
    Epoch Arrival Time: 1775345264.620460000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011158000 seconds]
    [Time delta from previous displayed frame: 0.011158000 seconds]
    [Time since reference or first frame: 11.310924000 seconds]
    Frame Number: 108
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 107]
    [Time from request: 0.011158000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
    109 11.311022      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 109: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.620558000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.620558000 UTC
    Epoch Arrival Time: 1775345264.620558000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 11.311022000 seconds]
    Frame Number: 109
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 110]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    110 11.322159      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 110: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.631695000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.631695000 UTC
    Epoch Arrival Time: 1775345264.631695000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011137000 seconds]
    [Time delta from previous displayed frame: 0.011137000 seconds]
    [Time since reference or first frame: 11.322159000 seconds]
    Frame Number: 110
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 109]
    [Time from request: 0.011137000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    111 11.322250      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 111: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.631786000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.631786000 UTC
    Epoch Arrival Time: 1775345264.631786000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000091000 seconds]
    [Time delta from previous displayed frame: 0.000091000 seconds]
    [Time since reference or first frame: 11.322250000 seconds]
    Frame Number: 111
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 112]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    112 11.333410      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 112: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.642946000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.642946000 UTC
    Epoch Arrival Time: 1775345264.642946000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011160000 seconds]
    [Time delta from previous displayed frame: 0.011160000 seconds]
    [Time since reference or first frame: 11.333410000 seconds]
    Frame Number: 112
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 111]
    [Time from request: 0.011160000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
    113 11.333508      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 113: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.643044000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.643044000 UTC
    Epoch Arrival Time: 1775345264.643044000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000098000 seconds]
    [Time delta from previous displayed frame: 0.000098000 seconds]
    [Time since reference or first frame: 11.333508000 seconds]
    Frame Number: 113
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 114]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    114 11.344596      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 114: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.654132000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.654132000 UTC
    Epoch Arrival Time: 1775345264.654132000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011088000 seconds]
    [Time delta from previous displayed frame: 0.011088000 seconds]
    [Time since reference or first frame: 11.344596000 seconds]
    Frame Number: 114
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704945bf010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 113]
    [Time from request: 0.011088000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 f0 5b 94 04 c7 ff ff 00 00 00 00 08 00   ....[...........
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    115 11.344696      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 115: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.654232000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.654232000 UTC
    Epoch Arrival Time: 1775345264.654232000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000100000 seconds]
    [Time delta from previous displayed frame: 0.000100000 seconds]
    [Time since reference or first frame: 11.344696000 seconds]
    Frame Number: 115
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 116]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    116 11.355770      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 116: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.665306000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.665306000 UTC
    Epoch Arrival Time: 1775345264.665306000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011074000 seconds]
    [Time delta from previous displayed frame: 0.011074000 seconds]
    [Time since reference or first frame: 11.355770000 seconds]
    Frame Number: 116
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 115]
    [Time from request: 0.011074000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    117 11.355878      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 117: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.665414000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.665414000 UTC
    Epoch Arrival Time: 1775345264.665414000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000108000 seconds]
    [Time delta from previous displayed frame: 0.000108000 seconds]
    [Time since reference or first frame: 11.355878000 seconds]
    Frame Number: 117
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 118]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 0b 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    118 11.366946      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 118: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.676482000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.676482000 UTC
    Epoch Arrival Time: 1775345264.676482000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011068000 seconds]
    [Time delta from previous displayed frame: 0.011068000 seconds]
    [Time since reference or first frame: 11.366946000 seconds]
    Frame Number: 118
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 117]
    [Time from request: 0.011068000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    119 11.367022      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 119: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.676558000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.676558000 UTC
    Epoch Arrival Time: 1775345264.676558000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000076000 seconds]
    [Time delta from previous displayed frame: 0.000076000 seconds]
    [Time since reference or first frame: 11.367022000 seconds]
    Frame Number: 119
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 120]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 0b 00   ...4............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    120 11.378175      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 120: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.687711000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.687711000 UTC
    Epoch Arrival Time: 1775345264.687711000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011153000 seconds]
    [Time delta from previous displayed frame: 0.011153000 seconds]
    [Time since reference or first frame: 11.378175000 seconds]
    Frame Number: 120
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc704998d34b0
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 119]
    [Time from request: 0.011153000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 b0 34 8d 99 04 c7 ff ff 00 00 00 00 08 00   ...4............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
    121 11.661891      host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 121: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.971427000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.971427000 UTC
    Epoch Arrival Time: 1775345264.971427000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.283716000 seconds]
    [Time delta from previous displayed frame: 0.283716000 seconds]
    [Time since reference or first frame: 11.661891000 seconds]
    Frame Number: 121
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 122]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    122 11.673032      3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 122: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.982568000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.982568000 UTC
    Epoch Arrival Time: 1775345264.982568000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011141000 seconds]
    [Time delta from previous displayed frame: 0.011141000 seconds]
    [Time since reference or first frame: 11.673032000 seconds]
    Frame Number: 122
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ce0010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 121]
    [Time from request: 0.011141000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 10 00 ce 99 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
    123 11.673133      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 123: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.982669000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.982669000 UTC
    Epoch Arrival Time: 1775345264.982669000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000101000 seconds]
    [Time delta from previous displayed frame: 0.000101000 seconds]
    [Time since reference or first frame: 11.673133000 seconds]
    Frame Number: 123
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 124]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    124 11.684330      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 124: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.993866000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.993866000 UTC
    Epoch Arrival Time: 1775345264.993866000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011197000 seconds]
    [Time delta from previous displayed frame: 0.011197000 seconds]
    [Time since reference or first frame: 11.684330000 seconds]
    Frame Number: 124
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 123]
    [Time from request: 0.011197000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    125 11.684417      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 125: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:44.993953000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:44.993953000 UTC
    Epoch Arrival Time: 1775345264.993953000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000087000 seconds]
    [Time delta from previous displayed frame: 0.000087000 seconds]
    [Time since reference or first frame: 11.684417000 seconds]
    Frame Number: 125
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 126]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    126 11.695549      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 126: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.005085000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.005085000 UTC
    Epoch Arrival Time: 1775345265.005085000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011132000 seconds]
    [Time delta from previous displayed frame: 0.011132000 seconds]
    [Time since reference or first frame: 11.695549000 seconds]
    Frame Number: 126
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 125]
    [Time from request: 0.011132000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    127 11.695639      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 127: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.005175000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.005175000 UTC
    Epoch Arrival Time: 1775345265.005175000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000090000 seconds]
    [Time delta from previous displayed frame: 0.000090000 seconds]
    [Time since reference or first frame: 11.695639000 seconds]
    Frame Number: 127
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 128]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    128 11.706729      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 128: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.016265000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.016265000 UTC
    Epoch Arrival Time: 1775345265.016265000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011090000 seconds]
    [Time delta from previous displayed frame: 0.011090000 seconds]
    [Time since reference or first frame: 11.706729000 seconds]
    Frame Number: 128
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 127]
    [Time from request: 0.011090000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    129 11.706802      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 129: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.016338000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.016338000 UTC
    Epoch Arrival Time: 1775345265.016338000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000073000 seconds]
    [Time delta from previous displayed frame: 0.000073000 seconds]
    [Time since reference or first frame: 11.706802000 seconds]
    Frame Number: 129
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 130]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    130 11.717956      3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 130: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.027492000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.027492000 UTC
    Epoch Arrival Time: 1775345265.027492000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011154000 seconds]
    [Time delta from previous displayed frame: 0.011154000 seconds]
    [Time since reference or first frame: 11.717956000 seconds]
    Frame Number: 130
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 129]
    [Time from request: 0.011154000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
    131 11.718047      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 131: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.027583000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.027583000 UTC
    Epoch Arrival Time: 1775345265.027583000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000091000 seconds]
    [Time delta from previous displayed frame: 0.000091000 seconds]
    [Time since reference or first frame: 11.718047000 seconds]
    Frame Number: 131
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 132]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    132 11.729175      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 132: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.038711000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.038711000 UTC
    Epoch Arrival Time: 1775345265.038711000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011128000 seconds]
    [Time delta from previous displayed frame: 0.011128000 seconds]
    [Time since reference or first frame: 11.729175000 seconds]
    Frame Number: 132
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 131]
    [Time from request: 0.011128000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    133 11.729264      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 133: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.038800000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.038800000 UTC
    Epoch Arrival Time: 1775345265.038800000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000089000 seconds]
    [Time delta from previous displayed frame: 0.000089000 seconds]
    [Time since reference or first frame: 11.729264000 seconds]
    Frame Number: 133
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 134]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                       ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    134 11.740358      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 134: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.049894000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.049894000 UTC
    Epoch Arrival Time: 1775345265.049894000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011094000 seconds]
    [Time delta from previous displayed frame: 0.011094000 seconds]
    [Time since reference or first frame: 11.740358000 seconds]
    Frame Number: 134
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 133]
    [Time from request: 0.011094000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
    135 11.740437      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 135: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.049973000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.049973000 UTC
    Epoch Arrival Time: 1775345265.049973000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000079000 seconds]
    [Time delta from previous displayed frame: 0.000079000 seconds]
    [Time since reference or first frame: 11.740437000 seconds]
    Frame Number: 135
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 136]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    136 11.751584      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 136: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.061120000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.061120000 UTC
    Epoch Arrival Time: 1775345265.061120000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011147000 seconds]
    [Time delta from previous displayed frame: 0.011147000 seconds]
    [Time since reference or first frame: 11.751584000 seconds]
    Frame Number: 136
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 135]
    [Time from request: 0.011147000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    137 11.751670      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 137: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.061206000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.061206000 UTC
    Epoch Arrival Time: 1775345265.061206000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000086000 seconds]
    [Time delta from previous displayed frame: 0.000086000 seconds]
    [Time since reference or first frame: 11.751670000 seconds]
    Frame Number: 137
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 138]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    138 11.762801      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 138: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.072337000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.072337000 UTC
    Epoch Arrival Time: 1775345265.072337000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011131000 seconds]
    [Time delta from previous displayed frame: 0.011131000 seconds]
    [Time since reference or first frame: 11.762801000 seconds]
    Frame Number: 138
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 137]
    [Time from request: 0.011131000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    139 11.762894      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 139: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.072430000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.072430000 UTC
    Epoch Arrival Time: 1775345265.072430000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000093000 seconds]
    [Time delta from previous displayed frame: 0.000093000 seconds]
    [Time since reference or first frame: 11.762894000 seconds]
    Frame Number: 139
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 140]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 0b 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    140 11.774045      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 140: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.083581000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.083581000 UTC
    Epoch Arrival Time: 1775345265.083581000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011151000 seconds]
    [Time delta from previous displayed frame: 0.011151000 seconds]
    [Time since reference or first frame: 11.774045000 seconds]
    Frame Number: 140
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 139]
    [Time from request: 0.011151000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    141 11.774100      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 141: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.083636000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.083636000 UTC
    Epoch Arrival Time: 1775345265.083636000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000055000 seconds]
    [Time delta from previous displayed frame: 0.000055000 seconds]
    [Time since reference or first frame: 11.774100000 seconds]
    Frame Number: 141
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 142]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 0b 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    142 11.785272      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 142: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.094808000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.094808000 UTC
    Epoch Arrival Time: 1775345265.094808000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011172000 seconds]
    [Time delta from previous displayed frame: 0.011172000 seconds]
    [Time since reference or first frame: 11.785272000 seconds]
    Frame Number: 142
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 141]
    [Time from request: 0.011172000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
    143 11.803783      host                  3.3.0                 USB      36     GET DESCRIPTOR Request DEVICE
Frame 143: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.113319000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.113319000 UTC
    Epoch Arrival Time: 1775345265.113319000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.018511000 seconds]
    [Time delta from previous displayed frame: 0.018511000 seconds]
    [Time since reference or first frame: 11.803783000 seconds]
    Frame Number: 143
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 144]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: DEVICE (0x01)
    Language Id: no language specified (0x0000)
    wLength: 18
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 01   ................
0020  00 00 12 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    144 11.814899      3.3.0                 host                  USB      46     GET DESCRIPTOR Response DEVICE
Frame 144: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.124435000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.124435000 UTC
    Epoch Arrival Time: 1775345265.124435000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011116000 seconds]
    [Time delta from previous displayed frame: 0.011116000 seconds]
    [Time since reference or first frame: 11.814899000 seconds]
    Frame Number: 144
    Frame Length: 46 bytes (368 bits)
    Capture Length: 46 bytes (368 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 18
    [Request in: 143]
    [Time from request: 0.011116000 seconds]
    Control transfer stage: Complete (3)
DEVICE DESCRIPTOR
    bLength: 18
    bDescriptorType: 0x01 (DEVICE)
    bcdUSB: 0x0210
    bDeviceClass: Device (0x00)
    bDeviceSubClass: 0
    bDeviceProtocol: 0 (Use class code info from Interface Descriptors)
    bMaxPacketSize0: 64
    idVendor: Unknown (0xaa55)
    idProduct: Unknown (0x8866)
    bcdDevice: 0x0000
    iManufacturer: 1
    iProduct: 2
    iSerialNumber: 0
    bNumConfigurations: 1
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 12 00 00 00 03 12 01 10 02   ................
0020  00 00 00 40 55 aa 66 88 00 00 01 02 00 01         ...@U.f.......
```

```
No.     Time           Source                Destination           Protocol Length Info
    145 11.815007      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 145: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.124543000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.124543000 UTC
    Epoch Arrival Time: 1775345265.124543000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000108000 seconds]
    [Time delta from previous displayed frame: 0.000108000 seconds]
    [Time since reference or first frame: 11.815007000 seconds]
    Frame Number: 145
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 146]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 2
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    146 11.826130      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 146: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.135666000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.135666000 UTC
    Epoch Arrival Time: 1775345265.135666000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011123000 seconds]
    [Time delta from previous displayed frame: 0.011123000 seconds]
    [Time since reference or first frame: 11.826130000 seconds]
    Frame Number: 146
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc7049a02c010
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 145]
    [Time from request: 0.011123000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 10 c0 02 9a 04 c7 ff ff 00 00 00 00 08 00   ................
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    147 11.826218      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 147: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.135754000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.135754000 UTC
    Epoch Arrival Time: 1775345265.135754000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000088000 seconds]
    [Time delta from previous displayed frame: 0.000088000 seconds]
    [Time since reference or first frame: 11.826218000 seconds]
    Frame Number: 147
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 148]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: no language specified (0x0000)
    wLength: 4
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  00 00 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    148 11.837383      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 148: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.146919000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.146919000 UTC
    Epoch Arrival Time: 1775345265.146919000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011165000 seconds]
    [Time delta from previous displayed frame: 0.011165000 seconds]
    [Time since reference or first frame: 11.837383000 seconds]
    Frame Number: 148
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 147]
    [Time from request: 0.011165000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    149 11.837472      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 149: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.147008000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.147008000 UTC
    Epoch Arrival Time: 1775345265.147008000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000089000 seconds]
    [Time delta from previous displayed frame: 0.000089000 seconds]
    [Time since reference or first frame: 11.837472000 seconds]
    Frame Number: 149
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 150]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    150 11.848569      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 150: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.158105000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.158105000 UTC
    Epoch Arrival Time: 1775345265.158105000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011097000 seconds]
    [Time delta from previous displayed frame: 0.011097000 seconds]
    [Time since reference or first frame: 11.848569000 seconds]
    Frame Number: 150
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 149]
    [Time from request: 0.011097000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 02 00 00 00 03 10 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    151 11.848683      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 151: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.158219000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.158219000 UTC
    Epoch Arrival Time: 1775345265.158219000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000114000 seconds]
    [Time delta from previous displayed frame: 0.000114000 seconds]
    [Time since reference or first frame: 11.848683000 seconds]
    Frame Number: 151
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 152]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x01
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 16
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 01 03   ................
0020  09 04 10 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    152 11.859824      3.3.0                 host                  USB      44     GET DESCRIPTOR Response STRING
Frame 152: 44 bytes on wire (352 bits), 44 bytes captured (352 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.169360000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.169360000 UTC
    Epoch Arrival Time: 1775345265.169360000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011141000 seconds]
    [Time delta from previous displayed frame: 0.011141000 seconds]
    [Time since reference or first frame: 11.859824000 seconds]
    Frame Number: 152
    Frame Length: 44 bytes (352 bits)
    Capture Length: 44 bytes (352 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 16
    [Request in: 151]
    [Time from request: 0.011141000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 16
    bDescriptorType: 0x03 (STRING)
    bString: Cypress
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 10 00 00 00 03 10 03 43 00   ..............C.
0020  79 00 70 00 72 00 65 00 73 00 73 00               y.p.r.e.s.s.
```

```
No.     Time           Source                Destination           Protocol Length Info
    153 11.859914      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 153: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.169450000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.169450000 UTC
    Epoch Arrival Time: 1775345265.169450000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000090000 seconds]
    [Time delta from previous displayed frame: 0.000090000 seconds]
    [Time since reference or first frame: 11.859914000 seconds]
    Frame Number: 153
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 154]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    154 11.871093      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 154: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.180629000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.180629000 UTC
    Epoch Arrival Time: 1775345265.180629000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011179000 seconds]
    [Time delta from previous displayed frame: 0.011179000 seconds]
    [Time since reference or first frame: 11.871093000 seconds]
    Frame Number: 154
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 153]
    [Time from request: 0.011179000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    155 11.871182      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 155: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.180718000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.180718000 UTC
    Epoch Arrival Time: 1775345265.180718000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000089000 seconds]
    [Time delta from previous displayed frame: 0.000089000 seconds]
    [Time since reference or first frame: 11.871182000 seconds]
    Frame Number: 155
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 156]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    156 11.882409      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 156: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.191945000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.191945000 UTC
    Epoch Arrival Time: 1775345265.191945000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011227000 seconds]
    [Time delta from previous displayed frame: 0.011227000 seconds]
    [Time since reference or first frame: 11.882409000 seconds]
    Frame Number: 156
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 155]
    [Time from request: 0.011227000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```

```
No.     Time           Source                Destination           Protocol Length Info
    157 11.882491      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 157: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.192027000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.192027000 UTC
    Epoch Arrival Time: 1775345265.192027000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000082000 seconds]
    [Time delta from previous displayed frame: 0.000082000 seconds]
    [Time since reference or first frame: 11.882491000 seconds]
    Frame Number: 157
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 158]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    158 11.893613      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING[Malformed Packet]
Frame 158: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.203149000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.203149000 UTC
    Epoch Arrival Time: 1775345265.203149000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011122000 seconds]
    [Time delta from previous displayed frame: 0.011122000 seconds]
    [Time since reference or first frame: 11.893613000 seconds]
    Frame Number: 158
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 157]
    [Time from request: 0.011122000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
[Malformed Packet: USB]
    [Expert Info (Error/Malformed): Malformed Packet (Exception occurred)]
        [Malformed Packet (Exception occurred)]
        [Severity level: Error]
        [Group: Malformed]
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 02 00 00 00 03 04 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    159 11.893701      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 159: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.203237000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.203237000 UTC
    Epoch Arrival Time: 1775345265.203237000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000088000 seconds]
    [Time delta from previous displayed frame: 0.000088000 seconds]
    [Time since reference or first frame: 11.893701000 seconds]
    Frame Number: 159
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 160]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x00
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 4
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 00 03   ................
0020  09 04 04 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    160 11.904840      3.3.0                 host                  USB      32     GET DESCRIPTOR Response STRING
Frame 160: 32 bytes on wire (256 bits), 32 bytes captured (256 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.214376000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.214376000 UTC
    Epoch Arrival Time: 1775345265.214376000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011139000 seconds]
    [Time delta from previous displayed frame: 0.011139000 seconds]
    [Time since reference or first frame: 11.904840000 seconds]
    Frame Number: 160
    Frame Length: 32 bytes (256 bits)
    Capture Length: 32 bytes (256 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70497fd2950
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 4
    [Request in: 159]
    [Time from request: 0.011139000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 4
    bDescriptorType: 0x03 (STRING)
    wLANGID: English (United States) (0x0409)
0000  1c 00 50 29 fd 97 04 c7 ff ff 00 00 00 00 08 00   ..P)............
0010  01 03 00 03 00 80 02 04 00 00 00 03 04 03 09 04   ................
```

```
No.     Time           Source                Destination           Protocol Length Info
    161 11.904921      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 161: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.214457000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.214457000 UTC
    Epoch Arrival Time: 1775345265.214457000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000081000 seconds]
    [Time delta from previous displayed frame: 0.000081000 seconds]
    [Time since reference or first frame: 11.904921000 seconds]
    Frame Number: 161
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 162]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 2
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 0b 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 02 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    162 11.916077      3.3.0                 host                  USB      30     GET DESCRIPTOR Response STRING
Frame 162: 30 bytes on wire (240 bits), 30 bytes captured (240 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.225613000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.225613000 UTC
    Epoch Arrival Time: 1775345265.225613000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011156000 seconds]
    [Time delta from previous displayed frame: 0.011156000 seconds]
    [Time since reference or first frame: 11.916077000 seconds]
    Frame Number: 162
    Frame Length: 30 bytes (240 bits)
    Capture Length: 30 bytes (240 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 2
    [Request in: 161]
    [Time from request: 0.011156000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString:
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 02 00 00 00 03 08 03         ..............
```

```
No.     Time           Source                Destination           Protocol Length Info
    163 11.916127      host                  3.3.0                 USB      36     GET DESCRIPTOR Request STRING
Frame 163: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.225663000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.225663000 UTC
    Epoch Arrival Time: 1775345265.225663000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.000050000 seconds]
    [Time delta from previous displayed frame: 0.000050000 seconds]
    [Time since reference or first frame: 11.916127000 seconds]
    Frame Number: 163
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: host]
    [Destination: 3.3.0]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_GET_DESCRIPTOR_FROM_DEVICE (0x000b)
    IRP information: 0x00, Direction: FDO -> PDO
        0000 000. = Reserved: 0x00
        .... ...0 = Direction: FDO -> PDO (0x0)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Response in: 164]
    Control transfer stage: Setup (0)
Setup Data
    bmRequestType: 0x80
        1... .... = Direction: Device-to-host
        .00. .... = Type: Standard (0x0)
        ...0 0000 = Recipient: Device (0x00)
    bRequest: GET DESCRIPTOR (6)
    Descriptor Index: 0x02
    bDescriptorType: STRING (0x03)
    Language Id: English (United States) (0x0409)
    wLength: 8
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 0b 00   ..px............
0010  00 03 00 03 00 80 02 08 00 00 00 00 80 06 02 03   ................
0020  09 04 08 00                                        ....
```

```
No.     Time           Source                Destination           Protocol Length Info
    164 11.927215      3.3.0                 host                  USB      36     GET DESCRIPTOR Response STRING
Frame 164: 36 bytes on wire (288 bits), 36 bytes captured (288 bits) on interface \\.\USBPcap3, id 0
    Section number: 1
    Interface id: 0 (\\.\USBPcap3)
        Interface name: \\.\USBPcap3
        Interface description: USBPcap3
    Encapsulation type: USB packets with USBPcap header (152)
    Arrival Time: Apr  5, 2026 07:27:45.236751000 RTZ 7 (зима)
    UTC Arrival Time: Apr  4, 2026 23:27:45.236751000 UTC
    Epoch Arrival Time: 1775345265.236751000
    [Time shift for this packet: 0.000000000 seconds]
    [Time delta from previous captured frame: 0.011088000 seconds]
    [Time delta from previous displayed frame: 0.011088000 seconds]
    [Time since reference or first frame: 11.927215000 seconds]
    Frame Number: 164
    Frame Length: 36 bytes (288 bits)
    Capture Length: 36 bytes (288 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: usb]
USB URB
    [Source: 3.3.0]
    [Destination: host]
    USBPcap pseudoheader length: 28
    IRP ID: 0xffffc70499ac7870
    IRP USBD_STATUS: USBD_STATUS_SUCCESS (0x00000000)
    URB Function: URB_FUNCTION_CONTROL_TRANSFER (0x0008)
    IRP information: 0x01, Direction: PDO -> FDO
        0000 000. = Reserved: 0x00
        .... ...1 = Direction: PDO -> FDO (0x1)
    URB bus id: 3
    Device address: 3
    Endpoint: 0x80, Direction: IN
        1... .... = Direction: IN (1)
        .... 0000 = Endpoint number: 0
    URB transfer type: URB_CONTROL (0x02)
    Packet Data Length: 8
    [Request in: 163]
    [Time from request: 0.011088000 seconds]
    Control transfer stage: Complete (3)
STRING DESCRIPTOR
    bLength: 8
    bDescriptorType: 0x03 (STRING)
    bString: FX3
0000  1c 00 70 78 ac 99 04 c7 ff ff 00 00 00 00 08 00   ..px............
0010  01 03 00 03 00 80 02 08 00 00 00 03 08 03 46 00   ..............F.
0020  58 00 33 00                                       X.3.
```