

Assignment 01

Paul Jones and Matthew Klein
Professor Professor Kostas Bekris
Design and Analysis of Computer Algorithms (01.198.344)

February 12, 2014

Part A

Problem 1

In each of the following situations indicate whether $f = O(g)$ or $f = \Omega(g)$ or $f = \Theta(g)$:

1. $f(n) = \sqrt{2^{7x}}, g(n) = \lg(7^{2x})$

$$\begin{aligned}f(n) &= \sqrt{2^{7x}} = \sqrt{128^x} \\g(n) &= \lg(7^{2x}) = \lg(49^x) \\lg(49^1) &\approx 5.6 \\\sqrt{128^1} &\approx 11.3\end{aligned}$$

Notice that both of these functions only grow relative to x .

$$f = \Omega(g)$$

2. $f(n) = 2^{n \ln(n)}, g(n) = n!$

The factorial, that is $n!$, function grows much, much faster than 2^n .

$$f = \Omega(g)$$

3. $f(n) = \lg(\lg^*(n)), g(n) = \lg^*(\lg(n))$

$$f = \Theta(g)$$

4. $f(n) = \frac{\lg(n^2)}{n}, g(n) = \lg^*(n)$

$$f(n) = \frac{\lg(n^2)}{n} = \frac{2\lg(n)}{n}$$

$$f = \Theta(g)$$

5. $f(n) = 2^n, g(n) = n^{\lg(n)}$

This is comparing the exponential function to a function that is less than n^2 .

$$f = \Omega(g)$$

6. $f(n) = 2^{\sqrt{\ln(n)}}, g(n) = n(\lg(n))^3$

$$f(n) = 2^{\sqrt{n}}, g(n) = (2^n)(n^3)$$

$$f = \Omega g$$

7. $f(n) = e^{\cos(x)}, g(n) = \lg(x)$

$$f = \Omega(g)$$

8. $f(n) = \lg(n^2), g(n) = (\lg(n))^2$

$$f = \Theta(g)$$

9. $f(n) = \sqrt{4n^2 - 12n + 9}, g(n) = n^{\frac{3}{2}}$

$$f = \Theta(g)$$

10. $f(n) = \sum_{k=1}^n k, g(n) = (n+2)^2$

$$f = \Omega(g)$$

Problem 2

Algorithm 1: Number_Theoretic_Algorithm (integer n)

```

1  $N \leftarrow \text{Random\_Sample}(0, 2^n - 1)$ ;
2 if  $N$  is even then
3    $N \leftarrow N + 1$  /* Worse case, N is odd,  $2 \cdot N - 1$ . */ ;
4  $m \leftarrow N \bmod n$  /* worse case same as  $n$  */ ;
5 for  $j \leftarrow 0$  to  $m$  do
6   if Greatest_Common_Divisor( $j, N$ )  $\neq 1$  then
7     return FALSE; /* GCD is  $O(n)$  */
8   Compute  $x, z$  so that  $N - 1 = 2^z \cdot x$  and  $x$  is odd;
9    $y_0 \leftarrow (N - 1 - j)^x \bmod N$ ;
10  for  $i \leftarrow 1$  to  $m$  do
11     $y_i \leftarrow y_{i-1}^2 \bmod N$  ;
12     $y_i \leftarrow y_i + y_{i-1} \bmod N$ ;
13  if Low_Error_Primality_Test( $y_m$ ) == FALSE then
14    return FALSE /* Naive primality test is  $O(\sqrt{n})$  */ ;
15 return TRUE;

```

Compute the asymptotic running time of the above algorithm as a function of its input parameter, given:

- The running times of integer arithmetic operations (e.g., multiplication of two large n -bit numbers is $O(n^2)$).
- Assume that sampling a number N is an operation linear to the number of bits needed to represent this number.

Do not just present the final result. For each line of pseudo-code indicate the best running time for the corresponding operation given current knowledge from lectures and recitations and then show how the overall running time emerges.

Worse case running n operations with times $O(n)$, $O(n)$, and $O(\sqrt{n})$.
That's a run time of $O(2n^2 + n^{\frac{3}{2}})$, resulting in big-O of $O(n^2)$.

Part B

Problem 3

A tree with m children is $\log_m(N + 1) - 1$.

Two perfect trees = something i don't get

Problem 4

Problem 5

Part C

Problem 6

Problem 7

Part D

Problem 8

Problem 9