```
Query 1:
PATTERN AND(LongY ly, LongC lc, VLongO vo, VLongY vy)
WHERE ly.blD=lc.bID \( \) lc.bID=vo.bID \( \) vo.bID = vy.bID
WITHIN 24h

Query 2:
PATTERN AND(ShortC sc, LongO lo, LongY ly, VLongC vc)
WHERE sc.bID=lo.bID \( \) lo.bID=ly.bID \( \) ly.bID = vc.bID
WITHIN 24h

Query 3:
PATTERN AND(ShortO so, SEQ(LongO lo, VLongC vc), LongC lc)
WHERE so.bID=lo.bID \( \) lo.bID=vc.bID \( \) vc.bID = lc.bID
WITHIN 24h

Query 4 / QWL:
PATTERN SEQ(ShortO so, AND(ShortY sy, VLongC vc), LongY ly)
WHERE so.bID=sy.bID \( \) sy.bID=vc.bID \( \) vc.bID = ly.bID
WITHIN 24h

PATTERN AND(LongY ly, LongC lc, ShortC sc, VLongY vy)
WHERE ly.bID=lc.bID \( \) lc.bID=sc.bID \( \) sc.bID = vy.bID
WITHIN 24h
```

Listing 1: Queries used for Citi Bike Dataset.

1 CITI BIKE

Characterization for derivation of event types:

- (1) short trip < 100s
- (2) long trip $100s \le x \le 5000s$
- (3) very long trip > 5000s
- (4) old, year of birth ≤ 1962
- (5) young, year of birth ≥ 1962
- (6) customer (instead of member) if not year of birth given

Examples for Event Types:

LongC corresponds to a **long trip** with the driver being a **customer**.

ShortY corresponds to a **short trip** with the driver being a **young** member.

VLongO corresponds to a **verylong trips** with the driver being a member of age group **old**.

```
Query 1 (double Update):
PATTERN SEQ(Submit s, Update1 u1, Schedule h, Update2 u2)
WHERE s.uID=u1.uID \wedge u1.uID=c.uID \wedge c.uID=u2.uID
WITHIN 30min
Query 2 / QWL (failed updates):
PATTERN SEQ(Update2 u2, Schedule sh, Update1 u1, Lost lo)
WHERE u2.uID=sh.uID \land sh.uID=u1.uID \land u1.uID=lo.uID
WITHIN 30min
PATTERN SEQ(Update2 u2, Fail f, Update1 u1, Lost lo)
WHERE u2.uID=f.uID \land f.uID=u1.uID \land u1.uID=lo.uID
WITHIN 30min
Query 3 (lost task):
PATTERN SEQ(Submit su, Schedule sh, Lost 1, Kill k ,Update2 u2 )
WHERE su.jID=sh.jID \land sh.jID=1.jID \land 1.jID=k.jID
∧ k.jID=u2.jID
WITHIN 30min
Query 3 (unlucky job):
WHERE sh.jID=e.jID \(\Lambda\) e.jID=f.jID \(\Lambda\) f.jID=u1.jID
WITHIN 30min
```

Listing 2: Queries used for Google Cluster.

2 GOOGLE CLUSTER MONITORING

A description of the event types contained in the Google Cluster queries can be found at $https://drive.google.com/file/d/0B5g07T_gRDg9Z0lsSTEtTWtpOW8/view?resourcekey=0-cozD56gA4fUDdrkHnLJSrQ.$

- o Update1 corresponds to Update_Scheduled
- o Update2 corresponds to Update_Running