Tutorials Exercises W3Schools app iOS & Android NEW Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

Git Advanced Remote

‹ Previous Next ›

What Are Git Remotes?

SHARE

Remotes are references to remote repositories.

They let you collaborate, fetch, and push code to shared projects on services like GitHub, GitLab, or Bitbucket.

Why Use Multiple Remotes?

You can add more than one remote to your project. This is useful for:

- Collaborating with different teams (e.g., your fork and the main project)
- Mirroring repositories
- Maintaining backups

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

Example: Add a Remote

```
[user@localhost] $ git remote add upstream https://github.com/other/repo.g
```

How to Remove a Remote

To remove a remote repository:

Example: Remove a Remote

```
[user@localhost] $ git remote remove upstream
```

How to Rename a Remote

To change the name of an existing remote (for example, renaming `origin` to `main-origin`):

Example: Rename a Remote

```
[user@localhost] $ git remote rename origin main-origin
```

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

REMOVE ADS

How to List All Remotes

See all remotes and their URLs:

Example: List Remotes

```
[user@localhost] $ git remote -v
```

How to Show Remote Details

Get detailed information about a specific remote (such as fetch/push URLs and tracked branches):

Example: Show Remote Info

```
[user@localhost] $ git remote show upstream
```

How to Fetch from a Remote

Fetch changes from any remote:

Example: Fetch from Upstream

W3Schools Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

How to Push to a Remote

Push your local branch to a specific remote repository:

Example: Push to a Remote

```
[user@localhost] $ git push upstream main
```

How to Track a Remote Branch

To set up a local branch to track a branch from a remote:

Example: Track a Remote Branch

```
[user@localhost] $ git checkout -b new-feature upstream/new-feature
```

Note: Managing multiple remotes is common in open source projects (e.g., `origin` for your fork, `upstream` for the main project).

Troubleshooting and Best Practices

- If you get "remote not found", check the spelling of the remote name with `git remote -v`.
- If fetch or push fails, make sure you have access to the remote repository.
- Use `git remote show <name>` to see details and troubleshoot issues.
- Check your network connection if you cannot reach a remote server.

schools Tutorials Exercises
W3Schools app iOS & Android NEW
Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

‹ Previous
Sign in to track progress
Next ›

schools
Get Certified in Git
Boost your career with an official certification
$95
Get certified
REMOVE ADS

Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

FREE ACCOUNT
Track your progress
XP earned 0
Day streak 0
Spaces 0
League —
Sign in to track progress

NEW
Learn in Adventure Mode
Coding fundamentals as bite-sized lessons and challenges.
Download on the App Store
GET IT ON Google Play
Learn more about Adventure Mode >

PLUS SPACES

W3Schools
Tutorials Exercises
W3Schools app NEW
iOS & Android
Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE
PRACTICE CONTACT US

Top Tutorials
HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References
HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
AngularJS Reference
jQuery Reference

Top Examples
HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified
HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

Tutorials Exercises W3Schools app iOS & Android NEW Sign In

C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.