Git Pull Branch from GitHub

‹ Previous Next ›

Pulling a Branch from GitHub

SHARE

Now continue working on our new `branch` in our local Git.

Lets `pull` from our GitHub repository again so that our code is up-to-date:

Change Platform:

GitHub

Bitbucket

GitLab

Example

```
[user@localhost] $ git pull
remote: Enumerating objects: 5, done.
remote: Counting objects: 100% (5/5), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 3 (delta 2), reused 0 (delta 0), pack-reu
Unpacking objects: 100% (3/3), 851 bytes | 9.00 KiB/s,
```

schools Tutorials Exercises W3Schools app iOS & Android NEW Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

Now our main `branch` is up todate. And we can see that there is a new `branch` available on GitHub.

Do a quick `status` check:

Example

```
[user@localhost] $ git status
                   On branch master
                   Your branch is up to date with 'origin/master'.

                   nothing to commit, working tree clean
```

And confirm which branches we have, and where we are working at the moment:

Example

```
[user@localhost] $ git branch
                   * master
```

So, we do not have the new `branch` on our local Git. But we know it is available on GitHub. So we can use the `-a` option to see all local and remote branches:

Example

```
[user@localhost] $ git branch -a
                   * master
                     remotes/origin/html-skeleton
                     remotes/origin/master
```

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

We see that the branch `html-skeleton` is available remotely, but not on our local git. Lets check it out:

Example

```
[user@localhost] $ git checkout html-skeleton
Switched to a new branch 'html-skeleton'
Branch 'html-skeleton' set up to track remote branch 'h
```

And check if it is all up to date:

Example

```
[user@localhost] $ git pull
Already up to date.
```

Which branches do we have now, and where are we working from?

Example

```
[user@localhost] $ git branch
* html-skeleton
  master
```

Now, open your favourite editor and confirm that the changes from the GitHub branch carried over.

That is how you pull a GitHub branch to your local Git.

REMOVE ADS

‹ Previous

Sign in to track progress

Next ›

Learn it.
Get certified.
Get hired.

$95 per course
one-time payment

Exam and certificate included.

Get started

Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

FREE ACCOUNT
Track your progress
XP earned 0
Day streak 0
Spaces 0
League —

NEW
Learn in Adventure Mode
Coding fundamentals as bite-sized lessons and challenges.
Download on the App Store
GET IT ON Google Play
Learn more about

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
AngularJS Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate

Tutorials Exercises W3Schools app iOS & Android NEW Sign In

C++ C# AWS W3.CSS HOW TO BOOTSTRAP REACT MYSQL JQUE

jQuery Examples XML Certificate

FORUM ABOUT CAMPUS

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.