W3Schools app NEW iOS & Android
Sign In
Tutorials Exercises
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

MySQL ANY Operator

‹ Previous
Next ›

The MySQL ANY Operator

SHARE

The `ANY` operator is used to compare a value to every value returned by a subquery.

The `ANY` operator evaluates to TRUE if **at least one value** in the subquery result-set meet the condition.

ANY Syntax

```
SELECT column_name(s)
FROM table_name
WHERE column_name operator ANY (subquery);
```

Note: The *operator* must be a standard comparison operator (=, <>, !=, >, >=, <, or <=).

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

Demo Database

Below is a selection from the **"Products"** table in the Northwind sample database:

ProductID	ProductName	Price
1	Chais	18.00
2	Chang	19.00
3	Aniseed Syrup	10.00
4	Chef Anton's Cajun Seasoning	22.00

And a selection from the **"OrderDetails"** table:

OrderDetailID	ProductID	Quantity
1	11	12
2	42	10
3	72	5
4	14	9

REMOVE ADS

MySQL ANY Examples

The following SQL returns the ProductName if it finds ANY records in the "OrderDetails" table that has Quantity equal to 10 (this will return TRUE because the Quantity column has some

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

```
SELECT ProductName FROM Products
WHERE ProductID = ANY (
  SELECT ProductID
  FROM OrderDetails
  WHERE Quantity = 10
);
```

Try it Yourself »

The following SQL returns the ProductName if it finds ANY records in the "OrderDetails" table that has Quantity larger than 99 (this will return TRUE because the Quantity column has some values larger than 99):

Example

```
SELECT ProductName FROM Products
WHERE ProductID = ANY (
  SELECT ProductID
  FROM OrderDetails
  WHERE Quantity > 99
);
```

Try it Yourself »

The following SQL returns the ProductName if it finds ANY records in the "OrderDetails" table that has Quantity larger than 1000 (this will return FALSE because the Quantity column has no values larger than 1000):

Example

```
  WHERE Quantity > 1000
);
```

Try it Yourself »

‹ Previous

Sign in to track progress

Next ›



REMOVE ADS

FREE ACCOUNT
Track your progress

NEW
Learn in Adventure Mode

Tutorials Exercises

W3Schools app NEW
iOS & Android

Sign In

. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

Spaces 0

League —

Sign in to track progress



PLUS SPACES

GET CERTIFIED FOR TEACHERS

PRACTICE CONTACT US

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors

Tutorials Exercises

W3Schools app NEW
iOS & Android

Sign In

. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

FORUM ABOUT CAMPUS

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.