W3Schools
Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

MySQL DELETE Statement

‹ Previous Next ›

The MySQL DELETE Statement

SHARE

The `DELETE` statement is used to delete existing records in a table.

DELETE Syntax

```
DELETE FROM table_name WHERE condition;
```

Note: Be careful when deleting records in a table! Notice the `WHERE` clause in the `DELETE` statement. The `WHERE` clause specifies which record(s) should be deleted. If you omit the `WHERE` clause, all records in the table will be deleted!

CustomerID	CustomerName	ContactName	Address	City	PostalCode	Co
1	Alfreds Futterkiste	Maria Anders	Obere Str. 57	Berlin	12209	Ge
2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021	Me
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023	Me
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP	UK
5	Berglunds snabbköp	Christina Berglund	Berguvsvägen 8	Luleå	S-958 22	Sw

REMOVE ADS

SQL DELETE Example

The following SQL deletes the customer "Alfreds Futterkiste" from the "Customers" table:

Example

Get your own SQL Server

```
DELETE FROM Customers WHERE CustomerName='Alfreds Futterkiste';
```

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021	Me
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023	Me
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP	UK
5	Berglunds snabbköp	Christina Berglund	Berguvsvägen 8	Luleå	S-958 22	Sw

Delete All Records

It is possible to delete all records in a table, without deleting the table. This means that the table structure, attributes, and indexes will be intact.

```
DELETE FROM table_name;
```

The following SQL deletes ALL records in the "Customers" table, without deleting the table:

Example

```
DELETE FROM Customers;
```

```
DROP TABLE table_name;
```

The following SQL drops the entire "Customers" table:

Example

```
DROP TABLE Customers;
```

‹ Previous Sign in to track progress Next ›

Tutorials Exercises

W3Schools app NEW
iOS & Android

Sign In

. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

Learn it.
Get certified.
Get hired.

$95 per course
one-time payment

Exam and certificate included.

Get started

REMOVE ADS

FREE ACCOUNT

Track your progress

XP earned	0
Day streak	0
Spaces	0
League	—

Sign in to track progress

NEW

Learn in Adventure Mode

Coding fundamentals as bite-sized lessons and challenges.

Download on the App Store

GET IT ON Google Play

Learn more about Adventure Mode >



PLUS SPACES

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
AngularJS Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

Tutorials Exercises

W3Schools app NEW
iOS & Android

Sign In

. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.