W3Schools Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

React Custom Hooks

‹ Previous Next ›

You can make your own Hooks!

When you have components that can be used by multiple components, we can extract that component into a custom Hook.

Custom Hooks start with "use". Example: `useFetch`.

Build a Hook

SHARE

First, let us make an example without a custom Hook.

In the following code, we are fetching data from a URL and displaying it.

We will use the JSONPlaceholder service to fetch some fake data.

To learn more about fetching data, check out the JavaScript Fetch API section.

W3Schools Tutorials Exercises W3Schools app iOS & Android NEW Sign In
CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

```
import { useState, useEffect } from 'react';
import { createRoot } from 'react-dom/client';

const Home = () => {
  const [data, setData] = useState(null);

  useEffect(() => {
    fetch("https://jsonplaceholder.typicode.com/todos")
      .then((res) => res.json())
      .then((data) => setData(data));
 }, []);

  return (
    <>
      {data &&
        data.map((item) => {
          return <p key={item.id}>{item.title}</p>;
        })}
    </>
  );
};

createRoot(document.getElementById('root')).render(
  <Home />
);
```

Run Example »

The logic behind the fetch may be needed in other components as well, so we will turn that into a custom Hook.

Move the fetch logic to a new file to be used as a custom Hook.

W3Schools Tutorials Exercises W3Schools app iOS & Android NEW Sign In
CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

Example:

Move the fetch component into the new file:

useFetch.js

```
import { useState, useEffect } from "react";

const useFetch = (url) => {
  const [data, setData] = useState(null);

  useEffect(() => {
    fetch(url)
      .then((res) => res.json())
      .then((data) => setData(data));
  }, [url]);

  return [data];
};

export default useFetch;
```

Now we can import this Hook, and use it in any other component:

Example:

Import and use the newly created custom Hook:

main.jsx

```
import { createRoot } from 'react-dom/client';
import useFetch from "./useFetch";
```

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

```
  return (
    <>
      {data &&
        data.map((item) => {
          return <p key={item.id}>{item.title}</p>;
        })}
    </>
  );
};

createRoot(document.getElementById('root')).render(
  <Home />
);
```

Run Example »

REMOVE ADS

contains all of the logic needed to fetch our data.

We removed the hard-coded URL and replaced it with a `url` variable that can be passed to the custom Hook.

Lastly, we are returning our data from our Hook.

In `main.jsx`, we are importing our `useFetch` Hook and utilizing it like any other Hook. This is where we pass in the URL to fetch data from.

Now we can reuse this custom Hook in any component to fetch data from any URL.

‹ Previous Sign in to track progress Next ›



Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS



FREE ACCOUNT
Track your progress
XP earned 0
Day streak 0
Spaces 0
League —

NEW
Learn in Adventure Mode
Coding fundamentals as bite-sized lessons and challenges.
Download on the App Store
GET IT ON Google Play
Learn more about

Tutorials Exercises
W3Schools app NEW iOS & Android
Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS
PLUS SPACES
GET CERTIFIED FOR TEACHERS
PRACTICE CONTACT US

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
AngularJS Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate

Tutorials Exercises W3Schools app iOS & Android NEW Sign In

CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

jQuery Examples XML Certificate

FORUM ABOUT CAMPUS

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.