

Reader API

[_search_](#) [_notifications_](#) [_News_](#) [_box_Products_arrow_drop_down_](#)

[_Company_arrow_drop_down_](#)

Reader

Convert a URL to LLM-friendly input, by simply adding `r.jina.ai` in front.

[_code_API](#)

[_play_arrow_Demo](#)

[_attach_money_Pricing](#)

Reader API

Convert a URL to LLM-friendly input, by simply adding `r.jina.ai` in front.

[_zoom_out_map_](#)

[_key_](#)

API Key & Billing

[_code_](#)

Usage

[_more_horiz_](#)

More

[_chevron_left_chevron_right_](#)

[_home_](#)

Auto preview

[_forum_Raise issue](#)

[_help_outline_FAQ](#)

[_api__arrow_drop_down_](#)

[Status](#)

[_chevron_left_chevron_right_](#)

[_double_arrow_](#)

Use `r.jina.ai` to read a URL

This will return the main content of the page in clean, LLM-friendly text.

[_keyboard_arrow_down_](#)

Enter your URL

[_arrow_forward_](#)

`https://r.jina.ai/`

Reader URL

[_content_copy__open_in_new_](#)

[_search_](#)

Use `s.jina.ai` to search a query

This will search the web and returns URLs and contents, each in clean, LLM-friendly text.

[_keyboard_arrow_down_](#)

Enter your query

[_arrow_forward_](#)

`_key_`

`https://s.jina.ai/`

Reader URL

`_content_copy__open_in_new_`

`_fact_check_`

Use `g.jina.ai` for grounding

This will call our grounding engine do fact-checking.

`_science_`

Experimental

`_keyboard_arrow_down_`

Enter your query

`_arrow_forward_`

`_key_`

`https://g.jina.ai/`

Reader URL

[Read release note_arrow_forward_](#)

`_filter_alt_`

Common, Specific

Parameters

`_arrow_drop_down_`

Search Parameters/Headers

Add API Key for Higher Rate Limit

Enter your Jina API key to access a higher rate limit. For latest rate limit information, please refer to the table below.

[_open_in_new_Learn more](#)

Use POST Method

Use POST instead of GET method with a URL passed in the body. Useful for building SPAs with hash-based routing.

[_open_in_new_Learn more](#)

Content Format

You can control the level of detail in the response to prevent over-filtering. The default pipeline is optimized for most websites and LLM input.

Default

`_arrow_drop_down_`

Timeout

Maximum time to wait for the webpage to load. Note that this is NOT the total time for the whole end-to-end request.

Target Selector

Provide a list of CSS selector to focus on more specific parts of the page. Useful when your desired content doesn't show under the default settings.

body

.class

id

Wait For Selector

Provide a list of CSS selector to wait for specific elements to appear before returning. Useful when your desired content doesn't show under the default settings.

body

.class

id

Excluded Selector

Provide a list of CSS selector to remove the specified elements of the page. Useful when you want to exclude specific parts of the page like headers, footers, etc.

header

.class

id

Remove All Images

Remove all images from the response.

Gather All Links At the End

A "Buttons & Links" section will be created at the end. This helps the downstream LLMs or web agents navigating the page or take further actions.

Gather All Images At the End

An "Images" section will be created at the end. This gives the downstream LLMs an overview of all visuals on the page, which may improve reasoning.

JSON Response

The response will be in JSON format, containing the URL, title, content, and timestamp (if available). In Search mode, it returns a list of five entries, each following the described JSON structure.

Forward Cookie

Our API server can forward your custom cookie settings when accessing the URL, which is useful for pages requiring extra authentication. Note that requests with cookies will not be cached.

[_open_in_new_Learn more](#)

Image Caption

Captions all images at the specified URL, adding 'Image [idx]: [caption]' as an alt tag for those without one. This allows downstream LLMs to interact with the images in activities such as reasoning and summarizing.

Use a Proxy Server

Our API server can utilize your proxy to access URLs, which is helpful for pages accessible only through specific proxies.

[_open_in_new_Learn more](#)

Bypass the Cache

Our API server caches both Read and Search mode contents for a certain amount of time. To bypass this cache, set this header to true.

Github Flavored Markdown

Opt in/out features from GFM (Github Flavored Markdown).

Enabled

[_arrow_drop_down_](#)

Stream Mode

Stream mode is beneficial for large target pages, allowing more time for the page to fully render. If standard mode results in incomplete content, consider using Stream mode.

[_open_in_new_Learn more](#)

Browser Locale

Control the browser locale to render the page. Lots of websites serve different content based on the locale.

[_open_in_new_Learn more](#)

Enable iframe Extraction

Extracts and processes content from all embedded iframes within the DOM tree

Enable Shadow DOM Extraction

Traverses and extracts content from all Shadow DOM roots in the document

Local PDF/HTML file

POST

Use Reader on your local PDF and HTML file by uploading them. Only support pdf and html files. For HTML, please also specify a reference URL for better parsing related CSS/JS scripts.

[_upload_](#)

Pre-Execute Custom JavaScript

POST

Executes pre-processing JavaScript code, accepting either inline code string or remote script URL endpoint

[_open_in_new_Learn more](#)

[_upload_](#)

Request

Bash

Language

[_arrow_drop_down_](#)

```
curl https://r.jina.ai/https://example.com
```

[_content_copy_](#)

[_upload_](#)

Request (javascript)

```
fetch('https://r.jina.ai/https://example.com', {
  method: 'GET',
})
```

[_content_copy_](#)

[_send_GET RESPONSE](#)

[_key_](#)

API key

`_visibility_off__content_copy_`

Available tokens

`0_sync_`

This is your unique key. Store it securely!

[What is Reader?](#)

`https://example.com`

`https://r.jina.ai/https://example.com`

 LLM-friendly text
