Department of Nano Science Technology

Faculty of Technology

Wayamba University of Sri Lanka

Centralized Workshops and Laboratory Allocation Platform

Class Diagram

Submitted to: Dr. U.S. Liyanarachchi

Module: NANO2142

Submitted by: Group 1

Date of Submission

03 Nov 2026

UML Class Diagram & Structural Architecture Specification

System Architecture Document | Implementation: C++17 / Qt Widgets / SQLite

System Architecture Overview

The SYNCLAB system implements a modular layered object-oriented architecture in C++17/Qt. It decouples GUI widget controllers from core domain rules and persistence transactions using an Inversion of Control (IoC) / Repository Pattern.

- **Presentation Layer:** MainWindow inherits from QMainWindow and manages screen states via QStackedWidget. It embeds CustomCalendarWidget (extending QCalendarWidget) to paint status badges.
- **Domain Model & Logic:** StudentRecord serves as an encapsulated Data Transfer Object (DTO). AllocationRules acts as a static business service validating booking inputs.
- **Persistence Layer:** IDatabaseManager defines an abstract CRUD contract, concretely realized by SqliteDatabaseManager using ACID transactions and cascading SQLite foreign keys.

UML Class Diagram




Figure 1: UML Class Diagram for SYNCLAB Structural Architecture

Class Specifications & Contracts

Presentation Layer

- **MainWindow:** Primary controller inheriting from QMainWindow. Holds a private interface pointer IDatabaseManager* dbManager. Coordinates state transitions across the 5 wizard interfaces via Qt slots (onNextClicked, submitData, loadAdminData).
- **CustomCalendarWidget:** Subclasses QCalendarWidget. Overrides paintCell(QPainter*, QRect, QDate) to render Approved, Pending, and Rejected badge counts directly onto calendar days.

Domain & Business Logic Layer

- **StudentRecord:** Encapsulated entity modeling 15 fields including identifiers (id, passcode), student credentials (indexNo, name, department, email), allocation metadata (category, recordDate, timeSlots, supervisorName, projectName), and audit records (status, adminRemarks, createdAt).
- **AllocationRules:** Static domain service enforcing validation rules (non-empty entries, regex email formats, valid slot sets) and state initialization without coupling to the GUI.

Data Access Layer

- **IDatabaseManager:** Pure abstract repository interface defining transactions, slot conflict checks (isTimeSlotAvailable), and status modifications.
- **SqliteDatabaseManager:** Concrete driver using QSqlDatabase. Executes foreign-key-enabled schema setups and multi-row slot updates within atomic SQLite transactions.

Relationship & Multiplicity Mapping

The structural coupling, association types, and multiplicity constraints between architectural components are summarized below:

Source Class	Target Class	Relationship	Multiplicity	Architectural Role / Contract
MainWindow	CustomCalendarWidget	*Composition*	1 → 1	Embedded UI component; owned directly by parent window.
MainWindow	StudentRecord	*Dependency*	1 → 1	Active session state holder passed across wizard views.

MainWindow	AllocationRules	*Dependency*	1 → 1	Static business service invoked for pre-submission checks.
MainWindow	IDatabaseManager	*Dependency*	1 → 1	Operates via repository interface pointer (IoC pattern).
SqliteDatabaseManager	IDatabaseManager	*Realization*	1 → 1	Implements pure virtual CRUD and transaction contracts.
AllocationRules	StudentRecord	*Dependency*	1 → 1	Inspects record fields to validate constraints.
IDatabaseManager	StudentRecord	*Dependency*	1 → ∗	Serializes, queries, and mutates database records.