

PPL Assignment - Question6

API Documentation

April 10, 2017

Contents

Contents	1
1 Module ppl-assignment-CosmicCoder96.q6.boy'	2
1.1 Variables	2
1.2 Class Boy	2
1.2.1 Methods	2
1.3 Class Geek	2
1.3.1 Methods	2
1.4 Class Generous	3
1.4.1 Methods	3
1.5 Class Miser	3
1.5.1 Methods	3
2 Module ppl-assignment-CosmicCoder96.q6.couple'	4
2.1 Variables	4
2.2 Class Boy	4
2.2.1 Methods	4
2.3 Class Couple	4
2.3.1 Methods	4
2.4 Class Girl	4
2.4.1 Methods	4
3 Module ppl-assignment-CosmicCoder96.q6.gift'	6
3.1 Variables	6
3.2 Class Gift	6
3.2.1 Methods	6
3.3 Class essentialGift	6
3.3.1 Methods	6
3.4 Class luxuryGift	6
3.4.1 Methods	7
3.5 Class utilityGift	7
3.5.1 Methods	7
4 Module ppl-assignment-CosmicCoder96.q6.girl	8
4.1 Variables	8
4.2 Class Girl	8
4.2.1 Methods	8

4.3	Class Choosy	8
4.3.1	Methods	8
4.4	Class Normal	9
4.4.1	Methods	9
4.5	Class Desperate	9
4.5.1	Methods	9
5	Module ppl-assignment-CosmicCoder96.q6.q4'	10
5.1	Functions	10
5.2	Variables	10
6	Module ppl-assignment-CosmicCoder96.q6.q6'	11
6.1	Functions	11
6.2	Variables	11
7	Module ppl-assignment-CosmicCoder96.q6.utility	12
7.1	Functions	12
7.2	Variables	12
8	Package ppl-assignment-CosmicCoder96.q6'	13
8.1	Modules	13
8.2	Variables	13
9	Script script-boys_list.txt	14
10	Script script-couple_list.txt	15
11	Script script-gift_list.txt	16
12	Script script-girls_list.txt	17

1 Module ppl-assignment-CosmicCoder96.q6.boy'

1.1 Variables

Name	Description
--package--	Value: None

1.2 Class Boy

Known Subclasses: ppl-assignment-CosmicCoder96.q6.boy.Geek, ppl-assignment-CosmicCoder96.q6.boy.Generous, ppl-assignment-CosmicCoder96.q6.boy.Miser

1.2.1 Methods

```
__init__(self, name, attractiveness, budget, intelligence_level, min_attraction_requirement,
committed, happiness)
```

```
commit(self)
```

```
isCommitted(self)
```

1.3 Class Geek

```

ppl-assignment-CosmicCoder96.q6.boy.Boy └─
                                         ppl-assignment-CosmicCoder96.q6.boy.Geek

```

1.3.1 Methods

```
__init__(self, name, attractiveness, budget, intelligence_level, min_attraction_requirement,
committed, happiness)
```

Overrides: ppl-assignment-CosmicCoder96.q6.boy.Boy.__init__

```
getHappiness(self, girl, total_gifts)
```

Inherited from ppl-assignment-CosmicCoder96.q6.boy.Boy(Section 2.2)

commit(), isCommitted()

1.4 Class Generous



1.4.1 Methods


<code>__init__</code> (<i>self</i> , <i>name</i> , <i>attractiveness</i> , <i>budget</i> , <i>intelligence_level</i> , <i>min_attraction_requirement</i> , <i>committed</i> , <i>happiness</i>) Overrides: ppl-assignment-CosmicCoder96.q6.boy.Boy.__init__
--

<code>getHappiness</code> (<i>self</i> , <i>girl</i> , <i>total_gifts</i>)

Inherited from ppl-assignment-CosmicCoder96.q6.boy.Boy(Section 2.2)

`commit()`, `isCommitted()`

1.5 Class Miser



1.5.1 Methods

<code>__init__</code> (<i>self</i> , <i>name</i> , <i>attractiveness</i> , <i>budget</i> , <i>intelligence_level</i> , <i>min_attraction_requirement</i> , <i>committed</i> , <i>happiness</i>) Overrides: ppl-assignment-CosmicCoder96.q6.boy.Boy.__init__
--

<code>getHappiness</code> (<i>self</i> , <i>girl</i> , <i>total_gifts</i>)

Inherited from ppl-assignment-CosmicCoder96.q6.boy.Boy(Section 2.2)

`commit()`, `isCommitted()`

2 Module ppl-assignment-CosmicCoder96.q6.couple'

2.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'ppl-assignment-CosmicCoder96.q6'</code>

2.2 Class Boy

Known Subclasses: ppl-assignment-CosmicCoder96.q6.boy.Geek, ppl-assignment-CosmicCoder96.q6.boy.ppl-assignment-CosmicCoder96.q6.boy.Miser

2.2.1 Methods

```
--init--(self, name, attractiveness, budget, intelligence_level,  
min_attraction_requirement, committed, happiness)
```

```
commit(self)
```

```
isCommitted(self)
```

2.3 Class Couple

2.3.1 Methods

```
--init--(self, boy, girl, happiness, compatibility)
```

2.4 Class Girl

Known Subclasses: ppl-assignment-CosmicCoder96.q6.girl.Choosy, ppl-assignment-CosmicCoder96.q6.girl.ppl-assignment-CosmicCoder96.q6.girl.Normal

2.4.1 Methods

```
--init--(self, name, attractiveness, maintainance_budget, intelligence_level,  
criterion, committed, happiness)
```

isCommitted(*self*)

commit(*self*)

3 Module ppl-assignment-CosmicCoder96.q6.gift'

3.1 Variables

Name	Description
<code>__package__</code>	Value: None

3.2 Class Gift

Known Subclasses: ppl-assignment-CosmicCoder96.q6.gift.essentialGift, ppl-assignment-CosmicCoder96.q6.gift.luxuryGift, ppl-assignment-CosmicCoder96.q6.gift.utilityGift

3.2.1 Methods

```
__init__(self, price, value, used=False)
```

3.3 Class essentialGift

```
ppl-assignment-CosmicCoder96.q6.gift.Gift └─ ppl-assignment-CosmicCoder96.q6.gift.essentialGift
```

3.3.1 Methods

```
__init__(self, price, value, used, Type)  
Overrides: ppl-assignment-CosmicCoder96.q6.gift.Gift.__init__
```

3.4 Class luxuryGift

```
ppl-assignment-CosmicCoder96.q6.gift.Gift └─ ppl-assignment-CosmicCoder96.q6.gift.luxuryGift
```

3.4.1 Methods

<code>--init__(self, price, value, used, difficulty, rating, Type)</code>

Overrides: <code>ppl-assignment-CosmicCoder96.q6.gift.Gift.__init__</code>
--

3.5 Class *utilityGift*

`ppl-assignment-CosmicCoder96.q6.gift.Gift` └─ **`ppl-assignment-CosmicCoder96.q6.gift.utilityGift`**

3.5.1 Methods

<code>--init__(self, price, value, used, utility_value, utility_class, Type)</code>

Overrides: <code>ppl-assignment-CosmicCoder96.q6.gift.Gift.__init__</code>
--

4 Module ppl-assignment-CosmicCoder96.q6.girl

4.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'ppl-assignment-CosmicCoder96.q6'</code>

4.2 Class Girl

Known Subclasses: `ppl-assignment-CosmicCoder96.q6.girl.Choosy`, `ppl-assignment-CosmicCoder96.q6.girl.Normal`

4.2.1 Methods

```
--init__(self, name, attractiveness, maintainance_budget, intelligence_level,
criterion, committed, happiness)
```

```
isCommitted(self)
```

```
commit(self)
```

4.3 Class Choosy

```
ppl-assignment-CosmicCoder96.q6.girl.Girl └─ ppl-assignment-CosmicCoder96.q6.girl.Choosy
```

4.3.1 Methods

```
--init__(self, name, attractiveness, maintainance_budget, intelligence_level,
criterion, committed, happiness)
```

Overrides: `ppl-assignment-CosmicCoder96.q6.girl.Girl.__init__`

```
getHappiness(self, boy, total_gifts, total_gift_value)
```

Inherited from `ppl-assignment-CosmicCoder96.q6.girl.Girl` (Section 4.2)

`commit()`, `isCommitted()`

4.4 Class Normal



4.4.1 Methods

```
__init__(self, name, attractiveness, maintainance_budget, intelligence_level,
criterion, committed, happiness)
```

Overrides: ppl-assignment-CosmicCoder96.q6.girl.Girl.__init__

```
getHappiness(self, boy, total_gifts, total_gift_value)
```

Inherited from ppl-assignment-CosmicCoder96.q6.girl.Girl(Section 4.2)

commit(), isCommitted()

4.5 Class Desperate



4.5.1 Methods

```
__init__(self, name, attractiveness, maintainance_budget, intelligence_level,
criterion, committed, happiness)
```

Overrides: ppl-assignment-CosmicCoder96.q6.girl.Girl.__init__

```
getHappiness(self, boy, total_gifts, total_gift_value)
```

Inherited from ppl-assignment-CosmicCoder96.q6.girl.Girl(Section 4.2)

commit(), isCommitted()

5 Module *ppl-assignment-CosmicCoder96.q6.q4'*

5.1 Functions

<code>generateBoyList()</code>

<code>generateGirlList()</code>

<code>giveGifts(<i>boy_list</i>, <i>girl_list</i>)</code>

<code>valentine(<i>k</i>, <i>couple_list</i>, <i>boy_list</i>, <i>girl_list</i>)</code>

5.2 Variables

Name	Description
<code>--package--</code>	Value: <code>'ppl-assignment-CosmicCoder96.q6'</code>
<code>boy_list</code>	Value: [<ppl-assignment-CosmicCoder96.q6.boy.Generous instance a...
<code>couple_list</code>	Value: [<ppl-assignment-CosmicCoder96.q6.couple.Couple instance ...
<code>girl_list</code>	Value: [<ppl-assignment-CosmicCoder96.q6.girl.Normal instance at...

6 Module ppl-assignment-CosmicCoder96.q6.q6'

6.1 Functions

<code>calendar(<i>t, k, couple_list, boy_list, girl_list</i>)</code>
--

<code>generateBoyList()</code>

<code>generateGirlList()</code>

<code>giveGifts(<i>boy_list, girl_list</i>)</code>
--

<code>q6()</code>

<code>valentine(<i>k, couple_list, boy_list, girl_list</i>)</code>
--

6.2 Variables

Name	Description
<code>__package__</code>	Value: 'ppl-assignment-CosmicCoder96.q6'

7 Module ppl-assignment-CosmicCoder96.q6.utility

7.1 Functions

```
randomName(size=6, chars= 'ABCDEFGHIJKLMNOPQRSTUVWXYZ')
```

```
generateBoyList()
```

```
generateGirlList()
```

```
generateGiftList()
```

```
makeCouples(mode, boy_list, girl_list)
```

```
giveGifts(boy_list, girl_list)
```

```
k_most_happy_couples(couple_list)
```

```
k_least_happy_couples(couple_list)
```

```
valentine(k, couple_list, boy_list, girl_list)
```

```
calendar(t, k, couple_list, boy_list, girl_list)
```

7.2 Variables

Name	Description
<code>__package__</code>	Value: 'ppl-assignment-CosmicCoder96.q6'

8 Package ppl-assignment-CosmicCoder96.q6'

8.1 Modules

- **boy'** (*Section 1, p. 2*)
- **couple'** (*Section 2, p. 4*)
- **gift'** (*Section 3, p. 6*)
- **girl** (*Section 4, p. 8*)
- **q4'** (*Section 5, p. 10*)
- **q6'** (*Section 6, p. 11*)
- **utility** (*Section 7, p. 12*)

8.2 Variables

Name	Description
--package--	Value: None

9 Script script-boys_list.txt

10 Script script-couple_list.txt

11 Script script-gift_list.txt

12 Script script-girls_list.txt

Index

ppl-assignment-CosmicCoder96 (*package*)
 ppl-assignment-CosmicCoder96.q6' (*package*), 13
 ppl-assignment-CosmicCoder96.q6.boy' (*module*), 2–3
 ppl-assignment-CosmicCoder96.q6.couple' (*module*), 4–5
 ppl-assignment-CosmicCoder96.q6.gift' (*module*), 6–7
 ppl-assignment-CosmicCoder96.q6.girl (*module*), 8–9
 ppl-assignment-CosmicCoder96.q6.q4' (*module*), 10
 ppl-assignment-CosmicCoder96.q6.q6' (*module*), 11
 ppl-assignment-CosmicCoder96.q6.utility (*module*), 12
 ppl-assignment-CosmicCoder96.q6.boy.Boy (*class*), 2, 4
 ppl-assignment-CosmicCoder96.q6.boy.Boy.__init__ (*function*), 2, 4
 ppl-assignment-CosmicCoder96.q6.boy.Boy.commit (*function*), 2, 4
 ppl-assignment-CosmicCoder96.q6.boy.Boy.isCommitted (*function*), 2, 4
 ppl-assignment-CosmicCoder96.q6.boy.Geek (*class*), 2
 ppl-assignment-CosmicCoder96.q6.boy.Geek.getHappiness (*function*), 2
 ppl-assignment-CosmicCoder96.q6.boy.Generous (*class*), 2–3
 ppl-assignment-CosmicCoder96.q6.boy.Generous.getHappiness (*function*), 3
 ppl-assignment-CosmicCoder96.q6.boy.Miser (*class*), 3
 ppl-assignment-CosmicCoder96.q6.boy.Miser.getHappiness (*function*), 3
 ppl-assignment-CosmicCoder96.q6.couple.Couple (*class*), 4
 ppl-assignment-CosmicCoder96.q6.couple.Couple.__init__ (*function*), 4
 ppl-assignment-CosmicCoder96.q6.gift.essentialGift (*class*), 6
 ppl-assignment-CosmicCoder96.q6.gift.Gift (*class*), 6
 ppl-assignment-CosmicCoder96.q6.gift.Gift.__init__ (*function*), 6
 ppl-assignment-CosmicCoder96.q6.gift.luxuryGift (*class*), 6–7
 ppl-assignment-CosmicCoder96.q6.gift.utilityGift (*class*), 7
 ppl-assignment-CosmicCoder96.q6.q6.q6 (*function*), 11
 script-boys_list.txt (*script*), 14
 script-couple_list.txt (*script*), 15
 script-gift_list.txt (*script*), 16
 script-girls_list.txt (*script*), 17