

PPL Assignment

API Documentation

February 26, 2017

Contents

Contents	1
1 Module ppl_q1	2
1.1 Variables	2
1.2 Class ppl_q1	2
1.2.1 Methods	2
2 Module q1_boy	3
2.1 Variables	3
2.2 Class Boy	3
2.2.1 Methods	3
2.2.2 Properties	3
3 Module q1_couple	4
3.1 Variables	4
3.2 Class Couple	4
3.2.1 Methods	4
3.2.2 Properties	4
4 Module q1_final	5
4.1 Variables	5
5 Module q1_girl	6
5.1 Variables	6
5.2 Class Girl	6
5.2.1 Methods	6
5.2.2 Properties	6

1 Module *ppl.q1*

1.1 Variables

Name	Description
<code>--package--</code>	Value: None

1.2 Class *ppl.q1*

1.2.1 Methods


<code>run(<i>self</i>)</code>

2 Module q1_boy

2.1 Variables

Name	Description
<code>--package--</code>	Value: None

2.2 Class Boy



2.2.1 Methods

```
--init__(self, name=None, attractiveness=None, intelligence=None, budget=None,
type_of_boy=None)
```

`x.__init__(...)` initializes x; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

Inherited from object

`--delattr__()`, `--format__()`, `--getattr__()`, `--hash__()`, `--new__()`, `--reduce__()`, `--reduce_ex__()`,
`--repr__()`, `--setattr__()`, `--sizeof__()`, `--str__()`, `--subclasshook__()`

2.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class__</code>	

3 Module q1_couple

3.1 Variables

Name	Description
<code>--package--</code>	Value: None

3.2 Class Couple



3.2.1 Methods

```

__init__(self, boy_object, girl_object)

x.__init__(...) initializes x; see help(type(x)) for signature
Overrides: object.__init__ extit(inherited documentation)

```

Inherited from object

```

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

```

3.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

4 Module q1_final

4.1 Variables


Name	Description
ob1	Value: <code>pp1_q1()</code>

5 Module q1_girl

5.1 Variables

Name	Description
<code>--package--</code>	Value: None

5.2 Class Girl



5.2.1 Methods

<code>--init--</code> (<i>self</i>) <code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> extit(inherited documentation)
--

Inherited from object

`--delattr--`(), `--format--`(), `--getattr--`(), `--hash--`(), `--new--`(), `--reduce--`(), `--reduce_ex--`(),
`--repr--`(), `--setattr--`(), `--sizeof--`(), `--str--`(), `--subclasshook--`()

5.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

Index

- ppl.q1 (*module*), 2
 - ppl.q1.ppl.q1 (*class*), 2
 - ppl.q1.ppl.q1.run (*method*), 2
- q1_boy (*module*), 3
 - q1_boy.Boy (*class*), 3
- q1_couple (*module*), 4
 - q1_couple.Couple (*class*), 4
- q1_final (*module*), 5
- q1_girl (*module*), 6
 - q1_girl.Girl (*class*), 6