

PPL Assignment - Question 9

IIT2015099

Generated by Doxygen 1.8.13

Contents

1	Class Index	1
1.1	Class List	1
2	File Index	3
2.1	File List	3
3	Class Documentation	5
3.1	boys Class Reference	5
3.1.1	Detailed Description	5
3.1.2	Member Function Documentation	5
3.1.2.1	input()	6
3.1.2.2	logging()	6
3.1.2.3	readboyscount()	6
3.1.3	Member Data Documentation	6
3.1.3.1	attractiveness	6
3.1.3.2	budget	7
3.1.3.3	committed	7
3.1.3.4	girlname	7
3.1.3.5	happiness	7
3.1.3.6	intelligence	7
3.1.3.7	min_attractive	7
3.1.3.8	name	8
3.1.3.9	type	8
3.2	couples Class Reference	8

3.2.1	Detailed Description	8
3.2.2	Member Function Documentation	9
3.2.2.1	couplegifting()	9
3.2.2.2	input()	9
3.2.2.3	input1()	9
3.2.2.4	pairing()	9
3.2.2.5	readcouplecount()	10
3.2.3	Member Data Documentation	10
3.2.3.1	batt	10
3.2.3.2	bbud	10
3.2.3.3	bint	10
3.2.3.4	bname	10
3.2.3.5	btype	11
3.2.3.6	compatibility	11
3.2.3.7	gatt	11
3.2.3.8	gbud	11
3.2.3.9	gint	11
3.2.3.10	gname	11
3.2.3.11	gtype	12
3.2.3.12	happiness	12
3.3	gifts Class Reference	12
3.3.1	Detailed Description	12
3.3.2	Member Function Documentation	12
3.3.2.1	input()	13
3.3.2.2	readgiftscount()	13
3.3.3	Member Data Documentation	13
3.3.3.1	price	13
3.3.3.2	type	13
3.3.3.3	value	13
3.4	girls Class Reference	14

3.4.1	Detailed Description	14
3.4.2	Member Function Documentation	14
3.4.2.1	input()	14
3.4.2.2	readgirlscout()	14
3.4.3	Member Data Documentation	15
3.4.3.1	attractiveness	15
3.4.3.2	boyname	15
3.4.3.3	committed	15
3.4.3.4	happiness	15
3.4.3.5	intelligence	15
3.4.3.6	maintenance	16
3.4.3.7	name	16
3.4.3.8	need	16
3.4.3.9	type	16
3.5	kbest< T > Class Template Reference	16
3.5.1	Detailed Description	17
3.5.2	Member Function Documentation	17
3.5.2.1	ret_best()	17
3.6	util Class Reference	17
3.6.1	Detailed Description	17
3.6.2	Member Function Documentation	17
3.6.2.1	coupling()	18
3.6.2.2	gifting()	18
4	File Documentation	19
4.1	PPL/ques9/boys.cpp File Reference	19
4.2	PPL/ques9/couples.cpp File Reference	19
4.3	PPL/ques9/gifts.cpp File Reference	19
4.4	PPL/ques9/girls.cpp File Reference	20
4.5	PPL/ques9/kbest.cpp File Reference	20
4.6	PPL/ques9/main.cpp File Reference	20
4.6.1	Function Documentation	20
4.6.1.1	main()	20
4.7	PPL/ques9/randomgen.cpp File Reference	21
4.7.1	Function Documentation	21
4.7.1.1	main()	21
4.8	PPL/ques9/util.cpp File Reference	22

Chapter 1

Class Index

1.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

boys	5
couples	8
gifts	12
girls	14
kbest< T >	
Template returning the best values	16
util	17

Chapter 2

File Index

2.1 File List

Here is a list of all files with brief descriptions:

PPL/ques9/boys.cpp	19
PPL/ques9/couples.cpp	19
PPL/ques9/gifts.cpp	19
PPL/ques9/girls.cpp	20
PPL/ques9/kbest.cpp	20
PPL/ques9/main.cpp	20
PPL/ques9/randomgen.cpp	21
PPL/ques9/util.cpp	22

Chapter 3

Class Documentation

3.1 boys Class Reference

Public Member Functions

- int [readboyscount](#) ()
- int [input](#) ([boys](#) *boyss, int nb)
boys data input.
- int [logging](#) ([boys](#) *boyss, int nb)
inserts girlfriend for a boyfriend if exists into log file.

Public Attributes

- std::string [name](#)
- std::string [type](#)
- std::string [girlname](#)
- int [attractiveness](#)
- int [intelligence](#)
- int [budget](#)
- int [happiness](#)
- int [committed](#)
- int [min_attractive](#)

3.1.1 Detailed Description

Definition at line 2 of file boys.cpp.

3.1.2 Member Function Documentation

3.1.2.1 input()

```
int boys::input (
    boys * boyss,
    int nb ) [inline]
```

boys data input.

Definition at line 18 of file boys.cpp.

3.1.2.2 logging()

```
int boys::logging (
    boys * boyss,
    int nb ) [inline]
```

inserts girlfriend for a boyfriend if exists into log file.

Definition at line 32 of file boys.cpp.

3.1.2.3 readboyscount()

```
int boys::readboyscount ( ) [inline]
```

Increment count if this character is newline.

number of couples.

Definition at line 7 of file boys.cpp.

3.1.3 Member Data Documentation

3.1.3.1 attractiveness

```
int boys::attractiveness
```

Definition at line 6 of file boys.cpp.

3.1.3.2 budget

```
int boys::budget
```

Definition at line 6 of file boys.cpp.

3.1.3.3 committed

```
int boys::committed
```

Definition at line 6 of file boys.cpp.

3.1.3.4 girlname

```
std::string boys::girlname
```

Definition at line 5 of file boys.cpp.

3.1.3.5 happiness

```
int boys::happiness
```

Definition at line 6 of file boys.cpp.

3.1.3.6 intelligence

```
int boys::intelligence
```

Definition at line 6 of file boys.cpp.

3.1.3.7 min_attractive

```
int boys::min_attractive
```

Definition at line 6 of file boys.cpp.

3.1.3.8 name

```
std::string boys::name
```

Definition at line 5 of file boys.cpp.

3.1.3.9 type

```
std::string boys::type
```

Definition at line 5 of file boys.cpp.

The documentation for this class was generated from the following file:

- PPL/ques9/[boys.cpp](#)

3.2 couples Class Reference

Public Member Functions

- int [input](#) ([couples](#) *couple, int count)
- int [input1](#) ([couples](#) *couple, int count)
data read.
- int [readcouplecount](#) ()
- int [pairing](#) ([boys](#) *boyss, [girls](#) *girlss, int nb, int ng)
Pairing.
- int [couplegifting](#) ([couples](#) *couple, int count, [gifts](#) *gif, int ngf)
Gift Exchanges.

Public Attributes

- std::string [bname](#)
- std::string [btype](#)
- std::string [gname](#)
- std::string [gtype](#)
- int [bbud](#)
- int [gbud](#)
- int [batt](#)
- int [gatt](#)
- int [bint](#)
- int [gint](#)
- int [compatibility](#)
- double [happiness](#)

3.2.1 Detailed Description

Definition at line 8 of file couples.cpp.

3.2.2 Member Function Documentation

3.2.2.1 couplegifting()

```
int couples::couplegifting (
    couples * couple,
    int count,
    gifts * gif,
    int ngf ) [inline]
```

Gift Exchanges.

Definition at line 132 of file couples.cpp.

3.2.2.2 input()

```
int couples::input (
    couples * couple,
    int count ) [inline]
```

data read of couples.

Definition at line 14 of file couples.cpp.

3.2.2.3 input1()

```
int couples::input1 (
    couples * couple,
    int count ) [inline]
```

data read.

Definition at line 29 of file couples.cpp.

3.2.2.4 pairing()

```
int couples::pairing (
    boys * boyss,
    girls * girlss,
    int nb,
    int ng ) [inline]
```

Pairing.

Definition at line 54 of file couples.cpp.

3.2.2.5 readcouplecount()

```
int couples::readcouplecount ( ) [inline]
```

Increment count if this character is newline.

number of couples.

Definition at line 43 of file couples.cpp.

3.2.3 Member Data Documentation

3.2.3.1 batt

```
int couples::batt
```

Definition at line 12 of file couples.cpp.

3.2.3.2 bbud

```
int couples::bbud
```

Definition at line 12 of file couples.cpp.

3.2.3.3 bint

```
int couples::bint
```

Definition at line 12 of file couples.cpp.

3.2.3.4 bname

```
std::string couples::bname
```

Definition at line 11 of file couples.cpp.

3.2.3.5 btype

```
std::string couples::btype
```

Definition at line 11 of file couples.cpp.

3.2.3.6 compatibility

```
int couples::compatibility
```

Definition at line 12 of file couples.cpp.

3.2.3.7 gatt

```
int couples::gatt
```

Definition at line 12 of file couples.cpp.

3.2.3.8 gbud

```
int couples::gbud
```

Definition at line 12 of file couples.cpp.

3.2.3.9 gint

```
int couples::gint
```

Definition at line 12 of file couples.cpp.

3.2.3.10 gname

```
std::string couples::gname
```

Definition at line 11 of file couples.cpp.

3.2.3.11 gtype

```
std::string couples::gtype
```

Definition at line 11 of file couples.cpp.

3.2.3.12 happiness

```
double couples::happiness
```

Definition at line 13 of file couples.cpp.

The documentation for this class was generated from the following file:

- PPL/ques9/[couples.cpp](#)

3.3 gifts Class Reference

Public Member Functions

- int [readgiftscount](#) ()
- int [input](#) ([gifts](#) *gif, int ngf)
reading gifts data.

Public Attributes

- std::string [type](#)
- int [value](#)
attributes of gifts.
- int [price](#)

3.3.1 Detailed Description

Definition at line 1 of file gifts.cpp.

3.3.2 Member Function Documentation

3.3.2.1 input()

```
int gifts::input (
    gifts * gif,
    int ngf ) [inline]
```

reading gifts data.

Definition at line 17 of file gifts.cpp.

3.3.2.2 readgiftscount()

```
int gifts::readgiftscount ( ) [inline]
```

Increment count if this character is newline.

number of couples.

Definition at line 6 of file gifts.cpp.

3.3.3 Member Data Documentation

3.3.3.1 price

```
int gifts::price
```

Definition at line 5 of file gifts.cpp.

3.3.3.2 type

```
std::string gifts::type
```

Definition at line 4 of file gifts.cpp.

3.3.3.3 value

```
int gifts::value
```

attributes of gifts.

Definition at line 5 of file gifts.cpp.

The documentation for this class was generated from the following file:

- [PPL/ques9/gifts.cpp](#)

3.4 girls Class Reference

Public Member Functions

- int [readgirlscount](#) ()
- int [input](#) ([girls](#) *girlss, int ng)
reading girls data.

Public Attributes

- std::string [name](#)
- std::string [type](#)
- std::string [boyname](#)
- std::string [need](#)
- int [attractiveness](#)
attributes of girls.
- int [maintenance](#)
- int [intelligence](#)
- int [happiness](#)
- int [committed](#)

3.4.1 Detailed Description

Definition at line 1 of file girls.cpp.

3.4.2 Member Function Documentation

3.4.2.1 input()

```
int girls::input (
    girls * girlss,
    int ng ) [inline]
```

reading girls data.

Definition at line 17 of file girls.cpp.

3.4.2.2 readgirlscount()

```
int girls::readgirlscount ( ) [inline]
```

Increment count if this character is newline.

number of couples.

Definition at line 6 of file girls.cpp.

3.4.3 Member Data Documentation

3.4.3.1 attractiveness

```
int girls::attractiveness
```

attributes of girls.

Definition at line 5 of file girls.cpp.

3.4.3.2 boyname

```
std::string girls::boyname
```

Definition at line 4 of file girls.cpp.

3.4.3.3 committed

```
int girls::committed
```

Definition at line 5 of file girls.cpp.

3.4.3.4 happiness

```
int girls::happiness
```

Definition at line 5 of file girls.cpp.

3.4.3.5 intelligence

```
int girls::intelligence
```

Definition at line 5 of file girls.cpp.

3.4.3.6 maintenance

```
int girls::maintenance
```

Definition at line 5 of file girls.cpp.

3.4.3.7 name

```
std::string girls::name
```

Definition at line 4 of file girls.cpp.

3.4.3.8 need

```
std::string girls::need
```

Definition at line 4 of file girls.cpp.

3.4.3.9 type

```
std::string girls::type
```

Definition at line 4 of file girls.cpp.

The documentation for this class was generated from the following file:

- [PPL/ques9/girls.cpp](#)

3.5 kbest< T > Class Template Reference

Template returning the best values.

Public Member Functions

- void [ret_best](#) (T a[], int ar[], int n)

3.5.1 Detailed Description

```
template<class T>  
class kbest< T >
```

Template returning the best values.

Definition at line 1 of file kbest.cpp.

3.5.2 Member Function Documentation

3.5.2.1 ret_best()

```
template<class T>  
void kbest< T >::ret_best (  
    T a[],  
    int ar[],  
    int n ) [inline]
```

Definition at line 4 of file kbest.cpp.

The documentation for this class was generated from the following file:

- PPL/ques9/[kbest.cpp](#)

3.6 util Class Reference

Public Member Functions

- int [coupling](#) (int k)
- int [gifting](#) (int k)

3.6.1 Detailed Description

Definition at line 4 of file util.cpp.

3.6.2 Member Function Documentation

3.6.2.1 coupling()

```
int util::coupling (  
    int k ) [inline]
```

taking boys input from boys.txt

taking girls input from boys.txt.

first priority for selection of boys will be budget and their second priority will be according to the girl type and the top "k" are eligible for the girls.

Definition at line 7 of file util.cpp.

3.6.2.2 gifting()

```
int util::gifting (  
    int k ) [inline]
```

counting the number of couples.

Reading couples data from couple.txt.

Reading the types of gifts.

Gift exchanges among k best gifts,happiness and compatibility calculation and inserting into log file and fcalc.txt.

Definition at line 31 of file util.cpp.

The documentation for this class was generated from the following file:

- [PPL/ques9/util.cpp](#)

Chapter 4

File Documentation

4.1 PPL/ques9/boys.cpp File Reference

```
#include <fstream>
```

Classes

- class [boys](#)

4.2 PPL/ques9/couples.cpp File Reference

```
#include "girls.cpp"  
#include "boys.cpp"  
#include "gifts.cpp"  
#include <fstream>  
#include <ctime>  
#include <math.h>
```

Classes

- class [couples](#)

4.3 PPL/ques9/gifts.cpp File Reference

Classes

- class [gifts](#)

4.4 PPL/ques9/girls.cpp File Reference

Classes

- class [girls](#)

4.5 PPL/ques9/kbest.cpp File Reference

Classes

- class [kbest< T >](#)
Template returning the best values.

4.6 PPL/ques9/main.cpp File Reference

```
#include <iostream>
#include <stdio.h>
#include <stdlib.h>
#include "couples.cpp"
#include "util.cpp"
```

Functions

- int [main](#) (int argc, char **argv)

4.6.1 Function Documentation

4.6.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

Inserting the couples formed into log file and couples.txt

Inserting happiness and compatibility into fcalc.txt

Definition at line 7 of file main.cpp.

4.7 PPL/ques9/randomgen.cpp File Reference

```
#include <iostream>
#include "gifts.cpp"
```

Functions

- int [main](#) (int argc, char **argv)

4.7.1 Function Documentation

4.7.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

Randomly Generating different types of boys in boys.txt.

boy name.

boy type.

attractiveness.

intelligent.

budget.

minimum attr.

Randomly Generating different types of girls in girls.txt.

Name.

type.

type.

attractiveness.

intelligent.

maintenance.

different types of gift int gift.txt.

type.

Price.

Value.

luxury gifts will have more Price.

Value.

Generating the gifts in an sorted order of their price.

if gift is luxury keeping it in luxury.txt as well.

Definition at line 3 of file randomgen.cpp.

4.8 PPL/ques9/util.cpp File Reference

```
#include "kbest.cpp"
```

Classes

- class [util](#)