

PPL Assignment

API Documentation

February 26, 2017

Contents

Contents	1
1 Module boyGeek	2
1.1 Variables	2
1.2 Class boyGeek	2
1.2.1 Methods	2
1.2.2 Class Variables	2
2 Module boyGenerous	3
2.1 Variables	3
2.2 Class boyGenerous	3
2.2.1 Methods	3
2.2.2 Class Variables	3
3 Module boyMiser	4
3.1 Variables	4
3.2 Class boyMiser	4
3.2.1 Methods	4
3.2.2 Class Variables	4
4 Module couple	5
4.1 Variables	5
4.2 Class couple	5
4.2.1 Methods	5
5 Module coupleMaker	6
5.1 Variables	6
5.2 Class coupleMaker	6
5.2.1 Methods	6
6 Module driver	7
6.1 Functions	7
7 Module generator	8
7.1 Variables	8
7.2 Class randomGenerator	8
7.2.1 Methods	8

8	Module giftEssential	9
8.1	Variables	9
8.2	Class giftEssential	9
8.2.1	Methods	9
9	Module giftLuxury	10
9.1	Variables	10
9.2	Class giftLuxury	10
9.2.1	Methods	10
9.2.2	Class Variables	10
10	Module giftUtility	11
10.1	Variables	11
10.2	Class giftUtility	11
10.2.1	Methods	11
10.2.2	Class Variables	11
11	Module girlChoosy	12
11.1	Variables	12
11.2	Class girlChoosy	12
11.2.1	Methods	12
11.2.2	Class Variables	12
12	Module girlDesperate	13
12.1	Variables	13
12.2	Class girlDesperate	13
12.2.1	Methods	13
12.2.2	Class Variables	13
13	Module girlNormal	14
13.1	Variables	14
13.2	Class girlNormal	14
13.2.1	Methods	14
13.2.2	Class Variables	14
14	Module q1	15
14.1	Functions	15
15	Module reader	16
15.1	Variables	16
15.2	Class read	16
15.2.1	Methods	16

1 Module boyGeek

1.1 Variables

Name	Description
<code>--package--</code>	Value: None

1.2 Class boyGeek

1.2.1 Methods

<code>--init--(self, boy)</code>

<code>happinessCalculator(self, gIntelligence)</code>

<code>gifting(self, gMaintenanceCost, Gifts, giftBasket)</code>

1.2.2 Class Variables

Name	Description
happiness	Value: 0
amountSpent	Value: 0
gfName	Value: ''

2 Module *boyGenerous*

2.1 Variables

Name	Description
<code>--package--</code>	Value: None

2.2 Class *boyGenerous*

2.2.1 Methods

<code>__init__(self, boy)</code>
<code>happinessCalculator(self, gHappiness)</code>
<code>gifting(self, gMaintenanceCost, Gifts, giftBasket)</code>

2.2.2 Class Variables

Name	Description
<code>happiness</code>	Value: 0
<code>amountSpent</code>	Value: 0
<code>gfName</code>	Value: ''

3 Module boyMiser

3.1 Variables

Name	Description
<code>--package--</code>	Value: None

3.2 Class boyMiser

3.2.1 Methods

<code>__init__(self, boy)</code>

<code>gifting(self, gMaintenanceCost, Gifts, giftBasket)</code>

<code>happinessCalculator(self)</code>
--

3.2.2 Class Variables

Name	Description
<code>happiness</code>	Value: 0
<code>amountSpent</code>	Value: 0
<code>gfName</code>	Value: ''

4 Module couple

4.1 Variables

Name	Description
<code>--package--</code>	Value: None

4.2 Class couple

4.2.1 Methods

<code>__init__(self, boy, girl)</code>
--

<code>happinessCalcuator(self, boy, girl)</code>
--

<code>compatibilityCalculator(self, boy, girl)</code>

5 Module coupleMaker

5.1 Variables

Name	Description
Couples	Value: []
Gifts	Value: []
--package--	Value: None
arrBoys	Value: []
arrGirls	Value: []

5.2 Class coupleMaker

5.2.1 Methods

makeCouples(*self*)

Make Couples and print the gifting details of each

getMostHappy(*self*, *k*)

Prints the k most happy Couples

getMostCompatible(*self*, *k*)

Prints the k most compatible couples

6 Module driver

6.1 Functions

generateRandomInput()
Can be used to generate random Inputs

7 Module generator

7.1 Variables

Name	Description
<code>--package--</code>	Value: None

7.2 Class *randomGenerator*

7.2.1 Methods

<code>__init__(self, totalBoys, totalGirls, totalGifts)</code>
--

<code>generateBoys(self)</code>

<code>generateGirls(self)</code>

<code>generateGifts(self)</code>

8 Module *giftEssential*

8.1 Variables

Name	Description
<code>--package--</code>	Value: None

8.2 Class *giftEssential*

8.2.1 Methods

<code>--init--(<i>self</i>, <i>gift</i>)</code>

9 Module *giftLuxury*

9.1 Variables

Name	Description
<code>--package--</code>	Value: None

9.2 Class *giftLuxury*

9.2.1 Methods

<code>--init--(<i>self</i>, <i>gift</i>)</code>

9.2.2 Class Variables

Name	Description
<code>luxuryRating</code>	Value: 0
<code>obtainDiff</code>	Value: 0

10 Module *giftUtility*

10.1 Variables

Name	Description
<code>--package--</code>	Value: None

10.2 Class *giftUtility*

10.2.1 Methods

<code>--init--(<i>self</i>, <i>gift</i>)</code>

10.2.2 Class Variables

Name	Description
<code>utilityClass</code>	Value: None
<code>utilityValue</code>	Value: 0

11 Module girlChoosy

11.1 Variables

Name	Description
<code>--package--</code>	Value: None

11.2 Class girlChoosy

11.2.1 Methods

<code>--init--(self, girl)</code>

<code>happinessCalculator(self, giftBasket, amount)</code>
--

11.2.2 Class Variables

Name	Description
<code>happiness</code>	Value: 0
<code>costOfGiftsRec</code>	Value: 0
<code>bfName</code>	Value: ''

12 Module *girlDesperate*

12.1 Variables

Name	Description
<code>--package--</code>	Value: None

12.2 Class *girlDesperate*

12.2.1 Methods

<code>--init--(self, girl)</code>

<code>happinessCalculator(self, giftBasket, amount)</code>
--

12.2.2 Class Variables

Name	Description
<code>happiness</code>	Value: 0
<code>costOfGiftsRec</code>	Value: 0
<code>bfName</code>	Value: ''

13 Module *girlNormal*

13.1 Variables

Name	Description
<code>--package--</code>	Value: None

13.2 Class *girlNormal*

13.2.1 Methods

<code>__init__(self, girl)</code>

<code>happinessCalculator(self, giftBasket, amount)</code>
--

13.2.2 Class Variables

Name	Description
<code>happiness</code>	Value: 0
<code>costOfGiftsRec</code>	Value: 0
<code>bfName</code>	Value: ''

14 Module q1

14.1 Functions

allocate()
Allocates boys to girls

printCouples()
Prints Couples formed

performLog()
Writes the couple formation event into log file

15 Module reader

15.1 Variables

Name	Description
arrBoys	Value: []
arrGirls	Value: []
Gifts	Value: []
--package--	Value: None

15.2 Class read

15.2.1 Methods

```
--init--(self)
```

```
readcsvfile(self, charType)
```

Index

boyGeek (*module*), 2
 boyGeek.boyGeek (*class*), 2
 boyGeek.boyGeek.__init__ (*method*), 2
 boyGeek.boyGeek.gifting (*method*), 2
 boyGeek.boyGeek.happinessCalculator (*method*), 2
boyGenerous (*module*), 3
 boyGenerous.boyGenerous (*class*), 3
 boyGenerous.boyGenerous.__init__ (*method*), 3
 boyGenerous.boyGenerous.gifting (*method*), 3
 boyGenerous.boyGenerous.happinessCalculator (*method*), 3
boyMiser (*module*), 4
 boyMiser.boyMiser (*class*), 4
 boyMiser.boyMiser.__init__ (*method*), 4
 boyMiser.boyMiser.gifting (*method*), 4
 boyMiser.boyMiser.happinessCalculator (*method*), 4
couple (*module*), 5
 couple.couple (*class*), 5
 couple.couple.__init__ (*method*), 5
 couple.couple.compatibilityCalculator (*method*), 5
 couple.couple.happinessCalculator (*method*), 5
coupleMaker (*module*), 6
 coupleMaker.coupleMaker (*class*), 6
 coupleMaker.coupleMaker.getMostCompatible (*method*), 6
 coupleMaker.coupleMaker.getMostHappy (*method*), 6
 coupleMaker.coupleMaker.makeCouples (*method*), 6
driver (*module*), 7
 driver.generateRandomInput (*function*), 7
generator (*module*), 8
 generator.randomGenerator (*class*), 8
 generator.randomGenerator.__init__ (*method*), 8
 generator.randomGenerator.generateBoys (*method*), 8
 generator.randomGenerator.generateGifts (*method*), 8
 generator.randomGenerator.generateGirls (*method*), 8
giftEssential (*module*), 9
 giftEssential.giftEssential (*class*), 9
 giftEssential.giftEssential.__init__ (*method*), 9
 giftLuxury (*module*), 10
 giftLuxury.giftLuxury (*class*), 10
 giftLuxury.giftLuxury.__init__ (*method*), 10
 giftUtility (*module*), 11
 giftUtility.giftUtility (*class*), 11
 giftUtility.giftUtility.__init__ (*method*), 11
girlChoosy (*module*), 12
 girlChoosy.girlChoosy (*class*), 12
 girlChoosy.girlChoosy.__init__ (*method*), 12
 girlChoosy.girlChoosy.happinessCalculator (*method*), 12
girlDesperate (*module*), 13
 girlDesperate.girlDesperate (*class*), 13
 girlDesperate.girlDesperate.__init__ (*method*), 13
 girlDesperate.girlDesperate.happinessCalculator (*method*), 13
girlNormal (*module*), 14
 girlNormal.girlNormal (*class*), 14
 girlNormal.girlNormal.__init__ (*method*), 14
 girlNormal.girlNormal.happinessCalculator (*method*), 14
q1 (*module*), 15
 q1.allocate (*function*), 15
 q1.performLog (*function*), 15
 q1.printCouples (*function*), 15
reader (*module*), 16
 reader.read (*class*), 16
 reader.read.__init__ (*method*), 16
 reader.read.readcsvfile (*method*), 16