

SAPSprint Service



Copyright

© Copyright 2016 SAP AG. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors.

Microsoft, Windows, Excel, Outlook, and PowerPoint are registered trademarks of Microsoft Corporation.

IBM, DB2, DB2 Universal Database, System i, System i5, System p, System p5, System x, System z, System z10, System z9, z10, z9, iSeries, pSeries, xSeries, zSeries, eServer, z/VM, z/OS, i5/OS, S/390, OS/390, OS/400, AS/400, S/390 Parallel Enterprise Server, PowerVM, Power Architecture, POWER6+, POWER6, POWER5+, POWER5, POWER, OpenPower, PowerPC, BatchPipes, BladeCenter, System Storage, GPFS, HACMP, RETAIN, DB2 Connect, RACF, Redbooks, OS/2, Parallel Sysplex, MVS/ESA, AIX, Intelligent Miner, WebSphere, Netfinity, Tivoli and Informix are trademarks or registered trademarks of IBM Corporation.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

Adobe, the Adobe logo, Acrobat, PostScript, and Reader are either trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Oracle is a registered trademark of Oracle Corporation.

UNIX, X/Open, OSF/1, and Motif are registered trademarks of the Open Group.

Citrix, ICA, Program Neighborhood, MetaFrame, WinFrame, VideoFrame, and MultiWin are trademarks or registered trademarks of Citrix Systems, Inc.

HTML, XML, XHTML and W3C are trademarks or registered trademarks of W3C®, World Wide Web Consortium, Massachusetts Institute of Technology.

Java is a registered trademark of Sun Microsystems, Inc.

JavaScript is a registered trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape.

SAP, R/3, SAP NetWeaver, Duet, PartnerEdge, ByDesign, Clear Enterprise, SAP BusinessObjects Explorer and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries.

Business Objects and the Business Objects logo, BusinessObjects, Crystal Reports, Crystal Decisions, Web Intelligence, Xcelsius, and other Business Objects products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP France in the United States and in other countries.

All other product and service names mentioned are the trademarks of their respective companies. Data contained in this document serves informational purposes only. National product specifications may vary.

These materials are subject to change without notice. These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or

omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty

Icons in Body Text

Icon	Meaning
	Caution
	Example
	Note
	Recommendation
	Syntax

Additional icons are used in SAP Library documentation to help you identify different types of information at a glance. For more information, see *Help on Help → General Information Classes and Information Classes for Business Information Warehouse* on the first page of any version of *SAP Library*.

Typographic Conventions

Type Style	Description
<i>Example text</i>	Words or characters quoted from the screen. These include field names, screen titles, pushbuttons labels, menu names, menu paths, and menu options. Cross-references to other documentation.
Example text	Emphasized words or phrases in body text, graphic titles, and table titles.
EXAMPLE TEXT	Technical names of system objects. These include report names, program names, transaction codes, table names, and key concepts of a programming language when they are surrounded by body text, for example, SELECT and INCLUDE.
Example text	Output on the screen. This includes file and directory names and their paths, messages, names of variables and parameters, source text, and names of installation, upgrade and database tools.
Example text	Exact user entry. These are words or characters that you enter in the system exactly as they appear in the documentation.
<Example text>	Variable user entry. Angle brackets indicate that you replace these words and characters with appropriate entries to make entries in the system.
EXAMPLE TEXT	Keys on the keyboard, for example, F2 or ENTER.

SAPSprint Service	6
Printing Through SAPSprint.....	7
Installing SAPSprint	8



SAPSprint Service

Use

SAPSprint is a transfer program for print output using a Microsoft Windows operating system. SAPSprint replaces SAPlpd as an implementation of a print server and is required only for remote printing with Microsoft Windows. In this case, the host spool system (Microsoft Windows spooler) and the spool system (application server with a spool work process) are on different hosts. That is why the SAP spool system requires an external process that transfers the output requests from the SAP spool server to the Microsoft Windows spooler. This process is provided by the SAPSprint service.

Integration

SAPSprint comprises the program *sapsprint.exe* which contains the implementation of the Windows service and the receiver for print data from the SAP system. The SAPWIN data stream is processed in the *sapwin.dll* component. The *sapwin.dll* component is also used by the new front-end printing, as described in SAP Note [821519](#). SAPWIN processing errors therefore affect both print methods. Patches for SAPSprint and the new front-end printing are available in SAP Notes [927074](#) and [841175](#) respectively.

Prerequisites

SAPSprint runs as Windows service. In general, you do not have to change the default configuration settings of SAPSprint as Windows service except for one: You should change the local system account to a domain account. For this, open the list of services in your Windows system, right-click on the *SAPSprint* service, and choose *Properties*. On the *Log On* tab, check the option *This account* and enter a domain user account.

Features

SAPSprint preserves the features of SAPlpd as a transfer program:

- You can use SAPSprint in all Microsoft Windows systems.
- Like the line printer daemon lpd, SAPSprint accepts print data and forwards it to the host spooler.
- SAPSprint also interprets the special SWIN/SAPWIN data stream and converts it to GDI calls for Microsoft Windows. The system then uses the printer drivers that are available for Microsoft Windows and/or the printers. *sapwin.dll* contains the SAPWIN interpreter.

SAPSprint is implemented as a multithreaded Windows service and adds the following features:

- Error Bypassing
If an error occurs when printing on a device, this does not prevent printing on other devices defined in the system. In comparison, SAPlpd blocks output to all devices until the error is cleared manually. For more information, see [Printing Through SAPSprint \[Seite 7\]](#).
- Error autorecovery
SAPSprint is by default configured to restart automatically after an error and thus is more robust than SAPlpd.
- Logging and print file retention
You can configure SAPSprint to log information about print jobs as well as to retain print files after they are printed.

For more information, see [Setting the SAPSprint Log Level \[Seite Error! Bookmark not defined.\]](#).

- Command Line Administration

SAPSprint does not have a graphical user interface. You can set various configuration options for SAPSprint through a command line. By entering **SAPSprint -?** in the command line, you can view the most important configuration options. In comparison, SAPlpd was administered by directly accessing the Windows Registry Editor. You find a description of all configuration options in note 85469.

Enhanced Features

To be able to print Interactive Forms (previously also known as PDF-based forms) on a printer with any device type, you can additionally install the component SAPPDFPRINT. SAPPDFPRINT allows you to address any printer when printing Interactive Forms, in a similar way to using SAPWIN-based device types. SAPPDFPRINT requires either a Microsoft Windows print server with SAPSprint or SAP GUI for front-end printing. More information about this is available in the SAPPDFPRINT documentation, which is part of the delivery.



SAP Sprint or SAP GUI must be of the same release as SAPPDFPRINT.

Note that you should install SAPPDFPRINT before SAPSprint or SAP GUI, since SAPSprint or SAP GUI then automatically recognize this component.

Activities

Install SAPSprint. For more information, see [Installing SAPSprint \[Seite 8\]](#).



Printing Through SAPSprint


SAPSprint as a Service

SAPSprint is a multithreaded Windows service. For every output request to a particular device, SAPSprint opens a new thread.



The number of threads which SAPSprint can start is limited and depends on the operating system.

If an error occurs while printing on a device, only the thread to this device is affected. If the thread is blocked, it remains blocked until SAPSprint is restarted. As a result, jobs sent only to this device will fail until the service restart. However, you can safely print on another device defined in the system as the figure below shows.



In comparison, SAPlpd has a single process for all output requests. If an error occurs while printing to a device, it prevents output to any other device defined in the system until you restart SAPlpd manually.

Installing SAPSprint

Use

SAPSprint is release-independent and you can update it between releases. You install SAPSprint on the print server.

Prerequisites

- SAPSprint is downloaded and saved locally.
The SAPSprint installation is a single executable file (*xSprint.exe*). You can download it from service.sap.com/patches. You find detailed download and install instructions in note 894444.
- The installation host is running Microsoft Windows as the operating system.
- An implementation of the TCP/IP network protocol that supports WinSockets (the WINSOCK interface).
- You have write permissions to a directory on the file system.
You can specify the location of the directory during the installation.
- SAPlpd is uninstalled.
If SAPlpd is installed, uninstall it by deleting the SAPlpd installation directory.
If SAPlpd is installed as a service using the `srvany` tool, remove the service by executing the following command: **Instsrv SAPLPD remove**.

- If you want to print Interactive Forms (previously known as PDF-based forms) using SAPPDFPRINT, you should install this program before SAPSprint or SAP GUI, since SAPSprint or SAP GUI will then automatically recognize SAPPDFPRINT. More information about this is available in the SAPPDFPRINT documentation, which is part of the delivery.

Procedure

1. Run the *xSprint.exe*.
2. When prompted, specify the following:
 - a. SAPSprint installation directory
 - b. LPD port

The value determines the TCP/IP port that SAPSprint waits on. Port 515 is the standard port for printing using the S and U access method.

Leave the default value 515. Change the port number only if the Windows TCP/IP print service is also running on the installation host.

- c. LPD log path

Specifies the path to the log directory. The log directory contains log files and print jobs files. You can configure log files and print job files to be preserved or deleted by [setting SAPSprint log level](#) [Seite Error! Bookmark not defined.] after the installation.

Result

SAPSprint is installed and the service starts running automatically right after the installation. You can define printers with access methods S and U as usual.

See also:

Note [894444](#).