

February 22, 2020

1 Module Docu	mentation	1
1.1 Entities .		1
	1.1.0.1 ogit/ML/TrainedModel	1
	1.1.0.2 ogit/ML/PredictionModel	2
	1.1.0.3 ogit/ML/TrainingData	2
	1.1.0.4 ogit/Attachment	3
	1.1.0.5 ogit/Timeseries	4
1.2 Verbs .		5
	1.2.0.1 ogit/contains	5
	1.2.0.2 ogit/generates	5
	1.2.0.3 ogit/ML/trainedOn	5
	1.2.0.4 ogit/uses	6
	1.2.0.5 ogit/has	6
1.3 Attributes	<b>5</b>	7
	1.3.0.1 ogit/ML/endpoint	7
	1.3.0.2 ogit/url	7
	1.3.0.3 ogit/unit	7
	1.3.0.4 ogit/ML/size	8
	1.3.0.5 ogit/status	8
	1.3.0.6 ogit/createdAt	8
	1.3.0.7 ogit/accessControl	9
	1.3.0.8 ogit/ML/activeVersion	9
	1.3.0.9 ogit/content	9
	1.3.0.10 ogit/attachmentID	10
	1.3.0.11 ogit/name	10
	1.3.0.12 ogit/description	10
	1.3.0.13 ogit/ML/attributesSchema	11
	1.3.0.14 ogit/ML/trainedFrom	11
	1.3.0.15 ogit/lastUpdatedBy	11
	1.3.0.16 ogit/type	12
	1.3.0.17 ogit/isMutable	12
	1.3.0.18 ogit/sourceTable	12
	1.3.0.19 ogit/ML/requirements	13
	1.3.0.20 ogit/creator	13
	1.3.0.21 ogit/ML/meta	13
	1.3.0.22 ogit/lastUpdatedAt	14
	1.3.0.23 ogit/id	14
	1.3.0.24 ogit/size	14
	1.3.0.25 ogit/ML/trainData	15
	1.3.0.26 ogit/ML/trainingSummary	15
	1.3.0.27 ogit/instance	15

# **Chapter 1**

# **Module Documentation**

# 1.1 Entities

1.1.0.1 ogit/ML/TrainedModel

Trained machine learning model.

• id: http://www.purl.org/ogit/ML/TrainedModel

• valid-from: Tue Feb 18 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

• scope: NTO

· parent: ogit/Node

# attributes

- · mandatory:
  - ogit/name
- optional:
  - ogit/ML/meta
  - ogit/ML/requirements
  - ogit/ML/trainedFrom
  - ogit/ML/trainingSummary
  - ogit/attachmentID
  - ogit/status

# incoming edges

• ogit/uses <= ogit/ML/PredictionModel

1.1 Entities 2

#### outgoing edges

- ogit/ML/trainedOn => ogit/ML/TrainingData
- ogit/contains => ogit/Attachment

## 1.1.0.2 ogit/ML/PredictionModel

trained Prediction model which can be used by client directly.

• id: http://www.purl.org/ogit/ML/PredictionModel

valid-from: Tue Feb 18 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

• scope: NTO

· parent: ogit/Node

# attributes

- · mandatory:
  - ogit/name
- optional:
  - ogit/ML/activeVersion
  - ogit/ML/attributesSchema
  - ogit/ML/endpoint
  - ogit/description

# outgoing edges

- ogit/generates => ogit/Timeseries
- ogit/has => ogit/ML/TrainingData
- ogit/uses => ogit/ML/TrainedModel

## 1.1.0.3 ogit/ML/TrainingData

Training data for machine learning model.

- id: http://www.purl.org/ogit/ML/TrainingData
- valid-from: Tue Feb 18 00:00:00 UTC 2020
- · creator: Kaushik Gondaliya
- scope: NTO
- · parent: ogit/Node

1.1 Entities 3

## attributes

- · optional:
  - ogit/ML/size
  - ogit/ML/trainData
  - ogit/attachmentID
  - ogit/name

## incoming edges

- ogit/ML/trainedOn <= ogit/ML/TrainedModel
- ogit/has <= ogit/ML/PredictionModel</li>

# outgoing edges

• ogit/contains => ogit/Attachment

# 1.1.0.4 ogit/Attachment

This entity defines a file attachment that an IT service, issue, task or a ticket might have. The attachment itself is not saved in GraphIT, instead it contains an external url link for it.

- id: http://www.purl.org/ogit/Attachment
- · valid-from: Thu May 21 00:00:00 UTC 2015
- · creator: Peter Larem
- · scope: SGO
- · parent: ogit/Node

#### attributes

- · optional:
  - ogit/accessControl
  - ogit/content
  - ogit/createdAt
  - ogit/creator
  - ogit/id
  - ogit/lastUpdatedAt
  - ogit/lastUpdatedBy
  - ogit/name
  - ogit/size
  - ogit/sourceTable
  - ogit/type
  - ogit/url

1.1 Entities 4

# incoming edges

- ogit/contains <= ogit/ML/TrainedModel
- ogit/contains <= ogit/ML/TrainingData

## 1.1.0.5 ogit/Timeseries

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

• id: http://www.purl.org/ogit/Timeseries

• valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

• scope: SGO

· parent: ogit/Node

## attributes

- optional:
  - ogit/description
  - ogit/instance
  - ogit/isMutable
  - ogit/name
  - ogit/unit

# incoming edges

• ogit/generates <= ogit/ML/PredictionModel

1.2 Verbs 5

## 1.2 Verbs

## 1.2.0.1 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

```
• id: http://www.purl.org/ogit/contains
```

• valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

## **Allowed Connection**

- ogit/ML/TrainedModel => ogit/Attachment
- ogit/ML/TrainingData => ogit/Attachment

## 1.2.0.2 ogit/generates

Verb indicating if an entity generates another entity.

```
• id: http://www.purl.org/ogit/generates
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

#### **Allowed Connection**

• ogit/ML/PredictionModel => ogit/Timeseries

## 1.2.0.3 ogit/ML/trainedOn

it defines model trained on training data.

```
• id: http://www.purl.org/ogit/ML/trainedOn
```

• valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

#### **Allowed Connection**

• ogit/ML/TrainedModel => ogit/ML/TrainingData

1.2 Verbs 6

## 1.2.0.4 ogit/uses

This relationship indicates that some entity is used by some other.

• id: http://www.purl.org/ogit/uses

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

## **Allowed Connection**

• ogit/ML/PredictionModel => ogit/ML/TrainedModel

# 1.2.0.5 ogit/has

Indicates if an entity has another entity.

• id: http://www.purl.org/ogit/has

• valid-from: Thu Mar 28 00:00:00 UTC 2019

· creator: Kaushik Gondaliya

#### **Allowed Connection**

• ogit/ML/PredictionModel => ogit/ML/TrainingData

# 1.3 Attributes

# 1.3.0.1 ogit/ML/endpoint

endpoint of prediction model.

```
• id: http://www.purl.org/ogit/ML/endpoint
```

• valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/PredictionModel

## 1.3.0.2 ogit/url

Contains an URL (unified resource locator)

```
• id: http://www.purl.org/ogit/url
```

• valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- · optional:
  - ogit/Attachment

# 1.3.0.3 ogit/unit

Unit of measurement of some value.

```
• id: http://www.purl.org/ogit/unit
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

- optional:
  - ogit/Timeseries

#### 1.3.0.4 ogit/ML/size

The size of training data. Number of rows or entries.

```
• id: http://www.purl.org/ogit/ML/size
```

· valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/TrainingData

## 1.3.0.5 ogit/status

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems usefual in the application's semantic context.

```
• id: http://www.purl.org/ogit/status
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- · optional:
  - ogit/ML/TrainedModel

## 1.3.0.6 ogit/createdAt

Defines a point in time when a ticket/incident/event etc was created or recorded.

```
• id: http://www.purl.org/ogit/createdAt
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

- · optional:
  - ogit/Attachment

#### 1.3.0.7 ogit/accessControl

The access control level of this Node. Value could mean different things to different applications / policies. Initial intent is that policies would treat "public-read" (inspired by Amazon AWS S3 ACLs) to mean anyone would have read-only access to this node.

```
• id: http://www.purl.org/ogit/accessControl
```

valid-from: Thu Mar 26 00:00:00 UTC 2015

· creator: Chris Walker

used

- · optional:
  - ogit/Attachment

## 1.3.0.8 ogit/ML/activeVersion

currently active version of ML model.

```
• id: http://www.purl.org/ogit/ML/activeVersion
```

valid-from: Wed Feb 19 00:00:00 UTC 2020

• creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/PredictionModel

#### 1.3.0.9 ogit/content

A string holding any type of content: plain string, XML fragments, RDF documents, ...

```
• id: http://www.purl.org/ogit/content
```

valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

- · optional:
  - ogit/Attachment

#### 1.3.0.10 ogit/attachmentID

Node Id for attachment node.

• id: http://www.purl.org/ogit/attachmentID

• valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

#### used

- · optional:
  - ogit/ML/TrainedModel
  - ogit/ML/TrainingData

#### 1.3.0.11 ogit/name

Contains a name.

- id: http://www.purl.org/ogit/name
- valid-from: Thu May 21 00:00:00 UTC 2015
- · creator: Peter Larem

## used

- · mandatory:
  - ogit/ML/PredictionModel
  - ogit/ML/TrainedModel
- · optional:
  - ogit/Attachment
  - ogit/ML/TrainingData
  - ogit/Timeseries

# 1.3.0.12 ogit/description

Contains a description.

- id: http://www.purl.org/ogit/description
- valid-from: Thu May 21 00:00:00 UTC 2015
- · creator: Peter Larem

- · optional:
  - ogit/ML/PredictionModel
  - ogit/Timeseries

## 1.3.0.13 ogit/ML/attributesSchema

Information about attributes of training data, for example, How many columns, which type (String/Interger)

```
• id: http://www.purl.org/ogit/ML/attributesSchema
```

• valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/PredictionModel

## 1.3.0.14 ogit/ML/trainedFrom

Node Id of Traindata

- id: http://www.purl.org/ogit/ML/trainedFrom
- valid-from: Wed Feb 19 00:00:00 UTC 2020
- · creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/TrainedModel

## 1.3.0.15 ogit/lastUpdatedBy

Defines the last person or process who updated an entity.

- id: http://www.purl.org/ogit/lastUpdatedBy
- valid-from: Mon Jul 20 00:00:00 UTC 2015
- · creator: Aymen Ayoub

- · optional:
  - ogit/Attachment

#### 1.3.0.16 ogit/type

Type of an an entity.

```
• id: http://www.purl.org/ogit/type
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- · optional:
  - ogit/Attachment

## 1.3.0.17 ogit/isMutable

True if the value can be changed. E.g. after a service is provisioned.

```
• id: http://www.purl.org/ogit/isMutable
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- optional:
  - ogit/Timeseries

## 1.3.0.18 ogit/sourceTable

Contains the source table, that stores where the data are coming from.

```
• id: http://www.purl.org/ogit/sourceTable
```

valid-from: Thu Aug 20 00:00:00 UTC 2015

• creator: Aymen Ayoub

- · optional:
  - ogit/Attachment

## 1.3.0.19 ogit/ML/requirements

required information such as name and Version of the machine learning Frameworks, z.B. keras+tensorflow 1.20

```
• id: http://www.purl.org/ogit/ML/requirements
```

• valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/TrainedModel

## 1.3.0.20 ogit/creator

Creator of an entity.

- id: http://www.purl.org/ogit/creator
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- · creator: Aymen Ayoub

used

- optional:
  - ogit/Attachment

## 1.3.0.21 ogit/ML/meta

Meta infromation about machine learning model

- id: http://www.purl.org/ogit/ML/meta
- valid-from: Wed Feb 19 00:00:00 UTC 2020
- creator: Kaushik Gondaliya

- · optional:
  - ogit/ML/TrainedModel

## 1.3.0.22 ogit/lastUpdatedAt

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

```
• id: http://www.purl.org/ogit/lastUpdatedAt
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- · optional:
  - ogit/Attachment

1.3.0.23 ogit/id

General id.

```
• id: http://www.purl.org/ogit/id
```

· valid-from: Thu May 21 00:00:00 UTC 2015

· creator: Peter Larem

used

- · optional:
  - ogit/Attachment

1.3.0.24 ogit/size

The size, e.g. of a file.

- id: http://www.purl.org/ogit/size
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- · creator: arago Technologies

- · optional:
  - ogit/Attachment

#### 1.3.0.25 ogit/ML/trainData

if training data < 10Mb, it can be stored directly in this attribute (for Example as JSON). Attachment can be used for larger amount of training data. However, one of the trainData or attachmentID should be used, not both

```
• id: http://www.purl.org/ogit/ML/trainData
```

valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/TrainingData

## 1.3.0.26 ogit/ML/trainingSummary

summary about training the machine learning model

```
• id: http://www.purl.org/ogit/ML/trainingSummary
```

valid-from: Wed Feb 19 00:00:00 UTC 2020

· creator: Kaushik Gondaliya

used

- · optional:
  - ogit/ML/TrainedModel

## 1.3.0.27 ogit/instance

Defines the name of an instance.

- id: http://www.purl.org/ogit/instance
- · valid-from: Wed Aug 03 00:00:00 UTC 2016
- · creator: Philipp Pelchmann

- · optional:
  - ogit/Timeseries