

---

## Automation

---

January 3, 2020

<b>1 Module Documentation</b>	<b>1</b>
1.1 Entities	1
1.1.0.1 ogit/Forum/KnowledgeBundle	1
1.1.0.2 ogit/Organization	2
1.1.0.3 ogit/Forum/KnowledgeItemHistory	2
1.1.0.4 ogit/Question	3
1.1.0.5 ogit/Automation/ActionApplicability	4
1.1.0.6 ogit/Forum/Workflow	4
1.1.0.7 ogit/Forum/Topic	5
1.1.0.8 ogit/ServiceManagement/ChangeRequest	5
1.1.0.9 ogit/Automation/MARSNode	6
1.1.0.10 ogit/ServiceManagement/SubTask	10
1.1.0.11 ogit/Comment	11
1.1.0.12 ogit/Region	12
1.1.0.13 ogit/ServiceManagement/Order	12
1.1.0.14 ogit/OSLC-crtv/ServiceInstance	13
1.1.0.15 ogit/ServiceManagement/Incident	14
1.1.0.16 ogit/Cost/PlanningTemplate	15
1.1.0.17 ogit/Automation/Item	15
1.1.0.18 ogit/Forum/Rating	16
1.1.0.19 ogit/Forum/WorkflowStep	16
1.1.0.20 ogit/Person	17
1.1.0.21 ogit/Knowledge/AcquisitionSession	17
1.1.0.22 ogit/Task	18
1.1.0.23 ogit/Forum/KnowledgeBundleHistory	19
1.1.0.24 ogit/Automation/AutomationIssue	19
1.1.0.25 ogit/Automation/MARSModel	21
1.1.0.26 ogit/Automation/KnowledgeItemAttribute	22
1.1.0.27 ogit/Automation/Variable	22
1.1.0.28 ogit/Automation/KnowledgePool	23
1.1.0.29 ogit/Automation/Trigger	23
1.1.0.30 ogit/ServiceManagement/Service	24
1.1.0.31 ogit/ServiceManagement/Ticket	24
1.1.0.32 ogit/Cost/CostElement	25
1.1.0.33 ogit/Forum/FeedEntry	26
1.1.0.34 ogit/Forum/Reply	26
1.1.0.35 ogit/Forum/ShortId	27
1.1.0.36 ogit/Automation/MARSNodeTemplate	27
1.1.0.37 ogit/Automation/KIRanking	28
1.1.0.38 ogit/Attachment	29
1.1.0.39 ogit/Automation/MAID	29
1.1.0.40 ogit/ServiceManagement/Problem	30

1.1.0.41	ogit/Automation/ActionCapability	31
1.1.0.42	ogit/ConfigurationItem	31
1.1.0.43	ogit/Automation/KnowledgeItem	33
1.1.0.44	ogit/Hyperlink	35
1.1.0.45	ogit/Software/Application	35
1.1.0.46	ogit/Automation/KnowledgeBundle	36
1.1.0.47	ogit/Data/Log	37
1.1.0.48	ogit/Network/NetworkInterface	37
1.1.0.49	ogit/ServiceManagement/Report	38
1.1.0.50	ogit/ServiceManagement/Offering	38
1.1.0.51	ogit/Automation/MARSModelTemplate	39
1.1.0.52	ogit/Environment	39
1.1.0.53	ogit/MARS/Resource	40
1.1.0.54	ogit/Location	41
1.1.0.55	ogit/Automation/History	41
1.1.0.56	ogit/Asset	42
1.1.0.57	ogit/Event	42
1.1.0.58	ogit/Forum/Profile	43
1.1.0.59	ogit/Software/SoftwareComponent	44
1.1.0.60	ogit/Forum/Post	44
1.1.0.61	ogit/Automation/DynamicEngineData	45
1.1.0.62	ogit/Forum/Tag	46
1.1.0.63	ogit/Automation/ActionHandler	46
1.1.0.64	ogit/Automation/Configuration	47
1.1.0.65	ogit/License	47
1.1.0.66	ogit/Timeseries	48
1.2	Verbs	49
1.2.0.1	ogit/contains	49
1.2.0.2	ogit/defines	49
1.2.0.3	ogit/hosts	50
1.2.0.4	ogit/runsOn	50
1.2.0.5	ogit/worksOn	50
1.2.0.6	ogit/assignedTo	51
1.2.0.7	ogit/generates	51
1.2.0.8	ogit/specifies	51
1.2.0.9	ogit/solves	52
1.2.0.10	ogit/forks	52
1.2.0.11	ogit/derivesFrom	52
1.2.0.12	ogit/describes	53
1.2.0.13	ogit/creates	53
1.2.0.14	ogit/associates	53
1.2.0.15	ogit/connects	54

1.2.0.16 ogit/deployedTo	54
1.2.0.17 ogit/locatedIn	55
1.2.0.18 ogit/versions	55
1.2.0.19 ogit/corresponds	55
1.2.0.20 ogit/Forum/rates	56
1.2.0.21 ogit/affects	56
1.2.0.22 ogit/OSLC-crtv/runsOn	56
1.2.0.23 ogit/implements	57
1.2.0.24 ogit/provides	57
1.2.0.25 ogit/owns	57
1.2.0.26 ogit/dependsOn	58
1.2.0.27 ogit/belongs	58
1.2.0.28 ogit/uses	58
1.2.0.29 ogit/plans	59
1.2.0.30 ogit/reportedOn	59
1.2.0.31 ogit/Forum/downloads	59
1.2.0.32 ogit/consistsOf	60
1.2.0.33 ogit/relates	60
1.3 Attributes	61
1.3.0.1 ogit/_modified-by	61
1.3.0.2 ogit/Automation/serviceType	61
1.3.0.3 ogit/ciType	61
1.3.0.4 ogit/reviewedAt	62
1.3.0.5 ogit/Automation/serialNumber	62
1.3.0.6 ogit/Automation/servletName	62
1.3.0.7 ogit/Automation/deployToEngine	63
1.3.0.8 ogit/Automation/cpuCoreCount	63
1.3.0.9 ogit/Automation/serviceId	63
1.3.0.10 ogit/manufacturer	64
1.3.0.11 ogit/ServiceManagement/testPlan	64
1.3.0.12 ogit/Data/timeToLive	64
1.3.0.13 ogit/certainty	65
1.3.0.14 ogit/currency	65
1.3.0.15 ogit/category	65
1.3.0.16 ogit/_id	66
1.3.0.17 ogit/comment	66
1.3.0.18 ogit/Automation/osVersion	66
1.3.0.19 ogit/assignedAt	67
1.3.0.20 ogit/endOfWarranty	67
1.3.0.21 ogit/postalCode	67
1.3.0.22 ogit/Automation/buildType	68
1.3.0.23 ogit/Automation/cpuManufacturer	68

1.3.0.24 ogit/Automation/virtualMachineName . . . . .	68
1.3.0.25 ogit/productOrderNumber . . . . .	69
1.3.0.26 ogit/Automation/maidFormalRepresentation . . . . .	69
1.3.0.27 ogit/Automation/environmentFilter . . . . .	69
1.3.0.28 ogit/RL/totalReward . . . . .	70
1.3.0.29 ogit/checkedOutAt . . . . .	70
1.3.0.30 ogit/email . . . . .	70
1.3.0.31 ogit/Automation/moveToProductionAt . . . . .	71
1.3.0.32 ogit/ServiceManagement/resolvedAt . . . . .	71
1.3.0.33 ogit/urgency . . . . .	71
1.3.0.34 ogit/deliveredAt . . . . .	72
1.3.0.35 ogit/Automation/osServicePack . . . . .	72
1.3.0.36 ogit/Automation/rankingType . . . . .	72
1.3.0.37 ogit/alternativeName . . . . .	73
1.3.0.38 ogit/isCritical . . . . .	73
1.3.0.39 ogit/asset . . . . .	73
1.3.0.40 ogit/Automation/portNumberListener . . . . .	74
1.3.0.41 ogit/function . . . . .	74
1.3.0.42 ogit/positionNumber . . . . .	74
1.3.0.43 ogit/ServiceManagement/customer . . . . .	75
1.3.0.44 ogit/isValid . . . . .	75
1.3.0.45 ogit/Automation/memory . . . . .	75
1.3.0.46 ogit/integrity . . . . .	76
1.3.0.47 ogit/Automation/companyName . . . . .	76
1.3.0.48 ogit/ServiceManagement/scheduledStartAt . . . . .	76
1.3.0.49 ogit/Automation/suspendUntil . . . . .	77
1.3.0.50 ogit/country . . . . .	77
1.3.0.51 ogit/businessCategory . . . . .	77
1.3.0.52 ogit/Automation/middlewareType . . . . .	78
1.3.0.53 ogit/Automation/serviceName . . . . .	78
1.3.0.54 ogit/project . . . . .	78
1.3.0.55 ogit/Automation/licenseAvailability . . . . .	79
1.3.0.56 ogit/question . . . . .	79
1.3.0.57 ogit/maintenanceState . . . . .	79
1.3.0.58 ogit/_creator . . . . .	80
1.3.0.59 ogit/notification . . . . .	80
1.3.0.60 ogit/changeLog . . . . .	80
1.3.0.61 ogit/ServiceManagement/externalTicketId . . . . .	81
1.3.0.62 ogit/sourceId . . . . .	81
1.3.0.63 ogit/url . . . . .	81
1.3.0.64 ogit/licenseKey . . . . .	82
1.3.0.65 ogit/uri . . . . .	82

1.3.0.66 ogit/purchasedAt	83
1.3.0.67 ogit/Automation/cpuCount	83
1.3.0.68 ogit/timestamp	83
1.3.0.69 ogit/Automation/databaseSchema	84
1.3.0.70 ogit/mobilePhone	84
1.3.0.71 ogit/Automation/additionalMacAddress	84
1.3.0.72 ogit/severity	85
1.3.0.73 ogit/Automation/knowledgeItemTier	85
1.3.0.74 ogit/connectorId	85
1.3.0.75 ogit/Automation/dataClassification	86
1.3.0.76 ogit/Automation/firmwareVersion	86
1.3.0.77 ogit/effort	86
1.3.0.78 ogit/startedAt	87
1.3.0.79 ogit/value	87
1.3.0.80 ogit/assetTag	87
1.3.0.81 ogit/ipAddress	88
1.3.0.82 ogit/licenseType	88
1.3.0.83 ogit/unit	88
1.3.0.84 ogit/Automation/todo	89
1.3.0.85 ogit/Automation/knowledgeItemFormalRepresentation	89
1.3.0.86 ogit/Automation/installCount	89
1.3.0.87 ogit/installedAt	90
1.3.0.88 ogit/Automation/knowledgeItemId	90
1.3.0.89 ogit/Automation/marsNodeFormalRepresentation	90
1.3.0.90 ogit/updateCount	91
1.3.0.91 ogit/Knowledge/archived	91
1.3.0.92 ogit/installStatus	91
1.3.0.93 ogit/city	92
1.3.0.94 ogit/Automation/systemClass	92
1.3.0.95 ogit/Automation/diskCount	92
1.3.0.96 ogit/mode	93
1.3.0.97 ogit/Automation/automationState	93
1.3.0.98 ogit/ServiceManagement/incidentStatus	93
1.3.0.99 ogit/taskLog	94
1.3.0.100 ogit/status	94
1.3.0.101 ogit/createdAt	94
1.3.0.102 ogit/ServiceManagement/workAround	95
1.3.0.103 ogit/ServiceManagement/rootCause	95
1.3.0.104 ogit/Forum/username	95
1.3.0.105 ogit/model	96
1.3.0.106 ogit/Automation/domain	96
1.3.0.107 ogit/Automation/lifecycle	96

1.3.0.108 ogit/lastName . . . . .	97
1.3.0.109 ogit/Automation/cpuModel . . . . .	97
1.3.0.110 ogit/Automation/buildName . . . . .	97
1.3.0.111 ogit/Automation/applInstanceType . . . . .	98
1.3.0.112 ogit/modificationTime . . . . .	98
1.3.0.113 ogit/ServiceManagement/problemStatus . . . . .	98
1.3.0.114 ogit/Automation/knowledgeItemSyntaxVersion . . . . .	99
1.3.0.115 ogit/Automation/maxIdleTime . . . . .	99
1.3.0.116 ogit/priority . . . . .	99
1.3.0.117 ogit/shortDescription . . . . .	100
1.3.0.118 ogit/Automation/serviceClass . . . . .	100
1.3.0.119 ogit/middleName . . . . .	100
1.3.0.120 ogit/resource . . . . .	100
1.3.0.121 ogit/ServiceManagement/targetFinishAt . . . . .	101
1.3.0.122 ogit/accessControl . . . . .	101
1.3.0.123 ogit/ServiceManagement/ticketId . . . . .	102
1.3.0.124 ogit/justification . . . . .	102
1.3.0.125 ogit/invoiceNumber . . . . .	102
1.3.0.126 ogit/response . . . . .	103
1.3.0.127 ogit/ServiceManagement/externalTicketSource . . . . .	103
1.3.0.128 ogit/Automation/diskSpace . . . . .	103
1.3.0.129 ogit/soxClass . . . . .	104
1.3.0.130 ogit/closedAt . . . . .	104
1.3.0.131 ogit/ServiceManagement/taskStatus . . . . .	104
1.3.0.132 ogit/ServiceManagement/resolutionCode . . . . .	105
1.3.0.133 ogit/expiresAt . . . . .	105
1.3.0.134 ogit/streetAddress . . . . .	105
1.3.0.135 ogit/businessCriticality . . . . .	106
1.3.0.136 ogit/leaseContract . . . . .	106
1.3.0.137 ogit/_owner . . . . .	106
1.3.0.138 ogit/securityClass . . . . .	106
1.3.0.139 ogit/serialNumber . . . . .	107
1.3.0.140 ogit/firstName . . . . .	107
1.3.0.141 ogit/Automation/optionalParameters . . . . .	107
1.3.0.142 ogit/assignedGroup . . . . .	108
1.3.0.143 ogit/macAddress . . . . .	108
1.3.0.144 ogit/Automation/osName . . . . .	108
1.3.0.145 ogit/version . . . . .	109
1.3.0.146 ogit/title . . . . .	109
1.3.0.147 ogit/Automation/appServer . . . . .	109
1.3.0.148 ogit/class . . . . .	110
1.3.0.149 ogit/Automation/sendHistory . . . . .	110

1.3.0.150 ogit/content . . . . .	110
1.3.0.151 ogit/confidentiality . . . . .	111
1.3.0.152 ogit/Automation/deployStatus . . . . .	111
1.3.0.153 ogit/Automation/rankMap . . . . .	111
1.3.0.154 ogit/lastOccurredAt . . . . .	112
1.3.0.155 ogit/Automation/isDeployed . . . . .	112
1.3.0.156 ogit/Automation/processingNode . . . . .	112
1.3.0.157 ogit/Automation/issueFormalRepresentation . . . . .	113
1.3.0.158 ogit/_tags . . . . .	113
1.3.0.159 ogit/ServiceManagement/scheduledFinishAt . . . . .	113
1.3.0.160 ogit/name . . . . .	114
1.3.0.161 ogit/Automation/software . . . . .	115
1.3.0.162 ogit/Automation/originNode . . . . .	115
1.3.0.163 ogit/description . . . . .	115
1.3.0.164 ogit/finishedAt . . . . .	116
1.3.0.165 ogit/Automation/host . . . . .	117
1.3.0.166 ogit/Automation/weightMap . . . . .	117
1.3.0.167 ogit/externalId . . . . .	117
1.3.0.168 ogit/impact . . . . .	118
1.3.0.169 ogit/contact . . . . .	118
1.3.0.170 ogit/Automation/defaultSigma . . . . .	118
1.3.0.171 ogit/Automation/appInfrastructureType . . . . .	119
1.3.0.172 ogit/revision . . . . .	119
1.3.0.173 ogit/Automation/issueType . . . . .	119
1.3.0.174 ogit/orderedAt . . . . .	120
1.3.0.175 ogit/faultCount . . . . .	120
1.3.0.176 ogit/risk . . . . .	120
1.3.0.177 ogit/lastUpdatedBy . . . . .	121
1.3.0.178 ogit/ServiceManagement/fallbackPlan . . . . .	121
1.3.0.179 ogit/Automation/defaultRank . . . . .	121
1.3.0.180 ogit/isRoot . . . . .	122
1.3.0.181 ogit/openedAt . . . . .	122
1.3.0.182 ogit/Automation/virtualSystemName . . . . .	122
1.3.0.183 ogit/expirationDate . . . . .	123
1.3.0.184 ogit/officePhone . . . . .	123
1.3.0.185 ogit/phone . . . . .	123
1.3.0.186 ogit/acknowledgeState . . . . .	124
1.3.0.187 ogit/deadline . . . . .	124
1.3.0.188 ogit/Automation/osLicense . . . . .	124
1.3.0.189 ogit/fax . . . . .	125
1.3.0.190 ogit/Automation/databaseServer . . . . .	125
1.3.0.191 ogit/Automation/portNumber . . . . .	125



1.3.0.192 ogit/Automation/webServer	126
1.3.0.193 ogit/type	126
1.3.0.194 ogit/Automation/softwareKey	126
1.3.0.195 ogit/Automation/installPath	127
1.3.0.196 ogit/Automation/licenseName	127
1.3.0.197 ogit/capacity	127
1.3.0.198 ogit/Automation/contextPath	128
1.3.0.199 ogit/Automation/cpuSpeed	128
1.3.0.200 ogit/Automation/processingTimestamp	128
1.3.0.201 ogit/otherPhone	129
1.3.0.202 ogit/subCategory	129
1.3.0.203 ogit/isMutable	129
1.3.0.204 ogit/Automation/servletClass	130
1.3.0.205 ogit/sourceTable	130
1.3.0.206 ogit/creator	130
1.3.0.207 ogit/ServiceManagement/implementationPlan	131
1.3.0.208 ogit/Datacenter/rackUnit	131
1.3.0.209 ogit/availability	131
1.3.0.210 ogit/ServiceManagement/allowedForNewBusiness	132
1.3.0.211 ogit/Automation/firewallStatus	132
1.3.0.212 ogit/lastScannedAt	132
1.3.0.213 ogit/capacityAvailable	133
1.3.0.214 ogit/subType	133
1.3.0.215 ogit/pendingChange	133
1.3.0.216 ogit/Automation/exchangeRate	134
1.3.0.217 ogit/ServiceManagement/sourceStatus	134
1.3.0.218 ogit/Automation/patchNumber	134
1.3.0.219 ogit/Automation/cpuType	135
1.3.0.220 ogit/Automation/dataPrivacy	135
1.3.0.221 ogit/inventoryNumber	135
1.3.0.222 ogit/message	136
1.3.0.223 ogit/webPage	136
1.3.0.224 ogit/Automation/objectIdentifier	136
1.3.0.225 ogit/lastUpdatedAt	137
1.3.0.226 ogit/modelNumber	137
1.3.0.227 ogit/Automation/fqdn	137
1.3.0.228 ogit/Automation/osKey	138
1.3.0.229 ogit/Automation/brand	138
1.3.0.230 ogit/Automation/licenseType	138
1.3.0.231 ogit/market	139
1.3.0.232 ogit/Automation/virtualSystemType	139
1.3.0.233 ogit/Automation/affectedNodeId	139

1.3.0.234 ogit/Automation/osManufacturer . . . . .	140
1.3.0.235 ogit/id . . . . .	140
1.3.0.236 ogit/occurenceCount . . . . .	141
1.3.0.237 ogit/ServiceManagement/solution . . . . .	141
1.3.0.238 ogit/creationTime . . . . .	141
1.3.0.239 ogit/subject . . . . .	142
1.3.0.240 ogit/checkedInAt . . . . .	142
1.3.0.241 ogit/summary . . . . .	142
1.3.0.242 ogit/lastClearedAt . . . . .	143
1.3.0.243 ogit/Automation/adminUrl . . . . .	143
1.3.0.244 ogit/MARS/Resource/class . . . . .	143
1.3.0.245 ogit/Automation/marsNodeType . . . . .	144
1.3.0.246 ogit/Automation/command . . . . .	144
1.3.0.247 ogit/Automation/basicConfigId . . . . .	144
1.3.0.248 ogit/Automation/parentIssue . . . . .	145
1.3.0.249 ogit/size . . . . .	145
1.3.0.250 ogit/serviceContract . . . . .	145
1.3.0.251 ogit/Automation/serviceStatus . . . . .	146
1.3.0.252 ogit/vendor . . . . .	146
1.3.0.253 ogit/firstOccurredAt . . . . .	146
1.3.0.254 ogit/validFrom . . . . .	147
1.3.0.255 ogit/Automation/governingContract . . . . .	147
1.3.0.256 ogit/Automation/systemType . . . . .	147
1.3.0.257 ogit/Automation/tcpPort . . . . .	148
1.3.0.258 ogit/position . . . . .	148
1.3.0.259 ogit/reportedAt . . . . .	148
1.3.0.260 ogit/Automation/webhook . . . . .	149
1.3.0.261 ogit/Automation/logLevel . . . . .	149
1.3.0.262 ogit/ServiceManagement/targetStartAt . . . . .	149
1.3.0.263 ogit/Automation/mandatoryParameters . . . . .	150
1.3.0.264 ogit/ServiceManagement/reportedSource . . . . .	150
1.3.0.265 ogit/RL/state . . . . .	150
1.3.0.266 ogit/ServiceManagement/task . . . . .	151
1.3.0.267 ogit/instance . . . . .	151
1.3.0.268 ogit/Automation/sendData . . . . .	151
1.3.0.269 ogit/isSupported . . . . .	152
1.3.0.270 ogit/operationalStatus . . . . .	152
1.3.0.271 ogit/validTo . . . . .	152
1.3.0.272 ogit/ServiceManagement/changeStatus . . . . .	153
1.3.0.273 ogit/Automation/projectName . . . . .	153

# Chapter 1

## Module Documentation

### 1.1 Entities

#### 1.1.0.1 ogit/Forum/KnowledgeBundle

Deprecated in favor of ogit/Automation/KnowledgeBundle. A grouping of ogit/Automation/↔ KnowledgeItems into a package.

- id: <http://www.purl.org/ogit/Forum/KnowledgeBundle>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

#### incoming edges

- [ogit/connects](#) ≤ [ogit/Automation/KnowledgeItem](#)

#### outgoing edges

- [ogit/connects](#) ⇒ [ogit/Automation/KnowledgeItem](#)
- [ogit/contains](#) ⇒ [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) ⇒ [ogit/Automation/KnowledgeItem](#)

### 1.1.0.2 ogit/Organization

An identity that represents an organization, company, or some other grouping of Person objects. Entities of this type should be created with a predefined ID. Those IDs should be named like a domain name, i.e. a concatenation of some strings separated with a dot. If organization data is created from a LDAP then a mapping like "cn=John Doe,dc=example,dc=com" => "john\_doe.example.com" should be employed. The ogit/function attribute should be used to tell what kind of grouping an entity of type Organization is: company, department, group, ...

- id: <http://www.purl.org/ogit/Organization>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/businessCategory](#)
  - [ogit/city](#)
  - [ogit/country](#)
  - [ogit/description](#)
  - [ogit/email](#)
  - [ogit/function](#)
  - [ogit/phone](#)
  - [ogit/postalCode](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/streetAddress](#)
  - [ogit/webPage](#)

#### outgoing edges

- [ogit/owns](#) => [ogit/Automation/MARSNode](#)

### 1.1.0.3 ogit/Forum/KnowledgeItemHistory

Deprecated in favor of [ogit/VersioningData](#). A data container of [ogit/Automation/KnowledgeItems](#) changes.

- id: <http://www.purl.org/ogit/Forum/KnowledgeItemHistory>
- valid-from: Fri Nov 13 00:00:00 UTC 2015
- creator: [bmmore@arago.de](mailto:bmmore@arago.de)
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/Automation/deployToEngine](#)
  - [ogit/Automation/knowledgeItemFormalRepresentation](#)
- optional:
  - [ogit/Automation/knowledgeItemTier](#)
  - [ogit/accessControl](#)
  - [ogit/changeLog](#)
  - [ogit/creationTime](#)
  - [ogit/description](#)
  - [ogit/isValid](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/relates](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.4 ogit/Question**

This structure allows an automation engine to create data requests for existing Issues which should be filled by human user. Additionally could be used to create new Issue from some form.

- id: <http://www.purl.org/ogit/Question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/capacity](#)
  - [ogit/question](#)
  - [ogit/response](#)
  - [ogit/status](#)

## incoming edges

- [ogit/associates](#) <= [ogit/Automation/AutomationIssue](#)

1.1.0.5 [ogit/Automation/ActionApplicability](#)

Defines the applicability of an action handler, such as on [ogit/\\_id](#).

- id: <http://www.purl.org/ogit/Automation/ActionApplicability>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Automation/environmentFilter](#)
- optional:
  - [ogit/Automation/mandatoryParameters](#)
  - [ogit/Automation/optionalParameters](#)

## incoming edges

- [ogit/provides](#) <= [ogit/Automation/ActionHandler](#)

## outgoing edges

- [ogit/provides](#) => [ogit/Automation/ActionCapability](#)

1.1.0.6 [ogit/Forum/Workflow](#)

A Workflow defines a series of steps that must be completed in order.

- id: <http://www.purl.org/ogit/Forum/Workflow>
- valid-from: Mon Sep 18 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/title](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/AutomationIssue](#)

1.1.0.7 [ogit/Forum/Topic](#)

A Topic is a SubForum with a specific topic associated. Use to divide forums into sub-forums. However the entity is general enough to be used for anything that has a given subject.

- id: <http://www.purl.org/ogit/Forum/Topic>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/description](#)
  - [ogit/title](#)
- optional:
  - [ogit/accessControl](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

1.1.0.8 [ogit/ServiceManagement/ChangeRequest](#)

This entity type defines a change request ticket

- id: <http://www.purl.org/ogit/ServiceManagement/ChangeRequest>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/changeStatus](#)
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/fallbackPlan](#)
  - [ogit/ServiceManagement/implementationPlan](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/scheduledStartAt](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/targetFinishAt](#)
  - [ogit/ServiceManagement/targetStartAt](#)
  - [ogit/ServiceManagement/testPlan](#)
  - [ogit/assignedGroup](#)
  - [ogit/category](#)
  - [ogit/effort](#)
  - [ogit/finishedAt](#)
  - [ogit/justification](#)
  - [ogit/reportedAt](#)
  - [ogit/reviewedAt](#)
  - [ogit/risk](#)
  - [ogit/startedAt](#)

**outgoing edges**

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

**1.1.0.9 ogit/Automation/MARSNode**

Using this entity type to represent MARS nodes is deprecated. New applications should prefer the entity types from ogit/MARS NTO.

IT Objects will be represented in MARS Modell with MARS nodes. The MARS model builds upon four basic types of objects with a single type of relationship. Basically the objects which are in fact called "nodes" represent both views - the business perspective and the technical view. The technical components are modeled in the machine and software layers while the application and resource layers describe the business view of the IT environment.

- id: <http://www.purl.org/ogit/Automation/MARSNode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node



## attributes

- optional:
  - `ogit/Automation/additionalMacAddress`
  - `ogit/Automation/adminUrl`
  - `ogit/Automation/appInfrastructureType`
  - `ogit/Automation/appInstanceType`
  - `ogit/Automation/appServer`
  - `ogit/Automation/basicConfigId`
  - `ogit/Automation/brand`
  - `ogit/Automation/buildName`
  - `ogit/Automation/buildType`
  - `ogit/Automation/companyName`
  - `ogit/Automation/contextPath`
  - `ogit/Automation/cpuCoreCount`
  - `ogit/Automation/cpuCount`
  - `ogit/Automation/cpuManufacturer`
  - `ogit/Automation/cpuModel`
  - `ogit/Automation/cpuSpeed`
  - `ogit/Automation/cpuType`
  - `ogit/Automation/dataClassification`
  - `ogit/Automation/dataPrivacy`
  - `ogit/Automation/databaseSchema`
  - `ogit/Automation/databaseServer`
  - `ogit/Automation/deployStatus`
  - `ogit/Automation/diskCount`
  - `ogit/Automation/diskSpace`
  - `ogit/Automation/domain`
  - `ogit/Automation/exchangeRate`
  - `ogit/Automation/firewallStatus`
  - `ogit/Automation/firmwareVersion`
  - `ogit/Automation/fqdn`
  - `ogit/Automation/host`
  - `ogit/Automation/installCount`
  - `ogit/Automation/installPath`
  - `ogit/Automation/isDeployed`
  - `ogit/Automation/licenseAvailability`
  - `ogit/Automation/licenseName`
  - `ogit/Automation/licenseType`
  - `ogit/Automation/lifecycle`
  - `ogit/Automation/marsNodeFormalRepresentation`
  - `ogit/Automation/marsNodeType`
  - `ogit/Automation/memory`
  - `ogit/Automation/middlewareType`
  - `ogit/Automation/moveToProductionAt`

- [ogit/Automation/objectIdentifier](#)
- [ogit/Automation/osKey](#)
- [ogit/Automation/osLicense](#)
- [ogit/Automation/osManufacturer](#)
- [ogit/Automation/osName](#)
- [ogit/Automation/osServicePack](#)
- [ogit/Automation/osVersion](#)
- [ogit/Automation/patchNumber](#)
- [ogit/Automation/portNumber](#)
- [ogit/Automation/portNumberListener](#)
- [ogit/Automation/projectName](#)
- [ogit/Automation/serialNumber](#)
- [ogit/Automation/serviceId](#)
- [ogit/Automation/serviceName](#)
- [ogit/Automation/serviceStatus](#)
- [ogit/Automation/serviceType](#)
- [ogit/Automation/servletClass](#)
- [ogit/Automation/servletName](#)
- [ogit/Automation/software](#)
- [ogit/Automation/softwareKey](#)
- [ogit/Automation/systemClass](#)
- [ogit/Automation/systemType](#)
- [ogit/Automation/tcpPort](#)
- [ogit/Automation/virtualMachineName](#)
- [ogit/Automation/virtualSystemName](#)
- [ogit/Automation/virtualSystemType](#)
- [ogit/Automation/webServer](#)
- [ogit/Datacenter/rackUnit](#)
- [ogit/connectorId](#)
- [ogit/creationTime](#)
- [ogit/endOfWarranty](#)
- [ogit/id](#)
- [ogit/ipAddress](#)
- [ogit/macAddress](#)
- [ogit/manufacturer](#)
- [ogit/modificationTime](#)
- [ogit/name](#)
- [ogit/serialNumber](#)

#### incoming edges

- [ogit/OSLC-crtv/runsOn](#) <= [ogit/OSLC-crtv/ServiceInstance](#)
- [ogit/affects](#) <= [ogit/Automation/MARSNode](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)

- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/affects`  $\leq$  `ogit/Event`
- `ogit/belongs`  $\leq$  `ogit/Attachment`
- `ogit/consistsOf`  $\leq$  `ogit/Environment`
- `ogit/contains`  $\leq$  `ogit/Automation/MARSModel`
- `ogit/contains`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/corresponds`  $\leq$  `ogit/ConfigurationItem`
- `ogit/dependsOn`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/deployedTo`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/describes`  $\leq$  `ogit/Asset`
- `ogit/hosts`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/owns`  $\leq$  `ogit/Organization`
- `ogit/provides`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/relates`  $\leq$  `ogit/Automation/AutomationIssue`
- `ogit/relates`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/relates`  $\leq$  `ogit/Automation/MARSNodeTemplate`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Report`
- `ogit/relates`  $\leq$  `ogit/ConfigurationItem`
- `ogit/relates`  $\leq$  `ogit/Event`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/runsOn`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/uses`  $\leq$  `ogit/Software/SoftwareComponent`
- `ogit/worksOn`  $\leq$  `ogit/Automation/AutomationIssue`

## outgoing edges

- `ogit/affects => ogit/ServiceManagement/Service`
- `ogit/affects => ogit/Automation/MARSNode`
- `ogit/assignedTo => ogit/Person`
- `ogit/associates => ogit/Cost/CostElement`
- `ogit/contains => ogit/Network/NetworkInterface`
- `ogit/contains => ogit/Automation/MARSNode`
- `ogit/contains => ogit/Automation/DynamicEngineData`
- `ogit/corresponds => ogit/Software/Application`
- `ogit/dependsOn => ogit/Automation/MARSNode`
- `ogit/deployedTo => ogit/Automation/MARSNode`
- `ogit/generates => ogit/Data/Log`
- `ogit/generates => ogit/Timeseries`
- `ogit/hosts => ogit/Automation/MARSNode`
- `ogit/locatedIn => ogit/Location`
- `ogit/locatedIn => ogit/Region`
- `ogit/provides => ogit/Automation/MARSNode`
- `ogit/relates => ogit/Automation/MARSNodeTemplate`
- `ogit/relates => ogit/Automation/MARSNode`
- `ogit/relates => ogit/License`
- `ogit/relates => ogit/Automation/KnowledgeItem`
- `ogit/runsOn => ogit/Automation/MARSNode`
- `ogit/uses => ogit/Automation/Configuration`

## 1.1.0.10 ogit/ServiceManagement/SubTask

This entity type defines sub-tasks for a ticket. Mostly used for ChangeRequest. Common alternative names with same meaning are: task, activity, work order.

- id: <http://www.purl.org/ogit/ServiceManagement/SubTask>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/scheduledStartAt](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/targetFinishAt](#)
  - [ogit/ServiceManagement/targetStartAt](#)
  - [ogit/ServiceManagement/taskStatus](#)
  - [ogit/assignedGroup](#)
  - [ogit/description](#)
  - [ogit/effort](#)
  - [ogit/finishedAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/name](#)
  - [ogit/startedAt](#)
  - [ogit/taskLog](#)
  - [ogit/type](#)

**outgoing edges**

- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)

**1.1.0.11 ogit/Comment**

Defines comments for a ticket, issue or another type of entity. Also known as WorkLog, ChangeLog or HistoryEntry.

- id: <http://www.purl.org/ogit/Comment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/content](#)
  - [ogit/creator](#)
  - [ogit/id](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.12 [ogit/Region](#)

A region is always something that has a certain geographic extension (a country, a county, ) whereas [ogit/Location](#) usually refers to specific place usually having an address

- id: <http://www.purl.org/ogit/Region>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

## incoming edges

- [ogit/locatedIn](#) <= [ogit/Automation/MARSNode](#)

1.1.0.13 [ogit/ServiceManagement/Order](#)

Defines an order.

- id: <http://www.purl.org/ogit/ServiceManagement/Order>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/externalTicketSource](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

## incoming edges

- [ogit/implements](#) <= [ogit/Automation/MARSModel](#)

## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

1.1.0.14 [ogit/OSLC-crtv/ServiceInstance](#)

A Service Instance is the representation of a service offering that was selected by the customer and then instantiated for that specific customer. Service Instances are supported by definite and measurable warranties or guarantees that the expected level of service/value will be met. Instances of the resource carry exposure from the group that is responsible for supporting the offering externally to the group that is utilizing the offering. It is common to group or nest instances together to form a service instance hierarchy. This resource definition does not represent the individual processes and/or activities that comprise an overall service except in the case where such processes are viewed as an independent service. In this condition, an instance of ServiceInstance would be created to represent the ServiceInstance of the process, then creating a hierarchy of ServiceInstances (to the containing ServiceInstance).

- id: <http://www.purl.org/ogit/OSLC-crtv/ServiceInstance>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: [ogit/Node](#)

## incoming edges

- `ogit/deployedTo` <= `ogit/Automation/KnowledgeItem`

## outgoing edges

- `ogit/OSLC-crtv/runsOn` => `ogit/Automation/MARSNode`
- `ogit/uses` => `ogit/Automation/KnowledgePool`

1.1.0.15 `ogit/ServiceManagement/Incident`

This entity type defines an incident ticket.

- id: `http://www.purl.org/ogit/ServiceManagement/Incident`
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: `ogit/Node`

## attributes

- optional:
  - `ogit/ServiceManagement/customer`
  - `ogit/ServiceManagement/incidentStatus`
  - `ogit/ServiceManagement/reportedSource`
  - `ogit/ServiceManagement/resolutionCode`
  - `ogit/ServiceManagement/resolvedAt`
  - `ogit/ServiceManagement/solution`
  - `ogit/ServiceManagement/sourceStatus`
  - `ogit/ServiceManagement/task`
  - `ogit/assignedGroup`
  - `ogit/category`
  - `ogit/id`
  - `ogit/reportedAt`

## outgoing edges

- `ogit/affects` => `ogit/Automation/MARSNode`
- `ogit/corresponds` => `ogit/Automation/AutomationIssue`
- `ogit/reportedOn` => `ogit/Automation/MARSNode`



#### 1.1.0.16 ogit/Cost/PlanningTemplate

A Planning Template is an estimated planning of cost elements referring to an Implementation Template and a Planning Parameter. It will consist of a recursive set of sub-templates, connected through an edge, where each one of them will represent a service. For a general overview: see the NTO description on github.

- id: <http://www.purl.org/ogit/Cost/PlanningTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

##### outgoing edges

- [ogit/plans](#) => [ogit/Automation/MARSModelTemplate](#)

#### 1.1.0.17 ogit/Automation/Item

Item describing a condition for an automation issue (e.g. Request) that would correspond to a technical characteristic, which would activate the automation Trigger.

- id: <http://www.purl.org/ogit/Automation/Item>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

##### attributes

- mandatory:
  - [ogit/name](#)

##### incoming edges

- [ogit/contains](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) <= [ogit/Automation/Item](#)
- [ogit/contains](#) <= [ogit/Automation/Trigger](#)

##### outgoing edges

- [ogit/contains](#) => [ogit/Automation/KnowledgeItemAttribute](#)
- [ogit/contains](#) => [ogit/Automation/Item](#)

## 1.1.0.18 ogit/Forum/Rating

Rating is used to rank nodes based on an arbitrary integer `value`

- id: <http://www.purl.org/ogit/Forum/Rating>
- valid-from: Wed Aug 12 00:00:00 UTC 2015
- creator: [bneal@arago.de](mailto:bneal@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/value](#)
- optional:
  - [ogit/content](#)

## outgoing edges

- [ogit/Forum/rates](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.19 ogit/Forum/WorkflowStep

A Workflow Step defines part of a workflow

- id: <http://www.purl.org/ogit/Forum/WorkflowStep>
- valid-from: Mon Sep 18 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/title](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.20 [ogit/Person](#)

A Person represents a human identity.

- id: <http://www.purl.org/ogit/Person>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/alternativeName](#)
  - [ogit/email](#)
  - [ogit/fax](#)
  - [ogit/firstName](#)
  - [ogit/lastName](#)
  - [ogit/middleName](#)
  - [ogit/mobilePhone](#)
  - [ogit/notification](#)
  - [ogit/officePhone](#)
  - [ogit/otherPhone](#)
  - [ogit/position](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/title](#)
  - [ogit/webPage](#)

## incoming edges

- [ogit/assignedTo](#) <= [ogit/Automation/MARSNode](#)

1.1.0.21 [ogit/Knowledge/AcquisitionSession](#)

Entity to describe a Knowledge Acquisition Session, linking to Conversation, Structured Task Steps and the Knowledge

- id: <http://www.purl.org/ogit/Knowledge/AcquisitionSession>
- valid-from: Tue Mar 14 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/Knowledge/archived](#)
  - [ogit/description](#)
  - [ogit/title](#)

**incoming edges**

- [ogit/relates](#) <= [ogit/Automation/AutomationIssue](#)

**outgoing edges**

- [ogit/defines](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.22 ogit/Task**

A task is a unit of execution.

- id: <http://www.purl.org/ogit/Task>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/positionNumber](#)
  - [ogit/question](#)
  - [ogit/response](#)
  - [ogit/status](#)
  - [ogit/type](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/solves](#) <= [ogit/Automation/KnowledgeItem](#)

1.1.0.23 `ogit/Forum/KnowledgeBundleHistory`

A point-in-time snapshot of an `ogit/Forum/KnowledgeBundle`

- id: <http://www.purl.org/ogit/Forum/KnowledgeBundleHistory>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: `ogit/Node`

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.24 `ogit/Automation/AutomationIssue`

Dynamic information exists within an automation engine in the form of Issues otherwise referred to as Task or Situational Data. From the technical perspective an Issue is a number of attributes (Key/Value tuples) with unique names. From the logical point of view Issues contain information about the change of states on a system. Issues can be injected into an automation engine from external systems e.g. Monitoring or result from the execution of a Knowledge Item. By comparing an Issue with the Issue Condition of a Knowledge Item an automation engine decides which Knowledge Items are processed in which order. If multiple Knowledge Items can be applied to an Issue the KI with the more precisely defined IssueCondition is processed first.

- id: <http://www.purl.org/ogit/Automation/AutomationIssue>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: `ogit/Node`

**attributes**

- optional:
  - `ogit/Automation/deployStatus`
  - `ogit/Automation/isDeployed`
  - `ogit/Automation/issueFormalRepresentation`
  - `ogit/Automation/issueType`
  - `ogit/Automation/maxIdleTime`
  - `ogit/Automation/originNode`
  - `ogit/Automation/parentIssue`
  - `ogit/Automation/processingNode`
  - `ogit/Automation/processingTimestamp`
  - `ogit/Automation/suspendUntil`
  - `ogit/Automation/webhook`
  - `ogit/RL/state`
  - `ogit/RL/totalReward`
  - `ogit/creationTime`
  - `ogit/modificationTime`
  - `ogit/status`
  - `ogit/subject`

**incoming edges**

- `ogit/connects`  $\leq$  `ogit/Forum/Workflow`
- `ogit/contains`  $\leq$  `ogit/Forum/KnowledgeBundle`
- `ogit/contains`  $\leq$  `ogit/Forum/KnowledgeBundleHistory`
- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/SubTask`
- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/corresponds`  $\leq$  `ogit/Event`
- `ogit/creates`  $\leq$  `ogit/Forum/Profile`
- `ogit/relates`  $\leq$  `ogit/Forum/FeedEntry`
- `ogit/worksOn`  $\leq$  `ogit/Automation/KnowledgeItem`

**outgoing edges**

- [ogit/associates](#) => [ogit/Question](#)
- [ogit/contains](#) => [ogit/Task](#)
- [ogit/contains](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/contains](#) => [ogit/Automation/Item](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/generates](#) => [ogit/Automation/History](#)
- [ogit/relates](#) => [ogit/Knowledge/AcquisitionSession](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)
- [ogit/worksOn](#) => [ogit/Automation/MARSNode](#)

**1.1.0.25 ogit/Automation/MARSModel**

A collection of MARSNodes allows to address all MARS nodes belonging together in a certain way at once the relationship from MARSModel to MARSNode is 'ogit/contains'. examples are: All MARS nodes describing the IT of one data center, or all MARS nodes associated with the same contract. In such cases you would connect the other entity (data center, contract) with the MARSModel node instead creating links to any MARSNode being part of that model.

- id: <http://www.purl.org/ogit/Automation/MARSModel>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

**outgoing edges**

- [ogit/contains](#) => [ogit/Automation/MARSNode](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/implements](#) => [ogit/ServiceManagement/Order](#)

1.1.0.26 `ogit/Automation/KnowledgeItemAttribute`

Contains key-value pairs (together with mode) found inside Issue subitems.

- id: <http://www.purl.org/ogit/Automation/KnowledgeItemAttribute>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
  - [ogit/value](#)
- optional:
  - [ogit/mode](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/Item](#)

1.1.0.27 `ogit/Automation/Variable`

Variable definition to be used in KnowledgeItem

- id: <http://www.purl.org/ogit/Automation/Variable>
- valid-from: Mon Feb 09 00:00:00 UTC 2015
- creator: Kaushik Gondaliya
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/Automation/todo](#)
  - [ogit/\\_id](#)
  - [ogit/accessControl](#)
  - [ogit/creator](#)
  - [ogit/description](#)
  - [ogit/name](#)
- optional:
  - [ogit/\\_tags](#)



## 1.1.0.28 ogit/Automation/KnowledgePool

A grouping of ogit/Automation/KnowledgeItems and ogit/Automation/KnowledgeBundles for user or automation engine.

- id: <http://www.purl.org/ogit/Automation/KnowledgePool>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [druss@arago.de](mailto:druss@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)

## incoming edges

- [ogit/uses](#) <= [ogit/Automation/Configuration](#)
- [ogit/uses](#) <= [ogit/OSLC-crtv/ServiceInstance](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/contains](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/uses](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.29 ogit/Automation/Trigger

Trigger of a KI having a set of Subitems.

- id: <http://www.purl.org/ogit/Automation/Trigger>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/description](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/Item](#)

1.1.0.30 [ogit/ServiceManagement/Service](#)

A technology service item, which combined or not with other technology services can constitute a service offering ([ogit/ServiceManagement/Offering](#)).

- id: <http://www.purl.org/ogit/ServiceManagement/Service>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/description](#)
  - [ogit/name](#)
  - [ogit/uri](#)

## incoming edges

- [ogit/affects](#) <= [ogit/Automation/MARSNode](#)

1.1.0.31 [ogit/ServiceManagement/Ticket](#)

This entity defines any type of tickets. For specific behaviour of tickets, please check specific entities (e.g. [ogit/ServiceManagement/Incident](#)).

- id: <http://www.purl.org/ogit/ServiceManagement/Ticket>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/ticketId](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

1.1.0.32 [ogit/Cost/CostElement](#)

The cost element is a type of cost for an activity, an ordered service or a business unit or budget. There are 3 levels of cost elements: Top Level, Middle Level, Bottom Level. Between the different levels, for each cost element there could be two types of edges: Incoming and Outgoing. Each type of edge could have two types of connections↔: consistsOf and contributesTo. E.g. a cost element CPU consists in 30% of a HR cost element. The HR cost element contributes in 40% to the cost of the CPU cost element. This percentage values will then be saved in the entity Distribution, which will be connected to the cost element. For a general overview: see the NTO description on github.

- id: <http://www.purl.org/ogit/Cost/CostElement>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## incoming edges

- [ogit/associates](#) <= [ogit/Automation/MARSNode](#)
- [ogit/associates](#) <= [ogit/Automation/MARSNodeTemplate](#)

1.1.0.33 [ogit/Forum/FeedEntry](#)

A single entry in a newsfeed or other stream of items. Unlikely to contain many attributes of its own, more likely to link users with items describing the event.

- id: <http://www.purl.org/ogit/Forum/FeedEntry>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## outgoing edges

- [ogit/relates](#) => [ogit/Automation/AutomationIssue](#)

1.1.0.34 [ogit/Forum/Reply](#)

A response to a some other entity

- id: <http://www.purl.org/ogit/Forum/Reply>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/content](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.35 ogit/Forum/ShortId

A Reference to another Entity, used to track access via a specific channel/referrer. For example in TabTab, a Post has many shortIds which relate to different sharing methods, e.g. one for Twitter, one for Yammer, one for Email, etc... TabTab uses them as 'short urls' in the App and redirect the user to the correct content after tracking the access by the channel (*ogit/function*) attribute. The *ogit/function* attribute is used for this as the function of this shortId is to track a specific channel of inbound traffic. The ShortId can be used without this channel/referrer data, albeit to more limited use. The *ogit/id* attribute in this instance would be a short URL safe string.

- id: <http://www.purl.org/ogit/Forum/ShortId>
- valid-from: Thu Apr 23 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/function](#)

## outgoing edges

- [ogit/specifies](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.36 ogit/Automation/MARSNodeTemplate

Entity similar to MARSNode but used to create ogit/Automation/MARSTemplate's, which are used to define a vendor implementation template of an ordered service offering and to enable definition of cost elements (*ogit/Cost/Cost↔Element*) attached to it. Automation/MarsNode can not be reused for template reasons.

- id: <http://www.purl.org/ogit/Automation/MARSNodeTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/Automation/marsNodeFormalRepresentation](#)
- optional:
  - [ogit/Automation/marsNodeType](#)
  - [ogit/status](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Automation/MARSModelTemplate](#)
- [ogit/describes](#) <= [ogit/Asset](#)
- [ogit/relates](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/relates](#) <= [ogit/Automation/MARSNode](#)
- [ogit/relates](#) <= [ogit/Automation/MARSNodeTemplate](#)

**outgoing edges**

- [ogit/associates](#) => [ogit/Cost/CostElement](#)
- [ogit/relates](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/relates](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

**1.1.0.37 ogit/Automation/KIRanking**

A specific knowledge ranking configuration for HIRO.

- id: <http://www.purl.org/ogit/Automation/KIRanking>
- valid-from: Wed Apr 25 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/Automation/rankingType](#)
  - [ogit/Automation/weightMap](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/defaultRank](#)
  - [ogit/Automation/defaultSigma](#)
  - [ogit/Automation/rankMap](#)
  - [ogit/Automation/sendData](#)
  - [ogit/Automation/sendHistory](#)
  - [ogit/url](#)

**incoming edges**

- [ogit/uses](#) <= [ogit/Automation/Configuration](#)

## 1.1.0.38 ogit/Attachment

This entity defines a file attachment that an IT service, issue, task or a ticket might have. The attachment itself is not saved in GraphIT, instead it contains an external url link for it.

- id: <http://www.purl.org/ogit/Attachment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/accessControl](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/creator](#)
  - [ogit/id](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/lastUpdatedBy](#)
  - [ogit/name](#)
  - [ogit/size](#)
  - [ogit/sourceTable](#)
  - [ogit/type](#)
  - [ogit/url](#)

## outgoing edges

- [ogit/belongs](#) => [ogit/Automation/MARSNode](#)

## 1.1.0.39 ogit/Automation/MAID

The Monitoring-Automation Interface Description (MAID) is an abstract definition of

1. a timeseries to be monitored
2. desired normalizations of that timeseries
3. a set of condition->event mappings to apply to the timeseries or its normalizations

These time series definitions can be parameterized for more flexibility. Usually each MAID should describe exactly one raw timeseries. Depending of the type of monitoring or event management system connected to the engine, the corresponding adapter may choose to either supply the raw timeseries itself or directly create issues using the contained Event structures if it the raw data is not available.

The abstract MAID definitions are then mapped to the MARS model within the engine using so-called "Binding Blocks".

Thus MAID ensures that the arago Automation Engine is compatible to any monitoring system and can fully interact with them. By formalizing the interface the information verification process and definition of required add-ons to the monitoring systems becomes possible.

- id: <http://www.purl.org/ogit/Automation/MAID>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/Automation/maidFormalRepresentation](#)

#### outgoing edges

- [ogit/defines](#) => [ogit/Timeseries](#)
- [ogit/generates](#) => [ogit/Timeseries](#)

#### 1.1.0.40 ogit/ServiceManagement/Problem

This entity type defines a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/Problem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/problemStatus](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/rootCause](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/workAround](#)
  - [ogit/reportedAt](#)



## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

1.1.0.41 [ogit/Automation/ActionCapability](#)

Defines the capability of an action handler, such as remote execution via ssh.

- id: <http://www.purl.org/ogit/Automation/ActionCapability>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Automation/mandatoryParameters](#)
  - [ogit/description](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/optionalParameters](#)

## incoming edges

- [ogit/provides](#) <= [ogit/Automation/ActionApplicability](#)

1.1.0.42 [ogit/ConfigurationItem](#)

A configuration item.

- id: <http://www.purl.org/ogit/ConfigurationItem>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/Automation/governingContract](#)
  - [ogit/asset](#)
  - [ogit/assetTag](#)
  - [ogit/assignedAt](#)
  - [ogit/availability](#)
  - [ogit/businessCriticality](#)
  - [ogit/category](#)
  - [ogit/checkedInAt](#)
  - [ogit/checkedOutAt](#)
  - [ogit/ciType](#)
  - [ogit/class](#)
  - [ogit/comment](#)
  - [ogit/confidentiality](#)
  - [ogit/contact](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/deliveredAt](#)
  - [ogit/description](#)
  - [ogit/endOfWarranty](#)
  - [ogit/externalId](#)
  - [ogit/faultCount](#)
  - [ogit/impact](#)
  - [ogit/installStatus](#)
  - [ogit/installedAt](#)
  - [ogit/integrity](#)
  - [ogit/inventoryNumber](#)
  - [ogit/invoiceNumber](#)
  - [ogit/isCritical](#)
  - [ogit/isSupported](#)
  - [ogit/lastScannedAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/leaseContract](#)
  - [ogit/model](#)
  - [ogit/modelNumber](#)
  - [ogit/name](#)
  - [ogit/operationalStatus](#)
  - [ogit/orderedAt](#)
  - [ogit/pendingChange](#)
  - [ogit/priority](#)

- [ogit/productOrderNumber](#)
- [ogit/purchasedAt](#)
- [ogit/securityClass](#)
- [ogit/serviceContract](#)
- [ogit/shortDescription](#)
- [ogit/soxClass](#)
- [ogit/startedAt](#)
- [ogit/status](#)
- [ogit/subCategory](#)
- [ogit/subType](#)
- [ogit/type](#)
- [ogit/updateCount](#)
- [ogit/vendor](#)
- [ogit/version](#)

#### outgoing edges

- [ogit/corresponds](#) => [ogit/Automation/MARSNode](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

#### 1.1.0.43 [ogit/Automation/KnowledgeItem](#)

Formalized Knowledge stored in XML format. Serves as the building block for automation solutions.

A KnowledgeItem is a knowledge module, which is applied for execution of an issue. A KnowledgeItem checks therefor the information and decides if it will be executed. In that case, the KnowledgeItem executes operations, which serves the exploitation of information.

- id: <http://www.purl.org/ogit/Automation/KnowledgeItem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

#### attributes

- mandatory:
  - [ogit/Automation/knowledgeItemFormalRepresentation](#)
- optional:
  - [ogit/Automation/deployStatus](#)
  - [ogit/Automation/deployToEngine](#)
  - [ogit/Automation/isDeployed](#)
  - [ogit/Automation/knowledgeItemSyntaxVersion](#)
  - [ogit/Automation/knowledgeItemTier](#)
  - [ogit/accessControl](#)
  - [ogit/changeLog](#)
  - [ogit/creationTime](#)
  - [ogit/description](#)
  - [ogit/isValid](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

## incoming edges

- [ogit/Forum/downloads](#) <= [ogit/Forum/Profile](#)
- [ogit/Forum/rates](#) <= [ogit/Forum/Rating](#)
- [ogit/assignedTo](#) <= [ogit/Forum/Tag](#)
- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/connects](#) <= [ogit/Forum/KnowledgeBundle](#)
- [ogit/connects](#) <= [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/connects](#) <= [ogit/Forum/Post](#)
- [ogit/connects](#) <= [ogit/Forum/Reply](#)
- [ogit/connects](#) <= [ogit/Forum/WorkflowStep](#)
- [ogit/connects](#) <= [ogit/Comment](#)
- [ogit/contains](#) <= [ogit/Automation/KnowledgeBundle](#)
- [ogit/contains](#) <= [ogit/Automation/KnowledgePool](#)
- [ogit/contains](#) <= [ogit/Forum/KnowledgeBundle](#)
- [ogit/contains](#) <= [ogit/Forum/KnowledgeBundleHistory](#)
- [ogit/creates](#) <= [ogit/Forum/Profile](#)
- [ogit/defines](#) <= [ogit/Knowledge/AcquisitionSession](#)
- [ogit/derivesFrom](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/forks](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/relates](#) <= [ogit/Automation/MARSNode](#)
- [ogit/relates](#) <= [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/specifies](#) <= [ogit/Forum/ShortId](#)
- [ogit/uses](#) <= [ogit/Automation/KnowledgePool](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Forum/WorkflowStep](#)
- [ogit/connects](#) => [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/connects](#) => [ogit/Forum/Profile](#)
- [ogit/connects](#) => [ogit/Forum/Topic](#)
- [ogit/connects](#) => [ogit/Comment](#)
- [ogit/connects](#) => [ogit/Forum/Reply](#)
- [ogit/connects](#) => [ogit/Forum/KnowledgeBundle](#)
- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/connects](#) => [ogit/Forum/Post](#)
- [ogit/connects](#) => [ogit/Hyperlink](#)

- `ogit/contains` => `ogit/Automation/Trigger`
- `ogit/deployedTo` => `ogit/OSLC-crtv/ServiceInstance`
- `ogit/derivesFrom` => `ogit/Automation/KnowledgeItem`
- `ogit/forks` => `ogit/Automation/KnowledgeItem`
- `ogit/generates` => `ogit/Timeseries`
- `ogit/relates` => `ogit/Automation/MARSNodeTemplate`
- `ogit/solves` => `ogit/Task`
- `ogit/worksOn` => `ogit/Automation/AutomationIssue`

#### 1.1.0.44 `ogit/Hyperlink`

A representation of an (optionally) titled Hyperlink to some media. No protocol restrictions imposed.

- id: `http://www.purl.org/ogit/Hyperlink`
- valid-from: Tue Jun 09 00:00:00 UTC 2015
- creator: `cwalker@arago.de`
- scope: SGO
- parent: `ogit/Node`

##### attributes

- mandatory:
  - `ogit/url`
- optional:
  - `ogit/title`

##### incoming edges

- `ogit/connects` <= `ogit/Automation/KnowledgeItem`

#### 1.1.0.45 `ogit/Software/Application`

Represents any type of software application

- id: `http://www.purl.org/ogit/Software/Application`
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: `ogit/Node`

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)
  - [ogit/url](#)
  - [ogit/version](#)

## incoming edges

- [ogit/corresponds](#)  $\leq$  [ogit/Automation/MARSNode](#)

1.1.0.46 [ogit/Automation/KnowledgeBundle](#)

A grouping of [ogit/Automation/KnowledgeItems](#) into a package.

- id: <http://www.purl.org/ogit/Automation/KnowledgeBundle>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

## incoming edges

- [ogit/contains](#)  $\leq$  [ogit/Automation/KnowledgePool](#)
- [ogit/derivesFrom](#)  $\leq$  [ogit/Automation/KnowledgeBundle](#)

## outgoing edges

- [ogit/contains](#)  $\Rightarrow$  [ogit/Automation/KnowledgeItem](#)
- [ogit/derivesFrom](#)  $\Rightarrow$  [ogit/Automation/KnowledgeBundle](#)

## 1.1.0.47 ogit/Data/Log

This entity defines a log. It used to store a sequence of log records

- id: <http://www.purl.org/ogit/Data/Log>
- valid-from: Wed Jun 14 00:00:00 UTC 2017
- creator: [stravlos@arago.de](mailto:stravlos@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/Data/timeToLive](#)
  - [ogit/description](#)
  - [ogit/name](#)

## incoming edges

- [ogit/generates](#) <= [ogit/Automation/MARSNode](#)

## 1.1.0.48 ogit/Network/NetworkInterface

Logical or physical network interface.

- id: <http://www.purl.org/ogit/Network/NetworkInterface>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/id](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/MARSNode](#)

#### 1.1.0.49 ogit/ServiceManagement/Report

Reporting about IT service delivery

- id: <http://www.purl.org/ogit/ServiceManagement/Report>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

##### attributes

- optional:
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/version](#)

##### outgoing edges

- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

#### 1.1.0.50 ogit/ServiceManagement/Offering

This is a concrete offering from a vendor including one or more combined services from a catalog/collection/offering book.

- id: <http://www.purl.org/ogit/ServiceManagement/Offering>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

##### attributes

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/allowedForNewBusiness](#)
  - [ogit/capacityAvailable](#)
  - [ogit/category](#)
  - [ogit/currency](#)
  - [ogit/description](#)
  - [ogit/expirationDate](#)
  - [ogit/market](#)
  - [ogit/serialNumber](#)
  - [ogit/validFrom](#)



## outgoing edges

- [ogit/specifies](#) => [ogit/Automation/MARSModelTemplate](#)

1.1.0.51 [ogit/Automation/MARSModelTemplate](#)

Represents a set of interconnected MARSNodes, which will be used to define a vendor implementation template of an ordered service offering.

- id: <http://www.purl.org/ogit/Automation/MARSModelTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

## incoming edges

- [ogit/plans](#) <= [ogit/Cost/PlanningTemplate](#)
- [ogit/specifies](#) <= [ogit/ServiceManagement/Offering](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/MARSNodeTemplate](#)

1.1.0.52 [ogit/Environment](#)

An environment describes the overall structure a user, computer or program operates in.

- id: <http://www.purl.org/ogit/Environment>
- valid-from: Thu Feb 08 00:00:00 UTC 2018
- creator: Viktor Voss
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/name](#)

**outgoing edges**

- [ogit/consistsOf](#) => [ogit/Automation/MARSNode](#)

**1.1.0.53 ogit/MARS/Resource**

Vertices of this type are the 'R'-nodes in the MARS model. 'R' stands for 'Resource' and those nodes form the second highest layer in the A-R-S-M layer model. A 'Resource' node groups 'Software' nodes. It's up to the user whether this grouping is used to group software instance of the same software (e.g. all instances of an Oracle RAC) or software instance of different softwares (functional grouping, e.g. 'persistence')

- id: <http://www.purl.org/ogit/MARS/Resource>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/MARS/Resource/class](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/automationState](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/serviceStatus](#)
  - [ogit/url](#)

**outgoing edges**

- [ogit/uses](#) => [ogit/Automation/Configuration](#)

## 1.1.0.54 ogit/Location

A place where some service is offered or requested. In many cases this will be related to an address of an Organization. Similar to <http://purl.org/goodrelations/v1#Location>

- id: <http://www.purl.org/ogit/Location>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

## incoming edges

- [ogit/locatedIn](#) <= [ogit/Automation/MARSNode](#)

## 1.1.0.55 ogit/Automation/History

IssueHistoryEntry corresponds to element <HistoryEntry> from IssueOutputSchema.

- id: <http://www.purl.org/ogit/Automation/History>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/Automation/affectedNodeid](#)
  - [ogit/Automation/command](#)
  - [ogit/Automation/knowledgeItemId](#)
  - [ogit/Automation/logLevel](#)
  - [ogit/message](#)
  - [ogit/timestamp](#)

## incoming edges

- [ogit/generates](#) <= [ogit/Automation/AutomationIssue](#)

## outgoing edges

- [ogit/generates](#) => [ogit/Timeseries](#)

## 1.1.0.56 ogit/Asset

Assets represent a physical hold of a value and are situated in a location. Assets could correspond to one or more ogit/Automation/MARSNode's and can be physical or virtual. Assets of a Service Provider include anything that could contribute to the delivery of a Service. Assets can have a type, for example: Management, Organisation, Process, Knowledge, People, Information, Applications, Infrastructure, Financial Capital.

- id: <http://www.purl.org/ogit/Asset>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/id](#)
  - [ogit/name](#)

## outgoing edges

- [ogit/describes](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/describes](#) => [ogit/Automation/MARSNode](#)

## 1.1.0.57 ogit/Event

This entity defines any type of event records, e.g. ITSM/produced by event management systems, Business Process etc.

- id: <http://www.purl.org/ogit/Event>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/acknowledgeState](#)
  - [ogit/category](#)
  - [ogit/certainty](#)
  - [ogit/description](#)
  - [ogit/expiresAt](#)
  - [ogit/firstOccurredAt](#)
  - [ogit/impact](#)
  - [ogit/instance](#)
  - [ogit/isRoot](#)
  - [ogit/lastClearedAt](#)
  - [ogit/lastOccurredAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/maintenanceState](#)
  - [ogit/occurenceCount](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/resource](#)
  - [ogit/severity](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/summary](#)
  - [ogit/type](#)

**outgoing edges**

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

**1.1.0.58 ogit/Forum/Profile**

A User's persona within a forum. Linked to an [ogit/Identity](#) but separate, the Profile is the root node for most operations with a Forum.

- id: <http://www.purl.org/ogit/Forum/Profile>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/Forum/username](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/Forum/downloads](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/creates](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/creates](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.59 ogit/Software/SoftwareComponent**

Any type of Software Component

- id: <http://www.purl.org/ogit/Software/SoftwareComponent>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/id](#)

**outgoing edges**

- [ogit/uses](#) => [ogit/Automation/MARSNode](#)

**1.1.0.60 ogit/Forum/Post**

A Post is an online publication. Could be a blog post, or a posting on a forum/messageboard.

- id: <http://www.purl.org/ogit/Forum/Post>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/content](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.61 [ogit/Automation/DynamicEngineData](#)**

Dynamic information exists within the arago Automation Engine (aAE) used to store volatile data about current state of MARSNode or AutomationIssue.

- id: <http://www.purl.org/ogit/Automation/DynamicEngineData>
- valid-from: Thu Jun 25 00:00:00 UTC 2015
- creator: Mirosław Glusiuk
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/creationTime](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) <= [ogit/Automation/DynamicEngineData](#)
- [ogit/contains](#) <= [ogit/Automation/MARSNode](#)

**outgoing edges**

- [ogit/contains](#) => [ogit/Automation/DynamicEngineData](#)

## 1.1.0.62 ogit/Forum/Tag

A Tag used to categorise content. The required `key` attribute should be used as the unique identifier, and the `name` considered a display name.

- id: <http://www.purl.org/ogit/Forum/Tag>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)

## outgoing edges

- [ogit/assignedTo](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.63 ogit/Automation/ActionHandler

ActionHandler entity, that is connected to Configuration, one or more Capability, and Applicability nodes.

- id: <http://www.purl.org/ogit/Automation/ActionHandler>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/Automation/optionalParameters](#)

## incoming edges

- [ogit/uses](#) <= [ogit/Automation/Configuration](#)



## outgoing edges

- `ogit/provides => ogit/Automation/ActionApplicability`

## 1.1.0.64 ogit/Automation/Configuration

Configuration node to dynamically connect Knowledge Pools or Rankings to a HIRO installation.

- id: `http://www.purl.org/ogit/Automation/Configuration`
- valid-from: Wed Apr 25 00:00:00 UTC 2018
- creator: `cy@arago.de`
- scope: NTO
- parent: ogit/Node

## incoming edges

- `ogit/uses <= ogit/Automation/MARSNode`
- `ogit/uses <= ogit/MARS/Resource`

## outgoing edges

- `ogit/uses => ogit/Automation/ActionHandler`
- `ogit/uses => ogit/Automation/KIRanking`
- `ogit/uses => ogit/Automation/KnowledgePool`

## 1.1.0.65 ogit/License

This entity type allows to store license information or actual licenses.

- id: `http://www.purl.org/ogit/License`
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/createdAt](#)
  - [ogit/creator](#)
  - [ogit/deadline](#)
  - [ogit/expirationDate](#)
  - [ogit/id](#)
  - [ogit/licenseKey](#)
  - [ogit/licenseType](#)
  - [ogit/subject](#)
  - [ogit/validFrom](#)
  - [ogit/validTo](#)

**incoming edges**

- [ogit/relates](#) <= [ogit/Automation/MARSNode](#)

**1.1.0.66 ogit/Timeseries**

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

- id: <http://www.purl.org/ogit/Timeseries>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/instance](#)
  - [ogit/isMutable](#)
  - [ogit/name](#)
  - [ogit/unit](#)

**incoming edges**

- [ogit/defines](#) <= [ogit/Automation/MAID](#)
- [ogit/generates](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/generates](#) <= [ogit/Automation/History](#)
- [ogit/generates](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/generates](#) <= [ogit/Automation/MAID](#)
- [ogit/generates](#) <= [ogit/Automation/MARSModel](#)
- [ogit/generates](#) <= [ogit/Automation/MARSNode](#)

## 1.2 Verbs

### 1.2.0.1 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

- id: <http://www.purl.org/ogit/contains>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Task](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/Item](#)
- [ogit/Automation/DynamicEngineData](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/Item](#) => [ogit/Automation/KnowledgeItemAttribute](#)
- [ogit/Automation/Item](#) => [ogit/Automation/Item](#)
- [ogit/Automation/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/Trigger](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSModel](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSModelTemplate](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Network/NetworkInterface](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/Trigger](#) => [ogit/Automation/Item](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/KnowledgeBundleHistory](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeBundleHistory](#) => [ogit/Automation/KnowledgeItem](#)

### 1.2.0.2 ogit/defines

General relationship indicating that some entity defines some other.

- id: <http://www.purl.org/ogit/defines>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/MAID](#) => [ogit/Timeseries](#)
- [ogit/Knowledge/AcquisitionSession](#) => [ogit/Automation/KnowledgeItem](#)

**1.2.0.3 ogit/hosts**

verb which shows that an entity is hosted in another entity.

- id: <http://www.purl.org/ogit/hosts>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.4 ogit/runsOn**

Shows if a certain component is running on another component.

- id: <http://www.purl.org/ogit/runsOn>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.5 ogit/worksOn**

Indicates if one entity is currently working on another entity.

- id: <http://www.purl.org/ogit/worksOn>
- valid-from: Wed Jun 24 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/AutomationIssue](#)

### 1.2.0.6 ogit/assignedTo

Verb expressing which entity could be assigned to which another entity.

- id: <http://www.purl.org/ogit/assignedTo>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Person](#)
- [ogit/Forum/Tag](#) => [ogit/Automation/KnowledgeItem](#)

### 1.2.0.7 ogit/generates

Verb indicating if an entity generates another entity.

- id: <http://www.purl.org/ogit/generates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Timeseries](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/History](#)
- [ogit/Automation/History](#) => [ogit/Timeseries](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Timeseries](#)
- [ogit/Automation/MAID](#) => [ogit/Timeseries](#)
- [ogit/Automation/MARSModel](#) => [ogit/Timeseries](#)
- [ogit/Automation/MARSNode](#) => [ogit/Data/Log](#)
- [ogit/Automation/MARSNode](#) => [ogit/Timeseries](#)

### 1.2.0.8 ogit/specifies

One entity "specifies" another.

- id: <http://www.purl.org/ogit/specifies>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Forum/ShortId](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/Automation/MARSModelTemplate](#)

**1.2.0.9 ogit/solves**

One entity can "solve" another.

- id: <http://www.purl.org/ogit/solves>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/KnowledgeItem](#) => [ogit/Task](#)

**1.2.0.10 ogit/forks**

General relationship indicating that some entity forks some other, assuming the same type.

- id: <http://www.purl.org/ogit/forks>
- valid-from: Tue Jun 12 00:00:00 UTC 2018
- creator: Vitaly Teremasov

**Allowed Connection**

- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)

**1.2.0.11 ogit/derivesFrom**

The derivesFrom of a version. This verb could be generated internally.

- id: <http://www.purl.org/ogit/derivesFrom>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

**Allowed Connection**

- [ogit/Automation/KnowledgeBundle](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.12 ogit/describes

This relationship allows to associate additional information with an entity. The "described" node can have many "describing" nodes.

- id: <http://www.purl.org/ogit/describes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Asset](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Asset](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.13 ogit/creates

Indicates if one entity creates another one.

- id: <http://www.purl.org/ogit/creates>
- valid-from: Tue May 19 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Forum/Profile](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/Profile](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.14 ogit/associates

Verb indicating if an entity associates with another entity.

- id: <http://www.purl.org/ogit/associates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Question](#)
- [ogit/Automation/MARSNode](#) => [ogit/Cost/CostElement](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Cost/CostElement](#)

## 1.2.0.15 ogit/connects

Verb showing that an entity is physically/virtually connecting to another entity.

- id: <http://www.purl.org/ogit/connects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/WorkflowStep](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Profile](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Topic](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Comment](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Reply](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/KnowledgeBundle](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Post](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Hyperlink](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/KnowledgeItemHistory](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Post](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Reply](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Workflow](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/WorkflowStep](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Comment](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.16 ogit/deployedTo

Verb associates if something was deployed to another entity/component.

- id: <http://www.purl.org/ogit/deployedTo>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Automation/KnowledgeItem](#) => [ogit/OSLC-crtv/ServiceInstance](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)



## 1.2.0.17 ogit/locatedIn

indicate that something has its place somewhere

- id: <http://www.purl.org/ogit/locatedIn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Location](#)
- [ogit/Automation/MARSNode](#) => [ogit/Region](#)

## 1.2.0.18 ogit/versions

The version of a node. This verb is generated internally.

- id: <http://www.purl.org/ogit/versions>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

## Allowed Connection

- [ogit/VersioningData](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/VersioningData](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.19 ogit/corresponds

Indicates whether one entity could correspond to a more general one, e.g. an Incident could correspond to a Ticket

- id: <http://www.purl.org/ogit/corresponds>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Software/Application](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ConfigurationItem](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/AutomationIssue](#)

## 1.2.0.20 ogit/Forum/rates

This verb represents the `Rating` between two nodes

- id: <http://www.purl.org/ogit/Forum/rates>
- valid-from: Wed Aug 12 00:00:00 UTC 2015
- creator: [bneal@arago.de](mailto:bneal@arago.de)

## Allowed Connection

- [ogit/Forum/Rating](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.21 ogit/affects

The relationship indicates that one entity affects some other entity.

- id: <http://www.purl.org/ogit/affects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/ServiceManagement/Service](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.22 ogit/OSLC-crtv/runsOn

The ComputerSystem this SoftwareServer instance is running on.

- id: <http://www.purl.org/ogit/OSLC-crtv/runsOn>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

**Allowed Connection**

- [ogit/OSLC-crtv/ServiceInstance](#) => [ogit/Automation/MARSNode](#)

**1.2.0.23 ogit/implements**

Defines that an entity provides the implementation for another entity.

- id: <http://www.purl.org/ogit/implements>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/MARSModel](#) => [ogit/ServiceManagement/Order](#)

**1.2.0.24 ogit/provides**

Verb showing if one entity provides something to another.

- id: <http://www.purl.org/ogit/provides>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/ActionApplicability](#) => [ogit/Automation/ActionCapability](#)
- [ogit/Automation/ActionHandler](#) => [ogit/Automation/ActionApplicability](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.25 ogit/owns**

This relationship indicates that one entity owns some other.

- id: <http://www.purl.org/ogit/owns>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Organization](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.26 ogit/dependsOn

This relationship indicates that some entity is depending on some other. E.g. machine hosts software.

- id: <http://www.purl.org/ogit/dependsOn>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.27 ogit/belongs

Verb showing if one entity belongs to another.

- id: <http://www.purl.org/ogit/belongs>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Attachment](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.28 ogit/uses

This relationship indicates that some entity is used by some other.

- id: <http://www.purl.org/ogit/uses>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/Configuration](#) => [ogit/Automation/ActionHandler](#)
- [ogit/Automation/Configuration](#) => [ogit/Automation/KIRanking](#)
- [ogit/Automation/Configuration](#) => [ogit/Automation/KnowledgePool](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/Configuration](#)
- [ogit/MARS/Resource](#) => [ogit/Automation/Configuration](#)
- [ogit/OSLC-crtv/ServiceInstance](#) => [ogit/Automation/KnowledgePool](#)
- [ogit/Software/SoftwareComponent](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.29 ogit/plans

Verb showing how one entity plans/predicts on the content of another entity

- id: <http://www.purl.org/ogit/plans>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Cost/PlanningTemplate](#) => [ogit/Automation/MARSModelTemplate](#)

## 1.2.0.30 ogit/reportedOn

Indicates where a failure situation was initially observed. In case an incident record is created from an event management system this relationship points to the entity that represents the monitored device/endpoint. We call it "reportedOn" instead of "observedOn" to account for the close relation to "reportedAt", "reportedBy"

- id: <http://www.purl.org/ogit/reportedOn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.31 ogit/Forum/downloads

This verb represents that a "User" has downloaded a given Bundle

- id: <http://www.purl.org/ogit/Forum/downloads>
- valid-from: Thu Feb 25 00:00:00 UTC 2016
- creator: [bneal@arago.de](mailto:bneal@arago.de)

## Allowed Connection

- [ogit/Forum/Profile](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.32 ogit/consistsOf

It shows, that the destination entity is a non-exclusive part of the source.

- id: <http://www.purl.org/ogit/consistsOf>
- valid-from: Tue Feb 13 00:00:00 UTC 2018
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Environment](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.33 ogit/relates

General relationship indicating that one entity is related to another one.

- id: <http://www.purl.org/ogit/relates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Knowledge/AcquisitionSession](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSNode](#) => [ogit/License](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Automation/MARSNode](#)
- [ogit/Forum/FeedEntry](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeItemHistory](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Report](#) => [ogit/Automation/MARSNode](#)
- [ogit/ConfigurationItem](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/MARSNode](#)

## 1.3 Attributes

### 1.3.0.1 ogit/\_modified-by

[internally generated] The id of the identity who did the modification

- id: [http://www.purl.org/ogit/\\_modified-by](http://www.purl.org/ogit/_modified-by)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

### 1.3.0.2 ogit/Automation/serviceType

Contains the Type of a service.

- id: <http://www.purl.org/ogit/Automation/serviceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

### 1.3.0.3 ogit/ciType

Type of a configuration item. For example: VM, Server or Device.

- id: <http://www.purl.org/ogit/ciType>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.4 ogit/reviewedAt

Defines the time when something was actually reviewed. The values can combin date and time with time zone designator according to ISO 8601. Reviewed time is used in incident management.

- id: <http://www.purl.org/ogit/reviewedAt>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.5 ogit/Automation/serialNumber

Contains a the serial number of a device/component.

- id: <http://www.purl.org/ogit/Automation/serialNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.6 ogit/Automation/servletName

Contains the name if the servlet.

- id: <http://www.purl.org/ogit/Automation/servletName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



#### 1.3.0.7 `ogit/Automation/deployToEngine`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Boolean value, true if an automation Knowledge Item can deploy into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/deployToEngine>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Forum/KnowledgeItemHistory](#)
- optional:
  - [ogit/Automation/KnowledgeItem](#)

#### 1.3.0.8 `ogit/Automation/cpuCoreCount`

Contains the number of cpu cores.

- id: <http://www.purl.org/ogit/Automation/cpuCoreCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.9 `ogit/Automation/serviceId`

Contains the Id of the service.

- id: <http://www.purl.org/ogit/Automation/serviceId>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.10 ogit/manufacturere

Manufacturer of a device or component.

- id: <http://www.purl.org/ogit/manufacture>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.11 ogit/ServiceManagement/testPlan

Contains a test plan used in change management to define how a successful change implementation can be verified.

- id: <http://www.purl.org/ogit/ServiceManagement/testPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.12 ogit/Data/timeToLive

Defines how many seconds data will be kept before expire.

- id: <http://www.purl.org/ogit/Data/timeToLive>
- valid-from: Fri Feb 09 00:00:00 UTC 2018
- creator: [mglusiuk@arago.de](mailto:mglusiuk@arago.de)

used

- optional:
  - [ogit/Data/Log](#)

#### 1.3.0.13 ogit/certainty

Defines the certainty of an event

- id: <http://www.purl.org/ogit/certainty>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

#### 1.3.0.14 ogit/currency

A currency code, possibly according to ISO 4217.

- id: <http://www.purl.org/ogit/currency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

#### 1.3.0.15 ogit/category

Used to categorize things.

- id: <http://www.purl.org/ogit/category>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Offering](#)

## 1.3.0.16 ogit/\_id

[internally generated] The unique identifier. The id is automatically generated by GraphIT.

- id: [http://www.purl.org/ogit/\\_id](http://www.purl.org/ogit/_id)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/Variable](#)

## 1.3.0.17 ogit/comment

Contains a comment.

- id: <http://www.purl.org/ogit/comment>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.18 ogit/Automation/osVersion

Version of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.19 ogit/assignedAt**

Defines the time when something was actually assigned to a person/organization for example. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/assignedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.20 ogit/endOfWarranty**

End of warranty phase of a component

- id: <http://www.purl.org/ogit/endOfWarranty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)

**1.3.0.21 ogit/postalCode**

The postal code. For example, 60433.

- id: <http://www.purl.org/ogit/postalCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.22 `ogit/Automation/buildType`

Contains the build type of a component.

- id: <http://www.purl.org/ogit/Automation/buildType>
- valid-from: Wed Aug 19 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.23 `ogit/Automation/cpuManufacturer`

Contains the manufacturer of the cpu of a device.

- id: <http://www.purl.org/ogit/Automation/cpuManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.24 `ogit/Automation/virtualMachineName`

Contains the name of the virtual machine.

- id: <http://www.purl.org/ogit/Automation/virtualMachineName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.25 `ogit/productOrderNumber`

An integer, which displays the order number of a product.

- id: <http://www.purl.org/ogit/productOrderNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.26 `ogit/Automation/maidFormalRepresentation`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Contains a MAID in XML representation defined by MAIDSchema.

- id: <http://www.purl.org/ogit/Automation/maidFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/MAID](#)

#### 1.3.0.27 `ogit/Automation/environmentFilter`

Contains the specification/filtering of an environment.

- id: <http://www.purl.org/ogit/Automation/environmentFilter>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran

used

- mandatory:
  - [ogit/Automation/ActionApplicability](#)

**1.3.0.28** ogit/RL/totalReward

Specifies the total reward of the issue for Reinforcement Learning.

- id: <http://www.purl.org/ogit/RL/totalReward>
- valid-from: Thu Jan 02 00:00:00 UTC 2020
- creator: Rudi Schäfer

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.29** ogit/checkedOutAt

Defines the time when something was actually checked out. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedOutAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.30** ogit/email

An email address.

- id: <http://www.purl.org/ogit/email>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)



#### 1.3.0.31 `ogit/Automation/moveToProductionAt`

Defines the time when something was actually moved to production. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/Automation/moveToProductionAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.32 `ogit/ServiceManagement/resolvedAt`

Datetime indicating when a ticket was resolved. Can be used for incident or problem tickets when it is necessary to distinguish between the ticket resolving and ticket closure (`closedAt`). The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/resolvedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

#### 1.3.0.33 `ogit/urgency`

Contains the urgency which could be applied to a ticket, incident etc.

- id: <http://www.purl.org/ogit/urgency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.34 ogit/deliveredAt**

Defines a point in time when a component/device was actually delivered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/deliveredAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.35 ogit/Automation/osServicePack**

Contains the service pack for the operating system.

- id: <http://www.purl.org/ogit/Automation/osServicePack>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.36 ogit/Automation/rankingType**

Contains the type of KI ranking algorithm.

- id: <http://www.purl.org/ogit/Automation/rankingType>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- mandatory:
  - [ogit/Automation/KIRanking](#)

**1.3.0.37 ogit/alternativeName**

Alternative name of something. In context of a Person this can be the full name or an alias/nick name.

- id: <http://www.purl.org/ogit/alternativeName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.38 ogit/isCritical**

This field specifies if the CI is critical for day-to-day operation, such as an E-mail server or RDBMS server. If you open an incident on a critical CI, the incident indicates that this is a critical CI. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isCritical>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.39 ogit/asset**

This field represents an asset (device or component).

- id: <http://www.purl.org/ogit/asset>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.40 ogit/Automation/portNumberListener

Contains a port number listener.

- id: <http://www.purl.org/ogit/Automation/portNumberListener>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.41 ogit/function

Attribute used to specify a function that some entity does/provides. This is more specific than 'description'. Should contain a short string. At this level of specification it is still a free from string. However, unlike 'description', it is expected to contain some list of fixed values.

- id: <http://www.purl.org/ogit/function>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Forum/ShortId](#)
  - [ogit/Organization](#)

#### 1.3.0.42 ogit/positionNumber

An integer, which displays a position of numbering.

- id: <http://www.purl.org/ogit/positionNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Task](#)

**1.3.0.43** ogit/ServiceManagement/customer

The customer related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/customer>
- valid-from: Fri Jul 03 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.44** ogit/isValid

Boolean value, true if the object is valid.

- id: <http://www.purl.org/ogit/isValid>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.45** ogit/Automation/memory

Contains a the total physical memory (RAM) in MB.

- id: <http://www.purl.org/ogit/Automation/memory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.46 ogit/integrity**

A security principle that ensures data and Configuration Items are only modified by authorized personnel and Activities

- id: <http://www.purl.org/ogit/integrity>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.47 ogit/Automation/companyName**

Contains the company name of a component.

- id: <http://www.purl.org/ogit/Automation/companyName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.48 ogit/ServiceManagement/scheduledStartAt**

Defines a point in time when the work on a change is planned/scheduled to start. This date time is usually defined during change planning and/or approval. This datetime is set by change coordinator (e.g it is planned to be done at 7:30PM) The values must be combined date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.49 ogit/Automation/suspendUntil**

Contains the timestamp until which entity should not be processed by HIRO.

- id: <http://www.purl.org/ogit/Automation/suspendUntil>
- valid-from: Sat Jun 01 00:00:00 UTC 2019
- creator: [cy@arago.co](mailto:cy@arago.co)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.50 ogit/country**

Name of a country.

- id: <http://www.purl.org/ogit/country>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

**1.3.0.51 ogit/businessCategory**

The category of a business.

- id: <http://www.purl.org/ogit/businessCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.52 ogit/Automation/middlewareType

Contains information about the type of middleware. For example it database middleware, application server middleware or a message-oriented middleware.

- id: <http://www.purl.org/ogit/Automation/middlewareType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.53 ogit/Automation/serviceName

Contains the name of a service.

- id: <http://www.purl.org/ogit/Automation/serviceName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.54 ogit/project

Project name, for which the entity is being used.

- id: <http://www.purl.org/ogit/project>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)



**1.3.0.55** `ogit/Automation/licenseAvailability`

The availability of the license of a component.

- id: <http://www.purl.org/ogit/Automation/licenseAvailability>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.56** `ogit/question`

Contains a question.

- id: <http://www.purl.org/ogit/question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)
  - [ogit/Task](#)

**1.3.0.57** `ogit/maintenanceState`

Defines the state of maintenance.

- id: <http://www.purl.org/ogit/maintenanceState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.58** `ogit/_creator`

[internally generated] The id of the identity who created the node or edge

- id: [http://www.purl.org/ogit/\\_creator](http://www.purl.org/ogit/_creator)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.59** `ogit/notification`

A notification.

- id: <http://www.purl.org/ogit/notification>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.60** `ogit/changeLog`

String value describing a changelog of an entity.

- id: <http://www.purl.org/ogit/changeLog>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.61** `ogit/ServiceManagement/externalTicketId`

If a ticket was imported/duplicated from another system this attribute will define the ticket ID from the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.62** `ogit/sourceId`

The Id of the source system.

- id: <http://www.purl.org/ogit/sourceId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.63** `ogit/url`

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/url>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Hyperlink](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/KIRanking](#)
  - [ogit/MARS/Resource](#)
  - [ogit/Software/Application](#)

#### 1.3.0.64 [ogit/licenseKey](#)

A string containing a license key.

- id: <http://www.purl.org/ogit/licenseKey>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)

#### 1.3.0.65 [ogit/uri](#)

Unified resource identifier

- id: <http://www.purl.org/ogit/uri>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Service](#)

**1.3.0.66** ogit/purchasedAt

Defines a point in time when a component/device was actually purchased. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/purchasedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.67** ogit/Automation/cpuCount

An integer which shows the number of cps of a component.

- id: <http://www.purl.org/ogit/Automation/cpuCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.68** ogit/timestamp

Contains the timestamp in milliseconds.

- id: <http://www.purl.org/ogit/timestamp>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.69** `ogit/Automation/databaseSchema`

Contains information about the database schema. The schema is the skeleton structure that represents the logical view of the entire database

- id: <http://www.purl.org/ogit/Automation/databaseSchema>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.70** `ogit/mobilePhone`

A mobile phone number.

- id: <http://www.purl.org/ogit/mobilePhone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.71** `ogit/Automation/additionalMacAddress`

Contains an additional MAC address

- id: <http://www.purl.org/ogit/Automation/additionalMacAddress>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.72 ogit/severity

Stores a severity. E.g. Some event management systems might store a severity field.

- id: <http://www.purl.org/ogit/severity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)

#### 1.3.0.73 ogit/Automation/knowledgeItemTier

Numeric value describing KnowledgeItem Tier.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemTier>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

#### 1.3.0.74 ogit/connectorId

The Id of the connector.

- id: <http://www.purl.org/ogit/connectorId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.75** `ogit/Automation/dataClassification`

Data classification of a component.

- id: <http://www.purl.org/ogit/Automation/dataClassification>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.76** `ogit/Automation/firmwareVersion`

Version of the firmware.

- id: <http://www.purl.org/ogit/Automation/firmwareVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.77** `ogit/effort`

Defines how much time was spent on the actual work for a change, task, or similar entity. The values is expected to be in format HH:MM, e.g. 1:00 for 1 hour effort.

- id: <http://www.purl.org/ogit/effort>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)



**1.3.0.78 ogit/startedAt**

Defines a point in time when the work on a change, task, or similar entity was actually started. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/startedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.79 ogit/value**

Contains a value of a key / value pair.

- id: <http://www.purl.org/ogit/value>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/KnowledgeItemAttribute](#)
  - [ogit/Forum/Rating](#)

**1.3.0.80 ogit/assetTag**

This field specifies the asset tag number/code.

- id: <http://www.purl.org/ogit/assetTag>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.81 ogit/ipAddress**

The IP address of a component/hardware device.

- id: <http://www.purl.org/ogit/ipAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.82 ogit/licenseType**

Type of the License e.g. community/enterprise.

- id: <http://www.purl.org/ogit/licenseType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)

**1.3.0.83 ogit/unit**

Unit of measurement of some value.

- id: <http://www.purl.org/ogit/unit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Timeseries](#)

**1.3.0.84 ogit/Automation/todo**

Boolean value, true if variable is todo variable.

- id: <http://www.purl.org/ogit/Automation/todo>
- valid-from: Mon Feb 09 00:00:00 UTC 2015
- creator: Kaushik Gondaliya

used

- mandatory:
  - [ogit/Automation/Variable](#)

**1.3.0.85 ogit/Automation/knowledgeItemFormalRepresentation**

Contains an automation Knowledge Item (KI) in XML representation defined by KiSchema.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.86 ogit/Automation/installCount**

Contains an integer. This integer can be adjust automatically when software is added to or deleted from configuration items (CIs).

- id: <http://www.purl.org/ogit/Automation/installCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.87** `ogit/installedAt`

Defines a point in time when a component/device was actually installed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/installedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.88** `ogit/Automation/knowledgeItemId`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Contains a KnowledgeItemID in string representation.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.89** `ogit/Automation/marsNodeFormalRepresentation`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Contains MARS in XML representation defined by MARSSchema2013.

- id: <http://www.purl.org/ogit/Automation/marsNodeFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/MARSNodeTemplate](#)
- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.90 ogit/updateCount**

Contains the count of the records updated.

- id: <http://www.purl.org/ogit/updateCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.91 ogit/Knowledge/archived**

Boolean indicating whether the session is archived or not

- id: <http://www.purl.org/ogit/Knowledge/archived>
- valid-from: Fri Jul 26 00:00:00 UTC 2019
- creator: Vitaly Teremasov

used

- optional:
  - [ogit/Knowledge/AcquisitionSession](#)

**1.3.0.92 ogit/installStatus**

An installation status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/installStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

1.3.0.93 `ogit/city`

Name of a city.

- id: <http://www.purl.org/ogit/city>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

1.3.0.94 `ogit/Automation/systemClass`

Contains the class of the system.

- id: <http://www.purl.org/ogit/Automation/systemClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

1.3.0.95 `ogit/Automation/diskCount`

An integer which shows the number of disks of a component.

- id: <http://www.purl.org/ogit/Automation/diskCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.96 ogit/mode**

Contains the type of filter for the value contained in the entity "Attribute" and corresponding to one of the following strings: eq, ne, lt, le, gt, ge, exists, notexists, string, notstring, regex, notregex

- id: <http://www.purl.org/ogit/mode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItemAttribute](#)

**1.3.0.97 ogit/Automation/automationState**

A value of 'Manual' will mark a node as not eligible for Issue processing

- id: <http://www.purl.org/ogit/Automation/automationState>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Resource](#)

**1.3.0.98 ogit/ServiceManagement/incidentStatus**

Defines the status of an incident record/ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/incidentStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

#### 1.3.0.99 ogit/taskLog

In cases where the log for a Task is maintained as a single string it will be stored in taskLog. In all other case consider using ogit/Timeseries.

- id: <http://www.purl.org/ogit/taskLog>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

#### 1.3.0.100 ogit/status

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems usefual in the application's semantic context.

- id: <http://www.purl.org/ogit/status>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNodeTemplate](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)
  - [ogit/Question](#)
  - [ogit/Task](#)

#### 1.3.0.101 ogit/createdAt

Defines a point in time when a ticket/incident/event etc was created or recorded.

- id: <http://www.purl.org/ogit/createdAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/License](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)



**1.3.0.102** `ogit/ServiceManagement/workAround`

Defines a work around for a known problem until a permanent solution is defined.

- id: <http://www.purl.org/ogit/ServiceManagement/workAround>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.103** `ogit/ServiceManagement/rootCause`

Root cause for example of a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/rootCause>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.104** `ogit/Forum/username`

A unique username for a member of a Forum

- id: <http://www.purl.org/ogit/Forum/username>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: Chris Walker

used

- mandatory:
  - [ogit/Forum/Profile](#)

## 1.3.0.105 ogit/model

Model of a device.

- id: <http://www.purl.org/ogit/model>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.106 ogit/Automation/domain

Contains the domain name.

- id: <http://www.purl.org/ogit/Automation/domain>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.107 ogit/Automation/lifecycle

Contains the lifecycle state of a MARSNode. If value is 'decommissioned' this node is ignored by engine, graph and UI.

- id: <http://www.purl.org/ogit/Automation/lifecycle>
- valid-from: Thu May 11 00:00:00 UTC 2017
- creator: Philipp Kähltz

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Resource](#)

**1.3.0.108 ogit/lastName**

Last name of a person.

- id: <http://www.purl.org/ogit/lastName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.109 ogit/Automation/cpuModel**

Contains the model of the cpu.

- id: <http://www.purl.org/ogit/Automation/cpuModel>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.110 ogit/Automation/buildName**

Contains the build name of a component.

- id: <http://www.purl.org/ogit/Automation/buildName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.111 ogit/Automation/appInstanceType**

Contains the instance type.

- id: <http://www.purl.org/ogit/Automation/appInstanceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.112 ogit/modificationTime**

Modification time.

- id: <http://www.purl.org/ogit/modificationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.113 ogit/ServiceManagement/problemStatus**

defines the status of a problem record

- id: <http://www.purl.org/ogit/ServiceManagement/problemStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.114** `ogit/Automation/knowledgeItemSyntaxVersion`

Contains an automation Knowledge Item (KI) syntax version.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemSyntaxVersion>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)

**1.3.0.115** `ogit/Automation/maxIdleTime`

Sets the maximum idle time of an AutomationIssue. HIRO Engine internally manages the idle time for each AutomationIssue. Whenever a KnowledgeItem gets applied it is reset to zero. If maximum idle time is reached the AutomationIssue is regarded as 'cannot be processed anymore until more knowledge is provided'

- id: <http://www.purl.org/ogit/Automation/maxIdleTime>
- valid-from: Mon Jul 22 00:00:00 UTC 2019
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.116** `ogit/priority`

Priority of a ticket. The actual semantics might depend on the ticket type (Incident, Service Request, ...)

- id: <http://www.purl.org/ogit/priority>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.117 ogit/shortDescription**

Contains a short description.

- id: <http://www.purl.org/ogit/shortDescription>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.118 ogit/Automation/serviceClass**

Contains the class of the service.

- id: <http://www.purl.org/ogit/Automation/serviceClass>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

**1.3.0.119 ogit/middleName**

Middle name of a person.

- id: <http://www.purl.org/ogit/middleName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.120 ogit/resource**

Defines the name of an resource on an instance e.g. disk or database.

- id: <http://www.purl.org/ogit/resource>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.121** `ogit/ServiceManagement/targetFinishAt`

Defines a point in time when the work on a change should be finished. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.122** `ogit/accessControl`

The access control level of this Node. Value could mean different things to different applications / policies. Initial intent is that policies would treat "public-read" (inspired by Amazon AWS S3 ACLs) to mean anyone would have read-only access to this node.

- id: <http://www.purl.org/ogit/accessControl>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: Chris Walker

used

- mandatory:
  - [ogit/Automation/Variable](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/KnowledgeBundle](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeBundle](#)
  - [ogit/Forum/KnowledgeBundleHistory](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Forum/Topic](#)

**1.3.0.123** ogit/ServiceManagement/ticketId

ID of the ticket in the source system, e.g. the ID of the ticket in BMC.

- id: <http://www.purl.org/ogit/ServiceManagement/ticketId>
- valid-from: Tue May 26 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.124** ogit/justification

Justification for a ChangeRequest

- id: <http://www.purl.org/ogit/justification>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.125** ogit/invoiceNumber

Contains an invoice number. This number is used as identifier for security purposes.

- id: <http://www.purl.org/ogit/invoiceNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)



**1.3.0.126 ogit/response**

Contains the response for a question.

- id: <http://www.purl.org/ogit/response>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)
  - [ogit/Task](#)

**1.3.0.127 ogit/ServiceManagement/externalTicketSource**

If a ticket was imported/duplicated from another system this will contain a string indentifying the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)

**1.3.0.128 ogit/Automation/diskSpace**

An integer which contains the disk space in GB.

- id: <http://www.purl.org/ogit/Automation/diskSpace>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.129 ogit/soxClass**

This attribute specifies, if an entity has a Sarbanes Oxley (SOX) classification that applies to it. The out-of-box data is: Critical or Non Critical

- id: <http://www.purl.org/ogit/soxClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.130 ogit/closedAt**

Will defined the time when a ticket was closed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/closedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.131 ogit/ServiceManagement/taskStatus**

Defines the status of a task.

- id: <http://www.purl.org/ogit/ServiceManagement/taskStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.132** `ogit/ServiceManagement/resolutionCode`

Optional resolution code that may be provided during an incident or problem along with the solution description.

- id: <http://www.purl.org/ogit/ServiceManagement/resolutionCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.133** `ogit/expiresAt`

Defines the date something expires.

- id: <http://www.purl.org/ogit/expiresAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.134** `ogit/streetAddress`

The street address. For example, Eschersheimer Landstr. 526-532

- id: <http://www.purl.org/ogit/streetAddress>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

**1.3.0.135** ogit/businessCriticality

The business criticality of a process/service/CI.

- id: <http://www.purl.org/ogit/businessCriticality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.136** ogit/leaseContract

This field specifies the lease contract covering a service.

- id: <http://www.purl.org/ogit/leaseContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.137** ogit/\_owner

[internally generated] The id of the identity who owns the node

- id: [http://www.purl.org/ogit/\\_owner](http://www.purl.org/ogit/_owner)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.138** ogit/securityClass

Contains the security class of an entity/device.

- id: <http://www.purl.org/ogit/securityClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.139 ogit/serialNumber**

A string representing a any kind of serial number. see <http://purl.org/goodrelations/v1#serialNumber>

- id: <http://www.purl.org/ogit/serialNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.140 ogit/firstName**

First name of a person

- id: <http://www.purl.org/ogit/firstName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.141 ogit/Automation/optionalParameters**

Contains optional parameters as key/value mapping

- id: <http://www.purl.org/ogit/Automation/optionalParameters>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran

used

- optional:
  - [ogit/Automation/ActionApplicability](#)
  - [ogit/Automation/ActionCapability](#)
  - [ogit/Automation/ActionHandler](#)

**1.3.0.142 ogit/assignedGroup**

Assigned Group to a Service Management process.

- id: <http://www.purl.org/ogit/assignedGroup>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.143 ogit/macAddress**

The mac address of a component.

- id: <http://www.purl.org/ogit/macAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.144 ogit/Automation/osName**

Contains operating system name.

- id: <http://www.purl.org/ogit/Automation/osName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.145 ogit/version**

Any string representation of version information. no restrictions are imposed on that base attribute

- id: <http://www.purl.org/ogit/version>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Software/Application](#)

**1.3.0.146 ogit/title**

Title of any kind. In the context of a Person this can be a courtesy title, an academic title, or a job title.

- id: <http://www.purl.org/ogit/title>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Forum/Topic](#)
  - [ogit/Forum/Workflow](#)
  - [ogit/Forum/WorkflowStep](#)
- optional:
  - [ogit/Hyperlink](#)
  - [ogit/Knowledge/AcquisitionSession](#)
  - [ogit/Person](#)

**1.3.0.147 ogit/Automation/appServer**

Contains application server.

- id: <http://www.purl.org/ogit/Automation/appServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.148 ogit/class

Class of a component/device.

- id: <http://www.purl.org/ogit/class>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.149 ogit/Automation/sendHistory

Boolean flag whether issue history should be sent to decision service.

- id: <http://www.purl.org/ogit/Automation/sendHistory>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

## 1.3.0.150 ogit/content

A string holding any type of content: plain string, XML fragments, RDF documents, ...

- id: <http://www.purl.org/ogit/content>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Forum/Post](#)
  - [ogit/Forum/Reply](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Forum/Rating](#)



**1.3.0.151 ogit/confidentiality**

Contains information about the confidentiality related to a device or an entity.

- id: <http://www.purl.org/ogit/confidentiality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.152 ogit/Automation/deployStatus**

String value, represents the status if an automation Knowledge Item is not deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/deployStatus>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.153 ogit/Automation/rankMap**

Contains KI ranking values.

- id: <http://www.purl.org/ogit/Automation/rankMap>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.154 ogit/lastOccurredAt**

Defines the date of last occurrence of an event

- id: <http://www.purl.org/ogit/lastOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.155 ogit/Automation/isDeployed**

Obsolete attribute. Not used for HIRO  $\geq 6$ . Boolean value, true if an automation Knowledge Item is deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/isDeployed>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.156 ogit/Automation/processingNode**

Defines where an AutomationIssue is currently being processed or was being processed last. Must contain a valid vertex id. Replaces the free attribute '/CurrentNodeID'

- id: <http://www.purl.org/ogit/Automation/processingNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.157** `ogit/Automation/issueFormalRepresentation`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Contains an issue in XML representation defined by IssueSchema.

- id: <http://www.purl.org/ogit/Automation/issueFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.158** `ogit/_tags`

[internally generated] Used for individual search.

- id: [http://www.purl.org/ogit/\\_tags](http://www.purl.org/ogit/_tags)
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/Variable](#)

**1.3.0.159** `ogit/ServiceManagement/scheduledFinishAt`

Defines a point in time when the work on a change is planned/scheduled to be finished. This date time is usually defined during change planning and/or approval. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

## 1.3.0.160 ogit/name

Contains a name.

- id: <http://www.purl.org/ogit/name>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/ActionCapability](#)
  - [ogit/Automation/ActionHandler](#)
  - [ogit/Automation/Item](#)
  - [ogit/Automation/KIRanking](#)
  - [ogit/Automation/KnowledgeBundle](#)
  - [ogit/Automation/KnowledgeItemAttribute](#)
  - [ogit/Automation/KnowledgePool](#)
  - [ogit/Automation/MARSModelTemplate](#)
  - [ogit/Automation/Variable](#)
  - [ogit/Event](#)
  - [ogit/Forum/KnowledgeBundle](#)
  - [ogit/Forum/KnowledgeBundleHistory](#)
  - [ogit/Forum/Profile](#)
  - [ogit/Forum/Tag](#)
  - [ogit/Location](#)
  - [ogit/MARS/Resource](#)
  - [ogit/Organization](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/Software/Application](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/Attachment](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSModel](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Data/Log](#)
  - [ogit/Environment](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Region](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

**1.3.0.161 ogit/Automation/software**

A software component.

- id: <http://www.purl.org/ogit/Automation/software>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.162 ogit/Automation/originNode**

Defines where an AutomationIssue starts/started its lifecycle. Must contain a valid vertex id. Replaces the free attribute '/NodeID'

- id: <http://www.purl.org/ogit/Automation/originNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.163 ogit/description**

Contains a description.

- id: <http://www.purl.org/ogit/description>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/ActionCapability](#)
  - [ogit/Automation/Trigger](#)
  - [ogit/Automation/Variable](#)
  - [ogit/Forum/Topic](#)
- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSMModel](#)
  - [ogit/Automation/MARSMModelTemplate](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Data/Log](#)
  - [ogit/Event](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Knowledge/AcquisitionSession](#)
  - [ogit/Location](#)
  - [ogit/Organization](#)
  - [ogit/Region](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
  - [ogit/Software/Application](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

#### 1.3.0.164 [ogit/finishedAt](#)

Defines a point in time when the work on a change, task, or similar entity was actually finished. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/finishedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.165** ogit/Automation/host

Contains the host name.

- id: <http://www.purl.org/ogit/Automation/host>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.166** ogit/Automation/weightMap

Contains fingerprint weight values for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/weightMap>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- mandatory:
  - [ogit/Automation/KIRanking](#)

**1.3.0.167** ogit/externalId

The External Id of a component.

- id: <http://www.purl.org/ogit/externalId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.168 ogit/impact**

Will contain the impact, for example of a ticket. In this case the actual semantics would depend on the ticket type, which could correspond to an Incident, Service Request, etc.

- id: <http://www.purl.org/ogit/impact>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.169 ogit/contact**

This field displays the device/CI/component owner who is the person assigned to the device/CI/component and uses it on a day-to-day basis. Support contacts are secondary contacts who may have access to a CI for example.

- id: <http://www.purl.org/ogit/contact>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.170 ogit/Automation/defaultSigma**

Contains the default sigma value for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/defaultSigma>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)



**1.3.0.171 ogit/Automation/appInfrastructureType**

Contains the application infrastructure type.

- id: <http://www.purl.org/ogit/Automation/appInfrastructureType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.172 ogit/revision**

Contains the revision of versioned data.

- id: <http://www.purl.org/ogit/revision>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

used

- mandatory:
  - [ogit/VersioningData](#)

**1.3.0.173 ogit/Automation/issueType**

Contains the type of the issue.

- id: <http://www.purl.org/ogit/Automation/issueType>
- valid-from: Thu Nov 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

## 1.3.0.174 ogit/orderedAt

Defines a point in time when a component/device was actually ordered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/orderedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.175 ogit/faultCount

Contains fault count related to a component

- id: <http://www.purl.org/ogit/faultCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.176 ogit/risk

Used to store the result of a risk analysis.

- id: <http://www.purl.org/ogit/risk>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.177 ogit/lastUpdatedBy**

Defines the last person or process who updated an entity.

- id: <http://www.purl.org/ogit/lastUpdatedBy>
- valid-from: Mon Jul 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.178 ogit/ServiceManagement/fallbackPlan**

Defines instructions of how to revert in case a change fails.

- id: <http://www.purl.org/ogit/ServiceManagement/fallbackPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.179 ogit/Automation/defaultRank**

Contains the default rank for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/defaultRank>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.180 ogit/isRoot**

Defines if an event is root.

- id: <http://www.purl.org/ogit/isRoot>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.181 ogit/openedAt**

Time when a ticket or task was created/opened. The values could combine date and time with time zone designator according to ISO 8601 for service management tickets. For most tickets there is no real difference between creation and opened time. In case such a distinction is relevant the "createdAt" attribute can be used.

- id: <http://www.purl.org/ogit/openedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.182 ogit/Automation/virtualSystemName**

Contains the name of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.183 ogit/expirationDate**

Defines a point in time when something becomes invalid the format is described at <http://purl.org/goodrelations/v1#validThrough>

- id: <http://www.purl.org/ogit/expirationDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.184 ogit/officePhone**

The phone number in the office.

- id: <http://www.purl.org/ogit/officePhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.185 ogit/phone**

a phone number

- id: <http://www.purl.org/ogit/phone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

**1.3.0.186 ogit/acknowledgeState**

Defines the state of acknowledgement.

- id: <http://www.purl.org/ogit/acknowledgeState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.187 ogit/deadline**

Defines a point in time when a deadline is reached.

- id: <http://www.purl.org/ogit/deadline>
- valid-from: Mon Dec 19 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/License](#)

**1.3.0.188 ogit/Automation/osLicense**

License of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osLicense>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.189** ogit/fax

The number of a fax.

- id: <http://www.purl.org/ogit/fax>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.190** ogit/Automation/databaseServer

Contains information about the database server.

- id: <http://www.purl.org/ogit/Automation/databaseServer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.191** ogit/Automation/portNumber

Contains a port number.

- id: <http://www.purl.org/ogit/Automation/portNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.192** ogit/Automation/webServer

Contains an webServer.

- id: <http://www.purl.org/ogit/Automation/webServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.193** ogit/type

Type of an an entity.

- id: <http://www.purl.org/ogit/type>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Task](#)

**1.3.0.194** ogit/Automation/softwareKey

Contains the key of a software.

- id: <http://www.purl.org/ogit/Automation/softwareKey>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



**1.3.0.195** ogit/Automation/installPath

Contains the installation path of a component.

- id: <http://www.purl.org/ogit/Automation/installPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.196** ogit/Automation/licenseName

Contains the license name of a component.

- id: <http://www.purl.org/ogit/Automation/licenseName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.197** ogit/capacity

General Capacity

- id: <http://www.purl.org/ogit/capacity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)

**1.3.0.198** `ogit/Automation/contextPath`

Contains the context path of a component.

- id: <http://www.purl.org/ogit/Automation/contextPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.199** `ogit/Automation/cpuSpeed`

An floating point number which shows the cpu speed in GHZ.

- id: <http://www.purl.org/ogit/Automation/cpuSpeed>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.200** `ogit/Automation/processingTimestamp`

Contains the timestamp indicating last time an aumation issue was processed.

- id: <http://www.purl.org/ogit/Automation/processingTimestamp>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.201 ogit/otherPhone**

The number of an other phone.

- id: <http://www.purl.org/ogit/otherPhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.202 ogit/subCategory**

Used to give a subcategory to things.

- id: <http://www.purl.org/ogit/subCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.203 ogit/isMutable**

True if the value can be changed. E.g. after a service is provisioned.

- id: <http://www.purl.org/ogit/isMutable>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Timeseries](#)

**1.3.0.204** `ogit/Automation/servletClass`

Contains the class of the servlet.

- id: <http://www.purl.org/ogit/Automation/servletClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.205** `ogit/sourceTable`

Contains the source table, that stores where the data are coming from.

- id: <http://www.purl.org/ogit/sourceTable>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.206** `ogit/creator`

Creator of an entity.

- id: <http://www.purl.org/ogit/creator>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- mandatory:
  - [ogit/Automation/Variable](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)
  - [ogit/License](#)

**1.3.0.207** `ogit/ServiceManagement/implementationPlan`

Used to define detail implementation instructions.

- id: <http://www.purl.org/ogit/ServiceManagement/implementationPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.208** `ogit/Datacenter/rackUnit`

The name of the RackUnit within a datacenter.

- id: <http://www.purl.org/ogit/Datacenter/rackUnit>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.209** `ogit/availability`

Contains information about the availability of a service/device.

- id: <http://www.purl.org/ogit/availability>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.210** `ogit/ServiceManagement/allowedForNewBusiness`

If the value of this flag is true, the service could be offered in a store to new users for order. If flag is false, the service will only be available to users with already existing instances/entities of a specific service.

- id: <http://www.purl.org/ogit/ServiceManagement/allowedForNewBusiness>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.211** `ogit/Automation/firewallStatus`

Contains information about the firewall status.

- id: <http://www.purl.org/ogit/Automation/firewallStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.212** `ogit/lastScannedAt`

Defines a point in time when a component/device was actually scanned last time. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/lastScannedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.213 ogit/capacityAvailable**

If the flag is true, then service can be ordered by new instance. If the flag is false, the service cannot temporarily be ordered due to capacity reasons.

- id: <http://www.purl.org/ogit/capacityAvailable>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.214 ogit/subType**

A subtype of an an entity.

- id: <http://www.purl.org/ogit/subType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.215 ogit/pendingChange**

This field indicates whether or not there are any changes pending against a component/device. When you close or open a change for this component/device, this action sets or clears the flag..

- id: <http://www.purl.org/ogit/pendingChange>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.216** `ogit/Automation/exchangeRate`

Contains the data rate exchanged.

- id: <http://www.purl.org/ogit/Automation/exchangeRate>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.217** `ogit/ServiceManagement/sourceStatus`

It can be used to define application specific status values, which are not allowed by a normalized status, e.g. incidentStatus, changeStatus etc.

- id: <http://www.purl.org/ogit/ServiceManagement/sourceStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.218** `ogit/Automation/patchNumber`

Contains a patch number.

- id: <http://www.purl.org/ogit/Automation/patchNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



**1.3.0.219 ogit/Automation/cpuType**

Contains the cpu type of a device.

- id: <http://www.purl.org/ogit/Automation/cpuType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.220 ogit/Automation/dataPrivacy**

Data privacy of a component.

- id: <http://www.purl.org/ogit/Automation/dataPrivacy>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.221 ogit/inventoryNumber**

This field specifies the inventory component number for the a device as defined by the company-defined device inventory number in the model table. The system uses this number to provide data on the Manufacturer, Model, and Version fields if available.

- id: <http://www.purl.org/ogit/inventoryNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.222 ogit/message

Contains a message.

- id: <http://www.purl.org/ogit/message>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

## 1.3.0.223 ogit/webPage

A web page.

- id: <http://www.purl.org/ogit/webPage>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

## 1.3.0.224 ogit/Automation/objectIdentifier

Contains a system object identifier.

- id: <http://www.purl.org/ogit/Automation/objectIdentifier>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.225 ogit/lastUpdatedAt**

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

- id: <http://www.purl.org/ogit/lastUpdatedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.226 ogit/modelNumber**

ModelNumber of a device.

- id: <http://www.purl.org/ogit/modelNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.227 ogit/Automation/fqdn**

Contains a fully qualified domain name.

- id: <http://www.purl.org/ogit/Automation/fqdn>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.228** ogit/Automation/osKey

Product key for the Operating System.

- id: <http://www.purl.org/ogit/Automation/osKey>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.229** ogit/Automation/brand

Contains the brand of a component/device.

- id: <http://www.purl.org/ogit/Automation/brand>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.230** ogit/Automation/licenseType

Contains the license type of a component.

- id: <http://www.purl.org/ogit/Automation/licenseType>
- valid-from: Sun May 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.231** ogit/market

Indicates market, for which an entity may be applicable.

- id: <http://www.purl.org/ogit/market>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.232** ogit/Automation/virtualSystemType

Contains the type of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.233** ogit/Automation/affectedNodeId

Contains the ID of the node which is affected by this entity.

- id: <http://www.purl.org/ogit/Automation/affectedNodeId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

## 1.3.0.234 ogit/Automation/osManufacturer

Contains the manufacturer of the operating system.

- id: <http://www.purl.org/ogit/Automation/osManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.235 ogit/id

General id.

- id: <http://www.purl.org/ogit/id>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/Forum/ShortId](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/Attachment](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Comment](#)
  - [ogit/License](#)
  - [ogit/Network/NetworkInterface](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Software/SoftwareComponent](#)
  - [ogit/Task](#)

**1.3.0.236** ogit/occurenceCount

Defines the number an event occurred.

- id: <http://www.purl.org/ogit/occurenceCount>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.237** ogit/ServiceManagement/solution

Solution description, for example that is usually provided during incident resolving. This field is also use for problem tickets. There is defines the permanent solution desription for a problem.

- id: <http://www.purl.org/ogit/ServiceManagement/solution>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.238** ogit/creationTime

Creation time of an entity.

- id: <http://www.purl.org/ogit/creationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.239 ogit/subject**

Contains the subject.

- id: <http://www.purl.org/ogit/subject>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/License](#)

**1.3.0.240 ogit/checkedInAt**

Defines the time when something was actually checked in. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedInAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.241 ogit/summary**

A summary/short description, for example of a ticket.

- id: <http://www.purl.org/ogit/summary>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)



**1.3.0.242** `ogit/lastClearedAt`

Defines the date an event has been cleared.

- id: <http://www.purl.org/ogit/lastClearedAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.243** `ogit/Automation/adminUrl`

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/Automation/adminUrl>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.244** `ogit/MARS/Resource/class`

Used to classify Resource nodes. Will contain values like: 'Backend', 'Database', and so on. Replaces 'Resource↔ Class' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Resource/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Resource](#)

**1.3.0.245** `ogit/Automation/marsNodeType`

Obsolete attribute. Not used for HIRO  $\geq 6$ . Contains The Type of the Mars Node. Should be one of Application, Machine, Software, Resource.

- id: <http://www.purl.org/ogit/Automation/marsNodeType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/Automation/MARSNodeTemplate](#)
  - [ogit/MARS/Resource](#)

**1.3.0.246** `ogit/Automation/command`

Contains an automation command.

- id: <http://www.purl.org/ogit/Automation/command>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.247** `ogit/Automation/basicConfigId`

Contains the internal identifier of the basic configuration of a component .

- id: <http://www.purl.org/ogit/Automation/basicConfigId>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.248** `ogit/Automation/parentIssue`

Contains the ID of the issue which created this issue.

- id: <http://www.purl.org/ogit/Automation/parentIssue>
- valid-from: Sat Jun 01 00:00:00 UTC 2019
- creator: [cy@arago.co](mailto:cy@arago.co)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.249** `ogit/size`

The size, e.g. of a file.

- id: <http://www.purl.org/ogit/size>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: arago Technologies

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.250** `ogit/serviceContract`

This field specifies the contract covering a service.

- id: <http://www.purl.org/ogit/serviceContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.251 ogit/Automation/serviceStatus**

Contains the status of a service.

- id: <http://www.purl.org/ogit/Automation/serviceStatus>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Resource](#)

**1.3.0.252 ogit/vendor**

Contains the vendor of a device or software/hardware component.

- id: <http://www.purl.org/ogit/vendor>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.253 ogit/firstOccurredAt**

Defines the date of first occurrence of an event

- id: <http://www.purl.org/ogit/firstOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.254 ogit/validFrom**

Defines a point in time when something becomes valid.

- id: <http://www.purl.org/ogit/validFrom>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.255 ogit/Automation/governingContract**

Contains information about the governing contract.

- id: <http://www.purl.org/ogit/Automation/governingContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.256 ogit/Automation/systemType**

Contains the type of the system.

- id: <http://www.purl.org/ogit/Automation/systemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.257 ogit/Automation/tcpPort**

The tcp port.

- id: <http://www.purl.org/ogit/Automation/tcpPort>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.258 ogit/position**

Indicates user's position. This field contains a string value.

- id: <http://www.purl.org/ogit/position>
- valid-from: Tue Oct 18 00:00:00 UTC 2016
- creator: Arthur Shoba

used

- optional:
  - [ogit/Person](#)

**1.3.0.259 ogit/reportedAt**

Defines the time when something was actually reported. The values can combine date and time with time zone designator according to ISO 8601. Reported time is used in incident management in the following manner: in most cases the reported time equals the time when the incident is created. In some cases, e.g. the incident is created after the helpdesk has already worked on some request before it was decided to create an incident, the reported time might differ from ticket creation/opening time.

- id: <http://www.purl.org/ogit/reportedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.260** ogit/Automation/webhook

a http callback (<https://en.wikipedia.org/wiki/Webhook>)

- id: <http://www.purl.org/ogit/Automation/webhook>
- valid-from: Sat Jun 01 00:00:00 UTC 2019
- creator: arago GmbH

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.261** ogit/Automation/logLevel

Contains the numeric log level of the history entry.

- id: <http://www.purl.org/ogit/Automation/logLevel>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.262** ogit/ServiceManagement/targetStartAt

Defines a point in time when the work on a change should start. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.263** `ogit/Automation/mandatoryParameters`

Contains mandatory parameters as key/value mapping

- id: <http://www.purl.org/ogit/Automation/mandatoryParameters>
- valid-from: Mon Apr 01 00:00:00 UTC 2019
- creator: Oday Jubran

used

- mandatory:
  - [ogit/Automation/ActionCapability](#)
- optional:
  - [ogit/Automation/ActionApplicability](#)

**1.3.0.264** `ogit/ServiceManagement/reportedSource`

Can be used to define how a ticket was communicated. It could define some kind of communication channel ("← ServiceDesk", "Email") or, e.g. for Incident records, it might define that the ticket was produced automatically from an event management system.

- id: <http://www.purl.org/ogit/ServiceManagement/reportedSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.265** `ogit/RL/state`

Specifies the state of the issue for Reinforcement Learning.

- id: <http://www.purl.org/ogit/RL/state>
- valid-from: Thu Jan 02 00:00:00 UTC 2020
- creator: Rudi Schäfer

used

- optional:
  - [ogit/Automation/AutomationIssue](#)



**1.3.0.266** `ogit/ServiceManagement/task`

A task related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/task>
- valid-from: Mon Jul 06 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

**1.3.0.267** `ogit/instance`

Defines the name of an instance.

- id: <http://www.purl.org/ogit/instance>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)
  - [ogit/Timeseries](#)

**1.3.0.268** `ogit/Automation/sendData`

Boolean flag whether issue data should be sent to decision service.

- id: <http://www.purl.org/ogit/Automation/sendData>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.269** ogit/isSupported

Indicates whether the service currently is supported. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isSupported>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.270** ogit/operationalStatus

An operational status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/operationalStatus>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.271** ogit/validTo

Defines a point in time when something stops being valid.

- id: <http://www.purl.org/ogit/validTo>
- valid-from: Tue Nov 29 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/License](#)

**1.3.0.272** `ogit/ServiceManagement/changeStatus`

Defines the status of a change record within the service management.

- id: <http://www.purl.org/ogit/ServiceManagement/changeStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.273** `ogit/Automation/projectName`

Contains the project name of a component.

- id: <http://www.purl.org/ogit/Automation/projectName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)