
OSLC-core

June 4, 2020

1 OSLC-core	1
2 Module Documentation	2
2.1 Entities	2
2.1.0.1 ogit/OSLC-core/Error	2
2.1.0.2 ogit/OSLC-core/Preview	2
2.1.0.3 ogit/OSLC-core/QueryCapability	2
2.1.0.4 ogit/OSLC-core/Discussion	3
2.1.0.5 ogit/OSLC-core/PrefixDefinition	3
2.1.0.6 ogit/OSLC-core/Comment	3
2.1.0.7 ogit/OSLC-core/OAuthConfiguration	3
2.1.0.8 ogit/OSLC-core/ServiceProvider	4
2.1.0.9 ogit/OSLC-core/Property	4
2.1.0.10 ogit/OSLC-core/Compact	4
2.1.0.11 ogit/OSLC-core/Publisher	4
2.1.0.12 ogit/OSLC-core/ServiceProviderCatalog	5
2.1.0.13 ogit/OSLC-core/Dialog	5
2.1.0.14 ogit/OSLC-core/CreationFactory	5
2.1.0.15 ogit/OSLC-core/ExtendedError	5
2.1.0.16 ogit/OSLC-core/ResponseInfo	6
2.1.0.17 ogit/OSLC-core/AllowedValues	6
2.1.0.18 ogit/OSLC-core/Service	6
2.1.0.19 ogit/OSLC-core/ResourceShape	6
2.2 Verbs	7
2.2.0.1 ogit/OSLC-core/executes	7
2.2.0.2 ogit/OSLC-core/discussedBy	7
2.2.0.3 ogit/OSLC-core/valueType	7
2.2.0.4 ogit/OSLC-core/details	7
2.2.0.5 ogit/OSLC-core/instanceShape	8
2.2.0.6 ogit/OSLC-core/describes	8
2.2.0.7 ogit/OSLC-core/comment	8
2.2.0.8 ogit/OSLC-core/serviceProviderCatalog	8
2.2.0.9 ogit/OSLC-core/extendedError	9
2.2.0.10 ogit/OSLC-core/nextPage	9
2.2.0.11 ogit/OSLC-core/range	9
2.2.0.12 ogit/OSLC-core/oauthAccessTokenURI	9
2.2.0.13 ogit/OSLC-core/creationFactory	10
2.2.0.14 ogit/OSLC-core/oauthConfiguration	10
2.2.0.15 ogit/OSLC-core/selectionDialog	10
2.2.0.16 ogit/OSLC-core/results	10
2.2.0.17 ogit/OSLC-core/valueShape	11
2.2.0.18 ogit/OSLC-core/propertyDefinition	11

2.2.0.19	ogit/OSLC-core/service	11
2.2.0.20	ogit/OSLC-core/allowedValues	11
2.2.0.21	ogit/OSLC-core/moreInfo	12
2.2.0.22	ogit/OSLC-core/property	12
2.2.0.23	ogit/OSLC-core/resourceShape	12
2.2.0.24	ogit/OSLC-core/inReplyTo	12
2.2.0.25	ogit/OSLC-core/authorizationURI	13
2.2.0.26	ogit/OSLC-core/creationDialog	13
2.2.0.27	ogit/OSLC-core/domain	13
2.2.0.28	ogit/OSLC-core/futureAction	13
2.2.0.29	ogit/OSLC-core/resourceType	14
2.2.0.30	ogit/OSLC-core/partOfDiscussion	14
2.2.0.31	ogit/OSLC-core/occurs	14
2.2.0.32	ogit/OSLC-core/modifiedBy	14
2.2.0.33	ogit/OSLC-core/queryBase	15
2.2.0.34	ogit/OSLC-core/queryCapability	15
2.2.0.35	ogit/OSLC-core/oauthRequestTokenURI	15
2.3	Attributes	16
2.3.0.1	ogit/OSLC-core/shortTitle	16
2.3.0.2	ogit/OSLC-core/readOnly	16
2.3.0.3	ogit/OSLC-core/shortId	16
2.3.0.4	ogit/OSLC-core/statusCode	16
2.3.0.5	ogit/OSLC-core/prefix	16
2.3.0.6	ogit/OSLC-core/defaultValue	17
2.3.0.7	ogit/OSLC-core/rel	17
2.3.0.8	ogit/OSLC-core/isMemberProperty	17
2.3.0.9	ogit/OSLC-core/hintWidth	17
2.3.0.10	ogit/OSLC-core/label	17
2.3.0.11	ogit/OSLC-core/hidden	18
2.3.0.12	ogit/OSLC-core/prefixBase	18
2.3.0.13	ogit/OSLC-core/name	18
2.3.0.14	ogit/OSLC-core/maxLength	18
2.3.0.15	ogit/OSLC-core/allowedValue	18
2.3.0.16	ogit/OSLC-core/totalCount	19
2.3.0.17	ogit/OSLC-core/prefixDefinition	19
2.3.0.18	ogit/OSLC-core/message	19
2.3.0.19	ogit/OSLC-core/hintHeight	19

Chapter 1

OSLC-core

OSLC is a collection of specifications for software integration. This module contains entities for the OSLC core model.

Chapter 2

Module Documentation

2.1 Entities

2.1.0.1 ogit/OSLC-core/Error

Basis for forming an error response.

- id: <http://www.purl.org/ogit/OSLC-core/Error>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.2 ogit/OSLC-core/Preview

The UI Preview representation.

- id: <http://www.purl.org/ogit/OSLC-core/Preview>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.3 ogit/OSLC-core/QueryCapability

The QueryCapability definition included in a ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/QueryCapability>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.4 ogit/OSLC-core/Discussion

A Discussion resource is intended to represent a sequence of comments or notes regarding the associated resource

- id: <http://www.purl.org/ogit/OSLC-core/Discussion>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.5 ogit/OSLC-core/PrefixDefinition

The PrefixDefinition definition included in ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/PrefixDefinition>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.6 ogit/OSLC-core/Comment

A Comment resource represents a single note, or comment, in a discussion thread.

- id: <http://www.purl.org/ogit/OSLC-core/Comment>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.7 ogit/OSLC-core/OAuthConfiguration

The OAuthConfiguration definition included in ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/OAuthConfiguration>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.8 ogit/OSLC-core/ServiceProvider

The Service Provider resource

- id: <http://www.purl.org/ogit/OSLC-core/ServiceProvider>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.9 ogit/OSLC-core/Property

A Property resource describes one allowed or required property of a resource.

- id: <http://www.purl.org/ogit/OSLC-core/Property>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.10 ogit/OSLC-core/Compact

The Compact representation, fetched as application/x-osl-compact+xml

- id: <http://www.purl.org/ogit/OSLC-core/Compact>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.11 ogit/OSLC-core/Publisher

The Publisher definition included in ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/Publisher>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.12 ogit/OSLC-core/ServiceProviderCatalog

The Service Provider Catalog resource

- id: <http://www.purl.org/ogit/OSLC-core/ServiceProviderCatalog>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.13 ogit/OSLC-core/Dialog

The Dialog definition included in ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/Dialog>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.14 ogit/OSLC-core/CreationFactory

The CreationFactory definition included in a ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/CreationFactory>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.15 ogit/OSLC-core/ExtendedError

Extended error information.

- id: <http://www.purl.org/ogit/OSLC-core/ExtendedError>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.16 ogit/OSLC-core/ResponseInfo

The ResponseInfo included in query results.

- id: <http://www.purl.org/ogit/OSLC-core/ResponseInfo>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.17 ogit/OSLC-core/AllowedValues

Allowed values for one property.

- id: <http://www.purl.org/ogit/OSLC-core/AllowedValues>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.18 ogit/OSLC-core/Service

The Service definition included in a ServiceProvider.

- id: <http://www.purl.org/ogit/OSLC-core/Service>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.1.0.19 ogit/OSLC-core/ResourceShape

The Resource Shape used for creation, query and modify. Formally, a shape S applies to a resource R if there is a triple R rdf:type T and there is a triple S oslc:describes T, or if there is a triple R oslc:instanceShape S.

- id: <http://www.purl.org/ogit/OSLC-core/ResourceShape>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: ogit/Node

2.2 Verbs

2.2.0.1 ogit/OSLC-core/executes

Link from a currently available action to the future action it realizes.

- id: <http://www.purl.org/ogit/OSLC-core/executes>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.2 ogit/OSLC-core/discussedBy

A series of notes and comments about this resource.

- id: <http://www.purl.org/ogit/OSLC-core/discussedBy>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.3 ogit/OSLC-core/valueType

A URI that indicates the value type, for example XML Schema or RDF URIs for literal value types, and OSLC-specified for others. If this property is omitted, then the value type is unconstrained.

- id: <http://www.purl.org/ogit/OSLC-core/valueType>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.4 ogit/OSLC-core/details

A URL that may be used to retrieve a web page to determine additional details about the service provider.

- id: <http://www.purl.org/ogit/OSLC-core/details>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.5 ogit/OSLC-core/instanceShape

The URI of a Resource Shape that describes the possible properties.

- id: <http://www.purl.org/ogit/OSLC-core/instanceShape>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.6 ogit/OSLC-core/describes

This shape describes resources that are of the RDF type given by the object of the osc:describes predicate. Formally, a shape S applies to a resource R if there is a triple R rdf:type T and there is a triple S osc:describes T.

- id: <http://www.purl.org/ogit/OSLC-core/describes>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.7 ogit/OSLC-core/comment

Comment about the resource.

- id: <http://www.purl.org/ogit/OSLC-core/comment>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.8 ogit/OSLC-core/serviceProviderCatalog

Additional service provider catalog.

- id: <http://www.purl.org/ogit/OSLC-core/serviceProviderCatalog>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.9 ogit/OSLC-core/extendedError

Extended (additional) error information.

- id: <http://www.purl.org/ogit/OSLC-core/extendedError>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.10 ogit/OSLC-core/nextPage

Link to next page of response.

- id: <http://www.purl.org/ogit/OSLC-core/nextPage>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.11 ogit/OSLC-core/range

For properties with a resource value-type, Providers MAY also specify the range of possible resource types allowed, each specified by URI. The default range is <http://open-services.net/ns/core#Any>.

- id: <http://www.purl.org/ogit/OSLC-core/range>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.12 ogit/OSLC-core/oauthAccessTokenURI

URI for obtaining OAuth access token.

- id: <http://www.purl.org/ogit/OSLC-core/oauthAccessTokenURI>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.13 ogit/OSLC-core/creationFactory

Enables clients to create new resources.

- id: <http://www.purl.org/ogit/OSLC-core/creationFactory>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.14 ogit/OSLC-core/oauthConfiguration

Defines the three OAuth URLs required for a client to act as an OAuth consumer.

- id: <http://www.purl.org/ogit/OSLC-core/oauthConfiguration>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.15 ogit/OSLC-core/selectionDialog

Enables clients to select a resource via UI.

- id: <http://www.purl.org/ogit/OSLC-core/selectionDialog>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.16 ogit/OSLC-core/results

Used to hold the results of dialog action or JSON query results (default). The JSON query result attribute 'oslc↔:results' is used whenever a provider doesn't have a suitable property already in its model for such purposes.

- id: <http://www.purl.org/ogit/OSLC-core/results>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.17 ogit/OSLC-core/valueShape

if the value-type is a resource type, then Property MAY provide a shape value to indicate the Resource Shape that applies to the resource.

- id: <http://www.purl.org/ogit/OSLC-core/valueShape>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.18 ogit/OSLC-core/propertyDefinition

URI of the property whose usage is being described.

- id: <http://www.purl.org/ogit/OSLC-core/propertyDefinition>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.19 ogit/OSLC-core/service

Describes a service offered by the service provider.

- id: <http://www.purl.org/ogit/OSLC-core/service>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.20 ogit/OSLC-core/allowedValues

Resource with allowed values for the property being defined. Range of oslc:AllowedValues

- id: <http://www.purl.org/ogit/OSLC-core/allowedValues>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.21 ogit/OSLC-core/moreInfo

A resource giving more information on the error SHOULD be of an HTML content-type.

- id: <http://www.purl.org/ogit/OSLC-core/moreInfo>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.22 ogit/OSLC-core/property

The properties that are allowed or required by this shape.

- id: <http://www.purl.org/ogit/OSLC-core/property>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.23 ogit/OSLC-core/resourceShape

A Creation Factory MAY provide Resource Shapes that describe shapes of resources that may be created.

- id: <http://www.purl.org/ogit/OSLC-core/resourceShape>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.24 ogit/OSLC-core/inReplyTo

Reference to comment this comment is in reply to.

- id: <http://www.purl.org/ogit/OSLC-core/inReplyTo>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.25 ogit/OSLC-core/authorizationURI

URI for obtaining OAuth authorization.

- id: <http://www.purl.org/ogit/OSLC-core/authorizationURI>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.26 ogit/OSLC-core/creationDialog

Enables clients to create a resource via UI.

- id: <http://www.purl.org/ogit/OSLC-core/creationDialog>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.27 ogit/OSLC-core/domain

Namespace URI of the specification that is implemented by this service. In most cases this namespace URI will be for an OSLC domain, but other URIs MAY be used.

- id: <http://www.purl.org/ogit/OSLC-core/domain>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.28 ogit/OSLC-core/futureAction

A predicate that links to an action that is not currently executable on the subject resource, but may be executable in the future and/or on other resources. For example, in OSLC Automation this is expected to link from an `oslc_auto:AutomationPlan` to an `oslc:Action` resource with zero bindings (as it is not executable), with the meaning that the executable form of the action may be available on `oslc_auto:AutomationResult` resources generated by executing that Automation Plan. Similarly, resource shapes can allow discovery of actions available on the output of a creation factory.

- id: <http://www.purl.org/ogit/OSLC-core/futureAction>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.29 ogit/OSLC-core/resourceType

The expected resource type URI of the resource that will be created using this creation factory. These would be the URIs found in the result resource's rdf:type property.

- id: <http://www.purl.org/ogit/OSLC-core/resourceType>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.30 ogit/OSLC-core/partOfDiscussion

Reference to owning Discussion resource .

- id: <http://www.purl.org/ogit/OSLC-core/partOfDiscussion>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.31 ogit/OSLC-core/occurs

MUST be either <http://open-services.net/ns/core#Exactly-one>, <http://open-services.net/ns/core#Zero-or-one>, <http://open-services.net/ns/core#Zero-or-many> or <http://open-services.net/ns/core#One-or-many>.

- id: <http://www.purl.org/ogit/OSLC-core/occurs>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.32 ogit/OSLC-core/modifiedBy

The URI of a resource describing the entity that most recently modified this resource. The link target is usually a foaf:Person or foaf:Agent, but could be any type. This is modeled after dcterms:creator, but Dublin Core currently has no equivalent property.

- id: <http://www.purl.org/ogit/OSLC-core/modifiedBy>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.33 ogit/OSLC-core/queryBase

The base URI to use for queries. Queries may be invoked either by HTTP GET or HTTP POST. For HTTP GET, a query URI is formed by appending a key=value pair to the base URI. For HTTP POST, the query parameters are encoded as content with media type application/x-www-form-urlencoded and sent in the request body. The base URI MAY accept other query languages and media types in the request body, e.g. application/sparql-query for SPARQL queries.

- id: <http://www.purl.org/ogit/OSLC-core/queryBase>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.34 ogit/OSLC-core/queryCapability

Enables clients query across a collection of resources.

- id: <http://www.purl.org/ogit/OSLC-core/queryCapability>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.2.0.35 ogit/OSLC-core/oauthRequestTokenURI

URI for obtaining OAuth request token.

- id: <http://www.purl.org/ogit/OSLC-core/oauthRequestTokenURI>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

2.3 Attributes

2.3.0.1 ogit/OSLC-core/shortTitle

Shorter form of dcterms:title for the resource.

- id: <http://www.purl.org/ogit/OSLC-core/shortTitle>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.2 ogit/OSLC-core/readOnly

true if the property is read-only. If omitted, or set to false, then the property is writable. Providers SHOULD declare a property read-only when changes to the value of that property will not be accepted after the resource has been created, e.g. on PUT/PATCH requests. Consumers should note that the converse does not apply: Providers MAY reject a change to the value of a writable property.

- id: <http://www.purl.org/ogit/OSLC-core/readOnly>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.3 ogit/OSLC-core/shortId

Shorter form of dcterms:identifier for the resource.

- id: <http://www.purl.org/ogit/OSLC-core/shortId>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.4 ogit/OSLC-core/statusCode

The HTTP status code reported with the error.

- id: <http://www.purl.org/ogit/OSLC-core/statusCode>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.5 ogit/OSLC-core/prefix

Namespace prefix to be used for this namespace.

- id: <http://www.purl.org/ogit/OSLC-core/prefix>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.6 ogit/OSLC-core/defaultValue

A default value for property, inlined into property definition.

- id: <http://www.purl.org/ogit/OSLC-core/defaultValue>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.7 ogit/OSLC-core/rel

If present and set to 'alternate' then indicates that work-around is provided, behavior for other values is undefined.

- id: <http://www.purl.org/ogit/OSLC-core/rel>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.8 ogit/OSLC-core/isMemberProperty

Used to define when a property is a member of a container, useful for query.

- id: <http://www.purl.org/ogit/OSLC-core/isMemberProperty>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.9 ogit/OSLC-core/hintWidth

Values MUST be expressed in relative length units as defined in the W3C Cascading Style Sheets Specification (CSS 2.1) Em and ex units are interpreted relative to the default system font (at 100% size).

- id: <http://www.purl.org/ogit/OSLC-core/hintWidth>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.10 ogit/OSLC-core/label

Very short label for use in menu items.

- id: <http://www.purl.org/ogit/OSLC-core/label>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.11 ogit/OSLC-core/hidden

A hint that indicates that property MAY be hidden when presented in a user interface.

- id: <http://www.purl.org/ogit/OSLC-core/hidden>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.12 ogit/OSLC-core/prefixBase

The base URI of the namespace.

- id: <http://www.purl.org/ogit/OSLC-core/prefixBase>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.13 ogit/OSLC-core/name

Name of property being defined, i.e. second part of property's Prefixed Name.

- id: <http://www.purl.org/ogit/OSLC-core/name>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.14 ogit/OSLC-core/maxLength

For String properties only, specifies maximum characters allowed. If not set, then there is no maximum or maximum is specified elsewhere.

- id: <http://www.purl.org/ogit/OSLC-core/maxLength>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.15 ogit/OSLC-core/allowedValue

value allowed for a property.

- id: <http://www.purl.org/ogit/OSLC-core/allowedValue>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.16 ogit/OSLC-core/totalCount

This optional property indicates the total number of results across all pages, its value should be non-negative. In the context of a query resource, this value SHOULD be the total number of results, i.e. the number of resources that match the query. In the context of other resources, the value SHOULD be the total number of property values (i.e. RDF triples) of the resource. Unless Stable Paging is in effect, the total count MAY vary as a client retrieves subsequent pages.

- id: <http://www.purl.org/ogit/OSLC-core/totalCount>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.17 ogit/OSLC-core/prefixDefinition

Defines a namespace prefix for use in JSON representations and in forming OSLC Query Syntax strings.

- id: <http://www.purl.org/ogit/OSLC-core/prefixDefinition>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.18 ogit/OSLC-core/message

An informative message describing the error that occurred.

- id: <http://www.purl.org/ogit/OSLC-core/message>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer

2.3.0.19 ogit/OSLC-core/hintHeight

Values MUST be expressed in relative length units as defined in the W3C Cascading Style Sheets Specification (CSS 2.1) Em and ex units are interpreted relative to the default system font (at 100% size).

- id: <http://www.purl.org/ogit/OSLC-core/hintHeight>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer