

Rajalakshmi Engineering College

Name: PRAVEEN P
Email: 240801249@rajalakshmi.edu.in
Roll no: 240801249
Phone: 8608588599
Branch: REC
Department: I ECE AF
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 3_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are a software developer tasked with building a module for a scientific calculator application. The primary function of this module is to convert infix mathematical expressions, which are easier for users to read and write, into postfix notation (also known as Reverse Polish Notation). Postfix notation is more straightforward for the application to evaluate because it removes the need for parentheses and operator precedence rules.

The scientific calculator needs to handle various mathematical expressions with different operators and ensure the conversion is correct. Your task is to implement this infix-to-postfix conversion algorithm using a stack-based approach.

Example

Input:

a+b

Output:

ab+

Explanation:

The postfix representation of (a+b) is ab+.

Input Format

The input is a string, representing the infix expression.

Output Format

The output displays the postfix representation of the given infix expression.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a+(b*e)

Output: abe*+

Answer

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
```

```
struct Stack {
    int top;
    unsigned capacity;
    char* array;
};
```

```
struct Stack* createStack(unsigned capacity) {
    struct Stack* stack = (struct Stack*)malloc(sizeof(struct Stack));
    if (!stack)
```

```
        return NULL;

        stack->top = -1;
        stack->capacity = capacity;
        stack->array = (char*)malloc(stack->capacity * sizeof(char));

        return stack;
    }
}
```

```
int isEmpty(struct Stack* stack) {
    return stack->top == -1;
}
```

```
char peek(struct Stack* stack) {
    return stack->array[stack->top];
}
```

```
char pop(struct Stack* stack) {
    if (!isEmpty(stack))
        return stack->array[stack->top--];
    return '$';
}
```

```
void push(struct Stack* stack, char op) {
    stack->array[++stack->top] = op;
}
```

```
// You are using GCC
#include <stdio.h>
#include <ctype.h>
#include <string.h>
```

```
#define MAX 100
```

```
char stack[MAX];
int top = -1;
```

```
// Function to return precedence of operators
int precedence(char op) {
    switch (op) {
        case '^': return 3;
        case '*':
        case '/': return 2;
```

```
        case '+':
        case '-': return 1;
        default: return 0;
    }
}
```

```
// Function to check if character is an operator
int isOperator(char c) {
    return c == '+' || c == '-' || c == '*' || c == '/' || c == '^';
}
```

```
// Function to push to stack
void push(char c) {
    if (top < MAX - 1)
        stack[++top] = c;
}
```

```
// Function to pop from stack
char pop() {
    if (top >= 0)
        return stack[top--];
    return '\0';
}
```

```
char peek() {
    if (top >= 0)
        return stack[top];
    return '\0';
}
```

```
void infixToPostfix(char* infix)
{
    char postfix[MAX];
    int j = 0;

    for (int i = 0; infix[i] != '\0'; i++) {
        char c = infix[i];

        if (isalnum(c)) {
            postfix[j++] = c;
        }
    }
}
```

```

    } else if (c == '(') {
        push(c);
    } else if (c == ')') {
        while (peek() != '(')
            postfix[j++] = pop();
        pop();
    } else if (isOperator(c)) {
        while (top != -1 && precedence(peek()) >= precedence(c)) {
            if (c == '^' && peek() == '^') break;
            postfix[j++] = pop();
        }
        push(c);
    }
}

while (top != -1)
    postfix[j++] = pop();

postfix[j] = '\0';

printf("%s", postfix);
}

int main() {
    char infix[MAX];
    scanf("%s", infix);
    infixToPostfix(infix);
    return 0;
}

int main() {
    char exp[100];
    scanf("%s", exp);

    infixToPostfix(exp);
    return 0;
}

```

Status : Correct

Marks : 10/10