

# Rajalakshmi Engineering College

Name: PRAVEEN P  
Email: 240801249@rajalakshmi.edu.in  
Roll no: 240801249  
Phone: 8608588599  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

##### *Input Format*

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.

The third line consists of an integer V, which is the value to delete from the BST.

### **Output Format**

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5  
10 5 15 2 7  
15

Output: 2 5 7 10

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
struct TreeNode* insert(struct TreeNode* root, int key)
{
```

```

    if(root == NULL)
    {
        return createNode(key);
    }
    if(key < root->data)
    {
        root->left = insert(root->left, key);
    }
    else if(key > root->data)
    {
        root->right = insert(root->right, key);
    }
    return root;
}

```

```

struct TreeNode* findMin(struct TreeNode* root)
{
    if(root == NULL)
    {
        return NULL;
    }
    while(root->left != NULL)
    {
        root = root->left;
    }
    return root;
}

```

```

struct TreeNode* deleteNode(struct TreeNode* root, int key)
{
    if(root == NULL)
    {
        return NULL;
    }
    if(key < root->data)
    {
        root->left = deleteNode(root->left, key);
    }
    else if(key > root->data)
    {
        root->right = deleteNode(root->right, key);
    }
}

```

```

else
{
    if(root->left == NULL && root->right == NULL)
    {
        free(root);
        return NULL;
    }
    else if(root->left == NULL || root->right == NULL)
    {
        struct TreeNode* temp;
        if(root->left == NULL)
        {
            temp = root->right;
        }
        else
        {
            temp = root->left;
        }
        free(root);
        return temp;
    }
    else
    {
        struct TreeNode* temp = findMin(root->right);
        root->data = temp->data;
        root->right = deleteNode(root->right,temp->data);
    }
}
return root;
}

```

```

void inorderTraversal(struct TreeNode* root)
{
    if(root == NULL)
    {
        return;
    }
    inorderTraversal(root->left);
    printf("%d ",root->data);
    inorderTraversal(root->right);
}

int main()

```

```
{
    int N, rootValue, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;
    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }
    scanf("%d", &V);
    root = deleteNode(root, V);
    inorderTraversal(root);
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10