Tracking dataset reuse in proteomics: a comprehensive analysis of PRIDE data download statistics

Suresh Hewapathirana[1], Jingwen Bai[1], Chakradhar Bandla[1], Selvakumar Kamatchinathan[1], Deepti J Kundu[1], Nithu Sara John[1], Boma Brown-Harry[1], Nandana Madhusoodanan[1], Joan Marc Riera Duocastella[1], Juan Antonio Vizcaíno[1], Yasset Perez-Riverol[1,*]

[1]European Molecular Biology Laboratory, European Bioinformatics Institute (EMBL-EBI), Wellcome Trust Genome Campus, Hinxton, Cambridge CB10 1SD, UK

*Corresponding author: yperez@ebi.ac.uk

Abstract

Understanding how scientific datasets are accessed and reused is essential for resource planning, impact assessment, and the evaluation of open science policies. Here we present the PRIDE Archive download tracking infrastructure and a comprehensive analysis of data download statistics records from the PRIDE proteomics database during the last 5 years (2021-2025), spanning 34,085 datasets (96.4% of all public PRIDE datasets) accessed from 213 countries. The infrastructure includes `nf-downloadstats`, a scalable open Nextflow pipeline for processing large-scale download logs, and DeepLogBot, an open deep-learning bot detection framework. After removing 88.0% of download traffic identified as automated, analysis of the remaining 19.1 million genuine individual file downloads reveals that the United States leads PRIDE data downloads (26.8% of all downloaded files), followed by the United Kingdom (23.6%) and Germany (22.5%). Downloads grew steadily from 1.2 million in 2021 to 5.3 million in 2025, with FTP and HTTP alternating as the dominant download protocol. Dataset reuse follows a highly concentrated distribution, with the top 1% of datasets accounting for 43.3% of all downloads. These findings provide actionable insights for repository infrastructure planning and demonstrate the importance of bot-aware analytics for scientific data resources.

Availability: The `nf-downloadstats` pipeline is available at `https://github.com/PRIDE-Archive/nf-downloadstats` and DeepLogBot at `https://github.com/ypriverol/deeplogbot`, both under the Apache 2.0 license.

Keywords: bot detection, data reuse, download analytics, PRIDE, proteomics

1 Introduction

The PRIDE database is the world-leading data repository for mass spectrometry-based proteomics [1]. As a founding member of the ProteomeXchange consortium, PRIDE enables researchers to share and access proteomics datasets globally, promoting transparency, reproducibility, and data reuse. Aligned with the FAIR principles - Findable, Accessible, Interoperable, and Reusable [2] - PRIDE supports open science by ensuring that public datasets are well-annotated and machine-readable. These principles are essential for maximizing the value of shared scientific data.

Understanding how much public datasets are reused is essential for assessing the scientific impact of a data resource such as PRIDE, and informing data-driven policies. While citations in scholarly publications offer one indicator of reuse, data download statistics can provide a more granular view of data demand from any data resource. In our previous work [3], we demonstrated that usage/downloads metrics can serve as complementary indicators of scientific

impact for a given publication, supporting improved data stewardship, resource allocation, and funding decisions. Beyond measuring the global impact of a data resource, download statistics are critical for designing more effective data infrastructures. Download patterns can inform the optimization of data access protocols, guide the prioritization of metadata curation and visualization features, and identify high-value datasets for targeted annotation or integration efforts. As public data volumes continue to grow, usage-driven strategies become increasingly important for improving dataset discoverability and reuse. For example, in the concrete case of PRIDE, frequently downloaded datasets - particularly those used as community benchmarks - could be prioritized for enhanced manual metadata curation/annotation (e.g., SDRF-based sample descriptions [4]) and enriched with curated tags and keywords, making them easier to find through search interfaces. Users could then combine these annotations with download counts as a proxy to identify the most relevant and community-validated datasets for reuse. Similarly, repositories can leverage download patterns to allocate faster transfer services and optimized storage for high-demand datasets, ensuring that the most reused data remain readily accessible. In contrast; knowing which datasets are less frecuently downloaded can help repositories to identify underused datasets that may benefit from improved metadata and file organization.

Despite their importance, systematic tracking of dataset downloads remains a major challenge across bioinformatics resources in general, including PRIDE and the other ProteomeXchange partners. Despite some common access statistics having been widely adopted across data resources [5], barriers include the absence of a standardized infrastructure for logging access events, technical complexities in aggregating usage data across distributed and heterogeneous transfer systems (e.g., FTP, HTTP), and ongoing concerns related to user privacy and data protection. Compounding these challenges, automated bot traffic contaminates download statistics - studies estimate that bots account for 30-70% of all internet traffic (https://cpl.thalesgroup.com/ppc/application-security/bad-bot-report), and scientific repositories are particularly attractive targets due to their open-access policies and valuable content [6]. Without accounting for this contamination, any analysis of repository usage risks drawing conclusions from inflated and distorted metrics. As bioinformatics resources continue to scale in both size and complexity, robust download analytics will become increasingly vital - not only for measuring impact - but also for enabling smarter, user-informed development of open data platforms.

Here, we present the PRIDE Archive download tracking open infrastructure, which includes `nf-downloadstats`, a large-scale Nextflow [7] workflow for processing extensive traffic logs, and DeepLogBot, a bot detection framework that implements two complementary algorithms to identify and remove automated traffic. Additionally, we have developed an infrastructure that integrates download statistics directly into the PRIDE Archive web interface, allowing users to sort datasets (e.g. as the result of searches) by total downloads - both raw and normalized by number of files in the dataset - and perform percentile-based analyses. Using these tools on 159.3 million download records spanning 2021 to 2025, we characterize global proteomics data download patterns as a proxy for data reuse, examining geographic distribution across countries and regions, temporal evolution of download activity, shifts in download protocol preferences, and the concentration of dataset downloads across the PRIDE collection. The workflow is open-source and we make available the resulting data, which can be used by PRIDE data submitters in e.g. grant reports and publications.

2 Methods

2.1 nf-downloadstats: Log Processing Pipeline

Download logs are stored in the EBI (European Bioinformatics Institute) file system as compressed, comma-delimited text files. Each log entry includes a timestamp, dataset accession,

filename, anonymized and non-reversible IP hash, download status, geographic location (geo), used download protocol (Globus, HTTP, Aspera, FTP), and dataset type. No personal or directly identifiable user data is stored. Log files are organized hierarchically by Protocol, Public/Private access, Year, Month, and Day. Individual log files can be large, ranging from 1 GB to 237 GB (Supplementary Notes Section S1).

Due to the large volume and size of download log files, we developed `nf-downloadstats` (`https://github.com/PRIDE-Archive/nf-downloadstats`), an open-source Nextflow workflow for large-scale processing of the original anonymized log files (Figure 1A). Each processing step is implemented as an independent Python module, performing tasks such as removing incomplete transfers and filtering for PRIDE-specific records. A custom log file parser addresses the heterogeneity and scale of download log data; due to inconsistencies in log entries such as variable column structures and incomplete records, additional filters retain only complete transfers associated with PRIDE datasets.

To efficiently process the large volume of log files, parallelization is employed using a high-performance computing (HPC) environment managed via Slurm. Log files are processed in batches, with batch sizes and filtering criteria defined in a user-friendly YAML configuration file. The output is a consolidated 4.7 GB Parquet file containing 159,327,635 individual download records spanning five years: from January 2021 through December 2025. Each record includes the download date, geolocation, dataset accession, filename, download method (protocol). The data covers 35,528 unique dataset accessions accessed from 235 countries.

For analysis, individual download events are aggregated at the *location* level, where each location represents a unique geographic coordinate. This aggregation produces 71,133 location profiles, each characterized by behavioral features including download volumes, user counts, temporal patterns, and access characteristics.

2.2 Bot Detection Framework

We implemented two complementary bot detection algorithms, each combining Isolation Forest anomaly detection [8] with a distinct classification strategy. Both methods share a common feature extraction pipeline that computes 90+ behavioral features per location, organized into four categories: activity features (download counts, user statistics), temporal features (hourly/yearly entropy, working hours ratio), behavioral features (burst patterns, circadian deviation, coordination scores), and discriminative features (file exploration patterns, user authenticity scores). Full feature descriptions are provided in Supplementary Notes Section S3.

The *rule-based* method applies YAML-configurable threshold patterns to classify each location into one of three categories: **bot** (automated scraping or crawling), **hub** (legitimate automation such as institutional mirrors or continuous integration/continuous deployment (CI/CD) pipelines), or **organic** (human researchers). Patterns are evaluated sequentially, with the first match determining classification. This approach prioritizes interpretability and configurability. The *deep* method augments rule-based classification with additional behavioral feature engineering, including bot interaction features (download concentration, temporal irregularity, composite bot score) and bot signature features (request velocity, access regularity, session anomaly patterns). These 40+ additional features enable more nuanced separation of the three categories. The method incorporates a two-stage classification pipeline: Stage 1 separates organic from automated traffic, and Stage 2 distinguishes malicious bots from legitimate automation (hubs) using a discriminative scoring system with behavioral validation.

To evaluate both algorithms, we constructed a ground truth dataset of 1,411 labeled locations (88 bots, 44 hubs, 1,279 organic) using high-confidence heuristic criteria (Supplementary Notes Section S5). Both methods were evaluated on a 1-million record sample; we computed precision, recall, and F1 score per category, with 1,000-iteration bootstrap confidence intervals for the macro F1. The Deep method achieves the highest macro F1 score (0.775, 95% CI: 0.731-0.818), with perfect bot recall (1.000) and strong hub detection (F1 = 0.718), while the Rules method

provides higher bot precision (0.506) but detects fewer hubs (F1 = 0.275, Supplementary Notes Section S6.)

We applied the Deep method - the best-performing algorithm - to the full dataset (Figure 1A), classifying each of the 71,133 locations as bot, hub (legitimate automation), or organic. Locations classified as bot (53.1%, representing 88.0% of download traffic) were removed prior to all downstream analyses (Figure 1B; Supplementary Notes Section S7). The remaining 33,354 non-bot locations (organic users and institutional hubs) account for 19.1 million downloads across 34,085 datasets and 213 countries. While the framework effectively removes the vast majority of automated noise, some borderline locations and download patterns inevitably fall near the decision boundary; a fraction of genuine downloads may be misclassified as bots (false positives) and, conversely, some low-volume automated activity may persist in the filtered data (false negatives). Users should therefore treat the cleaned download counts as robust estimates rather than exact values.



Figure 1: PRIDE Logs Workflow and classification results. (A) End-to-end pipeline comprising two components: `nf-downloadstats` (green dashed box) processes raw PRIDE download logs into a consolidated Parquet file, and DeepLogBot (blue dashed box) aggregates records to geographic locations and classifies them via two complementary algorithms (rule-based and deep architecture) using Isolation Forest anomaly detection and hierarchical classification. (B) Download share by classification category on the full dataset: bots account for 88.0% of all traffic despite representing 53.1% of locations.

3 Results

3.1 Global PRIDE Usage Patterns

Over the 2021–2025 study period, 19.1 million genuine individual file downloads were recorded across 34,085 datasets, representing 96.4% of all public PRIDE datasets, accessed from 213 countries. On average, each dataset has been downloaded 560 times (median 85), and the number of unique datasets accessed per year grew from 14,879 in 2021 to 33,376 in 2025, reflecting both the growing PRIDE collection and increasing data download. Download activity has grown substantially (Figure 2A): annual downloads increased from 1.2 million in 2021 to 3.5 million in 2022, reaching 5.3 million in 2025, representing a 352% growth over the five-year period.



Figure 2: Temporal trends in PRIDE usage. (A) Annual download volumes in millions of files. (B) Growth in unique datasets accessed and unique locations per year.

The geographic reach of PRIDE data reuse is truly global (Figure 3). The top five countries per download volumes are the United States (5.1 M downloads, 26.8%), the United Kingdom (4.5 M, 23.6%), Germany (4.3 M, 22.5%), South Korea (869 K, 4.6%), and Canada (691 K, 3.6%). Grouped by continent, Europe accounts for the largest share of downloads (55.7%), followed by the Americas (30.7%) and Asia (11.4%).



Figure 3: Geographic distribution of PRIDE downloads. Top 20 countries per download volumes after bot removal (2021-2025).

To characterize the relationship between user base size and download intensity, we plotted total downloads against unique users for the top 50 countries (Figure 4A). Download patterns vary considerably across countries. Some, such as France (10,844 users, 15 downloads/user) and Canada (9,124 users, 76 downloads/user), show broad user bases with moderate activity per-user, suggesting predominantly individual researchers. Others, such as Belgium (1,858 users, 629 downloads/user) and Denmark (1,301 users, 530 downloads/user), exhibit high per-user averages that likely reflect a smaller number of heavy institutional users or hub-like access points concentrating the download activity. Most countries fall on a spectrum between these extremes.

This variation highlights that aggregate download volume alone does not fully capture the nature of data reuse, and that the balance between distributed individual access and concentrated institutional access differs markedly across regions.

Although European countries account for the majority of PRIDE downloads, yearly trends reveal shifting dynamics (Figure 4B). Germany showed a pronounced peak in 2023 (2.4 M downloads) before declining, while the United Kingdom peaked in 2022 (1.8 M) with lower average number of data downloads since. Notably, PRIDE usage is growing in some low- and middle-income countries (LMIC, as defined by the Wellcome Trust based on the OECD DAC list [9]; Figure 4C) including India (55 K downloads), Mexico (23 K), and Brazil (12 K). This growth suggests that PRIDE is increasingly serving as a resource for researchers in developing nations, supporting broader global participation in proteomics data reuse.



Figure 4: Global country-level download patterns. (A) Total downloads versus unique users for the top 50 countries by download volume; bubble size and color represent downloads per user on a log scale, revealing broad individual access (lower right) versus concentrated institutional access (upper left). (B) Yearly download trends for the top 15 European countries showing shifting dominance. (C) Yearly download trends for low- and middle-income countries, demonstrating accelerating adoption since 2024.

3.2 Download Concentration

Dataset downloads follows a highly skewed distribution characteristic of heavy-tailed systems (Figure 5A). The Gini coefficient – a standard measure of inequality ranging from 0 (perfect equality) to 1 (maximum concentration) – of 0.84 indicates substantial inequality: the top 1% of datasets (341 datasets) account for 43.3% of all downloads, the top 10% account for 77.2%, and the bottom 50% of datasets collectively represent only 3.1% of downloads. Concretely, whereas the "average" dataset has received 85 downloads, the most popular one exceeds 355,000. The rank-frequency distribution reveals a characteristic long tail, with download counts dropping steeply beyond the top 1% of datasets.

Importantly, the most downloaded datasets are not one-time events but show sustained behaviour over multiple years (Figure 5B). Of the top 25 datasets, most have been actively downloaded in at least 4 of the 5 years covered (2021-2025). The most downloaded datasets fall into two main categories: community benchmark resources and tissue atlas datasets. The ProteomeTools synthetic peptide libraries (PXD004732, 355K downloads; PXD021013, 303K;

PXD010595, 255K) rank among the top five, reflecting their widespread use as training data for machine learning models and spectral library search engines. Tissue atlas datasets including, the deep proteome atlas of 29 human tissues (PXD010154, 308K downloads), A Draft Map of the Human Proteome (PXD000561, 299K), and the Quantitative Proteome Map of the Human Body (PXD016999, 41K), show sustained multi-year download activity, consistent with their role as reference maps for tissue-specific protein expression. A ranking of the top 20 most downloaded datasets and extended analyses are provided in Supplementary Notes Section S8.



Figure 5: Dataset downloads concentration and consistency. (A) Rank-frequency distribution on log-log scale; the dashed red line marks the top 1% boundary, beyond which download counts drop sharply (Gini coefficient = 0.84). (B) Download consistency heatmap for the top 25 most downloaded datasets (2021-2025, after bot removal); color intensity represents download count on a $\log_{10}$ scale. Most top datasets show sustained data download volumes across 4-5 years, indicating their role as community reference and benchmark datasets. (C) Relationship between EuropePMC reuse citations and download volume for the top 50 most downloaded datasets (n−1 correction to exclude the original publication including the submitted dataset); point color indicates download consistency (fraction of years active out of five), grey points represent datasets with no independent reuse citations.

To assess whether download popularity reflects broader scientific impact, we queried (EuropePMC) for "reuse citations" of each dataset accession among the top 50 most downloaded datasets, subtracting the original submission publication to count only independent reuse mentions (Figure 5C). Of these, 37 datasets (74%) have been cited in at least one independent publication beyond their original submission, with a median of 2 reuse citations and a maximum of 52 (dataset PXD000561). While the correlation between download volume and reuse citation count shows a positive trend, it does not reach statistical significance (Spearman $\rho =$

0.206, $p = 0.22$), suggesting that high download counts do not simply mirror citations including data reuse activities. It should be noted that EuropePMC covers only open access publications, which represent a fraction of the total scientific literature, potentially underestimating the true citation-based impact of these datasets. The lack of significant correlation between downloads and reuse citations (Spearman $\rho = 0.206$, $p = 0.22$) demonstrates that download statistics capture dimensions of dataset impact that are orthogonal to citation-based metrics: many heavily downloaded datasets have few or no reuse citations, and vice versa. This indicates that download activity – particularly sustained, multi-year download patterns – provides an independent and complementary measure of genuine community adoption that cannot be inferred from publication records alone.

3.3 File Transfer Protocol Usage

Download protocol preferences have shifted over the study period (Figure 6A). FTP was the dominant protocol in 2021, accounting for 65% of genuine downloads. HTTP overtook FTP in 2022 (54%), but FTP surged again in 2023 (79%), likely driven by institutional hub traffic that relies on FTP for bulk transfers. By 2025, HTTP re-emerged as the leading protocol (69%), reflecting broader adoption of web-based download tools. Despite superior transfer performance for large files, advanced file transfer protocols such as Aspera and Globus remain in early adoption stages, accounting for 3.3% and 1.0% of 2025 downloads, respectively. To lower adoption barriers, we released `pridepy` [10] in March 2025, a Python-based command-line tool that abstracts protocol complexity and enables seamless switching between FTP, Aspera, and Globus file transfers with a single command. A monthly breakdown of 2025 downloads (Figure 6B) shows emerging Aspera usage alongside sustained Globus adoption, indicating that providing user-friendly tooling can facilitate the transition to high-performance transfer protocols in scientific data repositories.



Figure 6: Download protocol usage. (A) Annual download volume by protocol (2021-2025), showing the alternation between FTP and HTTP dominance. (B) Monthly breakdown of 2025 showing protocol usage patterns.

3.4 Download Hubs

Our classification identified 664 institutional download hubs distributed across 58 countries (Figure 7), accounting for 18.0 million downloads (11.3% of total traffic). These hubs represent institutions that systematically and continuously download public proteomics data [11] for data reuse/reanalysis purposes, including institutional mirrors, research infrastructure nodes, and data aggregation services. The United States hosts the most hubs (155, 23.3%), followed by Germany (99), Japan (46), and the Netherlands (38), with total hub download volume led by the United States (4.7 M), the United Kingdom (4.5 M), and Germany (4.2 M). The geographic spread of hubs – spanning all six inhabited continents – demonstrates that systematic data

download for data reuse purposes seems not to be confined to a few centers but is a global phenomenon. Hub characteristics vary widely: some operate with very few users but extremely high per-user download rates (e.g., Dresden, Germany with 275 K downloads/user from 8 users, consistent with the behavior of a mirror), while others involve hundreds of users accessing data at a moderate intensity (e.g., Melbourne, Australia with 186 users).



Figure 7: Distribution and characteristics of 664 identified download hubs. (A) Geographic locations, with bubble size proportional to download volume. (B) Top 15 countries by number of hubs, annotated with total hub download volume. (C) Hub diversity: unique users versus total downloads on log-log scale, showing the range from single-user mirrors to multi-user reanalysis infrastructure.

3.5 File Type Download Patterns

More than 81% of all downloads originate from five countries, and developing countries are largely absent from the top 10. Analysis of file type download patterns across regions reveals distinct usage profiles (Figure 8): raw instrument files dominate downloads in all regions, accounting for 72-73% of traffic in East Asia and North America. LMIC countries show a lower raw file proportion (54%) with a corresponding increase in result files and processed spectra (peak list files) [11]. This imbalance highlights that most users currently need to download and reprocess raw data from scratch, even when search engine results already exist within the submission - underscoring the need for better infrastructure to make analysis results more discoverable and independently downloadable.



Figure 8: File type download patterns by region (after bot removal). (A) Percentage of downloads by file type category across four regions. LMIC countries show lower raw file usage and higher result/processed spectra downloads compared to East Asia and North America. (B) Aggregated view: raw + processed spectra (full reanalysis capability) versus results + metadata (lightweight reuse). LMIC countries have the lowest reanalysis-oriented profile (55%) and the highest lightweight reuse proportion (15%).

3.6 PRIDE Download Statistics Visualization

The aggregated download statistics produced by `nf-downloadstats` are stored in MongoDB and Elasticsearch to enable fast searching and visualization within the PRIDE Archive web interface. For each dataset, the total number of downloads is displayed alongside a gradient bar indicating its download percentile, with higher intensity representing datasets in the top 1% of downloads (Figure 9). Additionally, a yearly trend chart is provided for each dataset, illustrating download activity over time. Datasets can be sorted by both total downloads per project and a normalized metric that accounts for the number of files within each project, enabling users to identify highly reused datasets for benchmarking or reanalysis. These features allow PRIDE data submitters to use download statistics in grant reports and publications, and provide the community with a tool to discover highly reused datasets.



Figure 9: PRIDE Archive download statistics integration. Each dataset displays a gradient percentile bar and total download count. A popup trend chart shows yearly download activity, enabling users to assess dataset popularity and reuse trends directly within the PRIDE interface.

4 Discussion

Here we have performed a detailed study of the PRIDE data download statistics for the last 5 years (2021–2025). Intrestingly, 88.0% of PRIDE download traffic is automated is consistent with the high bot prevalence observed across scientific data repositories, which offer unauthenticated, persistent, and predictable access to valuable content [6]. Without filtering, the most "downloaded" datasets may simply be the most bot-targeted, rendering raw download volumes unreliable as scientific impact indicators – a consequential problem given that download statistics are increasingly used by funding agencies, institutions, and researchers as evidence of data impact alongside traditional citation metrics [3]. DeepLogBot demonstrates that a scalable deep learning approach combining Isolation Forest anomaly detection with behavioral classification can effectively recover genuine usage signals from heavily contaminated logs. The framework processes over 159 million records, generalizes across diverse bot behaviors without manual rule tuning, and distinguishes legitimate automation (institutional hubs) from harmful scraping – a distinction that rule-based methods alone handle poorly (hub F1 = 0.275 vs. 0.718). As AI-driven platforms that perform large-scale automated reanalysis become more prevalent, the boundary between harmful scraping and beneficial programmatic access will become increasingly blurred, and repositories will need adaptive classification schemes that evolve alongside legitimate automation patterns.

PRIDE download volumes have grown 352% in 5 years, from 1.2 million in 2021 to 5.3 million in 2025, confirming accelerating data downloads across a geographically broad user base (213 countries). Download intensity varies markedly: some countries exhibit broad individual user bases, while others show concentrated institutional access (e.g., Belgium with 629 downloads/user, Denmark with 530 downloads/user), suggesting that the nature of data downloads – individual exploration versus systematic reanalysis – differs between research communities. The 664 download hubs we identified reveal a global infrastructure of institutional data consumers, from single-user mirrors performing full-repository synchronization to multi-user reanalysis centers processing hundreds of datasets. This hub distribution provides an empirical map of where proteomics bioinformatics infrastructure exists and can inform ProteomeXchange decisions about potential PRIDE mirrors placement, edge caching, and regional resource allocation – for instance, countries with growing user bases but no local hubs (e.g., India, Brazil, Mexico) may benefit from targeted infrastructure support. FTP and HTTP have alternated as the dominant protocol, with the shift to HTTP dominance in 2025 (69%) reflecting both broader individual adoption and the growing importance of API-based programmatic access; advanced protocols (Aspera, Globus) remain in early stages (1.4% of genuine traffic), but tools such as `pridepy` [10] should lower adoption barriers as datasets continue to grow in size.

Dataset downloads are highly concentrated (Gini = 0.84), with the top 1% of datasets accounting for 43.3% of all downloads. While community reference datasets such as ProteomeTools (PXD004732) show sustained multi-year downloads – likely because its comprehensive synthetic peptide spectral libraries serve as training data for machine learning models, retention time predictors, and spectral library search engines across the field – the "long tail" of rarely downloaded datasets should not be disregarded: these datasets may gain future value through meta-analyses, machine learning applications, or integration into multi-omics studies. Repositories can better serve both ends of this distribution by investing in improved discoverability – richer metadata, curated tags, and recommendation systems – alongside prioritized access for high-demand datasets. Regional differences in file type usage, with LMIC countries showing higher reliance on processed results rather than raw files, suggest that computational capacity and bandwidth constraints shape data download patterns. The dominance of raw file downloads across all regions (Figure 8A) indicates that researchers currently lack easy access to analysis results within submissions, forcing them to re-download and reprocess raw data even when search engine outputs already exist. To address this, the PRIDE team is developing dedicated

infrastructure for discovering, browsing, and downloading result and analysis files independently of the full raw dataset, enabling researchers with limited computational resources to directly access quantification tables, identification lists, and processed spectra (peak list files) without the overhead of re-running search engines. In parallel, the PRIDE team will prioritize SDRF sample metadata annotation [4] for the most downloaded and community-relevant datasets identified in this study, making these high-impact submissions immediately reusable through standardized experimental design descriptions. Several complementary efforts support this vision: `quantms` [12] generates standardized reanalysis outputs from public datasets, the PTMExchange initiative (`https://www.proteomexchange.org/ptmexchange`) provides harmonised results coming from the reanalysis of PTM-enriched datasets, and the PRIDE team is collaborating with developers of widely used search engines – including DIA-NN [13], MaxQuant [14], and MSFragger [15] – to define standardized submission guidelines that ensure result files, quantification tables, and metadata are structured for immediate reuse. More broadly, the `nf-downloadstats` pipeline and DeepLogBot framework are applicable to any EBI open data repository facing similar challenges, including genomics (ENA/SRA), structural biology (PDB), and metabolomics (MetaboLights) resources.

5 Conclusion

We present the PRIDE database download tracking infrastructure, comprising `nf-downloadstats` and DeepLogBot, and the first comprehensive analysis of PRIDE data download statistics, processing 159 million records spanning 2021–2025. After removing 88.0% of automated traffic, the remaining 19.1 million genuine downloads across 34,085 datasets and 213 countries reveal a globally distributed user base, a transition toward HTTP-based access with emerging high-throughput protocols, a highly concentrated download distribution (Gini = 0.84), and 664 institutional download hubs spanning 58 countries. These findings provide actionable insights for repository infrastructure planning, potential PRIDE mirrors placement, and demonstrate the value of bot-aware analytics for scientific data resources.

PRIDE have integrated download statistics into the PRIDE web interface, enabling data submitters to use these metrics in grant reports and publications. Through `pridepy` [10] and dedicated infrastructure for result-level data access, we aim to lower barriers for researchers (particularly in LMIC) to discover and download analysis outputs without reprocessing full raw datasets. The `nf-downloadstats` pipeline and DeepLogBot framework are freely available and applicable to any EBI open data repository facing similar challenges.

Data and Code Availability

The `nf-downloadstats` pipeline is available at `https://github.com/PRIDE-Archive/nf-downloadstats` and the DeepLogBot software at `https://github.com/ypriverol/deeplogbot`, both under the Apache 2.0 license. Download log data is available upon request from the PRIDE team.

Author contributions

S.H. implemented the Nextflow workflow and collected the data; J.B. implemented the web interface for the download statistics components; C.B. and S.K. implemented the integration of the statistics components in the backend of PRIDE and databases; D.J.K., N.S.J., B.B-H., and N.M. contributed to reviewing the manuscript, the data generated, and curated some of the datasets; M.R.D. generated the infrastructure for log anonymization and provided the log files

to the PRIDE team; J.A.V. reviewed the manuscript; Y.P-R. designed the study, developed the bot detection framework, performed the analysis, and wrote the manuscript.

Acknowledgements – Funding

This work was supported by EMBL core funding; Wellcome Trust [223745/Z/21/Z]; Biotechnology and Biological Sciences Research Council [BB/Y513829/1, BB/S01781X/1, BB/V018779/1, BB/X001911/1]; Engineering and Physical Sciences Research Council [EP/Y035984/1]. Funding for open access charge: Wellcome. We thank the PRIDE team for their support and feedback on the development of the download tracking infrastructure and analysis. We also thank Professor Bernhard Kuster for the original discussion about this topic in 2024 during the HUPO conference in Dresden.

Conflict of Interest

The authors declare no conflict of interest.

References

[1] Perez-Riverol, Y., Bandla, C., Kundu, D. J., Kamatchinathan, S. *et al.*, The PRIDE database at 20 years: 2025 update, *Nucleic Acids Res* **2025**, *53*, D543–D553, DOI 10.1093/nar/gkae1011.

[2] Wilkinson, M. D., Dumontier, M., Aalbersberg, I. J., Appleton, G. *et al.*, The FAIR Guiding Principles for scientific data management and stewardship, *Sci Data* **2016**, *3*, 160018, DOI 10.1038/sdata.2016.18.

[3] Perez-Riverol, Y., Zorin, A., Dass, G., Vu, M.-T. *et al.*, Quantifying the impact of public omics data, *Nat Commun* **2019**, *10*, 3512, DOI 10.1038/s41467-019-11461-w.

[4] Dai, C., Füllgrabe, A., Pfeuffer, J., Solovyeva, E. M. *et al.*, A proteomics sample metadata representation for multiomics integration and big data analysis, *Nat Commun* **2021**, *12*, 5854, DOI 10.1038/s41467-021-26111-3.

[5] Perez-Riverol, Y., Csordas, A., Bai, J., Bernal-Llinares, M. *et al.*, Making proteomics data accessible and reusable: current state of proteomics databases and repositories, *Proteomics* **2019**, *19*, 1800371, DOI 10.1002/pmic.201800371.

[6] Orr, M. C., Ascher, J. S., Pickering, J., AI bots threaten online scientific infrastructure, *Nature* **2025**, *641*, 852, DOI 10.1038/d41586-025-01602-1.

[7] Di Tommaso, P., Chatzou, M., Floden, E. W., Prieto Barja, P. *et al.*, Nextflow enables reproducible computational workflows, *Nat Biotechnol* **2017**, *35*, 316–319, DOI 10.1038/nbt.3820.

[8] Liu, F. T., Ting, K. M., Zhou, Z.-H., *2008 Eighth IEEE International Conference on Data Mining*, **2008**, pp. 413–422, DOI 10.1109/ICDM.2008.17.

[9] Wellcome Trust,, *Low- and middle-income countries*, `https://wellcome.org/research-funding/guidance/prepare-to-apply/low-and-middle-income-countries`, **2025**, Based on OECD DAC list. Accessed February 2026.

[10] Kamatchinathan, S., Hewapathirana, S., Bandla, C., Perez-Riverol, Y., pridepy: A Python Package to Download and Search Data from PRIDE Database, *J Open Source Softw* **2025**, *10*, 7563, DOI 10.21105/joss.07563.

[11] Perez-Riverol, Y., Proteomic repository data submission, dissemination, and reuse: key messages, *Expert Rev Proteomics* **2022**, *19*, 297–310, DOI 10.1080/14789450.2022.2160324.

[12] Dai, C., Pfeuffer, J., Wang, H., Zheng, P. *et al.*, quantms: a cloud-based pipeline for quantitative proteomics enables the reanalysis of public proteomics data, *Nat Methods* **2024**, *21*, 1603–1607, DOI 10.1038/s41592-024-02343-1.

[13] Demichev, V., Messner, C. B., Vernardis, S. I., Lilley, K. S. *et al.*, DIA-NN: neural networks and interference correction enable deep proteome coverage in high throughput, *Nat Methods* **2020**, *17*, 41–44, DOI 10.1038/s41592-019-0638-x.

[14] Cox, J., Mann, M., MaxQuant enables high peptide identification rates, individualized p.p.b.-range mass accuracies and proteome-wide protein quantification, *Nat Biotechnol* **2008**, *26*, 1367–1372, DOI 10.1038/nbt.1511.

[15] Kong, A. T., Leprevost, F. V., Avtonomov, D. M., Mellacheruvu, D. *et al.*, MSFragger: ultrafast and comprehensive peptide identification in mass spectrometry-based proteomics, *Nat Methods* **2017**, *14*, 513–520, DOI 10.1038/nmeth.4256.