Select Product

JLCPCB

Standard PCB/PCBA | Advanced PCB/PCBA | SMT Stencil | Flex Heater | Mechatronic Parts | 3D Pr

Online PCB Quote

Re-Upload | Gerber Viewer

Detected 2 layer board of 10.92×80.39mm(0.43×3.16 inches).

Base Material	FR-4 / Flex / Aluminum / Copper Core / Rogers / PTFE Teflon
Substrate Type	25μm dielectric thickness / 50μm dielectric thickness / Transparent
Layers	1 / 2 / 4
Dimensions	90.39 * 70.92 mm
PCB Qty	20
Product Type	Industrial/Consumer electronics / Aerospace / Medical

PCB Specifications

Different Design	1 / 2 / 3 / 4
Delivery Format	Single PCB / Panel by Customer / Panel by JLCPCB
PCB Thickness	0.11mm / 0.12mm / 0.2mm
Coverlay Color	Yellow / Black / White
Silkscreen	White
Copper Type	Electro-deposited / Rolled Annealed
Surface Finish	ENIG
Gold Thickness	1 U" / 2 U"

High-spec Options

Outer Copper Weight	1/3 oz / 0.5 oz / 1 oz

Charge Details

Engineering fee

Surface Finish

Stiffener

Board

Confirm Production file

Standard PCBA Price

Components

Feeders Loading fee

SMT Assembly

Hand-soldering labor fee

Manual Assembly

PCB Build Time

4-5 days

Calculated Price

Additional charges may apply for special

NEXT

Shipping Estimate

DHL Express (DDP) 2-

Weight

Coupons Save $20.00

Coverlay Thickness	PI:12.5um/AD:15um · **PI:25um/AD:25um**
Gold Fingers	**No** · Yes
EDA Software	EasyEDA Pro · **Other**

Other software cannot add stiffener layer, so stiffeners cannot be automatically detected and require manual review. Learn how to design FPC on EasyEDA Pro >

EasyEDA discount: Save $7.26 per design. (No discount with other software)

Stiffener	Without · **Polyimide** · FR4 · Stainless Steel · 3M Tape
Polyimide Thickness	0.1mm · 0.15mm · 0.20mm · 0.225mm · **0.25mm**
PI Stiffener Lift Tab	**No** · Yes
EMI Shielding Film	**Without** · Both sides (Black ,18um) · Single side (Black ,18um)
Cutting Method	**Laser Cutting** · Punching
Confirm Production file	No · **Yes**
Mark on PCB	**Remove Mark** · Order Number(Specify Position) · 2D barcode (Serial Number) · Order Number
Electrical Test	**Flying Probe Fully Test**
Silkscreen on Stiffener	**No** · Yes

Advanced Options

PCB Remark

PCB Assembly

COUPON Assembly cost starting from $0 with coupon>

Assemble top side · Assemble bottom side

PCBA Type	Economic · **Standard** · What's the difference?
Assembly Side	**Top Side** · Bottom Side · Both Sides
PCBA Qty	**20** · Custom Qty · Qty from 2 to 20
Edge Rails/Fiducials	**Added by JLCPCB** · Added by Customer

The board size is modified to 90.39mm x 70.92mm to meet standard flex PCBA requirements: each side must be longer than 70mm, and four edge rails should be added. Learn More>

Confirm Parts Placement	No	Yes	We recommend you also confirm the production file of your PCB.
Stencil Storage	No	Yes	
Fixture Storage	No	Yes	
Parts Selection	By Customer	By JLCPCB	

Advanced Options

Bake Components	No	Photo Confirmation	No
Board Cleaning	No	Conformal Coating (cleaning included)	No
Packaging	Antistatic bubble fil	Special stencil	No
Depanel boards & edge rail before delivery	No	Solder Paste	High temp.
Flying Probe Test	No	Nitrogen reflow soldering	No
Function test	No	PCBA remark	No

I agree to the Terms and Conditions of JLCPCB assembly Service .

Stencil Order together with PCB Stencil Order Guide>

© 2026 JLCPCB.COM All Rights Reserved. Privacy Policy Terms & Conditions Cookies Policy