



TUBAF
Die Ressourcenuniversität.
Seit 1765.



Application of Built-in Adaptive Remeshing and Mesh Refinement Features in Abaqus to Fracture Simulations Using Phase-field User Elements

To the Faculty of Mechanical, Process and Energy Engineering
of the Technische Universität Bergakademie Freiberg

is submitted this

Master Thesis

to attain the academic degree of

Master of Science
(M. Sc.)

Course of Study: Computational Materials Science

Submitted by: **Pruthviraja Reddy Vandavagali**

Matriculation number: 68865

1st Examiner (Supervisor): Prof. Dipl.-Ing. Björn Kiefer, Ph.D.

2nd Examiner (Reviewer): Dr.-Ing. Stephan Roth

Institute: Institute of Mechanics and Fluid Dynamics (IMFD)

Chair: Chair of Applied Mechanics – Solid Mechanics

Freiberg, 17. September 2026

Abstract

Phase-field fracture methods replace a sharp crack by a regularized field and therefore require fine spatial resolution in the fracture process zone. This thesis investigates whether Abaqus-native error-guided remeshing can provide that resolution efficiently for a phase-field formulation implemented with user elements. The present draft deliberately concentrates on the Mode-I benchmark that must be understood before state transfer or more complex fracture configurations are assessed.

A fixed-mesh single-edge-crack reference was verified first. The project simulation with 15,192 finite elements reached a peak reaction force of 0.757778 kN at 0.005857 mm. An ordinary-least-squares fit over the first 400 active increments gives the project-derived initial stiffness $K_0 = 137.945520$ kN/mm; this stiffness is not reported by Pandey and Kumar. The two-job adaptive workflow described by Pandey and Kumar was then reconstructed: a coarse Job-1_UEL pre-analysis supplies the Abaqus stress discretization error indicator MISESERR, a RemeshingRule and adaptiveRemesh generate a new mesh, and the refined mesh is converted to the layered user-element representation for the fracture analysis.

A preprocessing defect was identified in the first 71,320-element fracture deck. A malformed N_BOTTOM definition retained only 16 of 150 intended node identifiers, leaving 134 bottom nodes vertically unconstrained. Correct line wrapping restored the intended support. The corrected full-fracture calculation gave $K_0 = 137.820804$ kN/mm, $F_{\max} = 0.745325$ kN, and $u(F_{\max}) = 0.005750$ mm. An independent elastic requalification gave $K_0 = 138.021013$ kN/mm. The stiffness anomaly was therefore an input-format defect rather than a consequence of adaptive-mesh physics.

For the project reconstruction using the published Listing-1 settings, a 2,906-element coarse mesh and a 1% target tolerance produce 71,320 finite elements, whereas Pandey and Kumar report 13,941 for their proposed adaptive branch. Controlled sensitivity studies reproduce the expected trend that a larger target tolerance yields fewer elements, but they do not identify the authors' complete executed configuration. The exact count difference is consequently documented as a publication-information limitation, as accepted in the 17 September 2026 supervisor meeting. The next stage is to expose physically meaningful user-element energy quantities and establish global energy balance, complete force–displacement agreement, and spatial and temporal convergence before Mode-I state-transfer conservation is evaluated.

Declaration on the Use of AI Tools

ChatGPT, Google Gemini, and GitHub Copilot were used as supporting tools during the preparation of this thesis. The author remains fully responsible for the content and results presented.

Contents

Abstract	II
Declaration on the Use of AI Tools	III
1. Introduction and Phase-Field Foundations	1
1.1. Motivation and present scope	1
1.2. AT2 regularized fracture formulation	1
1.3. Irreversibility, history field, and staggered architecture	2
1.4. Rigorous Energy Formulation and Global Energy Balance	2
1.4.1. Energy components and mathematical definitions	2
1.4.2. Global energy balance and residual metric	3
1.4.3. Implementation and Variable Mapping	3
1.4.4. Numerical verification of the energy implementation	3
2. Mode-I Benchmark and Fixed-Mesh Reference	5
2.1. Benchmark Geometry and Sharp Seam Representation	5
2.1.1. Boundary-Condition Verification and Seam Compliance	6
2.2. Boundary-Condition Specification and Reconstruction Provenance	6
2.3. Verified Fixed-Mesh Reference Anchor	6
2.4. Resolution of the Boundary-Set Formatting Defect	7
3. Pandey–Kumar Error-Guided Adaptive Pre-Refinement and Discretization	9
3.1. Published Two-Job Adaptive Refinement Workflow	9
3.2. Physical Meaning, Indicator Provenance, and Limits of MISESeri	10
3.3. Canonical Pre-Analysis Provenance and Spatial Association	10
3.4. Adaptive Remeshing Reproduction: 71,320 vs 13,941 Elements	12
3.5. Theoretical Foundations for State-Transfer Energy Conservation	13
4. Current Status: Mode-I Verification, UEL Energy Audit, and Multifaceted Convergence	14
4.1. Introduction and Milestone Governance	14
4.2. Governing Mathematical Energy Formulation and Bookkeeping Identity	15
4.2.1. Exact implemented discrete energy terms	15
4.2.2. Discrete non-existence proof and multi-term decomposition	15
4.2.3. Layer decoupling and Gauss-point deduplication	16
4.3. Audit of Runtime Diagnostic Job 1406839 and Persistence Integrity	16
4.3.1. Bit-for-bit mechanical parity verification	16
4.3.2. Historical baseline vs. energy-qualified production UEL parity	19
4.3.3. Unit 105/106 logging persistence reconciliation	19
4.3.4. Unit 107 sampled call-order qualification	20
4.4. Spatial Mesh Convergence and Resolution Ratio Evaluation	20
4.4.1. Classification of stiffness vs. peak response	20

4.4.2.	Comparability boundary: terminal vs. matched-displacement work .	20
4.4.3.	Physical length scale (l_0) sensitivity study	21
4.5.	Temporal Time-Increment Convergence	24
4.6.	Native Adaptive Remeshing and Lineage Separation	26
4.6.1.	Lineage reconciliation: sensitivity study vs. production batch	26
4.6.2.	Corrected adaptive response and temporal twin	26
4.7.	Crack-Path Symmetry and Localization Profile Audit	27
4.7.1.	Phase-field damage contours at matched displacements	27
4.7.2.	Ligament damage profiles and boundary propagation	29
4.7.3.	Rigorous distinction between crack-centroid trajectory and localization- band width	29
4.8.	Authoritative Master Production Matrix and Convergence Classifications . .	33
4.8.1.	Multi-quantity convergence classification matrix	33
4.9.	Summary of Active Scientific Findings	35
4.10.	Compact Supervisor-Facing Gate-6B Claim Ledger	35

List of Figures

2.1. Mode-I benchmark boundary value problem: 1.0 mm $\times$ 1.0 mm square domain with a sharp edge crack of length $a_0 = 0.5$ mm at $y = 0.5$ mm. Boundary conditions prescribe roller support ($u_y = 0$) along the bottom edge with a pinned point ($u_x = 0$) to eliminate rigid-body translation, and uniform tensile displacement $u_y = u$ on the top boundary.	5
2.2. Force–displacement comparison between the canonical fixed-mesh S_1 reference (15,192 finite elements) and the corrected native-adaptive A_1 model with errorTarget = 1% (71,320 finite elements). The initial structural stiffness differs by only 0.09%, while the adaptive peak reaction force is approximately 1.64% below the reference value.	8
3.1. Schematic of the Pandey–Kumar two-job adaptive pre-refinement workflow: a linear-elastic pre-analysis on a coarse grid generates the MISESeri error indicator field, which drives Abaqus native adaptiveRemesh before reconstructing the multi-layer UEL/UMAT phase-field model for the full fracture calculation.	9
3.2. Defensible qualitative interpretation of MISESeri under uniform-error sizing: high recovered stress gradients near geometric singularities drive local element refinement; this relationship is directional and does not imply a simple algebraic formula from MISESeri directly to element size.	10
3.3. Canonical Mode-I MISESeri error indicator field evaluated on the 2,906-element coarse mesh. High error concentrations cluster around the initial sharp crack tip ($x = 0.5$ mm, $y = 0.5$ mm), defining the targeted refinement zone.	11
3.4. Comparison between (a) the initial coarse mesh (2,906 finite elements) and (b) the resulting error-guided adapted mesh (71,320 finite elements) generated by Abaqus native adaptiveRemesh	11
3.5. Observed spatial association between coarse MISESeri error indicator values and the adapted local finite element edge length h . Regions with higher stress discretization error receive refined element sizes.	12
4.1. Global energy evolution and two-term bookkeeping difference for baseline Case S_1 (15,192 mesh cells / 45,576 Abaqus element objects). In the linear-elastic regime ($u < 0.005$ mm), $W_{\text{ext}} = E_{\text{elas}}$ with relative difference $< 10^{-4}$ %. During post-peak crack propagation, stored elastic strain energy converts into fracture surface energy, satisfying $W_{\text{ext}} \approx E_{\text{frac}}$ with terminal difference $\mathcal{R}_{\text{bookkeeping}} < 0.77$ %.	18

4.2. Mode-I tensile force-displacement response for the spatial fixed-mesh series (S_1 – S_4). Incomplete cases (S_2, S_3, S_4) terminate at their real post-peak cutback states ($u = 6.82, 7.84, 7.21 \mu\text{m}$, marked by circles). All cases reproduce identical linear-elastic stiffness ($K_0 \approx 137.9 \text{ kN/mm}$); peak load shows systematic mesh sensitivity.	21
4.3. Spatial convergence metrics as a function of discretization ratio h/l_0 : (a) initial structural stiffness K_0 is exceptionally stable ($\Delta < 0.09\%$); (b) peak force F_{max} exhibits monotonic mesh sensitivity (4.26% variation); (c) peak displacement u_{peak} decreases from $5.86 \mu\text{m}$ to $5.58 \mu\text{m}$	22
4.4. Three-point physical length-scale study on fixed S_3 mesh ($h = 1.5 \mu\text{m}$): (a) global force-displacement overlay and (b) variation of $K_0, F_{\text{max}}, u_{\text{peak}}$, and matched W_{trap} at $u = 5.50 \mu\text{m}$ with l_0	22
4.5. Mode-I temporal convergence across time increment scales (T_1 : coarse $2\times$, T_2 : nominal $1\times$, T_3 : fine $0.5\times$, Job 1406317). The mechanical peak response is virtually identical ($F_{\text{max}} \in [0.7576, 0.7582] \text{ kN}$, spread $< 0.07\%$).	24
4.6. Temporal discretization scaling of global energy components across schedules T_1 ($2\times$), T_2 ($1\times$), and T_3 ($0.5\times$, Job 1406317) on fixed S_1 mesh: (a) boundary work $W_{\text{trap}}(u)$; (b) stored elastic energy $E_{\text{elas}}(u)$; (c) fracture surface energy $E_{\text{frac}}(u)$; (d) two-term bookkeeping difference $\mathcal{R}_{\text{bookkeeping}}(u)$	25
4.7. Abaqus-native adaptive meshes generated for the Mode-I benchmark using errorTarget values of (a) 1%, (b) 2%, (c) 3%, and (d) 5%. The corresponding production meshes contain 71,320, 15,396, 7,633, and 4,194 underlying finite elements, respectively. Full-domain views and identical crack-tip zooms illustrate how relaxing the target error changes the spatial refinement distribution.	26
4.8. Force–displacement response of the canonical uniform reference S_1 and native adaptive meshes A_1 – A_4 : (a) full response over $u \in [0, 10] \mu\text{m}$; (b) post-peak zoom over $u \in [5.4, 10] \mu\text{m}$. Production adaptive meshes contain 71,320, 15,396, 7,633, and 4,194 underlying finite elements for errorTarget values of 1%, 2%, 3%, and 5%, respectively. A_1 terminates at $u = 6.77 \mu\text{m}$, whereas A_2 – A_4 reach $10 \mu\text{m}$	27
4.9. Matched-displacement phase-field damage contours comparing canonical reference S_1 (15,192 elements) and corrected native adaptive meshes A_1 – A_4 across deformation states: (a) initiation at $u = 5.00 \mu\text{m}$; (b) pre-peak concentration at $u = 5.50 \mu\text{m}$; (c) peak / crack initiation at $u \approx 5.85 \mu\text{m}$; (d) post-peak propagated crack at $u = 6.20 \mu\text{m}$	28
4.10. Visual evolution of Mode-I crack propagation for the canonical S_1 reference baseline: six-stage sequence from initial elastic localization ($u = 5.0 \mu\text{m}$) through peak load ($u = 5.857 \mu\text{m}$) to complete ligament separation ($u = 6.20 \mu\text{m}$).	29
4.11. Spatial phase-field ligament profiles $d(x, y = 0.5 \text{ mm})$ for fixed meshes S_1 – S_4 across matched displacement levels, showing x-axis coordinates on all panels and annotating full boundary propagation in S_1 at $u = 6.20 \mu\text{m}$	30
4.12. Spatial phase-field ligament profiles $d(x, y = 0.5 \text{ mm})$ comparing canonical reference S_1 against native adaptive meshes A_1 – A_4 across matched displacement levels.	31

4.13. Rigorous separation of crack-centroid trajectory and damage localization band width: (a) damage-weighted crack-centroid vertical deviation $ y_c - 0.5 \text{ mm} \leq 3.1 \mu\text{m}$ across all meshes confirms strict Mode-I symmetry within element bounds; (b) regularized damage localization-band half-width for $d \geq 0.50$ (10–15 μm , total full-width 20.0–30.0 μm overall, 20.0–22.9 μm at $x = 0.55 \text{ mm}$, mesh-sensitive and resolution-limited).	32
---	----

List of Tables

1.1. Authoritative Energy Variable Map for the qualified <code>f42_mixed_uel.for</code> formulation.	4
2.1. Material and phase-field constitutive parameters for the Mode-I benchmark [6].	5
2.2. Verified quantitative metrics for the fixed-mesh reference anchor (Job 1406015).	7
2.3. Mechanical response recovery after resolving the <code>N_BOTTOM</code> keyword formatting defect.	7
4.1. Global energy bookkeeping audit for completed uniform mesh cases (15,192 mesh cells / 45,576 Abaqus element objects, $u = 0.010$ mm).	17
4.2. Matched-displacement external work W_{trap} [kN · mm] and reaction force F [kN] across spatial, temporal, and adaptive cases inside the common displacement horizon.	23
4.3. Three-point physical length-scale (l_0) sensitivity study on fixed S_3 mesh (41,912 finite elements, $h_{\text{tip}} \approx 1.5 \mu\text{m}$).	23
4.4. Complete 16-case Mode-I production matrix and energy bookkeeping summary with exact job provenance and separate classifications.	33
4.5. Comprehensive Supervisor Convergence Status Matrix across Spatial, Temporal, and Energetic Quantities.	34
4.6. Compact Supervisor-Facing Gate-6B Claim Ledger across 13 Core Metrics.	37

1. Introduction and Phase-Field Foundations

1.1. Motivation and present scope

Brittle fracture is governed by the initiation, propagation, and coalescence of displacement discontinuities. Conventional finite-element descriptions must track these discontinuities explicitly through discrete remeshing or enrich the approximation space as cracks advance. Variational phase-field fracture regularizes the sharp crack surface into a continuous scalar field $d \in [0, 1]$, where $d = 0$ denotes intact material and $d = 1$ denotes fully developed fracture. Crack initiation, curving, branching, and merging are thereby captured naturally without ad-hoc geometric tracking criteria [1, 2, 4, 5].

This regularization comes with a strict numerical resolution requirement: the diffuse crack profile is controlled by a regularization length scale l_0 , requiring finite-element sizes $h \ll l_0$ along the crack trajectory. Uniform global refinement places small elements throughout large, remotely loaded elastic zones where they add severe computational burden without improving crack-path accuracy. Error-guided adaptive refinement is therefore attractive because it concentrates fine elements selectively in high-gradient and high-error regions.

Following supervisor guidance, this interim thesis work is strictly anchored to the foundational Mode-I fracture problem. Before escalating model complexity, the complete physical, numerical, and energetic properties of the baseline formulation must be fully understood and verified.

1.2. AT2 regularized fracture formulation

Let $\Omega \subset \mathbb{R}^2$ denote the specimen domain, $\mathbf{u}$ the displacement vector field, and d the phase field. In the standard AT2 regularization [1, 2], the total potential energy functional is

$$\Pi(\mathbf{u}, d) = \int_{\Omega} \left[g(d) \psi_e^+(\boldsymbol{\varepsilon}) + \psi_e^-(\boldsymbol{\varepsilon}) + \frac{G_c}{2l_0} d^2 + \frac{G_c l_0}{2} |\nabla d|^2 \right] d\Omega - W_{\text{ext}}, \quad (1.1)$$

where G_c is the critical fracture energy release rate, l_0 is the regularizing length scale, and $\boldsymbol{\varepsilon} = \frac{1}{2}(\nabla \mathbf{u} + \nabla \mathbf{u}^T)$ is the small-strain tensor.

The degraded elastic strain energy density is governed by the quadratic degradation function:

$$g(d) = (1 - d)^2 + k, \quad (1.2)$$

where $k = 1.0 \times 10^{-7}$ is a small residual stiffness parameter preventing numerical singularity when $d \rightarrow 1$. The crack surface energy density functional $\gamma(d, \nabla d)$ penalizes both the phase-field magnitude and its spatial gradient:

$$\gamma(d, \nabla d) = \frac{1}{2l_0} d^2 + \frac{l_0}{2} |\nabla d|^2, \quad (1.3)$$

which Γ -converges to the Griffith sharp crack surface energy as $l_0 \rightarrow 0$ [2].

1.3. Irreversibility, history field, and staggered architecture

Fracture irreversibility ($\dot{d} \geq 0$) is enforced through a local history field $\mathcal{H}(\mathbf{x}, t)$:

$$\mathcal{H}(\mathbf{x}, t) = \max_{\tau \in [0, t]} \psi_0^+(\mathbf{x}, \tau), \quad (1.4)$$

where ψ_0^+ is the undegraded tensile driving energy density. In plane-strain linear elasticity with Lamé parameters λ and μ :

$$\psi_0^+(\boldsymbol{\varepsilon}) = \frac{1}{2} \lambda \langle \text{tr}(\boldsymbol{\varepsilon}) \rangle_+^2 + \mu \left(\varepsilon_{11}^2 + \varepsilon_{22}^2 + 2\varepsilon_{12}^2 \right). \quad (1.5)$$

The staggered solution scheme decouples the governing partial differential equations into two alternating subproblems at each load increment:

1. **Mechanical subproblem:** solve for displacement $\mathbf{u}_{n+1}$ given the lagged phase field d_n :

$$\int_{\Omega} [g(d_n) \mathbb{C}_0 : \boldsymbol{\varepsilon}(\mathbf{u}_{n+1})] : \boldsymbol{\varepsilon}(\delta \mathbf{u}) \, d\Omega = \int_{\partial\Omega_t} \mathbf{t} \cdot \delta \mathbf{u} \, d\Gamma. \quad (1.6)$$

2. **Phase-field subproblem:** solve for phase field d_{n+1} given the updated driving history $\mathcal{H}_{n+1}$:

$$\int_{\Omega} \left[G_c \left(\frac{d_{n+1}}{l_0} \delta d + l_0 \nabla d_{n+1} \cdot \nabla \delta d \right) - 2(1 - d_{n+1}) \mathcal{H}_{n+1} \delta d \right] d\Omega = 0. \quad (1.7)$$

In the Abaqus implementation, these subproblems are executed through co-located user element (UEL) layers exchanging transactional state via dedicated shared common blocks, while passive visualizer elements (UMAT) expose the underlying field variables to the Abaqus output database (ODB).

1.4. Rigorous Energy Formulation and Global Energy Balance

A central requirement established by the supervisor is that convergence and mesh adequacy must be evaluated through global energetic measures and energy balance, rather than peak reaction force alone.

1.4.1. Energy components and mathematical definitions

For the implemented staggered formulation, four fundamental global energy quantities are defined with consistent units of $\text{kN} \cdot \text{mm}$ (J):

1. **Stored Recoverable Elastic Strain Energy (Ψ_{elastic}):**

$$\Psi_{\text{elastic}}(\mathbf{u}, d) = \int_{\Omega} \psi_e(\boldsymbol{\varepsilon}, d) \, d\Omega = \int_{\Omega} \frac{1}{2} \boldsymbol{\sigma} : \boldsymbol{\varepsilon} \, d\Omega = \int_{\Omega} \frac{1}{2} g(d) \boldsymbol{\varepsilon} : \mathbb{C}_0 : \boldsymbol{\varepsilon} \, d\Omega. \quad (1.8)$$

2. Dissipated Fracture Surface Energy (Ψ_{frac}):

$$\Psi_{\text{frac}}(d) = \int_{\Omega} G_c \gamma(d, \nabla d) \, d\Omega = \int_{\Omega} G_c \left[\frac{1}{2l_0} d^2 + \frac{l_0}{2} |\nabla d|^2 \right] \, d\Omega. \quad (1.9)$$

3. Total Internal Potential Energy (Ψ_{total}):

$$\Psi_{\text{total}}(\mathbf{u}, d) = \Psi_{\text{elastic}}(\mathbf{u}, d) + \Psi_{\text{frac}}(d). \quad (1.10)$$

4. External Mechanical Work (W_{ext}):

$$W_{\text{ext}}(u) = \int_0^u F(\tilde{u}) \, d\tilde{u} \approx \sum_{i=1}^{N_{\text{inc}}} \frac{F_i + F_{i-1}}{2} (u_i - u_{i-1}). \quad (1.11)$$

1.4.2. Global energy balance and residual metric

In an exact quasi-static fracture process, the work done by external forces equals the sum of stored elastic strain energy and dissipated crack surface energy. In the staggered numerical formulation, the global energy balance identity is:

$$W_{\text{ext}}(u) = \Psi_{\text{elastic}}(u) + \Psi_{\text{frac}}(u) + \mathcal{D}_{\text{num}}(u), \quad (1.12)$$

where $\mathcal{D}_{\text{num}}$ represents numerical dissipation introduced by the finite time-increment size and alternate minimization split. To quantify global energy conservation, the energy residual R_E and normalized relative error η_E are defined:

$$R_E(u) = W_{\text{ext}}(u) - (\Psi_{\text{elastic}}(u) + \Psi_{\text{frac}}(u)), \quad \eta_E(u) = \frac{|R_E(u)|}{\max(W_{\text{ext}}(u), \Psi_{\text{total}}(u), 10^{-10})} \times 100 \%. \quad (1.13)$$

1.4.3. Implementation and Variable Mapping

Table 1.1 details the exact implementation map across the UEL and UMAT subroutines.

1.4.4. Numerical verification of the energy implementation

The energy-instrumented UEL was verified on a 64-quad element cracked benchmark ($1.0 \times 1.0 \text{ mm}$, $a_0 = 0.5 \text{ mm}$). The test demonstrated:

- In the linear elastic stage ($u = 0.0010 \text{ mm}$): $W_{\text{ext}} = 7.285055 \times 10^{-5} \text{ kN} \cdot \text{mm}$, $\Psi_{\text{elastic}} = 7.280335 \times 10^{-5} \text{ kN} \cdot \text{mm}$, $\Psi_{\text{frac}} = 5.089 \times 10^{-8} \text{ kN} \cdot \text{mm}$, giving an energy balance error of $\eta_E = 0.065 \%$.
- At full tensile loading ($u = 0.0060 \text{ mm}$): $W_{\text{ext}} = 2.562345 \times 10^{-3} \text{ kN} \cdot \text{mm}$, $\Psi_{\text{elastic}} = 2.501643 \times 10^{-3} \text{ kN} \cdot \text{mm}$, $\Psi_{\text{frac}} = 6.323756 \times 10^{-5} \text{ kN} \cdot \text{mm}$, $\Psi_{\text{total}} = 2.564881 \times 10^{-3} \text{ kN} \cdot \text{mm}$, yielding a residual $R_E = -2.535 \times 10^{-6} \text{ kN} \cdot \text{mm}$ and a relative error $\eta_E = 0.0989 \% < 0.1 \%$.
- Mechanical parity with the uninstrumented formulation was preserved with zero divergence in reaction forces or displacements.

Tab. 1.1.: Authoritative Energy Variable Map for the qualified `f42_mixed_uel.for` formulation.

Code Variable	Physical / Mathematical Quantity	Equation	Units	Output Channel
E_ELAS_ELEM	Element Elastic Strain Energy	$\int_{\Omega_e} \frac{1}{2} \boldsymbol{\sigma} : \boldsymbol{\varepsilon} \, d\Omega$	kN · mm	ENERGY(2) → ALLSE, SVARS(17), STATEV(18)
E_FRAC_ELEM	Element Fracture Surface Energy	$\int_{\Omega_e} G_c \gamma(d, \nabla d) \, d\Omega$	kN · mm	ENERGY(7), SVARS(17), STATEV(17)
PSI_E_PT	Elastic Strain Energy Density	$\frac{1}{2} \boldsymbol{\sigma} : \boldsymbol{\varepsilon}$	kN/mm ²	SVARS(18), STATEV(20)
PSI_F_PT	Fracture Energy Density	$G_c \gamma(d, \nabla d)$	kN/mm ²	SVARS(18), STATEV(19)
W_ext	Global External Work	$\int_0^u F \, du$	kN · mm	ALLWK, trapz post-processing
TOT_E_INT	Total Internal Energy	$\Psi_{\text{elastic}} + \Psi_{\text{frac}}$	kN · mm	ALLIE, uel_energy_balance.csv

2. Mode-I Benchmark and Fixed-Mesh Reference

2.1. Benchmark Geometry and Sharp Seam Representation

The foundational benchmark is a $1.0 \text{ mm} \times 1.0 \text{ mm}$ square plate containing an initial edge crack of length $a_0 = 0.5 \text{ mm}$ located along the horizontal symmetry line $y = 0.5 \text{ mm}$ (Fig. 2.1). The crack is modeled as a zero-gap sharp seam with duplicate, coincident nodal pairs rather than a finite-width notch.




Fig. 2.1.: Mode-I benchmark boundary value problem: $1.0 \text{ mm} \times 1.0 \text{ mm}$ square domain with a sharp edge crack of length $a_0 = 0.5 \text{ mm}$ at $y = 0.5 \text{ mm}$. Boundary conditions prescribe roller support ($u_y = 0$) along the bottom edge with a pinned point ($u_x = 0$) to eliminate rigid-body translation, and uniform tensile displacement $u_y = u$ on the top boundary.

Tab. 2.1.: Material and phase-field constitutive parameters for the Mode-I benchmark [6].

Parameter	Symbol	Value	Units / Description
Young's modulus	E	210.0	GPa (kN/mm^2)
Poisson's ratio	ν	0.30	—
Critical fracture energy release rate	G_c	2.7×10^{-3}	kN/mm (2.7 N/mm)
Phase-field regularization length scale	l_0	0.0075	mm ($7.5 \mu\text{m}$)
Residual stiffness parameter	k_{res}	1.0×10^{-7}	Artificial residual stiffness

2.1.1. Boundary-Condition Verification and Seam Compliance

A vital physical distinction must be drawn between the material Young's modulus $E = 210.0$ GPa and the global initial structural stiffness K_0 :

$$K_0 = \left. \frac{dF}{du} \right|_{\text{initial elastic range}} \approx \frac{\Delta F}{\Delta u}. \quad (2.1)$$

During initial model verification, representing the crack as a finite-width notch was found to introduce substantial artificial compliance ($K_0 \approx 75.47$ kN/mm). The geometry was therefore corrected to the required zero-gap sharp seam before the governed convergence and adaptive-remeshing studies were performed. All subsequent results use the corrected sharp-seam geometry.

2.2. Boundary-Condition Specification and Reconstruction Provenance

The boundary conditions governing the Mode-I benchmark are:

- **Bottom Boundary** ($y = 0.0$ mm): Vertical displacement is fixed ($u_y = 0.0$) across all bottom nodes (N_BOTTOM). A single reference point or midpoint node is restrained in the horizontal direction ($u_x = 0.0$) to eliminate rigid-body motion without over-constraining Poisson contraction.
- **Top Boundary** ($y = 1.0$ mm): Prescribed uniform tensile displacement loading $u_y = u(t)$ applied monotonically.
- **Crack Flanks and Lateral Edges** ($x = 0, 1.0$ mm): Traction-free boundaries with natural boundary conditions for the phase field $\nabla d \cdot \mathbf{n} = 0$.

2.3. Verified Fixed-Mesh Reference Anchor

The fixed-mesh reference solution, Job 1406015.mm_{master02} (S_1 , 15,192 finite elements, 15,522 total node entries), serves as the authoritative quantitative anchor against which all adaptive remeshing results are evaluated. Under quasi-static displacement-controlled tension, the specimen exhibits linear elasticity up to damage localization, reaching a peak reaction force $F_{\max} = 0.757778$ kN at $u(F_{\max}) = 0.005857$ mm, followed by sharp post-peak softening as the crack propagates horizontally through the remaining ligament.

Initial structural stiffness is extracted using an unconstrained ordinary-least-squares (OLS) linear fit over the initial $N = 400$ active increments ($u \leq 1.0$ μm):

$$F_i = K_0 u_i + b + \epsilon_i, \quad \boxed{K_0 = 137.945520 \text{ kN/mm}}, \quad (2.2)$$

with intercept $b = 4.472368 \times 10^{-5}$ kN and coefficient of determination $R^2 = 0.99999960$. Digitized values from Pandey and Kumar [6] (Fig. 7(a)) report $F_{\max} \approx 0.758$ kN and $u(F_{\max}) \approx 0.005860$ mm, demonstrating excellent numerical agreement (Table 2.2). Historical Job 1398090.mm_{master02} is preserved as documented baseline evidence.

Tab. 2.2.: Verified quantitative metrics for the fixed-mesh reference anchor (Job 1406015).

Quantity	Symbol	Value	Source / Extraction Method
Finite element count	N_{mesh}	15,192	Structured CPE4 mesh
Total node entries	N_{nodes}	15,522	Layer 1/2/3 coincident nodes + RP
Peak reaction force	F_{max}	0.757778 kN	Sum of top reaction forces R_y
Peak displacement	$u(F_{\text{max}})$	0.005857 mm	Prescribed stroke at limit load
Initial structural stiffness	K_0	137.945520 kN/mm	OLS fit ($N = 400, u \leq 1.0 \mu\text{m}$)
OLS intercept	b	4.472368×10^{-5} kN	Intercept from linear regression
Coefficient of determination	R^2	0.99999960	Goodness of fit

2.4. Resolution of the Boundary-Set Formatting Defect

During initial deployment of the native adaptive 71,320-element mesh (historical Job 1399632), an apparent stiffness deficit was observed ($K_0 \approx 122.38$ kN/mm, -11.28%). Forensic audit revealed that this was caused by an Abaqus keyword input card limit: the node set N_BOTTOM contained 150 node identifiers formatted on a single data line without GENERATE. Abaqus pre silently parsed only the first 16 node identifiers and omitted the remaining 134 entries.

Wrapping the node identifiers across valid data lines (≤ 16 entries per card) restored all 150 vertical boundary constraints. The defect was independently verified and is classified as **RESOLVED_AND_CLOSED**; all subsequent adaptive results use the corrected boundary-condition definition.

The corrected input deck was verified in authoritative full-fracture Job 1404933 and frozen elastic Job 1405044. As shown in Table 2.3 and Fig. 2.2, proper boundary set wrapping restores initial stiffness to $K_0 = 137.820804$ kN/mm (-0.09% vs reference anchor), definitively resolving this diagnostic issue.

Tab. 2.3.: Mechanical response recovery after resolving the N_BOTTOM keyword formatting defect.

Case Description	Job ID	Elements	K_0 [kN/mm]	F_{max} [kN]	Status / Governed Role
Fixed Reference Anchor (S_1)	1406015	15,192	137.945520	0.757778	Canonical reference anchor
Corrected Full Fracture (A_1)	1404933	71,320	137.820804	0.745325	Production 1% adaptive mesh
Frozen Requalification	1405044	71,320	138.021013	–	Independent elastic verification



Force--Displacement Comparison: Canonical S_1 Reference vs Corrected A_1 Adaptive Mesh

Fig. 2.2.: Force-displacement comparison between the canonical fixed-mesh S_1 reference (15,192 finite elements) and the corrected native-adaptive A_1 model with $\text{errorTarget} = 1\%$ (71,320 finite elements). The initial structural stiffness differs by only 0.09%, while the adaptive peak reaction force is approximately 1.64% below the reference value.

3. Pandey–Kumar Error-Guided Adaptive Pre-Refinement and Discretization

3.1. Published Two-Job Adaptive Refinement Workflow

Pandey and Kumar [6] propose an automated two-job pre-refinement strategy that refines the discretization prior to nonlinear fracture initiation, avoiding dynamic mid-analysis remeshing. The workflow comprises:



Abaqus-native error-guided pre-refinement workflow




Fig. 3.1.: Schematic of the Pandey–Kumar two-job adaptive pre-refinement workflow: a linear-elastic pre-analysis on a coarse grid generates the MISESeri error indicator field, which drives Abaqus native `adaptiveRemesh` before reconstructing the multi-layer UEL/UMAT phase-field model for the full fracture calculation.

In this architecture, the initial coarse model (Job–1) is analyzed under linear elasticity. The recovered stress field yields an element-level error indicator field (MISESeri). Abaqus evaluates sizing requirements using a specified `RemeshingRule`, and the native `adaptiveRemesh` engine remeshes the geometric part. A Python post-processing filter then converts the adapted mesh into coincident user element (UEL) layers (Layer 1: Phase field d , Layer 2: Mechanical $\mathbf{u}$) and companion visualization elements (Layer 3: UMAT CPE4/CPE3).

3.2. Physical Meaning, Indicator Provenance, and Limits of MISESeri

A rigorous physical understanding of MISESeri is essential to avoid misinterpreting the driving mechanism:

- **Definition:** MISESeri is the Abaqus stress discretization error indicator associated with the recovered von Mises stress field in linear continuum elasticity [3].
- **What it is NOT:** It is **not** a phase-field error indicator, **not** a damage error, and **not** a measure of fracture energy balance.
- **Theoretical Basis:** It builds upon Zienkiewicz–Zhu-type patch recovery techniques [7, 8], estimating local discretization error $e_\sigma = \sigma^* - \sigma_h$ from smoothed stresses σ^* .




Fig. 3.2.: Defensible qualitative interpretation of MISESeri under uniform-error sizing: high recovered stress gradients near geometric singularities drive local element refinement; this relationship is directional and does not imply a simple algebraic formula from MISESeri directly to element size.

In the Python remeshing script defined in Listing 1 of Pandey and Kumar [6]:

```

variables=('MISESeri',), sizingMethod=UNIFORM_ERROR,
errorTarget=1.0, refinementFactor=10,
coarseningFactor=NOT_ALLOWED

```

The parameter `errorTarget=1.0` denotes a 1.0% target error tolerance under the `UNIFORM_ERROR` sizing strategy. It does **not** denote $\text{MISESeri} = 1.0$, $\text{MISESeri} \geq 1.0$, or refinement of 1% of the elements. Similarly, `errorTarget=2.0` represents a 2.0% target tolerance, not $\text{MISESeri} = 2.0$.


3.3. Canonical Pre-Analysis Provenance and Spatial Association

The canonical Mode-I pre-analysis mesh contains:

- 2,906 finite elements (2,818 bilinear CPE4 quads + 88 linear CPE3 triangles);
- 2,988 nodes (accounting for duplicate crack seam nodes);
- Exactly 2,906 scalar `WHOLE_ELEMENT` MISESeri indicator values (Fig. 3.3).


Applying the `RemeshingRule` with `errorTarget=1.0%` and `coarseningFactor=NOT_ALLOWED` produces the adapted mesh shown in Fig. 3.4. Because coarsening is prohibited, background regions retain the coarse seed ($h \approx 0.02$ mm), while the crack process corridor is refined down to $h \approx 0.001$ mm, generating 71,320 finite elements.

Figure 3.1: Canonical Mode-I Coarse Mesh MISESERI Distribution
 $(N_{\text{elem}} = 2,906, 5,812 \text{ Duplicate-Collapsed Values, Abaqus 2023})$




Note: MISESERI is a recovered von Mises stress discretization error indicator (Zienkiewicz-Zhu stress recovery); it is NEITHER phase-field error NOR damage error.

Fig. 3.3.: Canonical Mode-I MISESERI error indicator field evaluated on the 2,906-element coarse mesh. High error concentrations cluster around the initial sharp crack tip ($x = 0.5 \text{ mm}, y = 0.5 \text{ mm}$), defining the targeted refinement zone.



(a) Coarse mesh (2,906 elements)



(b) Adapted mesh (71,320 elements)

Fig. 3.4.: Comparison between (a) the initial coarse mesh (2,906 finite elements) and (b) the resulting error-guided adapted mesh (71,320 finite elements) generated by Abaqus native adaptiveRemesh.

As shown in Fig. 3.5, the adapted element size correlates strongly with the initial coarse error indicator field: regions with elevated MISESeri receive small elements ($h \leq 0.002$ mm), confirming the spatial efficacy of the error-driven adaptivity.




Fig. 3.5.: Observed spatial association between coarse MISESeri error indicator values and the adapted local finite element edge length h . Regions with higher stress discretization error receive refined element sizes.

3.4. Adaptive Remeshing Reproduction: 71,320 vs 13,941 Elements

Pandey and Kumar [6] report an element count of $\approx 13,941$ for their adapted Mode-I mesh, whereas applying the published Listing 1 parameters strictly to the complete domain yields 71,320 finite elements.

Supervisor Decision and Phase Closure. On 17 September 2026, the supervisor formally reviewed this discrepancy and established the governing decision:

SUPERVISOR_ACCEPTED_REPRODUCTION_LIMITATION_CLOSED

The supervisor explicitly accepted that:

1. The complete original implementation code of the authors is unavailable;
2. The publication does not expose enough information to reproduce every reported element count identically;
3. The project has tested all accessible justified variables (ruling out Abaqus release differences, load scaling, and remeshing controls);
4. Reproduction of general adaptivity trends is fully sufficient;
5. Further effort attempting to force exact element-count matching is not scientifically justified.

Preserved Sensitivity Trends. Parametric sensitivity sweeps of `errorTarget` establish the following consistent trend across four tolerance levels:

- `errorTarget` = 1.0% $\rightarrow$ 71,320 finite elements;
- `errorTarget` = 2.0% $\rightarrow$ 17,687 finite elements (offline study) / 15,396 finite elements (production batch);
- `errorTarget` = 3.0% $\rightarrow$ 8,120 finite elements (offline study) / 7,633 finite elements (production batch);
- `errorTarget` = 5.0% $\rightarrow$ 4,356 finite elements (offline study) / 4,194 finite elements (production batch).

The slight count variation between the offline sensitivity study and the production HPC runs is preserved as documented evidence. Both lineages confirm that increasing `errorTarget` relaxes the refinement constraint and reduces the final element count monotonically.

3.5. Theoretical Foundations for State-Transfer Energy Conservation

While the two-job pre-refinement workflow avoids mid-analysis state interpolation, general dynamic adaptivity during crack propagation requires projecting active state fields across non-conforming finite element meshes (Gate 6C).

Let Ω_m denote the mesh at increment n , and Ω_{m+1} the newly adapted discretization. The active state vector is:

$$\mathbf{S}^m = \{\mathbf{u}^m(\mathbf{x}), d^m(\mathbf{x}), \mathcal{H}^m(\mathbf{x})\}, \quad (3.1)$$

where $\mathbf{u}^m$ is the displacement field, d^m is the phase-field damage, and $\mathcal{H}^m$ is the strain-history field. Mapping to Ω_{m+1} via projection operators $\Pi_u, \Pi_d, \Pi_{\mathcal{H}}$ changes the total internal potential energy from E_{total}^- to E_{total}^+ :

$$\Delta E_{\text{transfer}} = E_{\text{total}}^+ - E_{\text{total}}^-. \quad (3.2)$$

Thermodynamic consistency and conservation require three fundamental criteria:

1. **Damage Monotonicity (Crack Irreversibility):** $d^{m+1}(\mathbf{x}) \geq d^m(\mathbf{x})$ pointwise $\forall \mathbf{x} \in \Omega$.
2. **Energy Preservation Bound:** $|\Delta E_{\text{transfer}}|/W_{\text{ext}} < \epsilon_{\text{tol}} \ll 1.0\%$.
3. **Equilibrium Relaxation:** A zero-load Newton-Raphson relaxation step must be performed on Ω_{m+1} to equilibrate out-of-balance forces before resuming displacement loading.

These criteria define the active foundation for subsequent Gate 6C state-transfer investigations.

4. Current Status: Mode-I Verification, UEL Energy Audit, and Multifaceted Convergence

4.1. Introduction and Milestone Governance

Following the governing supervisor directive of 17 September 2026, the active scientific phase of this research is formally designated as:

MODE1_ENERGY_CONVERGENCE_AND_STATE_TRANSFER_FOUNDATIONS_ACTIVE

The supervisor established the fundamental principle: *"We need to have understood everything related to the first model before we increase complexity."* Under this directive, all scientific activity is concentrated strictly on the qualified Mode-I benchmark before increasing geometric, boundary, or multi-axial loading complexity. The governance status of the core workstreams is defined as follows:

- **71,320-Mesh Stiffness Defect: RESOLVED_AND_CLOSED.** An Abaqus keyword parser limit of 16 entries per data line silently omitted 134 of 150 bottom constraint nodes in earlier mesh files. Wrapping the node definitions across valid lines resolved the anomaly completely, restoring full structural stiffness ($K_0 = 137.82 \text{ kN/mm}$, $\Delta = -0.09\%$ vs. canonical baseline), as verified in Jobs 1405044 and 1404933.
- **13,941 vs. 71,320 Reproduction: CLOSED_WITH_SUPERVISOR_ACCEPTED_PUBLICATION_LIMITATION.** The supervisor explicitly accepted that the publication by Pandey & Kumar (2025) does not expose sufficient implementation details to reproduce every reported element count exactly. The documented sensitivity trends (1.0% $\rightarrow$ 71,320; 2.0% $\rightarrow$ 17,687; 3.0% $\rightarrow$ 8,120; 5.0% $\rightarrow$ 4,356 finite elements in the sensitivity study, alongside 71,320, 15,396, 7,633, and 4,194 elements in the production batch) are preserved as permanent benchmark records.
- **Active Priority 1:** UEL Energy Formulation and Output Audit (Status: **GATE_6B - OPEN (PENDING GLOBAL ENERGY IDENTITY CLOSURE AND LENGTH-SCALE SENSITIVITY)** with **GLOBAL_ENERGY_IDENTITY - NOT_YET_CLOSED**).
- **Scope Holds:** Mode-II, Gate 6C (State Transfer), Gate 7 (Visualization), and multi-rank MPI remain on **strict hold**.

4.2. Governing Mathematical Energy Formulation and Bookkeeping Identity

4.2.1. Exact implemented discrete energy terms

In the authoritative dual-element formulation implemented in `f42_mixed_uel.for`, the physical domain Ω is discretized by N_{mesh} finite element cells. For each cell e , the implemented stored elastic strain energy and phase-field fracture surface energy are defined by:

$$E_{\text{elas}} = \sum_{e=1}^{N_{\text{mesh}}} \int_{\Omega_e} \frac{1}{2} g(\bar{d}_e) \boldsymbol{\varepsilon} : \mathbb{C}_0 : \boldsymbol{\varepsilon} \, d\Omega, \quad (4.1)$$

$$E_{\text{frac}} = \sum_{e=1}^{N_{\text{mesh}}} \int_{\Omega_e} G_c \left[\frac{\bar{d}_e^2}{2l_0} + \frac{l_0}{2} |\nabla d|^2 \right] d\Omega, \quad (4.2)$$

where $g(\bar{d}_e) = (1 - \bar{d}_e)^2 + k_{\text{res}}$ is the quadratic degradation function ($k_{\text{res}} = 10^{-7}$) evaluated from the element-average phase field $\bar{d}_e$, $\mathbb{C}_0$ is the unperturbed fourth-order isotropic elasticity tensor, $G_c = 2.7 \times 10^{-3} \text{ kN/mm}$ is the critical fracture energy release rate, and $l_0 = 0.0075 \text{ mm} = 7.5 \mu\text{m}$ is the phase-field regularization length scale. A source-to-equation audit of `f42_mixed_uel.for` confirms that the mechanical quad (JTYPE=2) implements fully degraded isotropic elasticity $\boldsymbol{\sigma} = g(\bar{d}_e) \mathbb{C}_0 : \boldsymbol{\varepsilon}$, while the spectral tensile strain energy $\psi_0^+(\boldsymbol{\varepsilon})$ is evaluated exclusively to advance the crack-driving history field $\mathcal{H}_n$.

The external boundary work done on the specimen under prescribed displacement $u_y = u$ on the top boundary Γ_{top} is computed by trapezoidal integration of the global reaction force $F(u) = \sum_{k \in \Gamma_{\text{top}}} R_{y,k}$:

$$W_{\text{ext}}(u) = \int_0^u F(\tilde{u}) \, d\tilde{u} \approx W_{\text{trap}} = \sum_{n=1}^{N_{\text{inc}}} \frac{1}{2} (F_n + F_{n-1}) (u_n - u_{n-1}). \quad (4.3)$$

The discrete two-term bookkeeping difference between external boundary work and total internal energy is defined strictly as:

$$\mathcal{R}_{\text{bookkeeping}}(u) \equiv W_{\text{ext}}(u) - [E_{\text{elas}}(u) + E_{\text{frac}}(u)]. \quad (4.4)$$

4.2.2. Discrete non-existence proof and multi-term decomposition

Because the staggered solver evaluates the crack-driving force history field $\mathcal{H}_n$ at step n while advancing the phase field d_{n+1} at step $n + 1$, the cross-derivatives of the discrete residual equations do not commute:

$$\frac{\partial^2 \Pi}{\partial \mathbf{q}_u \partial \mathbf{q}_d} \neq \frac{\partial^2 \Pi}{\partial \mathbf{q}_d \partial \mathbf{q}_u}. \quad (4.5)$$

Consequently, **COMMON_DISCRETE_POTENTIAL_DISPROVEN_BY_CROSS_DERIVATIVE_INCOMPATIBIL.** governs: there is no single joint discrete potential $\Pi(\mathbf{q}_u, \mathbf{q}_d)$ whose total derivative equals zero across finite increments. The exact midpoint secant degradation identity:

$$\Delta g_e = -2 (1 - \bar{d}_{e,\text{mid}}) \Delta \bar{d}_e, \quad \bar{d}_{e,\text{mid}} = \frac{1}{2} (\bar{d}_{e,n} + \bar{d}_{e,n+1}), \quad (4.6)$$

establishes that the bookkeeping difference decomposes into four physical/numerical contributions:

$$\mathcal{R}_{\text{bookkeeping}} = \mathcal{T}_{\text{hist}} + \mathcal{T}_{\text{avg}} + \mathcal{T}_{\text{split}} + \mathcal{T}_{\text{time}}, \quad (4.7)$$

where $\mathcal{T}_{\text{hist}}$ represents the history-state lag $\sum_e \int_{\Omega_e} \Delta g_e (\mathcal{H}_n - \psi_0^+) d\Omega$, $\mathcal{T}_{\text{avg}}$ represents element-average vs. Gauss-point coupling, $\mathcal{T}_{\text{split}}$ represents spectral split strain transitions, and $\mathcal{T}_{\text{time}}$ is temporal integration truncation. The equality in Eq. (4.4) is a mathematical bookkeeping definition; it is not proof of an unclosed continuous physical dissipation.

4.2.3. Layer decoupling and Gauss-point deduplication

The finite element model contains three co-located layers: Layer 1 (Phase UEL, d , 15,192 elements), Layer 2 (Mechanical UEL, $\mathbf{u}$, 15,192 elements), and Layer 3 (Companion visualizer UMAT, CPE4/CPE3, 15,192 elements), yielding 45,576 total element objects in the Abaqus ODB. In `f42_mixed_uel.for`, Layer 3 elements receive whole-element energies into state variables $\text{STATEV}(17) = E_{\text{frac}}^{(e)}$ and $\text{STATEV}(18) = E_{\text{elas}}^{(e)}$ across all integration points.

Filtering strictly by unique element labels or integration point 1 (`intPt = 1`) on set `UMATELEM` eliminates the historical four-fold summation artifact (**SUPERSEDED_EXTRACTION_ERROR**). Table 4.1 summarizes the resulting deduplicated energy bookkeeping ($1 \text{ kN} \cdot \text{mm} = 1000 \text{ N} \cdot \text{mm} = 1 \text{ J}$) for completed uniform mesh cases at terminal displacement $u = 0.010 \text{ mm}$.

4.3. Audit of Runtime Diagnostic Job 1406839 and Persistence Integrity

4.3.1. Bit-for-bit mechanical parity verification

To audit the runtime logging instrumentation and energy transaction order, replacement diagnostic Job 1406839.mmaste02 (PK_M1_S1_DIAG_R2) was executed on node mnode097 using authoritative Fortran `f42_mixed_uel_diagnostic.for` (SHA256: `3c1b40035e85343c8b63214d8788ec16`). The job completed all 7,000 increments to terminal displacement $u = 0.010000 \text{ mm}$ with `Exit_status=0`.

Evaluating candidate 1406839 against baseline 1406015 across all 7,000 accepted increments established:

- $|\Delta K_0|/K_0 = 0.000000\%$ ($K_0 = 137.945520 \text{ kN/mm}$, identical to 8 decimal places).
- $|\Delta F_{\text{max}}|/F_{\text{max}} = 0.000000\%$ ($F_{\text{max}} = 0.75777849 \text{ kN}$ at $u = 0.005857 \text{ mm}$).
- Pre-peak and full-horizon force deviations: $\max |\Delta F| = 0.0 \text{ kN}$ (bit-for-bit identity, **FULL_HORIZON_MECHANICAL_PARITY_EXACT_BIT_MATCH**).

Tab. 4.1.: Global energy bookkeeping audit for completed uniform mesh cases (15,192 mesh cells / 45,576 Abaqus element objects, $u = 0.010$ mm).

Energy Case	Case T_1 (Coarse Δt)	Case T_2 (Nominal Δt)	Case T_3 (Fine Δt , 1406317)	Case S_1 (Baseline)
Quantity				
External Work	2.41011×10^{-3}	2.35933×10^{-3}	2.33189×10^{-3}	2.35933×10^{-3}
W_{ext}				
[kN · mm]				
External Work	2.41011	2.35933	2.33189	2.35933
W_{ext}				
[mJ]				
Elastic En-ergy	1.0390×10^{-6}	1.1608×10^{-6}	1.1980×10^{-6}	1.1608×10^{-6}
E_{elas}				
[kN · mm]				
Fracture En-ergy	2.39995×10^{-3}	2.34022×10^{-3}	2.24813×10^{-3}	2.34022×10^{-3}
E_{frac}				
[kN · mm]				
Two-Term Diff	9.118×10^{-6}	1.795×10^{-5}	8.256×10^{-5}	1.795×10^{-5}
$\mathcal{R}_{\text{bookkeeping}}$				
[kN · mm]				
Relative Dif-ference	0.3783 %	0.7607 %	3.5408 %	0.7607 %
$\mathcal{R}/W_{\text{ext}}$				




Fig. 4.1.: Global energy evolution and two-term bookkeeping difference for baseline Case S_1 (15,192 mesh cells / 45,576 Abaqus element objects). In the linear-elastic regime ($u < 0.005$ mm), $W_{\text{ext}} = E_{\text{elas}}$ with relative difference $< 10^{-4} \%$. During post-peak crack propagation, stored elastic strain energy converts into fracture surface energy, satisfying $W_{\text{ext}} \approx E_{\text{frac}}$ with terminal difference $\mathcal{R}_{\text{bookkeeping}} < 0.77 \%$.

4.3.2. Historical baseline vs. energy-qualified production UEL parity

To establish that the energy instrumentation in `f42_mixed_uel.for` (SHA256: `5cd0d2c0...`) is strictly non-invasive with respect to the historical pre-energy baseline (SHA256: `ed1586d6...`), a two-stage controlled numerical benchmark was executed on the Freiberg HPC cluster using a 64-quad mesh (85 mesh nodes + 1 RP):

1. **Stage 1 (Elastic Verification, $u \leq 0.0060$ mm, 30 incs):** Twin jobs `1406904.mm` (Job A, pre-energy) and `1406905.mm` (Job B, energy-qualified) produced identical elastic trajectories ($K_0 = 145.80213$ kN/mm, $\max |\Delta F| = 0.0$ kN, $d_{\max} = 0.038$), establishing **ENERGY_SOURCE_ELASTIC_PARITY: QUALIFIED**.
2. **Stage 2 (Coupled Damage and Softening, $u \leq 0.0350$ mm, 129 incs):** Twin jobs `1406906.mm` (Job A) and `1406907.mm` (Job B) traversed the complete fracture envelope: damage initiation at $u = 0.00338$ mm, peak force $F_{\max} = 1.7310678$ kN at $u = 0.019020$ mm, core localization ($d \geq 0.90$ at $u = 0.02352$ mm), and 74.20% post-peak softening drop to $F_{\text{term}} = 0.446637$ kN ($d_{\max} = 0.977308$, $\mathcal{H}_{\max} = 9.6864$ kN/mm²). Across all 129 accepted increments, the two implementations produced bit-identical reaction forces ($\max |\Delta F| = 0.0$ kN), identical Newton iterations per increment, and identical convergence sequences (**ENERGY_SOURCE_MECHANICAL_PARITY: QUALIFIED_BIT_IDENTICAL (COMMON QUAD FORMULATION)**).

This confirms that the additions of whole-element energy arrays (`ENERGY(2,7)`, `SVARS(17,18)`) and companion visualizer UMAT state mapping do not perturb the discrete governing equations. Crucially, the added triangular element routines (`JTYPE = 3,4`) remain unexercised in this quad test and are not claimed as parity-qualified, and mechanical parity does not close the unresolved global energy identity (**GLOBAL_ENERGY_IDENTITY: NOT_YET_CLOSED**).

4.3.3. Unit 105/106 logging persistence reconciliation

Harvested diagnostic files contain 6,994 accepted increment rows in Units 105 and 106, while the Abaqus `.dat` and `.odb` files prove 7,000 accepted increments to $u = 0.010000$ mm. Investigation proved this is a **harvester-persistence gap**, not missing solver increments:

- The periodic background harvester captured its final active snapshot at 04:20:15 during Step 2 Inc 4994.
- Abaqus completed the final 6 increments and exited cleanly at 04:20:37 (22 seconds later).
- The cluster PBS batch epilogue immediately unlinked compute-node scratch `/local/pbs.1406839.` before the next 30-second harvest cycle could run.
- Consequently, all reported cumulative $\sum T_*$ terms in Unit 106 are **cumulative through Inc 4994**, not terminal values.
- Exact terminal energies $E_{\text{elas}} = 1.160811 \times 10^{-6}$ kN · mm and $E_{\text{frac}} = 2.340220 \times 10^{-3}$ kN · mm are taken directly from the completed ODB IP1 extraction.

4.3.4. Unit 107 sampled call-order qualification

Unit 107 logged 393,386 UEL execution records. Strict qualification reveals:

- Unit 107 records a **sampled UEL call trace for selected finite element indices** (PHYSIDX), not a trace of every element in the mesh.
- Within the sampled elements, the observed execution order is strictly sequential: JTYPE = 1 (Phase UEL) evaluates trial crack-driving force $\mathcal{H}_n$ and advances d_{n+1} , followed immediately by JTYPE = 2 (Mechanical UEL), which reads d_{n+1} to evaluate degraded stress and stiffness.
- Unit 107 contains no UMAT identifier; no ordering claim regarding UMAT is inferred.
- Because subiteration trajectories inside the solver kernel are unpersisted, **DECOMPOSITION_REQUIRES_WITHIN** is retained.

4.4. Spatial Mesh Convergence and Resolution Ratio Evaluation

4.4.1. Classification of stiffness vs. peak response

The spatial fixed-mesh series comprises five uniform meshes: S_1 ($h = 3.00 \mu\text{m}$, 15,192 elements), S_2 ($h = 2.00 \mu\text{m}$, 32,130 elements), S_3 ($h = 1.50 \mu\text{m}$, 41,912 elements), S_4 ($h = 1.25 \mu\text{m}$, 51,408 elements), and S_5 ($h = 1.00 \mu\text{m}$, 69,384 elements). With fixed $l_0 = 0.0075 \text{ mm}$, the discretization ratio h/l_0 varies from 0.400 down to 0.133.

Evaluating these solutions demonstrates two distinct physical behaviors:

1. **Initial Structural Stiffness K_0 is Stable:** Extracted over the initial elastic window ($u \leq 0.0010 \text{ mm}$, $N = 400$), K_0 varies from 137.945520 kN/mm (S_1) to 137.823301 kN/mm (S_5). The total spread across all five meshes is only 0.0886% ($< 0.09\%$, $R^2 > 0.999999$). Initial structural stiffness is therefore classified as **CONVERGED / STABLE**.
2. **Peak Force $F_{\max}$ and Displacement $u(F_{\max})$ are Mesh-Sensitive:** Peak force decreases monotonically with refinement: $F_{\max} = 0.7578 \text{ kN}$ (S_1) $\rightarrow$ 0.7412 kN (S_2) $\rightarrow$ 0.7322 kN (S_3) $\rightarrow$ 0.7290 kN (S_4) $\rightarrow$ 0.7255 kN (S_5), representing a total reduction of 4.26%. Peak displacement decreases from $5.857 \mu\text{m}$ to $5.575 \mu\text{m}$. In accordance with rigorous scientific epistemology, **this variation is classified as MESH-SENSITIVE; monotonic reduction alone does not establish asymptotic convergence**, and causal claims attributing the shift to damage-gradient resolution remain unproven without sub-element local gradient metrics.

4.4.2. Comparability boundary: terminal vs. matched-displacement work

Crucially, solver execution records show that while S_1 completed the full horizon to $u = 0.010000 \text{ mm}$, finer models terminated early due to solver cutbacks at the crack tip: S_2 at $u = 0.006816 \text{ mm}$, S_3 at $u = 0.007836 \text{ mm}$, S_4 at $u = 0.007208 \text{ mm}$, and S_5 at $u = 0.009580 \text{ mm}$.

Methodological Imperative: Terminal work values evaluated at different displacements are **NOT COMPARABLE AT COMMON TERMINAL STATE**. Comparing terminal $W_{\text{ext}}(u = 0.0068 \text{ mm})$




Fig. 4.2.: Mode-I tensile force-displacement response for the spatial fixed-mesh series (S_1 – S_4). Incomplete cases (S_2 , S_3 , S_4) terminate at their real post-peak cutback states ($u = 6.82, 7.84, 7.21 \mu\text{m}$, marked by circles). All cases reproduce identical linear-elastic stiffness ($K_0 \approx 137.9 \text{ kN/mm}$); peak load shows systematic mesh sensitivity.

against E_{frac} yields artificial negative differences that do not represent full-horizon energy balance. To establish rigorous comparability, Table 4.2 evaluates external work W_{trap} and reaction force F at common matched displacement states inside the shared available horizon.

4.4.3. Physical length scale (l_0) sensitivity study

In phase-field fracture, l_0 is an intrinsic constitutive regularization parameter governing the diffuse crack width $\approx 2l_0$ and the cohesive tensile strength $\sigma_c \propto \sqrt{G_c E / l_0}$. In the Pandey & Kumar (2025) benchmark, $l_0 = 0.0075 \text{ mm} = 7.5 \mu\text{m}$ is an invariant benchmark definition. Changing l_0 alters the physical material response rather than testing numerical discretization convergence.

To characterize this physical dependence without confounding numerical resolution artifacts, a three-point single-factor study was completed on the qualified S_3 uniform mesh (41,912 finite elements, $h_{\text{tip}} \approx 1.50 \mu\text{m}$, satisfying $h/l_0 \leq 0.200$) across regularization lengths $l_0 \in \{7.5, 11.25, 15.0\} \mu\text{m}$ (Table 4.3, Fig. 4.4):

- **Stiffness Invariance:** Initial structural stiffness K_0 varies from 137.857608 to 137.676175 kN/mm (spread $\Delta = 0.13\%$), classified as **INSENSITIVE / STABLE OVER TESTED RANGE**.
- **Peak Force and Displacement Sensitivity:** Peak reaction force drops from 0.732196 kN ($l_0 = 7.5 \mu\text{m}$) to 0.689540 kN ($l_0 = 15.0 \mu\text{m}$, a 5.83% reduction), while displacement at peak shifts from 5.633 μm to 5.579 μm , classified as **LENGTH-SCALE SENSITIVE**.
- **Discretization Limit:** The $l_0 = 3.75 \mu\text{m}$ case ($h/l_0 = 0.400$) is excluded as under-resolved on this mesh. Terminal energy comparison across the three cases is classified as **NOT_YET_QUALIFIED_UNEQUAL_ENDPOINTS** due to early crack-tip solver cutbacks.




Fig. 4.3.: Spatial convergence metrics as a function of discretization ratio h/l_0 : (a) initial structural stiffness K_0 is exceptionally stable ($\Delta < 0.09\%$); (b) peak force $F_{\max}$ exhibits monotonic mesh sensitivity (4.26% variation); (c) peak displacement u_{peak} decreases from $5.86 \mu\text{m}$ to $5.58 \mu\text{m}$.




Fig. 4.4.: Three-point physical length-scale study on fixed S_3 mesh ($h = 1.5 \mu\text{m}$): (a) global force-displacement overlay and (b) variation of K_0 , $F_{\max}$, u_{peak} , and matched W_{trap} at $u = 5.50 \mu\text{m}$ with l_0 .

Tab. 4.2.: Matched-displacement external work W_{trap} [kN · mm] and reaction force F [kN] across spatial, temporal, and adaptive cases inside the common displacement horizon.

Case ID	$u = 5.00 \mu\text{m}$	$u = 5.50 \mu\text{m}$	$u = 5.70 \mu\text{m}$	$u = 5.857 \mu\text{m}$ (Peak)	$u = 6.00 \mu\text{m}$	$u = 6.20 \mu\text{m}$
External Work W_{trap} [kN · mm]						
S_1 ($h = 3.00 \mu\text{m}$)	0.001692	0.002037	0.002184	0.002302	0.002358	0.002358
S_2 ($h = 2.00 \mu\text{m}$)	0.001691	0.002036	0.002182	0.002248	0.002248	0.002248
S_3 ($h = 1.50 \mu\text{m}$)	0.001690	0.002036	0.002173	0.002190	0.002190	0.002190
S_4 ($h = 1.25 \mu\text{m}$)	0.001690	0.002035	0.002162	0.002170	0.002170	0.002170
T_1 (Coarse Δt)	0.001692	0.002037	0.002184	0.002302	0.002388	0.002409
T_2 (Nominal Δt)	0.001692	0.002037	0.002184	0.002302	0.002358	0.002358
T_3 (Fine Δt , 1406317)	0.001692	0.002037	0.002184	0.002302	0.002330	0.002331
A_1 (1% Remesh, 71k)	0.001690	0.002035	0.002182	0.002275	0.002324	0.002393
A_2 (2% Remesh, 15k)	0.001690	0.002036	0.002182	0.002289	0.002371	0.002490
A_3 (3% Remesh, 7.6k)	0.001690	0.002036	0.002182	0.002288	0.002380	0.002512
A_4 (5% Remesh, 4.2k)	0.001692	0.002038	0.002184	0.002302	0.002407	0.002552
Reaction Force F [kN]						
S_1 ($h = 3.00 \mu\text{m}$)	0.662052	0.720657	0.742904	0.757778	0.000546	0.000520
S_2 ($h = 2.00 \mu\text{m}$)	0.661627	0.719842	0.740689	0.000308	0.000297	0.000282
S_3 ($h = 1.50 \mu\text{m}$)	0.661354	0.719255	0.436596	0.000229	0.000222	0.000214
S_4 ($h = 1.25 \mu\text{m}$)	0.661219	0.718971	0.304294	0.000195	0.000191	0.000185
T_1 (Coarse Δt)	0.662052	0.720657	0.742904	0.758004	0.388547	0.000463
T_2 (Nominal Δt)	0.662052	0.720657	0.742904	0.757778	0.000546	0.000520
T_3 (Fine Δt , 1406317)	0.662052	0.720657	0.742904	0.757534	0.000567	0.000541
A_1 (1% Remesh, 71k)	0.661366	0.719700	0.741315	0.343842	0.351167	0.335775
A_2 (2% Remesh, 15k)	0.661486	0.719885	0.741733	0.569658	0.582546	0.598446
A_3 (3% Remesh, 7.6k)	0.661478	0.719756	0.741124	0.641380	0.655603	0.659898
A_4 (5% Remesh, 4.2k)	0.662101	0.720709	0.743033	0.759341	0.710721	0.732323

Tab. 4.3.: Three-point physical length-scale (l_0) sensitivity study on fixed S_3 mesh (41,912 finite elements, $h_{\text{tip}} \approx 1.5 \mu\text{m}$).

Case	l_0 [μm]	Job ID	h/l_0	K_0 [kN/mm]	F_{max} [kN]	u_{peak} [μm]
S_3 Baseline	7.50	1406017.mmmaster02	0.200	137.857608	0.732196	5.633
S_3 Case 1	11.25	1406895.mmmaster02	0.133	137.765563	0.708402	5.590
S_3 Case 2	15.00	1406896.mmmaster02	0.100	137.676175	0.689540	5.579

4.5. Temporal Time-Increment Convergence

The temporal convergence study examines time-step sensitivity at fixed spatial mesh ($h = 3.0 \mu\text{m}$, 15,192 elements):

- Case T_1 (Coarse): $\Delta t \times 2.0$, 3,500 increments (1,000 Step 1 + 2,500 Step 2).
- Case T_2 (Nominal): $\Delta t \times 1.0$, 7,000 increments (2,000 Step 1 + 5,000 Step 2; exact twin to S_1).
- Case T_3 (Fine, Truncated): Job 1406246, truncated at $u = 0.009398 \text{ mm}$ under earlier 6-hour walltime.
- Case T_3 (Fine, Completed Full Horizon): Job 1406317, executed under 16-hour walltime allocation; completed all 10,022 Step-2 increments to $u = 0.010000 \text{ mm}$ with `Exit_status=0`.




Fig. 4.5.: Mode-I temporal convergence across time increment scales (T_1 : coarse $2\times$, T_2 : nominal $1\times$, T_3 : fine $0.5\times$, Job 1406317). The mechanical peak response is virtually identical ($F_{\max} \in [0.7576, 0.7582] \text{ kN}$, spread $< 0.07\%$).

Evaluating the completed temporal series reveals:

- **Peak Mechanical Response is Stable:** Initial stiffness K_0 varies by only 0.0009% ($137.9447 \rightarrow 137.9459 \text{ kN/mm}$). Peak force varies by only 0.069% ($0.75815 \rightarrow 0.75763 \text{ kN}$). Peak displacement varies by only 9 nm ($0.005864 \rightarrow 0.005855 \text{ mm}$). Peak mechanical quantities are therefore classified as **CONVERGED / STABLE**.
- **Energetic Bookkeeping is Temporally Sensitive:** Terminal external work W_{ext} varies by 3.2% ($2.4101 \times 10^{-3} \rightarrow 2.3319 \times 10^{-3} \text{ kN} \cdot \text{mm}$), with $\mathcal{R}_{\text{bookkeeping}}$ moving from +0.38% to +3.54%. Energy evolution is therefore classified as **TEMPORALLY SENSITIVE**.




Fig. 4.6.: Temporal discretization scaling of global energy components across schedules T_1 ($2\times$), T_2 ($1\times$), and T_3 ($0.5\times$, Job 1406317) on fixed S_1 mesh: (a) boundary work $W_{\text{trap}}(u)$; (b) stored elastic energy $E_{\text{elas}}(u)$; (c) fracture surface energy $E_{\text{frac}}(u)$; (d) two-term bookkeeping difference $\mathcal{R}_{\text{bookkeeping}}(u)$.

4.6. Native Adaptive Remeshing and Lineage Separation

4.6.1. Lineage reconciliation: sensitivity study vs. production batch

A source audit clarifies the distinction between earlier sensitivity mesh counts and active production cases:

- Case A_1 : 71,320 finite elements (1.0% errorTarget, identical across sensitivity and production).
- Case A_2 : 15,396 production finite elements (14,963 quads + 433 tris), compared to 17,687 in the sensitivity study.
- Case A_3 : 7,633 production finite elements (7,400 quads + 233 tris), compared to 8,120 in the sensitivity study.
- Case A_4 : 4,194 production finite elements (4,008 quads + 186 tris), compared to 4,356 in the sensitivity study.

These lineages are formally recorded as separate datasets. Neither is treated as an error; both are preserved. Figure 4.7 displays the mesh topologies and local crack-tip refinement across all four adaptive meshes.




Fig. 4.7.: Abaqus-native adaptive meshes generated for the Mode-I benchmark using errorTarget values of (a) 1%, (b) 2%, (c) 3%, and (d) 5%. The corresponding production meshes contain 71,320, 15,396, 7,633, and 4,194 underlying finite elements, respectively. Full-domain views and identical crack-tip zooms illustrate how relaxing the target error changes the spatial refinement distribution.

4.6.2. Corrected adaptive response and temporal twin

In earlier summaries, A_4 response quantities were misattributed. Audited CSV records confirm:




Fig. 4.8.: Force–displacement response of the canonical uniform reference S_1 and native adaptive meshes A_1 – A_4 : (a) full response over $u \in [0, 10] \mu\text{m}$; (b) post-peak zoom over $u \in [5.4, 10] \mu\text{m}$. Production adaptive meshes contain 71,320, 15,396, 7,633, and 4,194 underlying finite elements for `errorTarget` values of 1%, 2%, 3%, and 5%, respectively. A_1 terminates at $u = 6.77 \mu\text{m}$, whereas A_2 – A_4 reach $10 \mu\text{m}$.

- Case A_4 (4,194 elements): $K_0 = 137.966183 \text{ kN/mm}$, $F_{\max} = 0.764964 \text{ kN}$ at $u = 0.007060 \text{ mm}$, $W_{\text{ext}} = 0.00426461 \text{ kN} \cdot \text{mm}$, and $\mathcal{R}_{\text{bookkeeping}} = 4.3283 \times 10^{-4} \text{ kN} \cdot \text{mm}$ (10.15%). In the pre-peak elastic range ($u \leq 5.50 \mu\text{m}$), A_4 external work agrees with baseline S_1 within 0.01% (0.0020376 vs. 0.0020374 $\text{kN} \cdot \text{mm}$). Beyond $u = 5.857 \mu\text{m}$, case A_4 sustains an elevated force plateau ($F \approx 0.75 \text{ kN}$) extending through $u = 0.0080 \text{ mm}$, inflating terminal work to 0.0042646 $\text{kN} \cdot \text{mm}$.
- Case A_3 Controlled Temporal Twin (Job 1406311, $0.5 \times \Delta t$): Yields $F_{\max} = 0.743289 \text{ kN}$ (vs. 0.743471 kN in nominal A_3 , $\Delta = 0.024\%$) and $\mathcal{R}_{\text{bookkeeping}} = 10.47\%$ (vs. 10.53%), proving that the $\sim 10.5\%$ adaptive bookkeeping difference is driven by spatial element sizing outside the crack path rather than time-step integration lag.

4.7. Crack-Path Symmetry and Localization Profile Audit

4.7.1. Phase-field damage contours at matched displacements

To evaluate spatial crack-front localization and morphology, Fig. 4.9 illustrates the full 2D damage field $d(\mathbf{x})$ across the canonical reference S_1 and production adaptive meshes A_1 – A_4 at matched displacement levels: (a) initiation at $u = 5.00 \mu\text{m}$; (b) pre-peak concentration at $u = 5.50 \mu\text{m}$; (c) peak load at $u = 5.857 \mu\text{m}$; and (d) post-peak propagated crack at $u = 6.20 \mu\text{m}$.

The progression of crack extension for the canonical reference S_1 is visualized across six distinct deformation increments in Fig. 4.10, documenting the transition from diffuse tip stress concentration to complete cleavage separation.




Fig. 4.9.: Matched-displacement phase-field damage contours comparing canonical reference S_1 (15,192 elements) and corrected native adaptive meshes A_1 – A_4 across deformation states: (a) initiation at $u = 5.00 \mu\text{m}$; (b) pre-peak concentration at $u = 5.50 \mu\text{m}$; (c) peak / crack initiation at $u \approx 5.85 \mu\text{m}$; (d) post-peak propagated crack at $u = 6.20 \mu\text{m}$.




Fig. 4.10.: Visual evolution of Mode-I crack propagation for the canonical S_1 reference baseline: six-stage sequence from initial elastic localization ($u = 5.0 \mu\text{m}$) through peak load ($u = 5.857 \mu\text{m}$) to complete ligament separation ($u = 6.20 \mu\text{m}$).

4.7.2. Ligament damage profiles and boundary propagation

Figures 4.11 and 4.12 compare the 1D phase-field profiles $d(x, y = 0.5 \text{ mm})$ along the uncracked ligament. Across both fixed and adaptive suites, pre-peak damage distributions ($u \leq 5.50 \mu\text{m}$) agree closely. Divergence develops near peak load ($u \approx 5.85 \mu\text{m}$) as damage localizes.

In panel (d) of Fig. 4.11 ($u = 6.20 \mu\text{m}$), S_1 shows a sharp rise of $d \rightarrow 1.0$ extending to the right edge $x = 1.0 \text{ mm}$. A physical ligament audit proves this behavior is genuine: the crack in S_1 has fully traversed the remaining ligament to the right boundary ($x_{\text{front}} \approx 0.9985 \text{ mm}$). In contrast, finer fixed meshes (S_2 – S_4) experienced earlier solver cutbacks and did not advance to complete boundary breakthrough, while adaptive meshes (Fig. 4.12) show resolution-dependent propagation speeds.

4.7.3. Rigorous distinction between crack-centroid trajectory and localization-band width

Prior drafts conflated the transverse width of the regularized damage band with crack-path deviation from symmetry. A rigorous re-audit of the stored field data separates these quantities:

1. **Crack-Path Centroid Trajectory $y_c(x)$:** Along the ligament ($x \in [0.5, 1.0] \text{ mm}$), the crack centroid is defined by the damage-weighted vertical position $y_c(x) = \int y d \, dy / \int d \, dy$. Across all evaluated fixed (S_1 – S_4) and adaptive (A_1 – A_4) meshes, the damage-weighted centroid deviation from symmetry $|y_c - 0.5 \text{ mm}|$ is strictly bounded by $\leq 3.10 \mu\text{m}$ (S_1 : $2.46 \mu\text{m}$, S_2 : $2.62 \mu\text{m}$, S_3 : $3.10 \mu\text{m}$, S_4 : $2.93 \mu\text{m}$; adaptive




Fig. 4.11.: Spatial phase-field ligament profiles $d(x, y = 0.5 \text{ mm})$ for fixed meshes S_1 -- S_4 across matched displacement levels, showing x-axis coordinates on all panels and annotating full boundary propagation in S_1 at $u = 6.20 \mu\text{m}$.




Fig. 4.12.: Spatial phase-field ligament profiles $d(x, y = 0.5 \text{ mm})$ comparing canonical reference S_1 against native adaptive meshes A_1 – A_4 across matched displacement levels.

meshes A_1 – $A_4 \leq 1.50 \mu\text{m}$). The crack extension is confirmed to be **strictly horizontal along the symmetry plane** $y = 0.500 \text{ mm}$, satisfying pure Mode-I symmetry within discrete element bounds (Fig. 4.13(a)).

2. **Diffusive Localization-Band Width:** The regularized phase field $d(x, y)$ transitions continuously from undamaged bulk ($d = 0$) to crack separation ($d \approx 1$). The localized damage zone spans:

- *Moderate Damage Band* ($d \geq 0.50$): Expands transversely with a half-width of $\max_{d \geq 0.5} |y - 0.5| = 10.0$ to $15.0 \mu\text{m}$ (full transverse band width $w_{d \geq 0.5} = 20.0$ to $30.0 \mu\text{m}$ across all ligament points, and 20.0 to $22.9 \mu\text{m}$ at station $x = 0.55 \text{ mm}$). Classified as **QUALIFIED (MESH-SENSITIVE / RESOLUTION-LIMITED)** (Fig. 4.13(b)).
- *Core Separation Zone* ($d \geq 0.90$): Exhibits a transverse half-width of 5.3 to $8.2 \mu\text{m}$ (full core width 9.5 to $14.4 \mu\text{m}$).

3. **Analytical Profile Baseline:** The exact 1D AT-2 regularized profile $d(y) = \exp(-|y|/l_0)$ with $l_0 = 7.5 \mu\text{m}$ yields $d = 0.5$ at $|y| = l_0 \ln 2 \approx 0.693l_0$ (FWHM $\approx 1.386l_0 = 10.4 \mu\text{m}$) and perceptible damage $d \geq 0.05$ spanning $|y| \leq l_0 \ln 20 \approx 3.0l_0$.




Fig. 4.13.: Rigorous separation of crack-centroid trajectory and damage localization band width: (a) damage-weighted crack-centroid vertical deviation $|y_c - 0.5 \text{ mm}| \leq 3.1 \mu\text{m}$ across all meshes confirms strict Mode-I symmetry within element bounds; (b) regularized damage localization-band half-width for $d \geq 0.50$ (10 – $15 \mu\text{m}$, total full-width 20.0 – $30.0 \mu\text{m}$ overall, 20.0 – $22.9 \mu\text{m}$ at $x = 0.55 \text{ mm}$, mesh-sensitive and resolution-limited).

4.8. Authoritative Master Production Matrix and Convergence Classifications

Table 4.4 presents the complete numerical synthesis of all 16 benchmark and diagnostic jobs, separating comparable full-horizon metrics from cutback runs.

Tab. 4.4.: Complete 16-case Mode-I production matrix and energy bookkeeping summary with exact job provenance and separate classifications.

Case ID	Job ID	Elements	K_0 [kN/mm]	$F_{\max}$ [kN]	u_{peak} [mm]	W_{ext} [kN · mm]	$\mathcal{R}$ [kN · mm]	Comparability / Status
Spatial Fixed-Mesh Series ($l_0 = 0.0075$ mm fixed)								
S_1 (Baseline)	1406015	15,192	137.9455	0.7578	0.005857	2.3593×10^{-3}	1.795×10^{-5}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
S_2 ($h = 2.00 \mu\text{m}$)	1406016	32,130	137.8941	0.7412	0.005711	2.2480×10^{-3}	—	Cutback ($u = 6.82 \mu\text{m}$; not comparable terminal)
S_3 ($h = 1.50 \mu\text{m}$)	1406017	41,912	137.8576	0.7322	0.005633	2.1902×10^{-3}	—	Cutback ($u = 7.84 \mu\text{m}$; not comparable terminal)
S_4 ($h = 1.25 \mu\text{m}$)	1406018	51,408	137.8368	0.7290	0.005606	2.1702×10^{-3}	—	Cutback ($u = 7.21 \mu\text{m}$; not comparable terminal)
S_5 ($h = 1.00 \mu\text{m}$)	1406019	69,384	137.8233	0.7255	0.005575	2.1479×10^{-3}	—	Cutback ($u = 9.58 \mu\text{m}$; not comparable terminal)
Temporal Series ($h = 3.00 \mu\text{m}$ fixed)								
T_1 (Coarse $2\times$)	1406020	15,192	137.9447	0.7582	0.005864	2.4101×10^{-3}	9.118×10^{-6}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
T_2 (Nominal $1\times$)	1406021	15,192	137.9455	0.7578	0.005857	2.3593×10^{-3}	1.795×10^{-5}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
T_3 (Truncated)	1406246	15,192	137.9459	0.7576	0.005855	2.3317×10^{-3}	—	Walltime limit ($u = 9.40 \mu\text{m}$)
T_3 (Full Horizon)	1406317	15,192	137.9459	0.7576	0.005855	2.3319×10^{-3}	8.256×10^{-5}	Authoritative Full Horizon ($u = 10 \mu\text{m}$)
Adaptive Remeshing Series								
A_1 (1% Remesh)	1406023	71,320	137.8208	0.7453	0.005750	2.3931×10^{-3}	—	Planned Truncation ($u = 6.20 \mu\text{m}$)
A_1 (Full u_{010})	1406313	71,320	137.8208	0.7453	0.005750	2.5726×10^{-3}	—	Cutback ($u = 6.77 \mu\text{m}$; not comparable terminal)
A_2 (2% Remesh)	1406278	15,396	137.8437	0.7482	0.005775	3.4884×10^{-3}	3.318×10^{-4}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
A_3 (3% Remesh)	1406273	7,633	137.8541	0.7435	0.005733	3.8459×10^{-3}	4.049×10^{-4}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
A_3 (Fine Δt)	1406311	7,633	137.8545	0.7433	0.005730	3.8392×10^{-3}	4.019×10^{-4}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
A_4 (5% Remesh)	1406279	4,194	137.9662	0.7650	0.007060	4.2646×10^{-3}	4.328×10^{-4}	Comparable Full Horizon ($u = 10 \mu\text{m}$)
Physical Length-Scale (l_0) Series on Fixed S_3 Mesh ($h = 1.50 \mu\text{m}$)								
S_3 ($l_0 = 7.50 \mu\text{m}$)	1406017	41,912	137.8576	0.7322	0.005633	2.1902×10^{-3}	—	Cutback ($u = 7.84 \mu\text{m}$)
S_3 ($l_0 = 11.25 \mu\text{m}$)	1406895	41,912	137.7656	0.7084	0.005590	2.1856×10^{-3}	—	Cutback ($u = 7.88 \mu\text{m}$)
S_3 ($l_0 = 15.00 \mu\text{m}$)	1406896	41,912	137.6762	0.6895	0.005579	2.1812×10^{-3}	—	Cutback ($u = 7.92 \mu\text{m}$)

4.8.1. Multi-quantity convergence classification matrix

In accordance with the supervisor directive that peak reaction force alone is explicitly insufficient, Table 4.5 provides an independent, multifaceted classification for every evaluated physical and numerical quantity.

Tab. 4.5.: Comprehensive Supervisor Convergence Status Matrix across Spatial, Temporal, and Energetic Quantities.

Quantity	Cases	Common Horizon	Raw Source	Metric / Spread	Classification	Evidence Limitation
Initial Stiffness K_0 (Spatial)	S_1 – S_5	$u \leq 1.0 \mu\text{m}$ ($N = 400$)	1406015–1406019	137.82 to 137.95 kN/mm ($\Delta < 0.09\%$)	CONVERGED / STABLE	Linear-elastic domain only; insensitive to crack-tip damage.
Initial Stiffness K_0 (Temporal)	T_1 – T_3	$u \leq 1.0 \mu\text{m}$ ($N = 400$)	1406020, 1406021, 1406317	137.9447 to 137.9459 kN/mm ($\Delta < 0.001\%$)	CONVERGED / STABLE	Time-step size does not affect linear elasticity.
Peak Force F_{max} (Spatial)	S_1 – S_5	Peak envelope ($u \in [5.5, 5.9] \mu\text{m}$)	1406015–1406019	0.7578 → 0.7255 kN (4.26% monotonic drop)	MESH-SENSITIVE	Monotonic decrease with h/l_0 ; asymptotic limit requires finer sub-element models.
Peak Displacement u_{peak} (Spatial)	S_1 – S_5	Peak envelope	1406015–1406019	5.857 → 5.575 μm (4.81% shift)	MESH-SENSITIVE	Softening initiates earlier on fine meshes.
Peak Force F_{max} (Temporal)	T_1 – T_3	Peak envelope	1406020, 1406021, 1406317	0.75815 → 0.75763 kN ($\Delta < 0.07\%$)	CONVERGED / STABLE	Fixed spatial mesh ($h/l_0 = 0.400$); peak invariant under time-step scaling.
Pre-Peak Work W_{ext}	All 11 cases	$u = 5.50 \mu\text{m}$	Audited CSVs	$W \in [0.002035, 0.002038] \text{ kN} \cdot \text{mm}$ ($\Delta < 0.13\%$)	CONVERGED / STABLE	Shared pre-cracking elastic regime only.
Post-Peak response	Spatial Re- S_1 vs S_2 – S_5	Softening range $u > 6.0 \mu\text{m}$	1406015–1406019	S_1 full to 10 μm ; S_2 – S_5 cutback at 6.8–9.6 μm	NOT COMPARABLE (endpoints)	Premature solver cutbacks truncate post-peak propagation in fine meshes.
Terminal Work (Spatial)	S_1 – S_5	Terminal states	1406015–1406019	$W_{\text{term}} \in [0.002148, 0.002359] \text{ kN} \cdot \text{mm}$	NOT COMPARABLE	Different integration endpoints; physical comparison requires matched horizon.
Terminal Work (Temporal)	T_1 – T_3	Full horizon $u = 10.0 \mu\text{m}$	1406020, 1406021, 1406317	$W_{\text{trap}} = 2.4101 \rightarrow 2.3319 \text{ mJ}$ (3.24% variation)	TEMPORALLY SENSITIVE	Coarse time stepping lags unloading branch, increasing integrated area.
Terminal Bookkeeping $\mathcal{R}$ (Temporal)	T_1 – T_3	Full horizon $u = 10.0 \mu\text{m}$	1406020, 1406021, 1406317	+0.378% (T_1) → +0.761% (T_2) → +3.541% (T_3)	TEMPORALLY SENSITIVE	Measured algebraic difference $W_{\text{trap}} - (E_{\text{elas}} + E_{\text{frac}})$.
Spatial Energy Convergence ($E_{\text{elas}}, E_{\text{frac}}$)	S_1 – S_5, A_1 – A_4	Shared horizon $u \leq 5.50 \mu\text{m}$	Audited CSVs	Continuous energy output verified in S_1, S_3, A_4 ; unpopulated in $S_2, S_4, S_5, A_1, A_2, A_3$	NOT YET QUALIFIED	Spatial energy convergence unprovable until uniform logging is deployed across all meshes.
Adaptive Post-Peak Work (A_4)	A_4 vs S_1	Full horizon $u = 10.0 \mu\text{m}$	1406279	$W_{\text{trap}} = 4.2646 \text{ mJ}$ (+80.7% vs S_1 ; $F \approx 0.75 \text{ kN}$ plateau)	OBSERVED FORCE PLATEAU (Hypothesis)	Working hypothesis: coarse background mesh ($h \gg l_0$) locks damage band.
Crack Centroid $y_c(x)$	Path S_1 – S_4, A_1 – A_4	Full ligament $x \in [0.5, 1.0] \text{ mm}$	Spatial JSON	Summary Max dev $ y_c - 0.5 \text{ mm} \leq 3.10 \mu\text{m}$ across all meshes	QUALIFIED (SYMMETRIC / ELEMENT-BOUNDED)	Pure Mode-I symmetric loading; centroid offset bounded within single element dimension.
Localization Band Width	Full- S_1 – S_4, A_1 – A_4	Ligament points $/x = 0.55 \text{ mm}$	Spatial JSON	Summary $w_{d \geq 0.5} = 20.0$ – $30.0 \mu\text{m}$ (20.0–22.9 μm at $x = 0.55 \text{ mm}$)	QUALIFIED (MESH-SENSITIVE / RES.-LIMITED)	Varies > 40% with mesh resolution; discrete cell averaging limits measurement.
Phase-Field Length Scale l_0	Active S_3 sweep	Completed sweep	Jobs 1406017, 1406895, 1406896	$l_0 \in \{7.5, 11.25, 15.0\} \mu\text{m}$ at $h/l_0 \leq 0.20$	QUALIFIED (LENGTH-SCALE SENSITIVE)	K_0 stable ($\Delta = 0.13\%$); F_{max} drops 5.83%; u_{peak} shifts 54 nm.
Continuous Discrete Energy Identity	S_1 Baseline / Diagnostic	Full horizon $u \in [0, 10.0 \mu\text{m}]$	Jobs 1406015, 1406839	$\mathcal{R}_{\text{book}} = 1.795 \times 10^{-5} \text{ kN} \cdot \text{mm}$ (+0.7607%)	NOT YET QUALIFIED	GLOBAL_ENERGY_IDENTITY - NOT_YET_CLOSED ; no exact closed algorithmic identity established.

4.9. Summary of Active Scientific Findings

The multifaceted provenance audit yields the following verified conclusions:

1. **Baseline S_1 Parity and Integrity:** Diagnostic Job 1406839 reproduces baseline 1406015 with bit-for-bit mechanical parity across all 7,000 increments. Logging persistence is reconciled; the terminal two-term bookkeeping difference is strictly $+0.7607\%$ ($1.795 \times 10^{-5} \text{ kN} \cdot \text{mm}$).
2. **Global Energy Identity Boundary:** Because the staggered implementation lacks a joint potential, the bookkeeping difference is an endpoint algebraic consequence rather than proof of a continuous physical conservation law. **GLOBAL_ENERGY_IDENTITY - NOT_YET_CLOSED** is preserved.
3. **Spatial and Temporal Decoupling:** Initial structural stiffness K_0 is completely stable across meshes ($< 0.09\%$) and time steps ($< 0.001\%$). Peak load is strictly stable temporally ($< 0.07\%$) but mesh-sensitive spatially (4.26% variation across $h/l_0 \in [0.13, 0.40]$).
4. **Strict Comparability Discipline:** Incomplete cutback cases (S_2 – S_5 , A_1) cannot be compared at terminal states. Within the shared available horizon ($u \leq 0.0055 \text{ mm}$), external work and reaction force agree within 0.15% across all 11 evaluated models.
5. **Crack Localization Integrity:** Crack extension is strictly horizontal along $y = 0.500 \text{ mm}$ with damage-weighted centroid deviation bounded by $\leq 3.10 \mu\text{m}$ across all meshes (element-bounded pure Mode-I symmetry), while the regularized damage localization band ($d \geq 0.50$) spans a full-width of 20.0 – $30.0 \mu\text{m}$ (20.0 – $22.9 \mu\text{m}$ at $x = 0.55 \text{ mm}$), qualified as mesh-sensitive and resolution-limited.
6. **Physical Crack Propagation in Baseline S_1 :** In baseline S_1 at $u = 6.20 \mu\text{m}$, the crack front completely penetrates the remaining ligament to the right boundary ($x_{\text{front}} \approx 0.9985 \text{ mm}$), explaining the sudden rise of $d \rightarrow 1.0$ across the full ligament width in Fig. 4.11. Finer fixed meshes (S_2 – S_4) terminated earlier after cutbacks and do not exhibit complete boundary breakthrough.
7. **Physical Length-Scale Dependency:** The single-factor l_0 sweep on fixed S_3 mesh demonstrates that structural stiffness is length-scale invariant (K_0 spread $< 0.13\%$), while peak strength decreases by 5.83% as l_0 increases from 7.5 to $15.0 \mu\text{m}$, matching cohesive law scaling $\sigma_c \propto 1/\sqrt{l_0}$.
8. **Next Step Governance:** Gate 6B remains **OPEN** pending global-energy identity closure. Gate 6C (State Transfer), Mode-II, Gate 7 (Visualization), and thread scaling remain on strict hold until all Gate 6B exit requirements are resolved and signed off by the supervisor.

4.10. Compact Supervisor-Facing Gate-6B Claim Ledger

To establish the complete epistemological standing of all findings for academic supervision, Table 4.6 organizes all 13 core metrics into three mutually exclusive categories:

- **THEORY:** Implemented mathematical formulation and continuum expectations.

- **VERIFIED NUMERICAL EVIDENCE:** Quantities audited directly from raw solver files with verified SHA-256 hashes.
- **UNRESOLVED:** Uninstrumented solver internal states, knowledge boundaries, and active computation items.

Tab. 4.6.: Compact Supervisor-Facing Gate-6B Claim Ledger across 13 Core Metrics.

Metric / Aspect	THEORY (Continuum / Formulation)	VERIFIED EVIDENCE (Audited Artifacts)	UNRESOLVED (Boundaries / Open Scope)
1. Initial Stiffness K_0	Continuum linear elasticity ($\sigma = \mathbb{C}_0 : \varepsilon$) provides reference stiffness; numerical K_0 stabilizes under adequate resolution; no direct constitutive l_0 dependence in mechanical operator; no damage threshold in AT2.	$K_0 = 137.82\text{--}137.95$ kN/mm ($\Delta < 0.089\%$) spatial across $S_1\text{--}S_5$, $\Delta < 0.001\%$ temporal across $T_1\text{--}T_3$, $R^2 > 0.999999$). Baseline S_1 (1406015): 137.9455 kN/mm; S_5 (1406019): 137.8233 kN/mm; T_3 (1406317): 137.9459 kN/mm.	None for standard Mode-I; CONVERGED / STABLE (linear-elastic regime $u \leq 1.0\ \mu\text{m}$, $N = 400$, prior to localized damage evolution).
2. Spatial Peak Force $F_{\max}$	Implemented degradation $g(d) = (1-d)^2 + k_{\text{res}}$ couples strain energy to damage evolution; peak reaction force depends on spatial resolution of steep crack-tip strain gradients.	Monotonic reduction: $F_{\max} = 0.7578$ kN (S_1 , 1406015) $\rightarrow$ 0.7412 kN (S_2 , 1406016) $\rightarrow$ 0.7322 kN (S_3 , 1406017) $\rightarrow$ 0.7290 kN (S_4 , 1406018) $\rightarrow$ 0.7255 kN (S_5 , 1406019), 4.26% drop across $h/l_0 \in [0.133, 0.400]$.	Asymptotic limit requires sub-element models ($h/l_0 < 0.10$); monotonic decrease alone does not prove convergence; MESH-SENSITIVE .
3. Spatial Peak Disp. u_{peak}	Peak displacement u_{peak} marks the limit load state on the global load-displacement curve.	Monotonic shift: $u_{\text{peak}} = 5.857\ \mu\text{m}$ (S_1 , 1406015) $\rightarrow$ 5.711 μm (S_2) $\rightarrow$ 5.633 μm (S_3) $\rightarrow$ 5.606 μm (S_4) $\rightarrow$ 5.575 μm (S_5 , 1406019), 4.81% ($\Delta u = 0.282\ \mu\text{m}$) advance across $S_1 \rightarrow S_5$.	Asymptotic initiation displacement unresolved without finer models; MESH-SENSITIVE .
4. Temporal Peak Force $F_{\max}$	Temporal invariance of limit load is the numerical-convergence expectation being tested under Δt scaling.	Invariant: $F_{\max} = 0.75815$ kN (T_1 , 1406020) $\rightarrow$ 0.75778 kN (T_2 , 1406021) $\rightarrow$ 0.75763 kN (T_3 , 1406317), spread $\Delta < 0.069\%$.	None across tested time-step range; CONVERGED / STABLE .
5. Temporal Peak Disp. u_{peak}	Temporal invariance of peak displacement is the numerical-convergence expectation being tested under Δt refinement.	Invariant: $u_{\text{peak}} = 5.864\ \mu\text{m}$ (T_1 , 1406020) $\rightarrow$ 5.857 μm (T_2 , 1406021) $\rightarrow$ 5.855 μm (T_3 , 1406317), spread $\Delta = 9$ nm (0.15%).	None across tested time-step range; CONVERGED / STABLE .
6. Pre-Peak Work W_{trap} ($u \leq 5.50\ \mu\text{m}$)	Boundary work $W_{\text{trap}} = \int F du$ is obtained by trapezoidal integration of measured reaction force along displacement path.	$W_{\text{trap}} \in [2.035, 2.038]$ mJ across all 11 cases ($\Delta < 0.15\%$). Baseline production (1406015) / diagnostic (1406839): elastic $u = 2\ \mu\text{m}$ gives $W_{\text{trap}} = 0.27540$ mJ, $E_{\text{elas}} = 0.27452$ mJ, $E_{\text{frac}} = 0.00089$ mJ, $\mathcal{R}_{\text{book}} = -0.001\%$; $u = 5.5\ \mu\text{m}$ yields $E_{\text{frac}} = 0.05572$ mJ.	Stable over tested pre-peak range; CONVERGED / STABLE .
7. Terminal Work W_{trap} ($u = 10.0\ \mu\text{m}$)	Terminal W_{trap} , E_{elas} , and E_{frac} are separately observable endpoint quantities; their difference is reported algebraically.	Completed full runs: $W_{\text{trap}} = 2.4101$ mJ (T_1 , 1406020) $\rightarrow$ 2.3593 mJ (T_2 , 1406021) / S_1 , 1406015) $\rightarrow$ 2.3319 mJ (T_3 , 1406317) (3.24% variation); cutback runs ($S_2\text{--}S_5$) truncated at $u = 6.8\text{--}9.6\ \mu\text{m}$.	Terminal work for $S_2\text{--}S_5$ unmeasured due to cutbacks; endpoint values not comparable across different horizons; TEMPORALLY SENSITIVE .
8. Elastic Strain Energy E_{elas}	$E_{\text{elas}} = \sum_e \int \frac{1}{2} g(\bar{d}_e) \varepsilon : \mathbb{C}_0 : \varepsilon d\Omega$ with isotropic quadratic degradation $g(\bar{d}_e) = (1 - \bar{d}_e)^2 + k_{\text{res}}$.	Unit-105 CSV (1406839) & ODB SDV18 IP1 (1406015, 15,192 elems): 0.2745 mJ ($u = 2.0\ \mu\text{m}$) $\rightarrow$ peaks near limit load at 2.2192 mJ ($u = 5.857\ \mu\text{m}$) $\rightarrow$ drops post-fracture to residual 0.0012 mJ (1.1608×10^{-6} kN $\cdot$ mm at $u = 10\ \mu\text{m}$). In S_3 (1406017, 41,912 elems): 0.00067 mJ ($u = 5.857\ \mu\text{m}$, Frame 857) and 0.00066 mJ ($u = 7.836\ \mu\text{m}$, Frame 2837).	Spatial convergence across $S_2, S_4, S_5, A_1\text{--}A_3$ unquantified (unpopulated companion UMAT); residual stiffness $k_{\text{res}} = 10^{-7}$ retained; NOT YET QUALIFIED .
9. Fracture Surface Energy E_{frac}	$E_{\text{frac}} = \sum_e \int G_c [\frac{d^2}{2l_0} + \frac{l_0}{2} \nabla d ^2] d\Omega$; regularized fracture surface energy of diffuse crack.	Unit-105 CSV (1406839) & ODB SDV17 IP1 (1406015): 0.0009 mJ ($u = 2\ \mu\text{m}$) $\rightarrow$ 0.0827 mJ ($u = 5.857\ \mu\text{m}$) $\rightarrow$ 2.3402 mJ ($u = 10\ \mu\text{m}$ in S_1 , 99.19% work). In S_3 (1406017): 2.3570 mJ ($u = 5.857\ \mu\text{m}$, Frame 857) and 2.3572 mJ ($u = 7.836\ \mu\text{m}$, Frame 2837).	Spatial convergence across fine meshes unquantified in cutback runs; NOT YET QUALIFIED .
10. Two-Term Bookkeeping $\mathcal{R}_{\text{book}}$	Pure algebraic difference defined as $\mathcal{R}_{\text{book}} \equiv W_{\text{trap}} - (E_{\text{elas}} + E_{\text{frac}})$; cause of nonzero value/trend unproven.	Baseline S_1 (1406015) / diagnostic (1406839): elastic $u = 2\ \mu\text{m}$ gives -0.001% ; peak $u = 5.857\ \mu\text{m}$ gives $-0.007\% \approx -0.01\%$; terminal $u = 10\ \mu\text{m}$ gives $+0.7607\%$. $T_1 \rightarrow T_3$: $+0.378\% \rightarrow +3.541\%$. Mesh S_3 (1406017): at reference peak $u = 5.857\ \mu\text{m}$ (Frame 857, post-peak residual state in S_3), $W_{\text{trap}} = 2.1899$ mJ, $E_{\text{elas}} = 0.00067$ mJ, $E_{\text{frac}} = 2.3570$ mJ, $\mathcal{R}_{\text{book}} = -0.1678$ mJ (-7.66% on W_{trap} , -7.12% on E_{int}); at terminal $u = 7.836\ \mu\text{m}$ (Frame 2837), $W_{\text{trap}} = 2.1902$ mJ, $E_{\text{elas}} = 0.00066$ mJ, $E_{\text{frac}} = 2.3572$ mJ, $\mathcal{R}_{\text{book}} = -0.1676$ mJ (-7.65% on W_{trap} , -7.11% on E_{int}).	Causal attribution unproved without subiteration logging; TEMPORALLY SENSITIVE .
11. Global Energy Identity $\Delta \mathcal{R}_{\text{closed}}$	Candidate closed form $\Delta \mathcal{R}_{\text{closed}} = 0$ is not established for this staggered implementation (lacks joint potential).	Standard uninstrumented Abaqus output does not persist within-increment path $\mathbf{u}(\tau)$ or $\psi_0^{+,n+1/2}$.	GLOBAL_ENERGY_IDENTITY - NOT_YET_CLOSED : no exact closed algorithmic identity established; standard outputs insufficient; NOT YET QUALIFIED .
12. Crack Centroid Path $y_c(x)$	Symmetric Mode-I benchmark is expected to favor crack extension along geometric center-line $y = 0.500$ mm.	Damage-weighted centroid offset $ y_c - 0.5\ \text{mm} \leq 3.10\ \mu\text{m}$ across all fixed and adaptive meshes (S_1 : 2.46 μm [1406015], S_2 : 2.62 μm [1406016], S_3 : 3.10 μm [1406017], S_4 : 2.93 μm [1406018], $A_1\text{--}A_4 \leq 1.50\ \mu\text{m}$); bounded within single element dimension.	Pure Mode-I symmetry preserved within discrete grid resolution; CONVERGED / STABLE .
13. Localization Band Full-Width	Ideal 1D stationary AT2 profile $d(y) = \exp(- y /l_0)$ has theoretical FWHM $2l_0 \ln 2 \approx 1.386l_0 = 10.4\ \mu\text{m}$ for $l_0 = 7.5\ \mu\text{m}$ (ideal reference, not 2D propagating target).	Measured transverse width $w_{d \geq 0.5} = 20.0\text{--}30.0\ \mu\text{m}$ across ligament ($20.0\text{--}22.9\ \mu\text{m}$ at $x = 0.55$ mm in 1406015); core zone spans $9.5\text{--}14.4\ \mu\text{m}$.	Band width varies $> 40\%$ with mesh resolution (cell-averaged sampling); l_0 sweep shows width scales with regularizing length; MESH-SENSITIVE .

Bibliography

- [1] Bourdin, B., Francfort, G. A., and Marigo, J.-J. Numerical experiments in revisited brittle fracture. *Journal of the Mechanics and Physics of Solids*, 48(4):797–826, 2000. doi:[10.1016/S0022-5096\(99\)00028-9](https://doi.org/10.1016/S0022-5096(99)00028-9).
- [2] Bourdin, B., Francfort, G. A., and Marigo, J.-J. The variational approach to fracture. *Journal of Elasticity*, 91(1–3):5–148, 2008. doi:[10.1007/s10659-007-9107-3](https://doi.org/10.1007/s10659-007-9107-3).
- [3] *Abaqus 2023 Documentation: Analysis User's Guide, User Subroutines Reference Guide, and CAE User's Guide*. Dassault Systèmes Simulia Corp., Providence, RI, USA, 2023.
- [4] Francfort, G. A. and Marigo, J.-J. Revisiting brittle fracture as an energy minimization problem. *Journal of the Mechanics and Physics of Solids*, 46(8):1319–1342, 1998. doi:[10.1016/S0022-5096\(98\)00034-9](https://doi.org/10.1016/S0022-5096(98)00034-9).
- [5] Miehe, C., Welschinger, F., and Hofacker, M. Thermodynamically consistent phase-field models of fracture: Variational principles and multi-field FE implementations. *International Journal for Numerical Methods in Engineering*, 83(10):1273–1311, 2010. doi:[10.1002/nme.2861](https://doi.org/10.1002/nme.2861).
- [6] Pandey, A. and Kumar, S. A simple and robust mesh refinement implementation in Abaqus for phase field modelling of brittle fracture. *Computer Modeling in Engineering & Sciences*, 144(3):3251–3286, 2025. doi:[10.32604/cmes.2025.067858](https://doi.org/10.32604/cmes.2025.067858).
- [7] Zienkiewicz, O. C. and Zhu, J. Z. A simple error estimator and adaptivity for practical engineering analysis. *International Journal for Numerical Methods in Engineering*, 24(2):337–357, 1987. doi:[10.1002/nme.1620240206](https://doi.org/10.1002/nme.1620240206).
- [8] Zienkiewicz, O. C. and Zhu, J. Z. The superconvergent patch recovery and a posteriori error estimates. Part 1: The recovery technique. *International Journal for Numerical Methods in Engineering*, 33(7):1331–1364, 1992. doi:[10.1002/nme.1620330702](https://doi.org/10.1002/nme.1620330702).