

Application of Built in Adaptive Remeshing and Mesh Refinement Features in Abaqus to Phase Field Fracture Simulations

Mode I Supervisor Report

17 September 2026

Pruthviraja Reddy Vandavagali

Master Thesis in Computational Materials Science

Chair of Applied Mechanics IMFD

TU Bergakademie Freiberg

Executive Summary

The Mode-I benchmark reconstruction now has a verified fixed-mesh response anchor, a verified Abaqus-native pre-refinement workflow, and a causally resolved preprocessing defect. The remaining scientific question is the adaptive mesh count: the canonical project rule with `errorTarget=1.0` produces 71,320 finite elements, whereas Pandey and Kumar report 13,941 for their proposed adaptive mesh.

Important distinction between the two reported element counts. The 26,282-element mesh and the 13,941-element mesh do not represent the mesh before and after one adaptive-remeshing operation. They belong to two separate simulations. In the **standard PFM**, a manually refined crack-propagation corridor with $h = 0.003$ mm is embedded in a global $h = 0.02$ mm mesh, resulting in 26,282 finite elements. In the **proposed adaptive PFM**, the analysis starts again from a separate coarse mesh with global $h = 0.02$ mm and no equivalent manually pre-refined corridor. MISESeri then drives native adaptive remeshing to a final mesh of approximately 13,941 elements with local $h = 0.001$ mm. The paper does not report the initial coarse element count for this adaptive route.

Result	Verified value	Scientific meaning
Published standard PFM	26,282 elements	Global $h = 0.02$ mm plus manual $h = 0.003$ mm crack corridor
Published proposed adaptive PFM	13,941 elements	Separate coarse branch; initial count not reported; local $h = 0.001$ mm after remeshing
Project adaptive reconstruction	2,906 → 71,320	Canonical project pre-analysis and <code>errorTarget=1.0</code>
Fixed response anchor 1398090	$F_{\max} = 0.757778$ kN	Close agreement with the published Mode-I force-displacement response
Corrected nominal 1% 1404933	$K_0 = 137.820804$ kN/mm	Stiffness recovered after the N_BOTTOM repair

The reduction from 26,282 to 13,941 must not be interpreted as adaptive remeshing reducing the element count. The correct comparison is between two alternative meshing strategies. Within an adaptive-refinement route, refinement is expected to increase the count relative to that route’s own initial coarse mesh.

Source: Pandey and Kumar (2025), Sections 3.3 and 4.1; project Jobs 1398090, 1399632 and 1404933.

Mode I Benchmark and Quantitative Reference

The benchmark is a 1.0×1.0 mm square plate with a zero-gap horizontal crack of length $a_0 = 0.5$ mm along $y = 0.5$ mm. The publication specifies vertical Mode-I loading and lower-edge support. The single $u_x = 0$ restraint shown below removes rigid-body motion. A top-edge $U_1 = 0$ condition is a project reconstruction choice and is not presented as a published condition.




Figure 1: Mode-I geometry, crack, loading and boundary-condition provenance.




Figure 2: Full force-displacement comparison. Markers identify each peak; shading shows the project OLS range.

Published comparison: Pandey and Kumar (2025), Section 4.1 and Figure 7(a), support comparison of the force-displacement response. **Project-derived quantity:** $K_0 = 137.945520$ kN/mm is obtained from Job 1398090 by an OLS fit over the first 400 active increments; it is not a stiffness value reported by Pandey and Kumar.

Published Adaptive Workflow

The paper describes a two-job pre-refinement process. The coarse analysis is converted to the layered UEL/facsimile representation, MisesERI is requested on All_elem, and Abaqus native remeshing generates a separate refined input for the final phase-field solve.

Pandey-Kumar published two-job adaptive pre-refinement workflow




Figure 3: Published Job-1 to Job-2 adaptive pre-refinement workflow.

Paper reported proposed Mode-I mesh

Initial global size $h = 0.02$ mm
No local pre-refinement
Initial coarse count: **not reported**
Adaptive local size $h = 0.001$ mm
Final adapted count: **13,941**

Project reconstruction

Initial coarse pre-analysis: **2,906 finite elements**
MisesERI on 2,906 underlying elements
errorTarget=1.0
Native adaptiveRemesh
Final adapted count: **71,320**

The workflow is not a refinement of the 26,282-element standard-PFM mesh. Job-1_UEL belongs to the separate proposed adaptive branch, and Job-2_UEL is the refined result of that branch.

Source: Pandey and Kumar (2025), Section 3.3 and Listings 1-4; project canonical pre-analysis audit.

MISESeri and Uniform Error Sizing

MISESeri is an Abaqus stress discretization error indicator associated with the recovered von Mises stress field. A relatively large value indicates that the local finite-element stress representation is comparatively under-resolved. Under UNIFORM_ERROR sizing, such regions tend to demand a finer target mesh. Smaller-error regions demand less refinement. Because `coarseningFactor=NOT_ALLOWED`, the present rule does not use low-error regions to coarsen the mesh.




Figure 4: Defensible qualitative interpretation of MISESeri under the reported remeshing rule.

Canonical Mode-I Spatial Association: Coarse MISESeri vs Native 1% Mesh Refinement




Figure 5: Observed project relationship between coarse MISESeri and local size in the native 1% mesh. This is an empirical spatial association, not a universal sizing formula.

`errorTarget=1.0` specifies a **1% target error tolerance under Abaqus UNIFORM_ERROR sizing**. It does not mean “refine 1% of the elements,” and it is not the direct condition `MISESeri >= 0.01`. Abaqus combines the error field, target tolerance, size bounds, refinement factor and internal sizing logic. The exact internal MISESeri-to- h transformation has not been established from the available documentation or evidence.

Stiffness Anomaly and Boundary Set Repair

The low-stiffness 71,320-element branch was caused by malformed N_BOTTOM formatting, not by the adaptive mesh or phase-field constitutive response. The original set placed 150 node IDs on one free-format data line; Abaqus retained only the first 16, leaving 134 bottom nodes free vertically.




Figure 6: Initial elastic-range zoom. The corrected model and fixed reference overlap near 138 kN/mm; the defective branch remains near 122.38 kN/mm.




Figure 7: Verified preprocessing defect and deterministic repair.

Model	Elements	K_0 [kN/mm]	$F_{\max}$ [kN]	$u(F_{\max})$ [mm]
Fixed reference 1398090	15,192	137.945520	0.757778	0.005857
Defective diagnostic 1399632	71,320	about 122.38	0.478203	0.004150
Corrected nominal 1% 1404933	71,320	137.820804	0.745325	0.005750

A separate frozen-damage requalification, Job 1405044, independently recovered $K_0 = 138.021013$ kN/mm, confirming that stiffness recovery occurs before fracture evolution.

Abaqus Release Study

The canonical native remeshing operation was reproduced across the installed Linux releases. The generated adapted topology remained unchanged, so release version does not explain the 71,320-versus-13,941 discrepancy.

Abaqus environment	Adapted finite elements	Result
Abaqus 2019 Linux	71,320	same canonical adapted topology/artifact
Abaqus 2021 Linux	71,320	same
Abaqus 2022 Linux	71,320	same
Abaqus 2023 Linux	71,320	same

Within the tested Linux Abaqus 2019-2023 releases, release version does not explain the 71,320-versus-13,941 discrepancy.


The Abaqus 2019 PBS wrapper had a walltime/logging issue, but the generated remeshing artifact was available and matched the canonical result. Any Windows/Abaqus 2024 observation should be treated separately as a platform-plus-release-confounded sensitivity, not as a clean release comparison.

What the release result rules out

- A simple Linux release change from 2019 through 2023 does not change the adapted count.
- The element-count discrepancy therefore requires a different explanation, such as an unreported modeling, meshing or execution detail.
- This conclusion concerns the generated adaptive mesh artifact; it does not claim identity of every solver or scheduler detail.

Standard PFM versus Proposed Adaptive PFM versus This Reconstruction

All three lanes address the same Mode-I benchmark, but they are independent discretization strategies. The two paper counts are final counts from different simulations, while the project count pair explicitly shows the before-and-after values within one adaptive route.



Do not read horizontally as 26,282 -> 13,941. The branches are independent discretization strategies.

Paper adaptive route: initial count not reported -> 13,941 | Project adaptive route: 2,906 -> 71,320

Figure 8: Independent meshing branches and the only valid within-route count comparisons.

Do not read this figure horizontally as 26,282 → 13,941. The branches are independent discretization strategies.

Paper adaptive route: initial count not reported → 13,941. Project adaptive route: 2,906 → 71,320.

Abaqus uses MISESeri and the RemeshingRule settings to determine a spatial target-size field. The inputs and resulting mesh are observable, but the exact internal numerical transformation has not been established. The report therefore compares verified input fields, rule parameters, spatial patterns and resulting element counts rather than inventing a direct MISESeri-to- h equation.

Element Count Discrepancy Sensitivity Audit

The following one-factor tests show how the adapted count responds to controlled changes. Several factors materially change the count, but none reproduces 13,941 while retaining the published Mode-I RemeshingRule settings.

One-factor test	Adapted finite elements	Interpretation
Canonical $\text{errorTarget}=1.0$	71,320	baseline
Abaqus 2019 Linux	71,320	release insufficient
Abaqus 2021 Linux	71,320	release insufficient
Abaqus 2022 Linux	71,320	release insufficient
Abaqus 2023 Linux	71,320	release insufficient
$\text{outputFrequency}=\text{LAST_INCREMENT}$	71,320	no effect
$\text{refinementFactor}=3$	47,428	substantial effect; insufficient
coarsening enabled/default	71,037	negligible
minimum-size specification removed	71,320	no effect
maximum-size specification removed	70,736	negligible
coarse global seed 0.03 mm	48,919	substantial but insufficient
top-edge U_1 released	55,761	substantial but insufficient
CPE4 $\rightarrow$ CPE4R	103,706	wrong direction
CPS4 branch	58,679	confounded formulation sensitivity
$\text{errorTarget}=2.0$	17,687	sensitivity only; not evidence paper used 2%
$\text{errorTarget}=3.0$	8,120	sensitivity only
$\text{errorTarget}=5.0$	4,356	sensitivity only

Element-count proximity alone cannot identify the paper's executed setting. In particular, the 2%, 3% and 5% branches are sensitivity results; they do not show that Pandey and Kumar used a different errorTarget from the published value of 1.0.

Remaining Mode I Discrepancy and Current Scientific Conclusion

The canonical reconstruction produces 71,320 finite elements whereas Pandey and Kumar report 13,941 for their proposed Mode-I adaptive mesh. Abaqus release, output frequency, top lateral constraint, element formulation, global seed, coarsening, refinement factor, sizing bounds and error-target sensitivities have been investigated. Several parameters materially change the mesh count, but no tested case reproduces 13,941 while simultaneously preserving the retained published Mode-I RemeshingRule settings. The exact source of the discrepancy therefore remains unresolved.

Conclusions

- The fixed reference reproduces the published Mode-I force-displacement response closely.
- The paper’s 26,282-element standard mesh and 13,941-element adaptive mesh are separate branches, not the before-and-after states of one remeshing operation.
- The low-stiffness 71,320 branch was caused by malformed N_BOTTOM formatting and is resolved.
- The corrected 71,320-element model recovers K_0 but retains a modest peak-response difference.
- Canonical 1% native remeshing gives 71,320 finite elements versus the paper’s 13,941.
- Abaqus 2019-2023 does not explain the discrepancy.
- Multiple controlled sensitivities alter the adapted count but do not establish the reported 13,941 configuration.
- The remaining element-count discrepancy is the unresolved Mode-I reproduction question.

Comparison	Initial adaptive-branch count	Final adapted count
Pandey-Kumar adaptive route	not reported	13,941
Project adaptive route	2,906	71,320

References

1. Pandey, A. and Kumar, S. (2025). A Simple and Robust Mesh Refinement Implementation in Abaqus for Phase Field Modelling of Brittle Fracture. *Computer Modeling in Engineering and Sciences*, 144(3), 3251-3286. <https://doi.org/10.32604/cmes.2025.067858>.
2. Molnar, G. and Gravouil, A. (2017). 2D and 3D Abaqus implementation of a robust staggered phase-field solution for modeling brittle fracture. *Finite Elements in Analysis and Design*, 130, 27-38. <https://doi.org/10.1016/j.finel.2017.03.002>.
3. Msekh, M. A., Sargado, J. M., Jamshidian, M., Areias, P. M. and Rabczuk, T. (2015). Abaqus implementation of phase-field model for brittle fracture. *Computational Materials Science*, 96, 472-484. <https://doi.org/10.1016/j.commatsci.2014.05.071>.
4. Dassault Systemes. Abaqus 2023 Documentation. Analysis User's Guide, Theory Guide and input syntax documentation for adaptive remeshing and stress error indicators.

Primary Project Evidence

- Job 1398090 fixed response anchor and project OLS stiffness extraction.
- Job 1399632 defective preprocessing diagnostic and N_BOTTOM warning evidence.
- Job 1404933 corrected nominal-1% full-fracture response.
- Job 1405044 frozen-damage stiffness requalification.
- Canonical 2,906-element MISESeri pre-analysis and native 71,320-element adapted artifact.
- Controlled Abaqus 2019-2023 release study and one-factor mesh-count sensitivity records.

All job identifiers and numerical values in this report refer to project-controlled extraction artifacts. No element count, stiffness value or internal Abaqus sizing law has been inferred beyond the recorded evidence.