

Technical Progress Report

Mode-II Production Adaptive Remeshing Validation, Accurate Uniform Reference Reconciliation, and Final Master Thesis Candidate Synthesis

Author Pruthviraja Reddy Vandavagali (Matr. Nr. 68865)
Programme Master Thesis, TU Bergakademie Freiberg
Examiners Prof. Dipl.-Ing. Björn Kiefer, Ph.D. (1st Examiner) · Dr.-Ing. Stephan Roth (2nd Examiner)
Date 28 August 2026
Objective Accurate phase-field fracture with locally refined meshes, controlled state transfer, and an audited order-of-magnitude computational-cost reduction.

Progress since the 11 August report. The previously recorded open comparison boundary (adaptive force leveling off at ~ 0.1785 kN vs ~ 0.358 kN in uniform references) has been **systematically investigated, resolved, and verified in Stage G production runs**. Both adaptive-to-adaptive consistency and adaptive-to-uniform accuracy are now proven within $\leq 1.43\%$ error at a $> 12\times$ CPU runtime speedup.

Major validated result. The final production adaptive jobs (MM, Job 1394260, 2,206 elements; PK5, Job 1394261, 4,894 elements) completed 100% of the prescribed Mode-II shear loading ($u_1 = 0.0100$ mm). In the common pre-peak domain, Candidate 1 (MM) achieves a normalized L_2 force error of **1.4249%**, an external work error of **0.8134%**, and an initial elastic stiffness error of **0.2425%** relative to the authoritative uniform H_1 reference, while reducing CPU execution time by **12.16 $\times$** (19.98 min vs 241 min for H_2).

Current validation status. All seven validation ladder stages (A through G) are complete and validated. The 58-page thesis manuscript is compiled, verified with 0 errors/warnings, and frozen for supervisor review.

Pre-peak uniform verification	PASS	Locally refined adaptive calculations	PASS
Adaptive-to-uniform accuracy	PASS	Matched-state damage initiation	PASS
State-transfer formulation	VALIDATED	Physical invariant preservation ($d \in [0, 1]$)	PASS
Irreversibility audit (72 frames)	PASS	Computational speedup (12.16 $\times$)	PASS
Thesis manuscript build	VALIDATED	Supervisor role sign-off	HOLD

Status statement. The computational simulation campaign is officially closed. No additional HPC simulations are scientifically required. The thesis manuscript (`docs/thesis/THESIS_FACULTY_BUILD.pdf`) is submitted for supervisor role sign-off.


1. Resolution of the 11 August Force-Discrepancy Boundary

The 11 August progress report documented an exploratory comparison where two locally refined meshes (MM Job 1386469 and PK5 Job 1386470) exhibited high mutual agreement (0.16% discrepancy), but their late reaction force plateaued near ~ 0.1785 kN, whereas the uniform H_1/H_2 peak reached ~ 0.3581 kN.

Root-Cause Analysis and Physical Separation:

1. **Separation of Discrete Slit Testing from Continuum Fracture:** The preliminary exploratory decks included artificial discrete facet splitting (duplicate-node slit lines) intended for numerical transfer testing. Under pure shear loading, discrete slit insertion introduced kinematic boundary alterations that prematurely relaxed shear stresses.
2. **Governing Variational Formulation (CONTINUOUS_PHASE_ONLY):** In accordance with the formal scientific decision packet (STAGE_F_SCIENTIFIC_DECISION_PACKET.md), discrete facet cuts were isolated strictly to synthetic numerical operator testing (Stage F). Production adaptive remeshing (Stage G) was governed purely by continuous variational phase-field degradation $g(d) = (1 - d)^2 + k$ on the continuous plate geometry.

Production Re-Execution and Verification: Production meshes were coupled to the qualified mixed quadrilateral/triangle user subroutine (f42_mixed_uel.for) and executed under cluster jobs **1394260** (MM) and **1394261** (PK5). Both reached 100% completion ($u_1 = 0.01000$ mm, 2,500 increments, 0 cutbacks, exit status 0).



2. Discretization Statistics and Computational Resource Audit

Model / Case	Job ID	N_{phys}	N_{nodes}	CPU (s)	Wall (s)	Status / Endpoint
H_1 Reference	1386447	12,064	12,382	5,434.0	5,453.0	Cutback Cutoff ($u_1 = 0.00963$ mm)
H_2 Baseline	1386448	33,852	34,508	14,455.0	14,501.0	Walltime Censored ($u_1 = 0.00925$ mm)
Candidate 1 (MM)	1394260	2,206	2,294	1,189.0	1,199.0	Complete ($u_1 = 0.01000$ mm)
Candidate 2 (PK5)	1394261	4,894	4,998	2,609.0	2,622.0	Complete ($u_1 = 0.01000$ mm)

Execution and Convergence Notes:

- **H_1 Reference:** Reaches an interior reaction force of 0.3581 kN and terminates at $u_1 = 0.009630$ mm due to standard cutback limits during steep softening.
- **H_2 Ultra-Fine Baseline:** Walltime-censored at $u_1 = 0.009250$ mm after consuming 14,455 s CPU (4.01 h). Domain A is defined as the shared interval $0 \leq u_1 \leq 0.009250$ mm.
- **MM Adaptive (Candidate 1):** Uses 2,206 physical elements (81.7% element count reduction vs H_1). Completes 2,500 increments in 1,189 s CPU (19.98 min walltime), achieving a **12.16 $\times$ scheduler-CPU speedup** relative to the censored H_2 baseline.
- **PK5 Adaptive (Candidate 2):** Uses 4,894 physical elements (59.4% reduction vs H_1). Completes 2,500 increments in 2,609 s CPU (43.70 min walltime), achieving a **5.54 $\times$ scheduler-CPU speedup**.

3. Hard Physical Invariant and State-Admissibility Verification

Primary field output extracted independently across all 72 saved ODB field frames (51 frames in Step 1, 21 frames in Step 2) confirms strict adherence to continuum damage mechanics invariants:

Model	Phase Range d	Irreversibility	History Range $\mathcal{H}$ [MPa]	Monotonicity	Status
Candidate 1 (MM)	[0.0000, 0.9823]	0 violations	[0.00, 31.47]	0 violations	PASS
Candidate 2 (PK5)	[0.0000, 0.9840]	0 violations	[0.00, 35.36]	0 violations	PASS

- **Phase Boundedness:** $0 \leq d(\mathbf{x}, t) \leq 0.9840 \leq 1.0$ everywhere. Zero negative or unphysical overshoot values occur.
- **Pointwise Irreversibility:** Across all adjacent frame pairs, pointwise damage increments satisfy $d_{n+1}(\mathbf{x}) \geq d_n(\mathbf{x})$ with exactly **0 negative transitions**.
- **History Non-Negativity and Monotonicity:** $\mathcal{H} \geq 0$ and $\Delta\mathcal{H} \geq 0$ strictly hold at every integration point throughout the simulation.

4. Quantitative Accuracy in the Common Pre-Peak Domain

Over the common overlapping interval Domain A ($0 \leq u_1 \leq 0.009250$ mm), both locally refined candidates demonstrate close quantitative agreement with the authoritative uniform H_1 reference ($W_{\text{ext},H_1} = 0.00184893$ kN · mm):

Comparison Pair	Norm. L_2 Error (%)	Rel. Work Error (%)	Stiffness Error (%)	Assessment
Candidate 1 (MM) vs H_1 Ref	1.4249	0.8134	0.2425	Within Criterion ($\leq 2.0\%$)
Candidate 2 (PK5) vs H_1 Ref	1.1467	0.5751	0.1003	Within Criterion ($\leq 2.0\%$)
Candidate 1 (MM) vs H_2 Base	1.8632	1.0789	0.3067	Within Criterion ($\leq 2.0\%$)
Candidate 2 (PK5) vs H_2 Base	1.5868	0.8400	0.1644	Within Criterion ($\leq 2.0\%$)
MM vs PK5 (Mutual Agreement)	0.3003	0.2370	0.1420	High Consistency




Figure 1. Global Mode-II shear reaction force vs. prescribed displacement curves. Both production locally refined candidates (MM and PK5) track the H_1 reference curve throughout loading and complete the full trajectory to $u_1 = 0.01000$ mm.

5. Pointwise Discrepancy Reconciliation vs Global Error




Figure 2. Pointwise relative force discrepancy of locally refined candidates vs. the authoritative H_1 uniform reference over Domain A ($0 \leq u_1 \leq 9.25 \mu\text{m}$).

Reconciliation of Pointwise vs Integral Metrics:

- **Global Integral Accuracy:** Normalized L_2 curve errors (1.42% MM, 1.15% PK5) and relative work errors (0.81% MM, 0.58% PK5) integrate across the entire loading range and lie well within the $\leq 2.0\%$ acceptance gate.
- **Localized Initiation Peak:** Near damage initiation ($u_1 \approx 8.4\text{--}8.7 \mu\text{m}$), pointwise relative force errors temporarily peak at 3.81% (MM) and 3.21% (PK5). This localized discrepancy directly reflects the discrete frame sampling bracket difference ($\Delta u_1 = 0.25 \mu\text{m}$, crossing at 0.00775 mm for H_1 vs 0.00825 mm for MM/PK5). Once localized softening engages, pointwise errors drop back to $\leq 1.0\%$.

6. Computational Speedup and Efficiency




Figure 3. Mesh size reduction (log scale) and CPU execution time comparison between the fine H_2 baseline (censored at $u_1 = 9.25 \mu\text{m}$) and the complete production locally refined models (MM and PK5).

Case	Elements	CPU Time (s)	Scientifically Comparable Response Statement
H_1 Reference	12,064	5,434.0	Authoritative uniform reference; cutoff at $u_1 = 0.00963 \text{ mm}$
H_2 Baseline	33,852	14,455.0	Ultra-fine baseline; walltime-censored at $u_1 = 0.00925 \text{ mm}$
MM Adaptive	2,206	1,189.0	12.16× CPU speedup vs H_2 ; L_2 error = 1.42%; full endpoint
PK5 Adaptive	4,894	2,609.0	5.54× CPU speedup vs H_2 ; L_2 error = 1.15%; full endpoint

Supported conclusion. Both adaptive-to-adaptive repeatability (0.30% mutual difference) and adaptive-to-uniform accuracy ($< 1.43\% L_2$ error) are rigorously demonstrated. High-accuracy phase-field fracture simulation is achieved with greater than an order-of-magnitude runtime reduction (12.16×).

7. Overview of the Multi-Stage Validation Ladder (Stages A–G)

Stage	Focus & Scope	Governed Status	Key Scientific Outcome
Stage A	Baseline Molnar Mode-I	VALIDATED	Exact paper-matched benchmark reproduction ($l_0 = 0.015$ mm)
Stage B	Native Abaqus Restart	VALIDATED	Bit-for-bit binary solver restart repeatability
Stage C	Same-Mesh Reconstructed Restart	VALIDATED	Nodal/Gauss-point state re-ingestion formulation proof
Stage D	Nonmatching Transfer (Same Topology)	VALIDATED	Spatial interpolation proof with strict slit-barrier node isolation
Stage E	Multi-Resolution State Transfer	VALIDATED	State transfer across coarsened (R2) and refined (R1) meshes
Stage F	Synthetic Topology Benchmark	VALIDATED	State transfer across discrete mesh split (numerical test only)
Stage G	Production Adaptive Validation	VALIDATED	Production accuracy ($L_2 < 1.43\%$) & efficiency ($12.16\times$) proof

8. Thesis Manuscript Integration and Next Steps

The verified results, derivations, and figures are integrated into the official faculty LaTeX build:

- **Submission Candidate:** docs/thesis/THESIS_FACULTY_BUILD.pdf (58 pages, 0 errors, 0 warnings).
- **Candidate Checksum (SHA-256):** 17B1C94024FAA658C4D0A1A04225E36EDA8E3B5237BBD088C9AF2F3A8B8
- **Supervisor Review Package:** docs/thesis/SUPERVISOR_REVIEW_PACKAGE.md.

Provisional Candidate Roles for Supervisor Ratification:

1. **Candidate 1 (M2PROD_ADAPT_MM, 2,206 elements):** Recommended as the **Primary Production Efficiency Candidate** ($> 12\times$ runtime reduction, $1.42\%L_2$ error).
2. **Candidate 2 (M2PROD_ADAPT_PK5, 4,894 elements):** Recommended as the **Corridor Resolution Sensitivity Candidate** ($5.54\times$ runtime reduction, $1.15\%L_2$ error).