Latent Cartographer: a transformer trained on move sequences builds, uses and exposes a map

Belief tracking, egocentric localisation and probabilistic place cells in a 0.8M-parameter GPT

PS12007 · technical report · October 2026 · code & data github.com/PS12007/latent-cartographer · interactive demo ps12007.github.io/latent-cartographer

Abstract. We train a small GPT on random walks through a hidden 8×8 maze, written only as move tokens (`N E S W`); the start cell is given in a third of sequences and unknown in the rest. Because the walker chooses uniformly among open directions, the Bayes-optimal next-move distribution and the exact posterior over the walker's cell are computable, which gives ground truth for both behaviour and internal state. The model comes within 0.006 nats of the optimal loss. Its residual stream contains a linearly decodable belief over all 64 cells (KL 0.10 nats to the exact posterior, 98.7% cell accuracy once localised). That belief is causal: steering it to another cell changes the predicted legal moves to that cell's 90% of the time (random edits: 4%), and steering to every cell in turn recovers all 112 interior walls of the maze from the model alone. Mechanistically, one uniform-attention head integrates moves into a displacement. Middle layers then hold an egocentric sketch of walked passages, and editing a single remembered passage shifts the belief between candidate cells in the direction a map-matching account predicts. Location is recomputed from the move history at every token rather than carried forward. Early layers lay the cells out as a flat sheet in grid coordinates; the last MLP contains place cells whose activity tracks the posterior probability of their cell. Results replicate on three further mazes and a 12×12 maze, survive walking policies never seen in training, and extend to a "slippery" world where the belief must stay graded even when the start is known.

1 · Introduction

Whether sequence models trained on next-token prediction build internal models of the process that generated their data is a central question in interpretability. Board-game studies found decodable and causally editable board states in Othello-playing transformers [1, 2]. Work on hidden Markov processes showed that residual streams can encode Bayesian belief states [3]. A study of real taxi routes found that strong next-token prediction can coexist with an *incoherent* map [4]. Navigation is a natural middle ground. It has a spatial latent that can be drawn, a known neuroscience of path integration and place cells [5, 6, 7], and, when the generating process is chosen carefully, an exactly computable optimal observer.

We build such a setting and push it as far as a single small model allows: from behaviour to linear representations, to causal edits, to an end-to-end readout of the whole environment, and finally to heads, neurons and the geometry of the representation.

2 · Setup

World. A randomised depth-first-search maze on an 8×8 grid, with 35% of remaining interior walls removed so that the maze has loops. **Data.** Uniform random walks of 64 moves. A sequence is `[start, m₁, …, m₆₄]`, where `start` is either the start cell (35%) or an "unknown" token. **Model.** A pre-LayerNorm GPT with 4 blocks, d=128, 4 heads, learned positions and a 4-way output head (811k parameters), trained for 20k steps of batch 256 with next-token cross-entropy on *sampled* moves (≈330M tokens; 7.5 minutes on a laptop GPU). **Ground truth.** With uniform choice among open sides, the posterior over the current cell after moves $m_1..m_t$ follows the exact recursion $b_t(c') \propto \Sigma_c\, b_{t-1}(c)\cdot P(m_t|c)\cdot[c' = \text{next}(c, m_t)]$, and the optimal predictive distribution is $\Sigma_c\, b_t(c)\cdot P(m|c)$. We verify the filter against brute-force enumeration over start cells, and in the slippery variant over every slip pattern.




Figure 1. One unknown-start walk. Top: exact posterior. Bottom: belief decoded from the residual stream after block 3 by a linear probe. The decoded belief follows the multi-modal posterior as it collapses. In the last panel the probe slips one cell; across the test set it is exact on 96% of localised steps, and 64% of its errors are within one cell.

3 · Behaviour and representation

The model reaches cross-entropy 0.9929 nats against the optimal 0.9888, a KL of 0.0001 nats per move with a known start and 0.006 with an unknown start. We fit linear probes at the nine points of the residual stream (Fig. 2). Displacement since the start is linear after block 1 (R^2 0.97), then fades. A 64-way softmax probe trained against the exact posterior falls from KL 3.42 (embedding) to 0.10 (block 4 attention), with 98.7% top-1 accuracy once localised. It stays at KL 0.31 on steps where the posterior is still spread over several cells. Decoding the posterior from the model's own output distribution with an MLP gives only KL 1.64, so the stream carries far more than the 4-way prediction requires. A randomly initialised network of the same shape gives KL ≈3.3 at every layer.




Figure 2. Linear probes across depth for displacement, the full belief, and the current cell. Dashed: random initialisation. Dotted: time-only and output-decoded baselines.

4 · The belief is causal, and the maze can be extracted

On walks where the posterior is certain the walker is in cell c, we edit the newest token's residual vector only, toward a random cell c' with different open sides. Success means the set of moves given more than 10% probability equals the open sides of c'. Moving along the probe direction, $x + \alpha\|\mu_{c'} - \mu_c\| \cdot \mathrm{unit}(W_{c'} - W_c)$, succeeds 90% of the time after block 3 at $\alpha = 2$ (random direction of equal norm: 3.5%), with a dose-response that peaks and then declines. Replacing the whole vector with one from a walk that ends at c' succeeds 10%, 18%, 34%, 74% and 100% of the time at successive depths. Before block 3, later layers re-derive location from the history and overwrite edits at a single token. A minimum-norm edit $W^{+}(z' - z)$ that swaps two probe logits fails (≤6%). It also constrains the other 62 logits, which pulls the edit away from the directions the network reads.

Steering to each of the 64 cells and recording the allowed moves recovers **all 112 interior walls**. The edit does not persist: if the walk continues with a move legal from c', the next prediction ignores the edit (14% vs 14% unsteered). Location is recomputed at every token, a parallel style of computation consistent with analyses of fixed-depth transformers [8].




Figure 3. Steering success by depth for four edit types (left), and dose-response after block 3 (right).

5 · Mechanism: dead reckoning, an egocentric sketch, and matching

Rejected hypothesis. A natural parallel algorithm has each token mark the start cells its own move rules out and later layers average these exclusion masks. The single-step mask is not linearly decodable (balanced accuracy 0.58 vs 0.51 at random init). The cumulative set of surviving starts is only weakly recoverable even with an MLP probe (0.87 vs 0.77).

Egocentric sketch. What is decodable is a window of the walk relative to the walker's current position: which offsets have been visited and which passages walked. It peaks in block 3 (balanced accuracy 0.89 and 0.84, vs ≈0.6 at random init) and declines as the maze-frame position takes over. To test use, we take moments with exactly two candidate cells, A (true) and B, and write "this passage was walked" into the residual stream after block 3, for a passage not yet walked. A passage that exists only around B shifts P(B)/(P(A)+P(B)) by +0.28 ± 0.01 at α = 8. One that exists only around A shifts it by −0.11 ± 0.01, and one that exists around both by +0.06 ± 0.01 (n = 600). The opposite signs are what a map-matching mechanism predicts.




Figure 4. Editing one remembered passage moves the belief toward the candidate cell at which that passage exists. Bands: 95% intervals.

Heads. Mean-ablating single heads separates roles. Block-1 head 1 attends almost exactly uniformly (normalised entropy 0.999) and is the integrator: ablating it raises known-start KL from 0.0001 to 0.92. Block-1 head 3 reads the start token. Nine heads, concentrated in blocks 2 and 3, cost 7–80× more when the start is unknown than when it is given.




Figure 5. Damage from mean-ablating each head, for known-start (x) versus unknown-start (y) walks.

6 · Geometry and neurons

Averaging activations per cell over localised moments gives 64 points per layer. After block 1 two principal components carry 85% of their variance and redraw the maze as an intact sheet. Representational distances track grid distance (Spearman 0.90). Walking distance adds nothing given grid distance (partial 0.01), while grid distance adds a lot given walking distance (0.72), so this is a coordinate map, not a graph. By block 4 the grid structure is gone (0.02) and cells group by their wall configuration (0.49), the format needed for the output.




Figure 6. Left and centre: first two principal components of per-cell mean activations after blocks 1 and 4. Right: rank correlation of representational distance with grid distance, walking distance and wall dissimilarity.

Location-selective MLP neurons appear with depth: 0, 1, 18 and 127 of 512 in blocks 1–4. A neuron counts as a place cell if its cell explains most of its variance, far more than the cell's wall configuration does, within a compact field. When the model is uncertain, these neurons follow the posterior probability of their cell (mean r = 0.45) more closely than an indicator of the most likely cell (0.33) or of the true cell (0.24), for 98% of them. This graded code resembles probabilistic population codes proposed for Bayesian computation in the brain [9].

Template matching. If a place neuron for cell *c* performs the match, walked passages that exist around *c* should excite it and passages that would cross a wall there should inhibit it. Ridge regressions of 64 strong place neurons on the 98 egocentric passage features give receptive fields that correlate with the layout around the neuron's own cell (r = 0.79; other cells -0.01; own cell best of 64 for 92%). Because a neuron that merely fires at *c* would show the same pattern, we also measure causal receptive fields by writing each passage feature into the residual stream after block 3. They still single out the own cell (r = 0.30 vs -0.02; best of 64 for 58%, chance 1.6%), though more weakly (Fig. 8).




Figure 7. Six block-4 place cells (mean activation per cell), and the correlation of each place cell's activity with posterior probability versus with "most likely cell" on uncertain moments.




Figure 8. Top: passage layout around three place neurons' cells. Bottom: their causal receptive fields. Right: rank of the neuron's own cell among the 64 cell templates, against chance.

7 · Robustness and a slippery world

maze	KL to optimal (given / unknown)	probe cell acc.	steering (random)	walls	persistence
8×8, seed 0	0.0001 / 0.0062	98.7%	90% (4%)	112/112	14% / 14%
8×8, seed 1	0.0001 / 0.0054	98.4%	84% (3%)	112/112	14% / 14%
8×8, seed 2	0.0001 / 0.0052	98.9%	89% (3%)	112/112	12% / 12%
8×8, seed 3	0.0001 / 0.0058	98.1%	82% (4%)	112/112	14% / 14%
12×12, seed 0	0.0002 / 0.0131	96.4%	80% (4%)	261/264	12% / 12%

Each row is an independent model and maze. On walks that never backtrack, or that keep their heading 80% of the time, the predicted legal set stays correct (99.8% with a known start; 98.7–98.8% after localisation from an unknown start): the model learned the maze, not the walk statistics. Depth helps localisation far more than dead reckoning: unknown-start KL falls 0.21 → 0.044 → 0.015 → 0.006 → 0.0026 for 1, 2, 3, 4 and 6 blocks, while one block already reaches 0.003 with a known start.

In a SLIPPERY variant, 15% of moves silently fail, so the posterior stays uncertain even with a known start. The model reaches 0.014 nats of the optimum. A linear probe recovers the posterior with KL 0.42 (time-only baseline 2.63; slip-unaware dead reckoning 7.5), and its entropy follows the true entropy step by step ($r = 0.75$). The linear readout is more diffuse than the truth (+0.42 nats); an MLP readout reaches KL 0.32 and +0.17 nats, so most of the blur is the probe's.

8 · Limitations

All models share one architecture and small worlds, and the mechanistic analyses (Sections 5–6) were run on one maze. The matching step, where MLPs in blocks 3–4 compare the egocentric sketch with the stored maze, is only partly explained by the causal template effect, and the block-3 computation feeding the place neurons is untraced. Steering uses class-mean distances, computed with ground-truth labels, to set the edit size. Uniform random walks are friendly data, and the clean picture here may not survive partial observability or real trajectories [4].

References

1. K. Li et al. Emergent world representations: exploring a sequence model trained on a synthetic task. ICLR 2023.
2. N. Nanda, A. Lee, M. Wattenberg. Emergent linear representations in world models of self-supervised sequence models. 2023.
3. A. Shai et al. Transformers represent belief state geometry in their residual stream. NeurIPS 2024.
4. K. Vafa et al. Evaluating the world model implicit in a generative model. NeurIPS 2024.
5. A. Banino et al. Vector-based navigation using grid-like representations in artificial agents. Nature 2018.
6. C. Cueva, X.-X. Wei. Emergence of grid-like representations by training recurrent neural networks to perform spatial localization. ICLR 2018.

7. J. Whittington, J. Warren, T. Behrens. Relating transformers to models and neural representations of the hippocampal formation. ICLR 2022.
8. W. Merrill, J. Petty, A. Sabharwal. The illusion of state in state-space models. ICML 2024.
9. W. J. Ma, J. Beck, P. Latham, A. Pouget. Bayesian inference with probabilistic population codes. Nature Neuroscience 2006.