

Tidy data

PS239T

03 February, 2019

- I adapted the following content from Wickham's R for Data Science, his earlier paper published in the Journal of Statistical Software, and Efficient R Programming by Gillespie and Lovelace.
- The big picture
 - Tidying data with **tidyr**
 - Processing data with **dplyr**

1. What're tidy principles

1. The dataset: strucure (physical layout) + semantics (meaning)

1.1. Data structure

- rows and columns

1.2. Data semantics

- variables > values (numbers or strings)

2. Tidy tada: “provide a standard way to organize data values within a dataset.”

2.1 Tidy principles

- 1. Each variable forms a column.
- 2. Each observation forms a row.
- 3. Each type of observational unit forms a table.

```
# load library
library(tidyverse)
```

```
## -- Attaching packages ----- tidyverse 1.2.1 --
```

```
## v ggplot2 3.1.0      v purrr   0.3.0
## v tibble  2.0.1      v dplyr  0.7.8
## v tidyr   0.8.2      v stringr 1.3.1
## v readr   1.3.1      v forcats 0.3.0
```

```
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
```

```
# tidy data example
table1
```

```
## # A tibble: 6 x 4
##   country    year cases population
##   <chr>      <int> <int>      <int>
## 1 Afghanistan 1999    745   19987071
## 2 Afghanistan 2000   2666   20595360
## 3 Brazil      1999  37737  172006362
## 4 Brazil      2000  80488  174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

Practically, this approach is good because you're going to have consistency in the format of data across all the projects you're working on. Also, tidy data works well with key packages (e.g., dplyr, ggplot2) in R.

Computationally, this approach is useful for vectorized programming because "different variables from the same observation are always paired".

3. Messy datasets

3.1. Signs of messy datasets

- 1. Column headers are values, not variable names.
- 2. Multiple variables are not stored in one column.
- 3. Variables are stored in both rows and columns.
- 4. Multiple types of observational units are stored in the same table.
- 5. A single observational unit is stored in multiple tables.

4. Tidy tools

Either input or output or both of them can be messy. Tidy tools can fix these problems.

4.1. Tidy manipulation (organizing)

4.1.1. Gather (from wide to long)

table4a

```
## # A tibble: 3 x 3
##   country    `1999` `2000`
##   * <chr>      <int> <int>
## 1 Afghanistan    745    2666
## 2 Brazil        37737   80488
## 3 China         212258  213766
```

from long to wide

```
table4a %>%
  gather('1999', '2000', key = "year", value = "population")
```

```
## # A tibble: 6 x 3
##   country    year population
##   <chr>      <chr>      <int>
## 1 Afghanistan 1999          745
## 2 Brazil      1999        37737
```

```
## 3 China      1999      212258
## 4 Afghanistan 2000        2666
## 5 Brazil      2000      80488
## 6 China      2000      213766
```

```
# save the file
table4a_wide <- table4a %>%
  gather('1999', '2000', key = "year", value = "population")
```

4.1.2. Spread (from wide to long)

```
table4a_wide %>%
  spread(key = "year", value = "population")
```

```
## # A tibble: 3 x 3
##   country    `1999` `2000`
##   <chr>      <int> <int>
## 1 Afghanistan    745   2666
## 2 Brazil        37737 80488
## 3 China         212258 213766
```

4.1.3. Separate (split one into many columns)

```
table3
```

```
## # A tibble: 6 x 3
##   country    year rate
##   * <chr>    <int> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
table3 %>%
  separate(rate, into = c("cases", "population"))
```

```
## # A tibble: 6 x 4
##   country    year cases population
##   <chr>    <int> <chr>    <chr>
## 1 Afghanistan 1999 745    19987071
## 2 Afghanistan 2000 2666    20595360
## 3 Brazil      1999 37737    172006362
## 4 Brazil      2000 80488    174504898
## 5 China       1999 212258    1272915272
## 6 China       2000 213766    1280428583
```

```
table3_separated <- table3 %>%
  separate(rate, into = c("cases", "population"))
```

4.1.4. Unite (multiple columns into one column)

```
table3_separated %>%
  unite(rate, cases, population)
```

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>      <int> <chr>
## 1 Afghanistan 1999 745_19987071
## 2 Afghanistan 2000 2666_20595360
## 3 Brazil      1999 37737_172006362
## 4 Brazil      2000 80488_174504898
## 5 China       1999 212258_1272915272
## 6 China       2000 213766_1280428583
```

4.2. dplyr manipulation (process)

dplyr is better than the base R approaches to data processing:

- fast to run (due to its C++ backend) and intuitive to type
- works well with tidy data and databases

There are so many useful commands that come from dplyr: `filter()`, `slice()`, `arrange()`, `select()`, `rename()`, `distinct()`, `mutate()`, `summarize()`, `sample_n()`.

The pipe operator `%>%` originally comes from the `magrittr` package. The idea behind the pipe operator is similar to what we learned about chaining functions in high school. $f: B \rightarrow C$ and $g: A \rightarrow B$ can be expressed as $f(g(x))$. Basically, the pipe operator chains operations.

```
library(dplyr)
library(gapminder) # load gapminder package

gapminder # the data is already organized by tidy principles
```

```
## # A tibble: 1,704 x 6
##   country      continent  year lifeExp      pop gdpPercap
##   <fct>      <fct>      <int> <dbl>      <int>      <dbl>
## 1 Afghanistan Asia      1952   28.8   8425333    779.
## 2 Afghanistan Asia      1957   30.3   9240934    821.
## 3 Afghanistan Asia      1962   32.0  10267083    853.
## 4 Afghanistan Asia      1967   34.0  11537966    836.
## 5 Afghanistan Asia      1972   36.1  13079460    740.
## 6 Afghanistan Asia      1977   38.4  14880372    786.
## 7 Afghanistan Asia      1982   39.9  12881816    978.
## 8 Afghanistan Asia      1987   40.8  13867957    852.
## 9 Afghanistan Asia      1992   41.7  16317921    649.
## 10 Afghanistan Asia      1997   41.8  22227415    635.
## # ... with 1,694 more rows
```

```
names(gapminder) # the column names
```

```
## [1] "country" "continent" "year" "lifeExp" "pop" "gdpPercap"
```

```
gapminder %>%
  filter(continent == "Europe") %>% # filter by Europe
  group_by(country) %>% # group by country
  summarize(Mean = mean(gdpPercap)) %>% # collapse data by mean
  top_n(5, Mean) %>% # count only top 5 by mean
  arrange(desc(Mean)) # arrange by descending order
```

```
## # A tibble: 5 x 2
##   country      Mean
```

```
##   <fct>         <dbl>
## 1 Switzerland 27074.
## 2 Norway      26747.
## 3 Netherlands 21749.
## 4 Denmark     21672.
## 5 Germany     20557.

gapminder <- gapminder %>%
  rename(population = pop) # rename pop variable (old name = new name)

gapminder$pop # It should be NULL

## Warning: Unknown or uninitialised column: 'pop'.
## NULL
```

4.3. Modeling

Will not be extensively covered in this course.

4.4. Visualization

Will be covered in the future session.