PDS Quiz 1 Date:

Roll No : _____ Section : _____

Q1. Which of the following is an invalid variable name (identifier) in C?
(A)_grand_total (B) sum2 (C) 2nd_player (D) GrandTotal

Q2. What type of token is the word sizeof in C?
(A) Identifier (B) Keyword (C) Operator (D) Function

Q3. How does the C compiler explicitly identify a hexadecimal integer literal?
(A) It starts with a leading 0 (B) It starts with 0x or 0X
(C) It ends with an H (D) It is wrapped in single quotes

Q4. What is the value of the expression x = 5 + 3 * 2 % 4 according to operator precedence?
(A) 7 (B) 11 (C) 1 (D) 9

Q5. Which of the following is NOT a valid token type in C?
(A) Keywords (B) Identifiers (C) Comments (D) Operators

Q6. What will be the output of the following code snippet?cint x = 0;

```
if (x = 5) {
   printf("True");
} else {
   printf("False");
}
```

(A)True (B) False (C) Compilation Error (D) Runtime Error

Q7. When an if-else statement is nested without curly braces {}, a dangling else always pairs with:
(A)The very first if statement at the top.
(B)The closest preceding if statement in the same block.
(C)The closest preceding if statement that does not already have an else.
(D)It causes a syntax compilation error.

Q8. What happens during short-circuit evaluation in the expression
if (a == 0 && b++ > 5) if a is equal to 1?
(A)The program crashes with a segmentation fault.
(B)Both sides are checked, and b is incremented.
(C)The right side is skipped, and b is not incremented.
(D)The compiler generates a warning.

Q9. Which data types are strictly NOT allowed as expressions inside a switch() statement?
A) int B) char C) float and double D) Enumerations (enum)

Q10. What will happen if you omit the break; statement at the end of a matching case block in a switch statement?
(A)The program will throw a compilation error.
(B)Execution will fall through to the subsequent cases until a break or the end is reached.
(C)The loop will terminate instantly.
(D)The default case will execute immediately, skipping other cases.

Q11. Rewrite the following ternary condition as a standard if-else block: result = (score >= 40) ? 1 : 0;
(A)if (score >= 40) result = 0; else result = 1; (B)if (score >= 40) result = 1; else result = 0;
(C)if (result == 1) score = 40; (D)if (score < 40) result = 1; else result = 0;

Q12. What does an omitted condition in a for loop header—such as for(; ;)—default to?
(A)It evaluates to false and never runs. (B)It triggers a compilation error.
(C)It runs exactly one time. (D)It evaluates to true and creates an infinite loop.

Q13. What is the guaranteed minimum number of times a do-while loop body will execute?
(A)0 (B) 1 C) Depends on the condition variable initialization (D)Infinitely

Q14) int x = 2;
switch(x) {
case 1: printf("One ");
default: printf("Default ");
case 2: printf("Two ");
case 3: printf("Three ");
}
(A) Two (B) Two Three (C) Default Two Three (D) One Default Two Three

Q15. How do break and continue dynamically differ in their control flow inside loops?
(A)break exits the entire loop; continue skips the rest of the current iteration and goes to the next.
(B)continue exits the entire loop; break skips to the next iteration.
(C)break resets the loop counter variable to 0; continue does nothing.
(D)They are completely interchangeable tokens.

Q16. What is the output of the following code snippet?
for (int i = 1; i <= 5; i++) {
if (i == 3) {
continue;
}
printf("%d ", i);
}
A) 1 2 (B) 1 2 4 5 C) 1 2 3 4 5 D) 4 5

Q17. Which of the following represents a standard infinite loop syntax using a while loop?
(A)while(0 (B) while(1) (C) while(NULL) (D) while()

Q18. What is a critical danger of placing a continue statement before updating your loop control variable inside a while loop?
(A)It converts the loop into a switch statement.
(B)It will cause an immediate compiler warning.
(C)It can bypass the increment step entirely, creating an infinite loop.
(D)It automatically sets the variable to zero.

Q19. In a for loop header, what operator is used if you want to initialize or increment multiple variables at the same time (e.g., for(i=0, j=10; i<j; i++, j--))?
(A)Semi-colon (;) (B)Colon (:) (C)Comma (,) (D) Ampersand (&)

Q20. What will be the output of the following code execution?
int i = 1;
while(i <= 3) {
printf("%d ", i);
i++;
}
(A)1 2 3 (B)1 2 (C) 2 3 4 (D)1 1 1