

## MATERIAL SAFETY DATA SHEET

### Warren Unilube, Inc.

**Address:** 915 E. Jefferson Ave.  
West Memphis, AR 72301

**Phone:** (800) 428-9284

### PRODUCT IDENTIFICATION

**Trade Name:** Carquest Dexron III Mercon ATF

**Date Revised:** March 2, 2004

**Synonyms/product Code:** N.A.

**Chemical Name:** Petroleum Mineral Oil

**Family Description:** A complex combination of hydrocarbons from a petroleum fraction obtained by solvent crystallization plus additives.

**DOT Hazard Class:** Not Applicable

**NFPA Codes:** Health=1, Flammability=1, Reactivity=0

### COMPOSITION

#### Occupational Exposure Limits\*

<u>Product</u>	<u>CAS Number</u>	<u>Wt%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other</u>	<u>Units</u>
Carquest Dexron III Mercon ATF	Mixture	100	N.A.	N.A.		

---

**Ingredient(s):**

Solvent Dewaxed Heavy Paraffinic Additives Containing Acid Esters	64742-65-0	85	5	5	10 STEL	mg/m <sup>3</sup> **
	N.A.	<15	N.A.	N.A.	N.A.	N.A.

---

\* = 8-Hr. TWA unless otherwise specified.

\*\* = As mineral oil Mist

\*\*\* = All ingredients in this product are listed in the T.S.C.A. Inventory.

N.A. = Not Available

STEL = Short Term Exposure Limit; 15 minutes.

**PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point 760 mmHg:	N.A.	Melting Point:-40F
Vapor Pressure mmHg @ 100F:	N.A.	Vapor Density (air=1): N.A.
Solubility in H <sub>2</sub> O %:	Nil.	pH: N.A.
Specific Gravity (H <sub>2</sub> O):	0.8762	Evaporation Rate (ethyl ether =1):
% Volatile by Volume:	N.A.	Odor: Slight hydrocarbon odor
Viscosity (method, temp):	7.10 cst,100C	Appearance: Red Liquid

N.A. = Not Available

**FIRE AND EXPLOSION DATA**

Flash Point:	415F COC	
Flammable Limits in Air % by Vol.	Lower: N.A.	Upper: N.A.
Autoignition Temperature:		
Extinguishing Media:	Dry chemical, foam, carbon dioxide or water spray.	
Special Fire Fighting Procedure:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.	
Unusual Fire or Explosion Hazard:	May ignite when sufficient heat is applied.	

**REACTIVITY DATA**

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid/Incompatibility:	Strong oxidizing agents, heat, spark, flame and build-up of static electricity.
Hazardous Decomposition Products:	Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and combustion products of sulfur and nitrogen.

**HEALTH HAZARD DATA**

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No Occupational Exposure Limits:	IARC Monographs: No See <u>COMPOSITION</u> section.	OSHA Regulated: No
Effects of Overexposure:		
<u>Acute:</u> Eyes: The heavy paraffinic petroleum distillate fraction of this product is believed to be minimally irritating.		

Skin:	The heavy paraffinic petroleum distillate fraction of this product is believed to be minimally irritating.
Inhalation:	The inhalation hazards of this products components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits.
Ingestion:	Ingestion hazards range from practically non-toxic to minimally toxic for the components of this product. If vomiting occurs, product is an aspiration hazard.
<u>Chronic:</u>	Frequent or prolonged contact may cause skin irritation.
<b>Additional Medical and Toxicological Information:</b>	<b>May aggravate pre-existing dermatitis. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity in experimental animals of used oil.</b>

#### **EMERGENCY FIRST AID PROCEDURES**

<b>Eye Contact:</b>	Flush thoroughly with water for at least 15 minutes. Get medical attention.
<b>Skin Contact:</b>	Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical help.
<b>Inhalation:</b>	Remove to fresh air. Apply artificial respiration if not breathing. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head lower than hips to prevent aspiration.

#### **SPECIAL PROTECTION INFORMATION**

<b>Eye Protection:</b>	Remove contact lenses and wear chemical safety goggles where contact with liquid or mist may occur.
<b>Skin Protection:</b>	Wear impervious gloves when contact with skin may occur. Use face shields where splashing may occur.
<b>Inhalation:</b>	Use approved respiratory protective equipment for cleaning large spills or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels.
<b>Ventilation:</b>	Provide adequate ventilation to keep mist or vapors below occupational exposure levels.

#### **SPILL OR LEAK AND DISPOSAL PROCEDURES**

<b>Spill Procedures:</b>	Remove sources of heat or ignition including internal combustion engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with absorbent. Use approved respirator where occupational exposure limits may be exceeded.
--------------------------	---

**Waste Disposal:** Dispose through a licensed waste disposal company. Follow federal, state and local regulation.

#### **SPECIAL PRECAUTIONS AND COMMENTS**

**Storage Requirements:** Store in tightly closed containers in a dry cool place, away from sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment and equip with self closing valves, pressure vacuum bungs and flame arresters.

#### **SARA TITLE III INFORMATION**

<b><u>Acute</u></b>	<b><u>Chronic</u></b>	<b><u>Fire</u></b>	<b><u>Pressure</u></b>	<b><u>Reactive</u></b>
X	X			

#### **SARA Hazardous Substances**

<b><u>Ingredient</u></b>	<b><u>CAS NO.</u></b>	<b><u>%, WT</u></b>	<b><u>Sec 313</u></b>	<b><u>Sec 302</u></b>	<b><u>RQ, lb</u></b>	<b><u>TPQ, lb</u></b>
--------------------------	-----------------------	---------------------	-----------------------	-----------------------	----------------------	-----------------------

— None

Key: Sec 313 = Toxic Chemicals, Section 313  
 Sec 302 = Extremely Hazardous Substances (EHS)  
 RQ = Reportable Quantity of EHS  
 TPQ = Threshold Planning Quantity of EHS

#### **CALIFORNIA PROPOSITION 65 WARNING**

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.