

Material Safety Data Sheet

MSDS# P309

Page 1 of 3

Sanford Corporation
2711 Washington Boulevard
Bellwood, IL 60104

Telephone No:
Date of Last Revision:
Medical Emergency No:

1-800-323-0749
October 15, 2001
1-800-228-5635

SECTION ONE: PRODUCT INFORMATION

PRODUCT NAME: Pre-Tested Oil Colors

PRODUCT SIZES: 37 and 150 ml

PRODUCT CLASS: Artists' Oil Color

SECTION TWO: HAZARDOUS INGREDIENTS

INGREDIENTS	CAS #	PEL/TLV	MAX WT.%	NTP	IARC
Cobalt Pigment	N/A	N/A	45.0	-	-
Barium Sulfate	7727-43-7	10 mg/m ³	25.0	-	-

SECTION THREE: PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT: Not determined

MELTING POINT: Not determined

VAPOR PRESSURE: Not determined

SPECIFIC GRAVITY: Not determined

SPECIFIC VAPOR DENSITY (AIR = 1) Not determined

SOLUBILITY IN WATER: Not determined

REACTIVITY IN WATER: Non-reactive

EVAPORATION RATE (BUTYL ACETATE = 1): Not determined

APPEARANCE AND ODOR: Colored paints; oily odor

This Material Safety Data Sheet is applicable for the consumer use of the following products: P309

Sanford Corporation is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

SECTION FOUR: FIRE AND EXPLOSION INFORMATION**FLASH POINT (METHOD):** Not available**FLAMMABILITY LIMITS (% BY VOLUME):** LOWER: Not explosive UPPER: Not explosive**EXTINGUISHING MEDIA:** As appropriate for surrounding area.**FIRE FIGHTING PROCEDURES:** No special fire fighting procedures required.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Not combustible**SECTION FIVE: REACTIVITY DATA****STABILITY:** Stable**CONDITIONS TO AVOID:** Excessive heat**CHEMICAL INCOMPATIBILITY:** None known**HAZARDOUS DECOMPOSITION:** None known**HAZARDOUS POLYMERIZATION:** Will not occur.**SECTION SIX: HEALTH HAZARD DATA****PERMISSIBLE EXPOSURE LEVEL:** See Section Two for component PEL/TLV's.**PRIMARY ROUTES OF ENTRY:****Inhalation:** None under normal use conditions.**Skin:** None under normal use conditions.**Eye:** None under normal use conditions.**Ingestion:** May be harmful if swallowed.**EFFECTS/SYMPOTMS OF ACUTE EXPOSURE:** Harmful if swallowed.**EFFECTS/SYMPOTMS OF CHRONIC EXPOSURE:** Exposure may cause damage to the heart.**CARCINOGEN LISTING:** NTP: NO IARC: NO OSHA: NO

See Section Two for components affected.

Material Safety Data Sheet

MSDS# P309

Page 3 of 3

MEDICAL CONDITIONS USUALLY AGGRAVATED
BY OVEREXPOSURE TO THIS PRODUCT: Unknown

FIRST AID MEASURES:

- Inhalation: Remove to fresh air.
- Skin: Wash with soap and water.
- Eye: Rinse through with water. If irritation persists, seek medical attention.
- Ingestion: Seek prompt medical attention.

SECTION SEVEN: SPILL OR LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN DURING STORAGE/HANDLING: KEEP OUT OF REACH OF CHILDREN.

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: No special spill procedures required.

WASTE DISPOSAL METHOD: Dispose in accordance with Federal, State, and Local Regulations.

SECTION EIGHT: PROTECTIVE EQUIPMENT AND CONTROL MEASURES

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: None required.

OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC.): None

WORK/HYGIENE PRACTICES: PRECAUTIONS: Wash hands immediately after use. When using, do not eat, drink, or smoke. KEEP OUT OF REACH OF CHILDREN.

HMIS CODE	
Health	1
Flammability	0
Reactivity	0
Personal Protection	N/A

CONTAINS: Soluble cobalt

WARNING: May be harmful if swallowed. Exposure may cause damage to the heart.

WARNING: This product contains lead, a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

WARNING: This product contains an additional chemical known to the State of California to cause cancer.

0=Minimal/4=Extreme Hazard

May be used to comply with OSHA Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

