



Scott Specialty Gases

Material Safety Data Sheets

MSDS No: 75-71-8**Date: 03/09/2001**

SUPPLIER ADDRESS: 6141 Easton Road, Bldg. 1
PO Box 310
Plumsteadville, PA 18949-0310

EMERGENCY PHONE NUMBER: (215) 766-8861

1. CHEMICAL PRODUCT

PRODUCT NAME: DICHLORODIFLUOROMETHANE **SYNONYMS:** Freon 12, Halocarbon-12

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS #	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
DICHLORODIFLUOROMETHANE	CCl2F2	75-71-8	99+%	1000	1000	1000	NE

Note: NE = NONE ESTABLISHED

S/A = SIMPLE ASPHYXIAN

3. HAZARD IDENTIFICATION

***** EMERGENCY OVERVIEW *****

Liquid and gas under pressure.
Can cause rapid suffocation.
May cause frostbite.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Inhalation may cause asphyxiation due to dilution of available oxygen in the air. Symptoms include lightheadedness, giddiness, disorientation, shortness of breath, and possible cardiac arrhythmias. Skin and eye contact with liquid may cause frostbite. Pressure drop through valves and piping may cause extreme cold and frostbite on contact.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Heart disease. Cardiovascular problems.

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US ONLY):

NTP - No
IARC MONOGRAPHS - No
OSHA REGULATED - No

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

— EYE CONTACT: Immediately flush with copious amounts of water for at least 15 minutes.

SKIN CONTACT: If frostbite occurs, flush affected areas with lukewarm water.

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap

FLAMMABLE LIMITS: Nonflammable

LOWER:

UPPER:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

— SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use. Store away from oxidizers, combustible materials, and source of ignition or heat.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

— ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentration

below exposure limits.

EYE / FACE PROTECTION: Safety glasses or Face shield

— SKIN PROTECTION: Protective gloves to prevent contact with cold equipment.

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Slight ethereal odor.

PHYSICAL PRESSURE: Gas

VAPOR PRESSURE: @ 20 deg.C: 5.7 atm

VAPOR DENSITY (AIR=1): 4.16

BOILING POINT (C): -29.8

SOLUBILITY IN WATER: 20 deg.C: 0.028 wt. %

SPECIFIC GRAVITY (H₂O=1): Gas

— EVAPORATION RATE: Gas

ODOR THRESHOLD: N/Av

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Alkali or alkaline earth metals, powdered Al, Zn, and Be.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Hydrochloric acid, hydrofluoric acid, toxic fumes of phosgene, and fluorides. Halogens and carbonyl halides.

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC₅₀): 565,600 ppm, Rat 1 hour.

LETHAL DOSE 50 (LD₅₀): N/Ap

TERATOGENICITY: N/Ap

— REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

12. ECOLOGICAL INFORMATION

This material is a Class 1 ozone depleting material.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Dichlorodifluoromethane, R12
HAZARD CLASS: 2.2 (nonflammable)
IDENTIFICATION NUMBER: UN1028
REPORTABLE QUANTITIES: None
LABELING: NONFLAMMABLE GAS

ADR / RID (EU Only): Class 2, 2A

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 200-893-9

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

EU CLASSIFICATION: N/Av

R: N/Av

S: N/Av

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders

should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS: N/Ap - Not Applicable N/Av - Not Available SA - Simple Asphyxiant NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.