



Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 08/22/2019

Date of Issue: 02/08/2017

Supersedes Date: 09/07/2018 Version: 3.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Kaboom™ Foam-Tastic™ with OxiClean™

Product Code: 42000010; 42000005

Intended Use of the Product

Bathroom Cleaner

Name, Address, and Telephone of the Responsible Party

Company

Church & Dwight

500 Charles Ewing Blvd

Ewing Township, NJ 08628

T 1-800-524-1328

www.churchdwight.com

Emergency Telephone Number

Emergency Number : For Medical Emergency: 1-888-234-1828 (USA and Canada), 952-853-1925 (Outside USA and Canada); For Chemical Emergency (CHEMTREC): 1-800-424-9300 (USA and Canada), 1-703-741-5970 (Outside USA and Canada)

SECTION 2: HAZARDS IDENTIFICATION

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

Classification of the Substance or Mixture

GHS-US/CA Classification

Simple Asphy

Press. Gas (Comp.) H280

Skin Irrit. 2 H315

Eye Dam. 1 H318

Aquatic Acute 2 H401

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA) :



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H280 - Contains gas under pressure; may explode if heated.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

May displace oxygen and cause rapid suffocation.

Precautionary Statements (GHS-US/CA) : P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor.
P321 - Specific treatment (see section 4 on this SDS).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Isobutane	(CAS-No.) 75-28-5	4.491 - 4.99	Simple Asphy Flam. Gas 1, H220 Press. Gas (Liq.), H280
Tetrasodium EDTA	(CAS-No.) 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411 Comb. Dust
1-Dodecanamine, N,N-dimethyl-, N-oxide	(CAS-No.) 1643-20-5	2.480 - 2.736	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt	(CAS-No.) 137-16-6	0.5 – 1.5	Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Dam. 1, H318
Butane	(CAS-No.) 106-97-8	< 0.499	Simple Asphy Flam. Gas 1, H220 Press. Gas (Liq.), H280
Sodium hydroxide	(CAS-No.) 1310-73-2	0.1 - 1	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

breathing. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Do not induce vomiting. Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. Causes serious eye damage. Asphyxia by lack of oxygen: risk of death. Contact with gas escaping the container can cause frostbite.

Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sodium oxides. Sulfur oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe gas. Do not get in eyes, on skin, or on clothing. Do not breathe vapors, mist, or spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area.

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Asphyxiating gas at high concentrations. Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. Do not pressurize, cut, or weld containers.

Precautions for Safe Handling: Do not get in eyes, on skin, or on clothing. Do not breathe gas. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Ammonia. Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

Bathroom Cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	2 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
Saskatchewan	OEL Ceiling (mg/m ³)	2 mg/m ³
Yukon	OEL Ceiling (mg/m ³)	2 mg/m ³

Isobutane (75-28-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Manitoba	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers))

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Nova Scotia	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Nunavut	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Nunavut	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Northwest Territories	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Northwest Territories	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Ontario	OEL STEL (ppm)	1000 ppm (Butane, all isomers)
Prince Edward Island	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Saskatchewan	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Saskatchewan	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Butane (106-97-8)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
USA IDLH	US IDLH (ppm)	1600 ppm (>10% LEL)
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL STEL (ppm)	750 ppm
Manitoba	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
New Brunswick	OEL TWA (mg/m³)	1900 mg/m³
New Brunswick	OEL TWA (ppm)	800 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Nova Scotia	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Nunavut	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Nunavut	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Northwest Territories	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Northwest Territories	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Ontario	OEL STEL (ppm)	1000 ppm (Butane, all isomers)
Prince Edward Island	OEL STEL (ppm)	1000 ppm (explosion hazard (Butane, isomers)
Québec	VEMP (mg/m³)	1900 mg/m³
Québec	VEMP (ppm)	800 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm (Butane, all isomers)
Saskatchewan	OEL TWA (ppm)	1000 ppm (Butane, all isomers)
Yukon	OEL STEL (mg/m³)	1600 mg/m³
Yukon	OEL STEL (ppm)	750 ppm
Yukon	OEL TWA (mg/m³)	1400 mg/m³
Yukon	OEL TWA (ppm)	600 ppm

Exposure Controls

Appropriate Engineering Controls: For occupational/workplace settings: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Oxygen detectors should be used when asphyxiating gases may be released.

Personal Protective Equipment: For occupational/workplace settings and bulk quantities: Gloves. Protective clothing. Protective goggles. Respiratory protection of the dependent type.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory Protection: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Thermal Hazard Protection: Wear thermally resistant protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	:	Gas
Appearance	:	Dark blue liquid with gas propellant
Odor	:	Citrus
Odor Threshold	:	Not available
pH	:	12
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	Not available
Flash Point	:	non-flammable
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20°C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	1.01 g/ml
Solubility	:	Not available
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
Explosive Properties	:	Contains gas under pressure; may explode if heated

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Contains gas under pressure; may explode if heated.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

Incompatible Materials: Ammonia. Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified.

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation. (pH: 12)

Eye Damage/Irritation: Causes serious eye damage. (pH: 12)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Tetrasodium EDTA (64-02-8)	
LD50 Oral Rat	1780 mg/kg
Sodium hydroxide (1310-73-2)	
LD50 Oral Rat	325 mg/kg
Isobutane (75-28-5)	
LC50 Inhalation Rat	658 mg/l/4h
LC50 Inhalation Rat	11000 ppm
Butane (106-97-8)	
LC50 Inhalation Rat	30957 mg/m³ (Exposure time: 4 h)
Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt (137-16-6)	
LD50 Oral Rat	> 5000 mg/kg
LC50 Inhalation Rat	0.5 mg/l/4h
1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)	
ATE US/CA (oral)	500.00 mg/kg body weight

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Tetrasodium EDTA (64-02-8)	
LC50 Fish 1	41 mg/l (Exposure time: 96h - Species: Lepomis macrochirus)
EC50 Daphnia 1	625 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC50 Fish 2	59.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
ErC50 (algae)	3 mg/l (Exposure time: 96 h - Species: Green Algae)
ErC50 (other aquatic plants)	1.01 mg/l (Exposure time: 72 Hr - Species: Desmodesmus subspicatus)
Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	40 mg/l
1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)	
ErC50 (algae)	0.11 mg/l (72 hour)
NOEC Chronic Algae	0.004 mg/l

Persistence and Degradability

Kaboom™ Foam-Tastic™ with OxiClean™	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

Kaboom™ Foam-Tastic™ with OxiClean™	
Bioaccumulative Potential	Not established.
Tetrasodium EDTA (64-02-8)	
Log POW	5.01 (calculated)
Isobutane (75-28-5)	

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

BCF Fish 1	1.57 - 1.97
Log POW	2.88 (at 20 °C)
Butane (106-97-8)	
Log POW	2.89

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions. Empty gas cylinders should be returned to the vendor for recycling or refilling. Do not puncture or incinerate container.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In Accordance with DOT

Proper Shipping Name	: AEROSOLSnon-flammable, (each not exceeding 1 L capacity)
Hazard Class	: 2.2
Identification Number	: UN1950
Label Codes	: 2.2
ERG Number	: 126



In Accordance with IMDG

Proper Shipping Name	: AEROSOLS
Hazard Class	: 2.2
Identification Number	: UN1950
Label Codes	: 2.2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U



In Accordance with IATA

Proper Shipping Name	: AEROSOLS, NON-FLAMMABLE
Identification Number	: 2.2
Hazard Class	: UN1950
Label Codes	: 2.2
ERG Code (IATA)	: 2L



In Accordance with TDG

Proper Shipping Name	: AEROSOLS, NONFLAMMABLE
Hazard Class	: 2.2
Identification Number	: UN1950
Label Codes	: 2.2



SECTION 15: REGULATORY INFORMATION

US Federal and International Regulations

Kaboom™ Foam-Tastic™ with OxiClean™	
SARA Section 311/312 Hazard Classes	Physical hazard - Gas under pressure Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Simple asphyxiant
Tetrasodium EDTA (64-02-8)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Sodium hydroxide (1310-73-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

CERCLA RQ

1000 lb

Isobutane (75-28-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Butane (106-97-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt (137-16-6)

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

US State Regulations

Sodium hydroxide (1310-73-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Isobutane (75-28-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Butane (106-97-8)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Tetrasodium EDTA (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Glycine, N-methyl-N-(1-oxododecyl)-, sodium salt (137-16-6)

Listed on the Canadian DSL (Domestic Substances List)

1-Dodecanamine, N,N-dimethyl-, N-oxide (1643-20-5)

Kaboom™ Foam-Tastic™ with OxiClean™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 08/22/2019

Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

GHS Full Text Phrases:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Gas 1	Flammable gases Category 1
Met. Corr. 1	Corrosive to metals Category 1
Press. Gas (Comp.)	Gases under pressure Compressed gas
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H330	Fatal if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This Product Safety Data Sheet is offered solely for your information, consideration and investigation. Church & Dwight Co., Inc. provides no warranties; either expressed or implied, and assumes no responsibility for the accuracy or completeness of data contained herein. Church & Dwight Co., Inc. urges persons receiving this information to make their own determination as to the information suitability for their particular application.