



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: SUNSPRAY 6N

Manufacturer Information:

Sunoco, Inc. (R&M)
Ten Penn Center
1801 Market Street
Philadelphia, Pennsylvania, 19103-1699

Product Use:

Spray Oil
EPA Reg No. 862-10

Emergency Phone Numbers:

Chemtrec (800) 424-9300
Sunoco Inc. (800) 964-8861

Information:

Product Safety Information (610) 859-1120

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5	80 - 100
SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4	0 - 20

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

CAS No.	Governing Body	Exposure Limits

3. HAZARDS IDENTIFICATION

• EMERGENCY OVERVIEW

Danger! May cause respiratory tract irritation. Harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage.

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme

	Health	Fire	Reactivity	PPI
NFPA	1	1	0	
HMIS	1	1	0	X

• POTENTIAL HEALTH EFFECTS

• PRE-EXISTING MEDICAL CONDITIONS

The following diseases or disorders may be aggravated by exposure to this product: Skin; Respiratory system; Lung (asthma-like conditions);

• INHALATION

High vapor concentrations are irritating to the eyes, nose, throat, and lungs.

LC50 (mg/l): no data

LC50 (mg/m3): no data

LC50 (ppm): no data

• SKIN

Practically non-toxic if absorbed through the skin. Substance does not generally irritate and is only mildly irritating to the skin.

Draize Skin Score: no data

Out of 8.0

LD50 (mg/kg): no data

• EYES

Non-irritating to the eyes.

• INGESTION

Practically non-toxic if ingested. Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage.

LD50 (g/kg): > 30

4. FIRST AID MEASURES

• INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

• SKIN

Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse.

• EYES

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

• INGESTION

Do not induce vomiting! Do not give liquids! Get medical attention immediately.

5. FIRE FIGHTING MEASURES

• EXTINGUISHING MEDIA

Water spray; Regular foam; Dry chemical; Carbon dioxide;

• FIRE FIGHTING INSTRUCTIONS

Wear structural fire fighting gear.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				385 TYPICAL COC	F	N/A
Autoignition Temperature				650 ESTIMATED	F	N/A
Lower Explosion Limit				no data	%	N/A
Upper Explosion Limit				no data	%	N/A

6. ACCIDENTAL RELEASE MEASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

• HANDLING

Avoid breathing (dust, vapor, mist, gas). Wash thoroughly after handling.

• STORAGE

Store in a cool dry place. NFPA class IIIB storage. Flash point is greater than 200 degrees F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

• ENGINEERING CONTROLS

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use with adequate ventilation.

• PERSONAL PROTECTION

• EYE PROTECTION

Splash proof chemical goggles are recommended to protect against the splash of product.

• GLOVES or HAND PROTECTION

Protective gloves are recommended when prolonged skin contact cannot be avoided. The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Polyvinyl chloride (PVC); Neoprene; Nitrile; Polyvinyl alcohol; Viton;

• RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Respiratory protection is not usually needed unless product is heated or misted. Half-mask air purifying respirator with dust / mist filters or HEPA filter cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with dust / mist filters or HEPA filter cartridges is acceptable for exposures to fifty (50) times the exposure limit.

• OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: Polyvinyl alcohol (PVA); Polyvinyl chloride (PVC); Neoprene; Nitrile; Viton; Polyurethane; Remove contaminated clothing and wash before reuse. For non-fire emergencies, respiratory protection may be necessary and wear appropriate protective clothing to avoid contact with material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	COLORLESS FLUID	
Boiling Point		F	no data	
Bulk Density		lb/gal	no data	
Melting Point		F	no data	
Molecular Weight		g/mole	no data	
Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.86	N/A		

Solubility In Water		wt %	nil	
Odor		N/A	LITTLE ODOR.	
Odor Threshold		ppm	no data	
Vapor Pressure		mmHg	< 0.0001	@ 20 C
Viscosity (F)	69	SUS		@ 100 C
Viscosity (C)	12	CsT		@ 40 C
% Volatile		wt %	NIL	

10. STABILITY AND REACTIVITY

- **STABILITY**
Stable
- **CONDITIONS TO AVOID**
Avoid heat, sparks and open flame.
- **INCOMPATIBILITY**
Strong oxidizers
- **HAZARDOUS DECOMPOSITION PRODUCTS**
Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.
- **HAZARDOUS POLYMERIZATION**
Will not polymerize.

11. ECOLOGICAL INFORMATION

No data available This material is expected to be toxic to aquatic organisms.

12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is not a RCRA hazardous waste, if not contaminated. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

13. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>
DOT	Ground	PETROLEUM OIL NOIBN

<u>Governing Body</u>	<u>Mode</u>	<u>Hazard Class</u>	<u>UN/NA No.</u>	<u>Label</u>
DOT	Ground	N/A	N/A	

14. REGULATORY INFORMATION

<u>Regulatory List</u>	<u>Component</u>	<u>CAS No.</u>
Inventory - Australia (AICS)	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - Australia (AICS)	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - Canada - Domestic Substances List	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - Canada - Domestic Substances List	SEVERELY SOLVENT	64741-89-5

Inventory - China	REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - China	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - European EINECS Inventory	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - European EINECS Inventory	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - Japan - (ENCS)	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - Korea - Existing and Evaluated	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - Korea - Existing and Evaluated	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - Philippines Inventory (PICCS)	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - Philippines Inventory (PICCS)	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Inventory - TSCA - Sect. 8(b) Inventory	SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL	64741-88-4
Inventory - TSCA - Sect. 8(b) Inventory	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5
Massachusetts - Right To Know List	SEVERELY SOLVENT REFINED LIGHT PARAFFINIC PETROLEUM OIL	64741-89-5

Title III Classifications Sections 311,312:

- Acute: **YES**
- Chronic: **NO**
- Fire: **NO**
- Reactivity: **NO**
- Sudden Release of Pressure: **NO**

15. OTHER INFORMATION

No data available This product is in EPA Hazard Category IV. WHMIS Classification: not controlled. Please refer to the material safety data sheet for complete information. Limits for the product- 5mg/m3, Oil Mist Limit, (OSHA PEL/ACGIH TLV)