

Material Safety Data Sheet

RECEIVEDDAP Inc.
P.O. Box 277
Dayton, OH 45401 1989LARNER STATE HOSPITAL
ENGINEERING DEPARTMENTProduct: DAP VINYL SPACKLING
(INTERIOR)
Internal ID: 10405MSDS No: DAP / 10405
Revision: 1
Date: May 21, 1988National Paint
and Coatings
Association

Hazardous Material
Identification
System

HEALTH HAZARD	0 - Minimal
FLAMMABILITY HAZARD	0 - Minimal
REACTIVITY HAZARD	0 - Minimal
PERSONAL PROTECTION	B - Glasses, Gloves

SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name: DAP VINYL SPACKLING (INTERIOR)

PS-197

Description: Spackling Compound

CAS: Mixture

Shipping Name (49 CFR 172.101): NA
D.O.T. ID No. (49 CFR 172.101): NA
D.O.T. Label Required (49 CFR 172.101): NA
EPA Hazard Class - if discarded (40 CFR 261): NAManufacturer: DAP Inc.
P.O. Box 277
Dayton, OH 45401Phone: 1-800-543-3840
In Ohio:
1-513-253-7154

SECTION II. INGREDIENTS AND HAZARDS

Ingredient Name: Percent: Exposure Limits:

All ingredients are not regulated by OSHA and are considered trade secrets.

SECTION III. PHYSICAL DATA

Appearance & Odor: Opaque paste with a mild odor

Boiling point: 212°F
Vapor pressure: 17.5 @ 20°C
Water solubility (%): Soluble
Vapor density (air=1): < 1Evaporation rate: (n-butyl
acetate = 1):
< 1
Specific gravity (H₂O=1): 1.89
% volatile by volume: 20-30VOC less water less exempt solvent: 0 g/liter
VOC material: 0 g/liter

Material Safety Data Sheet

DAP Inc.
P.O. Box 277
Dayton, Ohio 45401

Product: DAP VINYL SPACKLING
(INTERIOR)
Internal ID: 10405
MSDS No: DAP / 10405
Revision: 1
Date: May 21, 1988

SECTION IV. FIRE AND EXPLOSION DATA

Flash Point (method): (C.C.) None Limits: LEL %: NA UEL %: NA
Extinguishing Media: Foam, carbon dioxide, dry chemicals
Unusual fire or explosion hazards: None known
Special fire-fighting procedures: Use water spray to cool exposed surfaces

SECTION V. REACTIVITY DATA

Material IS stable at room temperature. Hazardous polymerization will NOT occur
Chemical incompatibilities: Strong oxidizers and caustics
Conditions to avoid: Excessive heat
Hazardous decomposition Products: Normal Combustion products, i.e. CO_x, NO_x

SECTION VI. HEALTH HAZARD INFORMATION

This product is NOT considered a carcinogen by NTP, IARC, OSHA

Medical conditions which may be aggravated by contact: None known

Primary entry route(s): Skin contact

Acute effects: None known

Chronic effect(s): None known

First aid:

Eye contact: Flush with large amounts of water for 15 minutes.
Contact a physician.

Skin contact: Wash with soap and water.

Inhalation: Remove to fresh air. Contact a physician immediately.

Ingestion: Do not induce vomiting. Contact a physician immediately.

Material Safety Data Sheet

DAP Inc.
P.O. Box 277
Dayton, Ohio 45401

Product: DAP VINYL SPACKLING
(INTERIOR)
Internal ID: 10405

MSDS No: DAP / 10405
Revision: 1
Date: May 21, 1988

SECTION VII. SPILL, LEAK AND DISPOSAL PROCEDURES

Spill / Leak procedures: Scrape up dried material and place into containers.

Waste management / Disposal: This product is non-hazardous according to U.S.EPA's hazardous waste management regulations. Do not reuse empty container.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Personal protective equipment:

Goggles: Safety glasses recommended.

Gloves: Recommended

Respirator: None required. See ventilation section below.

Workplace considerations:

Ventilation: Normal room ventilation.

Safety stations:
Not required.

Contaminated equipment:
Wash contaminated clothing before reuse.

SECTION IX. SPECIAL PRECAUTIONS

Storage segregation: Store away from caustics and oxidizers.

Special handling / storage: Keep containers tightly closed when not in use. Keep out of reach of children. Keep containers from excessive heat and freezing.

DOT Class: NA

This data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

