

----- 000128.MSD
96.35.128

MATERIAL SAFETY DATA SHEET

Page 1 of 3

TRADE NAME: High Density Liquid Developer

DATE: January 2006
(Revised)

I. PRODUCT IDENTIFICATION:

Name/Synonym: 885 Developer

Part Number: 83-3-105059

Manufactured/Distributed by:

Presstek, Inc.
55 Executive Drive
Hudson, NH 03051

Emergency Phone - Day - (603) 595-7000
Night - Chemtrec (800) 424-9300

II. INGREDIENTS - Confidential Information for Safety/Health Use Only
(ALL EXPOSURE LIMITS ARE PPM UNLESS OTHERWISE NOTED)

Chemical Name	CAS#	OSHA PEL	ACGIH, TLV	NIOSH, EXPOSURE LIMITS TWA	STEL	NTP, IARC OSHA CARCINOGEN	WT %
Isoparaffinic Hydrocarbons	64742-48-9	300	400	400		No	75-98
Lauryl methacrylate/ vinyl acetate/butylacid maleate polymer	88214-93-7	NE	NE	NE		No	0.5-11

This product is an OSHA Class II combustible liquid as per
29 CFR 1910.106.

III. PHYSICAL PROPERTIES

Boiling Point (°F): 313-380°F	Specific Gravity (H2O=1): 0.75
Vapor Pressure (mmHg): 30-36	Melting Point: N/E
Vapor Density (Air=1): 5.1	Evaporation Rate
Solubility in Water: < 0.01	(butyl acetate=1): 0.3
Appearance/Odor: Black Liquid, Faint Hydrocarbon Odor	pH: N/A

IV. FIRE AND EXPLOSION HAZARD

Flash Point: 102-128°F TAG CC Flammable Limits: LEL: 0.7% UEL: 7.0%
Extinguishing Media: Foam, CO2, Dry Chemical.
Special Fire Fighting Procedure: UL Fire Class 30-40 with kerosene.
Avoid water; it trends to spread hydrocarbon fires.
Unusual Fire/Explosion Hazards: None.

N/A = Not Applicable
N/E = Not Established

Handling and Storage: Read and follow label directions. Do not reuse container. Store in cool well ventilated area away from heat and flame. For Commercial use only. Keep from reach of children

X. ENVIRONMENTAL DATA

Hazardous Substance (40 CFR 372: SARA Sec. 313)
None
Reportable Quantity (40 CFR 355: SARA Sec. 302)
None
Hazardous Substance (40 CFR 302: CERCLA Table 302.4)
None
RCRA Waste Number
D001
Volatile Organic Compounds
6.2 lbs./gallon or 743 grams/liter (calculated)
SARA Hazard Class
Acute: yes Chronic: no Fire: yes Pressure: no Reactivity: no

NFPA Hazard Rating
Health: 1 Flammability: 2 Reactivity: 0 Specific Hazard: N/A

XI. SHIPPING INFORMATION

* SURFACE Transportation:

Proper Shipping Name: Not regulated by DOT nor restricted by UPS.

* VESSEL/AIR Transportation:

Proper Shipping Name: Flammable Liquid, n.o.s., (Naphtha), 3, UN1993,
III, FP 102oF
Labeling: Vessel; None - (LTDQTY)
Air; "Flammable Liquid" label required.
NOTE:

The chemicals in this product are listed on the TSCA inventory.

XII. DISCLAIMER

The information contained in this Material Safety Data Sheet is furnished without warranty of any kind. Presstek believes that the information contained herein is current as of the revision data of this MSDS. Since the conditions of use of this product are beyond the control of Presstek, it is the obligation of the user to determine the conditions for safe use.