

MATERIAL SAFETY DATA SHEET 57100
KELLOGGS PROFESSIONAL PRODUCTS, INC.

SECTION 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: FOOD GRADE PURE SILICONE LUBRICANT 57100 **IDENTIFICATION NUMBER** 6262-A **DATE PRINTED:** 12/16/08
PRODUCT CLASS: FOOD GRADE SILICONE **PREPARER:** CUSTOMER SERVICE
SUPPLIER/DISTRIBUTOR: KELLOGG'S PROFESSIONAL PRODUCTS, INC.
MANUFACTURED FOR 325 PEARL STREET
SANDUSKY, OH 44870
EMERGENCY TELEPHONE: 419-625-6551 **M – F** 8:30AM – 5:00PM

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

ITEM:	CHEMICAL/ COMMON NAME	CAS NUMBER	WT/WT % (LESS THAN)
01	PROPANE/SOBUTANE/N-BUTANE	68476-86-8	45.0%
02	HYDROTREATED KEROSENE	64742-47-8	35.0%
02	N-HEPTANE	142-82-5	20.0%
03	2-PROPANONE	64-64-1	10.0%

EXPOSURE LIMITS

ITEM	ACGIH		OSHA		COMPANY	SKIN
	TLV – TWA	TLV – STEL	PEL – TWA	PEL – CEILING	TLV – TWA	
01	1000 PPM	N.E.	800 PPM	N.E.	N.E.	YES
02	N.E.	N.E.	N.E.	N.E.	N.E.	NO
03	400 PPM	500 PPM	400 PPM	500 PPM	N.E.	YES
04	750 PPM	1000 PPM	750 PPM	N.E.	N.E.	NO

* See section #16 for abbreviation legend.

SECTION 3 –HAZARDOUS IDENTIFICATION

*** **EMERGENCY OVERVIEW** *** Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE

EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

SKIN CONTACT: Prolonged or repeated contact can result in defatting / drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

INGESTION: This material may be harmful or fatal if swallowed. If a "corrosive" product, may cause severe and permanent damage to mouth, throat and stomach.

CHRONIC HAZARDS: Overexposure may cause nervous system damage, lung damage or kidney damage.

PRIMARY ROUTE (S) OF ENTRY: **SKIN CONTACT** **SKIN ABSORPTION** **INHALATION** **EYE CONTACT**

SECTION 4 – FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

FIRST AID – INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID – INGESTION: Get medical attention immediately. If swallowed, do **NOT** induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT -156 F

LOWER EXPLOSIVE LIMIT: 1.2 %
UPPER EXPLOSIVE LIMIT: 12.8 %

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: CO2 ALCOHOL DRY CHEMICAL FOAM WATER FOG

MATERIAL SAFETY DATA SHEET 57100 KELLOGGS PROFESSIONAL PRODUCTS, INC.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly banded and promptly returned to a drum re-conditioner, or properly disposed.

SPECIAL FIRE FIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

IF PRODUCT IS RELEASED / SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep from freezing.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A NIOSH / MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

PROTECTIVE EQUIPMENT; STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: -43 - 209° F

ODOR: SOLVENT

APPEARANCE: CLEAR

SOLUBILITY IN H2O: NEGLIGIBLE

FREEZE POINT: ND

VAPOR PRESSURE: ND

PHYSICAL STATE: AEROSOL

Coefficient of Water/Oil Distribution: Negligible

VAPOR DENSITY: Is heavier than air

ODOR THRESHOLD: ND

EVAPORATION RATE: Is faster than Butyl Acetate

SPECIFIC GRAVITY: 0.6803

pH @ 0.0 %: NA

VISCOSITY: NA

* See Section #16 for abbreviation legend

SECTION 10 –STABILITY AND REACTIVITY

CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES.

MATERIAL SAFETY DATA SHEET 57100 KELLOGGS PROFESSIONAL PRODUCTS, INC.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 – COMPONENT TOXICOLOGICAL PROPERTIES AND INFORMATION

PRODUCT LD50: 28710 mg / kg

PRODUCT LC50: 262398 ppm

CHEMICAL NAME	LD50	LC50
PROPANE / ISOBUTANE / N-BUTANE	NE	658000 MG/M3/4H/RAT
HYDROTREATED KEROSENE	ND	ND
N-HEPTANE	>7100 MG/KG/RAT	103000 MG/M3/4H/RAT
2-PROPANONE	5800 MG/KG/RAT	50100 MG/M3/8H/RAT
DIMETHYLSILOXANE	20000 MG/KG/RAT	NA

SECTION 12 – ECOLOGICAL INFORMATION

NO ECOLOGICAL INFORMATION

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14 – TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT TECHNICAL NAME: ORM-D

DOT HAZARD CLASS:

DOT UN/NA NUMBER:

PACKING GROUP:

HAZARD SUBCLASS:

RESP. GUIDE PAGE

SECTION 15 – REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS AS FOLLOWS:

OSHA: Hazardous by definition of Hazard communication Standard (29 CFR 1910.1200)

CERCLA – SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories.

IMMEDIATE HEALTH HAZARD

CHRONIC HEALTH HAZARD

FIRE HAZARD

PRESSURIZED GAS HAZARD

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC SUBSTANCES CONTROL ACT: This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
N-HEPTANE	142-82-5
DIMETHYLSILOXANE	63148-62-9

MATERIAL SAFETY DATA SHEET 57100
KELLOGGS PROFESSIONAL PRODUCTS, INC.

SECTION 15 – REGULATORY INFORMATION (CONTINUED)

U.S. STATE REGULATIONS AS FOLLOWS:

NEW JERSEY RIGHT-TO-KNOW: The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
DIMETHYLSILOXANE	63148-62-9

PENNSYLVANIA RIGHT-TO-KNOW: The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
DIMETHYLSILOXANE	63148-62-9

CALIFORNIA PROPOSITION 65: WARNING - The chemical (s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

NO PROPOSITION 65 CHEMICALS EXIST IN THIS PRODUCT.

INTERNATIONAL REGULATIONS AS FOLLOWS:

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings
CANADIAL WHMIS CLASS: No information available.

SECTION 16 – OTHER INFORMATION

HMIS RATINGS –	HEALTH: 2	FLAMMABILITY:	REACTIVITY:
LEGEND:	<i>N.A.- Not Applicable</i>	<i>N.E. – Not Established,</i>	<i>N.D – Not Determined</i>

Previous MSDS revision date: 12/16/08

* The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.