



F1-INTERIOR WOOD FINISHES

opies with OSHA hazard
communication standard
FRI 910.1200.

All Others HMIS Rating	
Health	* 2
Stability	2
Reactivity	0

Prepared
November 1988

THE GLIDDEN COMPANY
925 Euclid Avenue
Cleveland, Ohio 44115
Emergency Telephone
(216) 826-55

FIRE & EXPLOSION HAZARD DATA

Hazard Class: Combustible Liquid, except 40, 85, 5035 are Flammable Liquid
Extinguishing Media: Dry chemical or foam

Special Fire Fighting Procedures: Water may be used to cool and protect exposed containers.

Primary Route(s) of Exposure: Inhalation

Effects of Overexposure:

Skin Contact: Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting.

Ingestion: Amounts ingested incidental to consumer and industrial handling are not likely to cause injury; however, ingestion of larger amounts may cause lung inflammation and damage due to aspiration of material into lungs.

Emergency and First Aid Procedures:

Skin Contact: Wash off quickly with plenty of water, then soap and water, remove contaminated clothing. Wash contaminated clothing before reuse.

Ingestion: If swallowed, obtain medical treatment immediately

Medical Conditions Aggravated By Exposure: This product is not expected to aggravate existing medical conditions; however, ingredients contained in this product have been reported to aggravate preexisting eye, skin, respiratory disorders, lung disorders, asthma-like conditions.

Stability: Stable

Amines

Hazardous Decomposition Products: Carbon Monoxide
Carbon Dioxide

Hazardous Polymerization: Will not occur

Steps to be taken in case material is released or spilled: Comply with all applicable health and environmental regulations.

Eliminate all sources of ignition

Spills may be collected with non-combustible absorbent materials

Waste Disposal: Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

Respiratory Protection: Control environmental concentrations below applicable standards. Where respiratory protection is required, use only NIOSH/MSHA approved respirators in accordance with OSHA Standard 29 CFR 1910.134.

Ventilation: Provide dilution ventilation or local exhaust to prevent build-up of vapors

Personal Protective Equipment: Eye Wash
Safety Shower
Safety Glasses or Goggles
Impervious Gloves

SPECIAL PRECAUTIONS

Handling and Storage: Store below 100°F., except 5035, 40, 85 store below 80°F. Keep away from heat, sparks, and open flame.

Other Precautions: Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. If sanding is done, wear a dust mask to avoid breathing of sanding dust. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge.

Supplemental Health Information: Exposure to materials in this product have been associated with possible liver damage, kidney damage. Excessive inhalation of solvent vapors under uncontrolled conditions may lead to unconsciousness, respiratory failure, asphyxiation, and even death.

Attention: Products in this series contain ethylene glycol when tinted with Dramatone. Ethylene glycol can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.

**1600 SERIES & 40, 50, 51,
80, 81, 82, 83, 84, 85, 5035**